

SAFETY DATA SHEET

SDS ID NO.: Revision Date 0127MAR019 03/19/2018

1. IDENTIFICATION Product Name: Marathon Petroleum Gasoline - All Grades Gasoline: Regular Unleaded Gasoline: Conventional Regular Unleaded Gasoline: Mid Synonym: Grade Unleaded Gasoline: Conventional Mid Grade Unleaded Gasoline: Premium Unleaded Gasoline: Conventional Premium Unleaded Gasoline: Sub-Octane Gasoline: Regular RBOB; Super RBOB; Premium RBOB; RBOB; Reformulated Blend Stock For Oxygenated Blending; 84 Octane Gasoline; CBOB; Premium CBOB; Conventional Blend Stock for Oxygenate Blending; Recreational Gasoline; Recreational Gasoline; Recreational Unleaded Gasoline; 89 Recreational Gasoline; Brand 89 Recreational Gasoline; 7.0 Max RVP 89 Recreational Gasoline; BR 7.0 Max RVP 89 Recreational Gasoline; 90 Recreational Gasoline; 90 Marina Gasoline; Brand 91 Recreational Gasoline; 91 Recreational Gasoline; 91 Marina Gasoline; 90 Octane Midgrade Gasoline with No Ethanol; 0125MAR019; 0126MAR019; 0134MAR019; 0313MAR019; 0314MAR019 **Product Code:** 0127MAR019 **Chemical Family:** Complex Hydrocarbon Substance **Recommended Use:** Fuel. **Restrictions on Use:** All others.

Manufacturer, Importer, or Responsible Party Name and Address: MARATHON PETROLEUM COMPANY LP 539 South Main Street Findlay, OH 45840

SDS information (M-F, 8-5 PM EST): 1-419-421-3070

Emergency Telephone (24/7):

CHEMTREC: 1-800-424-9300 CCN#: 13740

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 1
Skin corrosion/irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Acute aquatic toxicity	Category 2
Chronic aquatic toxicity	Category 2

Hazards Not Otherwise Classified (HNOC)

Static accumulating flammable liquid

Label elements

EMERGENCY OVERVIEW

Danger

EXTREMELY FLAMMABLE LIQUID AND VAPOR May accumulate electrostatic charge and ignite or explode May be fatal if swallowed and enters airways Causes skin irritation May cause respiratory irritation May cause drowsiness or dizziness May cause genetic defects May cause cancer Suspected of damaging fertility or the unborn child Causes damage to organs (blood, blood-forming organs, immune system) through prolonged or repeated exposure Toxic to aquatic life with long lasting effects Appearance Clear yellow liquid Physical State Liquid Odor Hydrocarbon

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof electrical/ventilating/lighting/equipment Use only non-sparking tools. Take action to prevent static discharges Do not eat, drink or smoke when using this product Do not breathe mist/vapors/spray Use only outdoors or in a well-ventilated area Wear protective gloves/protective clothing/eye protection/face protection Wash hands and any possibly exposed skin thoroughly after handling Avoid release to the environment

Precautionary Statements - Response

IF exposed, concerned or you feel unwell: Get medical attention IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower If skin irritation occurs: Get medical attention Wash contaminated clothing before reuse IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor if you feel unwell IF SWALLOWED: Immediately call a POISON CENTER or doctor Do NOT induce vomiting In case of fire: Use water spray, fog or regular foam for extinction Collect spillage

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed Keep cool Store locked up

Precautionary Statements - Disposal

Dispose of contents/container at an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Gasoline is a complex combination of hydrocarbons consisting of paraffins, cycloparaffins, aromatic and olefinic hydrocarbons having molecular chains ranging in length from four to ten carbons. May contain small amounts of dye and other additives (>0.02%) which are not considered hazardous at the concentrations used.

Composition Information:

Name	CAS Number	% Concentration
Gasoline	86290-81-5	100
Heptane (mixed isomers)	142-82-5	2.5-26
Butane (mixed isomers)	106-97-8	0.5-19
Pentane (mixed isomers)	78-78-4	6.5-19
Hexane Isomers (other than n-Hexane)	107-83-5	2-12
Toluene	108-88-3	3-9.5
Xylene (mixed isomers)	1330-20-7	3.5-9.5
Benzene	71-43-2	0.1-4.9
n-Hexane	110-54-3	0.1-4.5
Cumene	98-82-8	0-4
1,2,4 Trimethylbenzene	95-63-6	1-4
Ethylbenzene	100-41-4	0.5-2.5
Cyclohexane	110-82-7	0-1.5
Octane	111-65-9	0-1.5
1,2,3-Trimethylbenzene	526-73-8	0-1
Naphthalene	91-20-3	0.1-0.5

Benzene concentration is percent by volume. All other concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume.

4. FIRST AID MEASURES

First Aid Measures

General Advice:	In case of accident or if you feel unwell, seek medical advice immediately (show directions for use or safety data sheet if possible).
Inhalation:	Remove to fresh air. If not breathing, institute rescue breathing. If breathing is difficult, ensure airway is clear, give oxygen and continue to monitor. If heart has stopped, immediately begin cardiopulmonary resuscitation (CPR). Keep affected person warm and at rest. If symptoms occur get medical attention.
Skin Contact:	Immediately wash exposed skin with plenty of soap and water while removing contaminated clothing and shoes. May be absorbed through the skin in harmful amounts. Get medical attention if irritation persists. Any injection injury from high pressure equipment should be evaluated immediately by a physician as potentially serious (See NOTES TO PHYSICIAN).
	Place contaminated clothing in closed container until cleaned or discarded. If clothing is to be laundered, inform the person performing the operation of contaminant's hazardous properties. Destroy contaminated, non-chemical resistant footwear.
Eye Contact:	Flush immediately with large amounts of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Gently remove contacts while flushing. Get medical attention if irritation persists.

Ingestion:	Do not induce vomiting because of danger of aspirating liquid into lungs, causing serious damage and chemical pneumonitis. If spontaneous vomiting occurs, keep head below hips, or if patient is lying down, turn body and head to side to prevent aspiration and monitor for breathing difficulty. Never give anything by mouth to an unconscious person. Keep affected person warm and at rest. GET IMMEDIATE MEDICAL ATTENTION.
Most important signs and symptom	s, both short-term and delayed with overexposure
Adverse Effects:	Irritating to the skin and mucous membranes. Symptoms may include redness, itching, and inflammation. May cause nausea, vomiting, diarrhea, and signs of nervous system depression: headache, drowsiness, dizziness, loss of coordination, disorientation and fatigue. Aspiration hazard. May cause coughing, chest pains, shortness of breath, pulmonary edema and/or chemical pneumonitis. Prolonged or repeated exposure may cause adverse effects on blood, blood-forming organs, and immune system. Repeated or prolonged skin contact may cause drying, reddening, itching and cracking.
Indication of any immediate medica	I attention and special treatment needed
Notes To Physician:	INHALATION: This material (or a component) sensitizes the myocardium to the effects of sympathomimetic amines. Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in individuals exposed to this material. Administration of sympathomimetic drugs should be avoided.
	SKIN: Leaks or accidents involving high-pressure equipment may inject a stream of material through the skin and initially produce an injury that may not appear serious. Only a small puncture wound may appear on the skin surface but, without proper treatment and depending on the nature, original pressure, volume, and location of the injected material, can compromise blood supply to an affected body part. Prompt surgical debridement of the wound may be necessary to prevent irreversible loss of function and/or the affected body part. High pressure injection injuries may be SERIOUS SURGICAL EMERGENCIES.
	INGESTION: This material represents a significant aspiration and chemical pneumonitis hazard. Induction of emesis is not recommended.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

For small fires, Class B fire extinguishing media such as CO2, dry chemical, foam (AFFF/ATC) or water spray can be used. For large fires, water spray, fog or foam (AFFF/ATC) can be used. Firefighting should be attempted only by those who are adequately trained and equipped with proper protective equipment.

Unsuitable extinguishing media

Do not use straight water streams to avoid spreading fire.

Specific hazards arising from the chemical

This product has been determined to be an extremely flammable liquid per the OSHA Hazard Communication Standard and should be handled accordingly. May accumulate electrostatic charge and ignite or explode. Vapors may travel along the ground or be moved by ventilation and ignited by many sources such as pilot lights, sparks, electric motors, static discharge, or other ignition sources at locations distant from material handling. Flashback can occur along vapor trail. For additional fire related information, see NFPA 30 or the Emergency Response Guidebook 128.

Hazardous combustion products

Smoke, carbon monoxide, and other products of incomplete combustion.

Explosion data Sensitivity to Mechanical Impact No. Sensitivity to Static Discharge Yes.

Special protective equipment and precautions for firefighters

Firefighters should wear full protective clothing and positive-pressure self-contained breathing apparatus (SCBA) with a full

face-piece, as appropriate. Avoid using straight water streams. Water may be ineffective in extinguishing low flash point fires, but can be used to cool exposed surfaces. Avoid excessive water spray application. Water spray and foam (AFFF/ATC) must be applied carefully to avoid frothing and from as far a distance as possible. Keep run-off water out of sewers and water sources.

Additional firefighting tactics

FIRES INVOLVING TANKS OR CAR/TRAILER LOADS: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Cool containers with flooding quantities of water until well after the fire is out. Do not direct water at source of leak or safety devices; icing may occur. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. ALWAYS stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles: if this is impossible, withdraw from area and let fire burn.

EVACUATION: Consider initial downwind evacuation for at least 1000 feet. If tank, rail car or tank truck is involved in a fire, ISOLATE for 5280 feet (1 mile) in all directions; also, consider initial evacuation of 5280 feet (1 mile) in all directions.

<u>NFPA</u>	Health 1	Flammability 3	Instability 0	Special Hazard -
	6. A			6
Personal precaution	ons:	Keep public away. Isolate and evacuate area. Shut off source if safe to do so. Eliminate all ignition sources.		
Protective equipm	ent:	Use personal protection measures as recommended in Section 8.		
Emergency procee	dures:	Advise authorities and National Response Center (800-424-8802) if the product has entered a water course or sewer. Notify local health and pollution control agencies, if appropriate.		
Environmental pre	ecautions:	Avoid release to the environment. Avoid subsoil penetration. Ethanol in gasoline phase seperates in contact with water. Monitor downstream for dissolved ethanol or other appropriate indicators.		
Methods and mate containment:	erials for	Contain liquid with sand or soil. Prevent spilled material from entering storm drains, sewers, and open waterways.		
Methods and mate up:	erials for cleaning	Use suitable absorbent materials s liquids. Recover and return free pr ensure all equipment is grounded	such as vermiculite, sar oduct to proper contain and bonded. Use only r	nd, or clay to clean up residual ers. When recovering free liquids non-sparking tools.
		7. HANDLING AND	STORAGE	
Safe Handling Pre	cautions:	NEVER SIPHON THIS PRODUCT practices. Static accumulating flam to eliminate the hazard from static oxidizers or other sources of ignitic ventilation. Flashback may occur a tools. Avoid contact with skin, eye Use only with adequate ventilation personal protection measures as r hygiene including removal of soile not cut, drill, grind or weld on emp to applicable EPA, OSHA, NFPA a	[•] BY MOUTH. Use approximable liquid. Bonding a electricity. Do not expo on. Vapors may travel a along vapor trails. No sr s and clothing. Avoid br . Avoid repeated and pr ecommended in Sectio d clothing and prompt v ty containers since expl and consistent state and	ropriate grounding and bonding and grounding may be insufficient se to heat, open flames, strong long the ground or be moved by noking. Use only non-sparking eathing fumes, gas, or vapors. rolonged skin contact. Use n 8. Exercise good personal vashing with soap and water. Do osive residues may remain. Refer d local requirements.
		Hydrocarbons are basically non-co- charged during mixing, filtering, pu- operations. If this charge reaches the vapors of flammable liquids. S from process equipment operating ingress of air into vacuum equipment presence of obvious ignition source	onductors of electricity a imping at high flow rate a sufficiently high level oudden release of hot of under elevated temper ent may result in ignition es. Nozzle spouts mus	and can become electrostatically s or loading and transfer , sparks can form that may ignite rganic chemical vapors or mists rature and pressure, or sudden n of vapors or mists without the t be kept in contact with the

containers or tank during the entire filling operation.

Portable containers should never be filled while in or on a motor vehicle or marine craft. Containers should be placed on the ground. Static electric discharge can ignite fuel vapors when filling non-grounded containers or vehicles on trailers. The nozzle spout must be kept in contact with the container before and during the entire filling operation. Use only approved containers.

A buildup of static electricity can occur upon re-entry into a vehicle during fueling especially in cold or dry climate conditions. The charge is generated by the action of dissimilar fabrics (i.e., clothing and upholstery) rubbing across each other as a person enters/exits the vehicle. A flash fire can result from this discharge if sufficient flammable vapors are present. Therefore, do not get back in your vehicle while refueling.

Cellular phones and other electronic devices may have the potential to emit electrical charges (sparks). Sparks in potentially explosive atmospheres (including fueling areas such as gas stations) could cause an explosion if sufficient flammable vapors are present. Therefore, turn off cellular phones and other electronic devices when working in potentially explosive atmospheres or keep devices inside your vehicle during refueling.

High-pressure injection of any material through the skin is a serious medical emergency even though the small entrance wound at the injection site may not initially appear serious. These injection injuries can occur from high-pressure equipment such as paint spray or grease or guns, fuel injectors, or pinhole leaks in hoses or hydraulic lines and should all be considered serious. High pressure injection injuries may be SERIOUS SURGICAL EMERGENCIES (See First Aid Section 4).

Storage Conditions:Store in properly closed containers that are appropriately labeled and in a cool,
well-ventilated area. Do not store near an open flame, heat or other sources of ignition.

Incompatible Materials

Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	ACGIH TLV	OSHA PELS:	OSHA - Vacated PELs	NIOSH IDLH
Gasoline 86290-81-5	300 ppm TWA 500 ppm STEL	-	300 ppm TWA 900 mg/m ³ TWA 500 ppm STEL 1500 mg/m ³ STEL	-
Heptane (mixed isomers) 142-82-5	400 ppm TWA 500 ppm STEL	TWA: 500 ppm TWA: 2000 mg/m³	400 ppm TWA 1600 mg/m ³ TWA 500 ppm STEL 2000 mg/m ³ STEL	750 ppm
Butane (mixed isomers) 106-97-8	1000 ppm STEL	-	800 ppm TWA 1900 mg/m³ TWA	-
Pentane (mixed isomers) 78-78-4	1000 ppm TWA	-	-	-
Hexane Isomers (other than n-Hexane) 107-83-5	500 ppm TWA 1000 ppm STEL	-	500 ppm TWA 1800 mg/m³ TWA 1000 ppm STEL 3600 mg/m³ STEL	-
Toluene 108-88-3	20 ppm TWA	TWA: 200 ppm Ceiling: 300 ppm	100 ppm TWA 375 mg/m³ TWA 150 ppm STEL 560 mg/m³ STEL	500 ppm
Xylene (mixed isomers) 1330-20-7	100 ppm TWA 150 ppm STEL	TWA: 100 ppm TWA: 435 mg/m³	100 ppm TWA 435 mg/m³ TWA 150 ppm STEL 655 mg/m³ STEL	900 ppm
Benzene 71-43-2	0.5 ppm TWA 2.5 ppm STEL	TWA: 10 ppm (applies to industry segments exempt	25 ppm Ceiling 1 ppm TWA	500 ppm

	Skin - potential significant contribution to overall exposure by the cutaneous route	from the benzene standard) TWA: 1 ppm STEL: 5 ppm (see 29 CFR 1910.1028)	5 ppm STEL	
n-Hexane 110-54-3	50 ppm TWA Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 500 ppm TWA: 1800 mg/m³	50 ppm TWA 180 mg/m³ TWA	1100 ppm
Cumene 98-82-8	50 ppm TWA	TWA: 50 ppm TWA: 245 mg/m ³ Skin	50 ppm TWA 245 mg/m³ TWA Limit applies to skin	900 ppm
1,2,4 Trimethylbenzene 95-63-6	25 ppm TWA	-	25 ppm TWA 125 mg/m³ TWA	-
Ethylbenzene 100-41-4	20 ppm TWA	TWA: 100 ppm TWA: 435 mg/m ³	100 ppm TWA 435 mg/m³ TWA 125 ppm STEL 545 mg/m³ STEL	800 ppm
Cyclohexane 110-82-7	100 ppm TWA	TWA: 300 ppm TWA: 1050 mg/m ³	300 ppm TWA 1050 mg/m³ TWA	1300 ppm
Octane 111-65-9	300 ppm TWA	TWA: 500 ppm TWA: 2350 mg/m ³	300 ppm TWA 1450 mg/m³ TWA 375 ppm STEL 1800 mg/m³ STEL	1000 ppm
1,2,3-Trimethylbenzene 526-73-8	25 ppm TWA	-	25 ppm TWA 125 mg/m³ TWA	-
Naphthalene 91-20-3	10 ppm TWA Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 10 ppm TWA: 50 mg/m³	10 ppm TWA 50 mg/m³ TWA 15 ppm STEL 75 mg/m³ STEL	250 ppm
Notes:	The manufacturer 1989 air contamin were vacated in 19	has voluntarily elected to ants standard in its SDS 992.	o provide exposure limits s, even though certain of	contained in OSHA's those exposure limits
Engineering measures:	Local or general e ventilation. Use m	xhaust required in an en- echanical ventilation equ	closed area or when ther ipment that is explosion-	e is inadequate proof.
Personal protective equipme	<u>nt</u>			
Eye protection:	Use goggles or fac	ce-shield if the potential f	or splashing exists.	
Skin and body protection:	Use nitrile rubber, suitability is based specific advice on	Viton® or PVA gloves fo on workplace conditions glove selection and brea	r repeated or prolonged s and usage. Contact the akthrough times.	skin exposure. Glove glove manufacturer for
Respiratory protection:	Use a NIOSH app there is the potent excessive vapors criteria cited in fec be used for fire fig	roved organic vapor che ial for airborne exposure are generated. Observe leral OSHA 29 CFR 1910 hting.	mical cartridge or supplie s to exceed permissible of respirator assigned prote 0.134. Self-contained bre	ed air respirators when exposure limits or if ection factors (APFs) athing apparatus should
Hygiene measures:	Handle in accorda skin, eyes and clo	nce with good industrial thing.	hygiene and safety pract	ice. Avoid contact with

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties		
Physical State	Liquid	
Appearance	Clear yellow liquid	
Color	Yellow	

Odor Odor Threshold	Hydrocarbon No data available.
<u>Property</u> Melting Point / Freezing Point Initial Boiling Point / Boiling Range Flash Point Evaporation Rate	Values (Method) No data available. 24-210 °C / 75-410 °F (ASTM D86) -43 °C / -45 °F No data available.
Flammability (solid, gas)	Not applicable.
Upper Flammability Limit:	7.6
Explosion limits:	No data available.
Vapor Pressure	5.5-15 psi (ASTM D4814)
vapor Density Specific Gravity / Relative Density	3-4 0.70-0.76
Water Solubility	No data available.
Solubility in other solvents	No data available.
Partition Coefficient	2.13-4.5 No data available
pH:	Not applicable
Autoignition Temperature	280 °C / 536 °F
Kinematic Viscosity	No data available. No data available
Explosive Properties	No data available.
VOC Content (%)	100%
Density Bulk Density	No data available.
Durk Density	

10. STABILITY AND REACTIVITY

Reactivity	The product is non-reactive under normal conditions.
Chemical stability	The material is stable at 70°F (21°C), 760 mmHg pressure.
Possibility of hazardous reactions	None under normal processing.
Hazardous polymerization	Will not occur.
Conditions to avoid	Excessive heat, sources of ignition, open flame.
Incompatible Materials	Strong oxidizing agents.
Hazardous decomposition products	None known under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Potential short-term adverse effects from overexposures

Inhalation	May cause irritation of respiratory tract. May cause drowsiness or dizziness. Breathing high concentrations of this material in a confined space or by intentional abuse can cause irregular heartbeats which can cause death.
Eye contact	Exposure to vapor or contact with liquid may cause mild eye irritation, including tearing, stinging, and redness.
Skin contact	Irritating to skin. Effects may become more serious with repeated or prolonged contact. May be absorbed through the skin in harmful amounts.
Ingestion	May be fatal if swallowed or vomited and enters airways. May cause irritation of the mouth,

throat and gastrointestinal tract.

Acute toxicological data

Name	Oral LD50	Dermal LD50	Inhalation LC50
Gasoline 86290-81-5	14000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
Heptane (mixed isomers) 142-82-5	-	3000 mg/kg (Rabbit)	103 g/m³ (Rat) 4 h
Butane (mixed isomers) 106-97-8	-	-	658 mg/L (Rat) 4 h
Pentane (mixed isomers) 78-78-4	-	-	450 mg/L (Mouse) 2 h
Hexane Isomers (other than n-Hexane) 107-83-5	> 5000 mg/kg (Rat)	-	-
Toluene 108-88-3	> 2000 mg/kg (Rat)	8390 mg/kg (Rabbit)	12.5 mg/L (Rat) 4 h
Xylene (mixed isomers) 1330-20-7	> 2000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.04 mg/L (Rat) 4 h
Benzene 71-43-2	> 2000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	> 20 mg/l (Rat) 4 h
n-Hexane 110-54-3	15000 mg/kg (Rat)	3000 mg/kg (Rabbit)	48000 ppm (Rat) 4 h
Cumene 98-82-8	> 2000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 20 mg/L (Rat) 6 h
1,2,4 Trimethylbenzene 95-63-6	3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	18,000 mg/m³ (Rat) 4 h
Ethylbenzene 100-41-4	> 2000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	17.2 mg/L (Rat) 4 h
Cyclohexane 110-82-7	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	13.9 mg/L (Rat) 4 h
Octane 111-65-9	-	-	118 g/m³ (Rat) 4 h
1,2,3-Trimethylbenzene 526-73-8	-	-	-
Naphthalene 91-20-3	490 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 340 mg/m³ (Rat) 1 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

NAPHTHAS: In a large epidemiological study on over 15,000 employees at several petroleum refineries and amongst residents located near these refineries, no increased risk of kidney cancer was observed in association with gasoline exposures (a similar material). In a similar study, no increased risk of kidney cancer was observed among petroleum refinery workers, but there was a slight trend in the incidence of kidney cancers among service station employees, especially after a 30-year latency period. Altered mental state, drowsiness, peripheral motor neuropathy, irreversible brain damage (so-called Petrol Sniffer's Encephalopathy), delirium, seizures, and sudden death have been reported from repeated overexposure to some hydrocarbon solvents, naphthas, and gasoline.

ISOPARAFFINS: Studies in laboratory animals have shown that long-term exposure to similar materials (isoparaffins) can cause kidney damage and kidney cancer in male laboratory rats. However, in-depth research indicates that these findings are unique to the male rat, and that these effects are not relevant to humans.

C9 AROMATIC HYDROCARBONS: A developmental inhalation study was conducted in laboratory mice. Increased implantation losses, reduced fetal weights, delayed ossification and an increased incidence of cleft palate were observed at the highest exposure level (1,500 ppm). This exposure level was extremely toxic to pregnant female mice (44% mortality). Reduced fetal body weights were also observed at 500 ppm. A multi-generation reproduction inhalation study was conducted in laboratory rats. Reductions in pup weights, pup weight gain, litter size, and pup survival were observed at

1,500 ppm, an exposure level at which significant maternal toxicity was observed. Reduced pup weight gain was also observed at 500 ppm.

BUTANES: Studies in laboratory animals indicate exposure to extremely high levels of butanes (1-10 or higher vol.% in air) may cause cardiac arrhythmias (irregular heartbeats) which may be serious or fatal.

PENTANES: Studies of pentane isomers in laboratory animals indicate exposure to extremely high levels (roughly 10 vol.%) may induce cardiac arrhythmias (irregular heartbeats) which may be serious or fatal.

TOLUENE: Case studies of persons abusing toluene suggest isolated incidences of adverse effects on the fetus including birth defects. Abuse of toluene at high concentrations (e.g., glue sniffing and solvent abuse) has been associated with adverse effects on the liver, kidney and nervous system, and can cause CNS depression, cardiac arrhythmias, and death. Studies of workers indicate longterm exposure may be related to impaired color vision and hearing. Some studies of workers suggest longterm exposure may be related to neurobehavioral and cognitive changes. Some of these effects have been observed in laboratory animals following repeated exposure to high levels of toluene. Several studies of workers suggest longterm exposure may be related to small increases in spontaneous abortions and changes in some gonadotropic hormones. However, the weight of evidence does not indicate toluene is a reproductive hazard to humans. Studies in laboratory animals indicate some changes in reproductive organs following high levels of exposure, but no significant effects on mating performance or reproduction were observed. Case studies of persons abusing toluene suggest isolated incidences of adverse effects on the fetus including birth defects. Findings in laboratory animals have been largely negative. Positive findings include small increases in minor skeletal and visceral malformations and developmental delays following very high levels of maternal exposure. Studies of workers indicate long-term exposure may be related to effects on the liver, kidney and blood, but these appear to be limited to changes in serum enzymes and decreased leukocyte counts. Adverse effects on the liver, kidney, thymus and nervous system were observed in animal studies following very high levels of exposure. The relevance of these findings to humans is not clear at this time.

XYLENES, ALL ISOMERS: Overexposure to xylene may cause upper respiratory tract irritation, headache, cyanosis, blood serum changes, nervous system damage and narcosis. Effects may be increased by the use of alcoholic beverages. Evidence of liver and kidney impairment were reported in workers recovering from a gross overexposure. Effects from Prolonged or Repeated Exposure: Impaired neurological function was reported in workers exposed to solvents including xylene. Studies in laboratory animals have shown evidence of impaired hearing following high levels of exposure. Studies in laboratory animals suggest some changes in reproductive organs following high levels of exposure but no significant effects on reproduction were observed. Studies in laboratory animals indicate skeletal and visceral malformations, developmental delays, and increased fetal resorptions following extremely high levels of maternal exposure with evidence of maternal toxicity. The relevance of these observations to humans is not clear at this time. Adverse effects on the liver, kidney, bone marrow (changes in blood cell parameters) were observed in laboratory animals following high levels of exposure. The relevance of these observations to humans is not clear at this time.

BENZENE: Studies of workers exposed to benzene show clear evidence that overexposure can cause cancer and other diseases of the blood forming organs including Acute Myelogenous Leukemia (AML), and Aplastic Anemia (AA), an often fatal disease. Some studies suggest overexposure to benzene may also be associated with Myelodysplastic Syndrome (MDS). Findings from a case control study of workers exposed to benzene was reported during the 2009 Benzene Symposium in Munich included an increase in Acute Myeloid Leukemias and Non-Hodgkins Lymphoid Neoplasms (NHLN) of the subtype follicular lymphoma (FL) in some occupational categories. Some studies of workers exposed to benzene have shown an association with increased rates of chromosome aberrations in circulating lymphocytes. One study of women workers exposed to benzene suggested a weak association with irregular menstruation. However, other studies of

workers exposed to benzene have not demonstrated clear evidence of an effect on fertility or reproductive outcome in humans. Benzene can cross the placenta and affect the developing fetus. Cases of AA have been reported in the offspring of persons severely overexposed to benzene. Studies in laboratory animals indicate that prolonged, repeated exposure to high levels of benzene vapor can cause bone marrow suppression and cancer in multiple organ systems. Studies in laboratory animals show evidence of adverse effects on male reproductive organs following high levels of exposure but no significant effects on reproduction have been observed. Embryotoxicity has been reported in studies of laboratory animals but effects were limited to reduced fetal weight and minor skeletal variations. Benzene has been classified as a proven human carcinogen by OSHA and a Group 1 (Carcinogenic to Humans) material by IARC. The current proposed IARC classification for benzene is summarized as follows: Sufficient evidence for Acute Myeloid Leukemia; limited evidence for Acute Lymphatic Leukemia, Chronic Lymphatic Leukemia, Non-Hodgkin Lymphoma, and Multiple Myeloma.

N-HEXANE: Long-term or repeated exposure to n-hexane can cause peripheral nerve damage. Initial symptoms are numbness of the fingers and toes. Also, motor weakness can occur in the digits, but may also involve muscles of the arms, thighs and forearms. The onset of these symptoms may be delayed for several months to a year after the beginning of exposure. Testicular atrophy and partial to full loss of the germ cell line were observed in sub-chronic high-dose inhalation studies of laboratory rodents. These effects appeared irreversible. Rodent reproduction studies have shown evidence of reduced fetal weight but no frank malformations.

CUMENE: Overexposure to cumene may cause upper respiratory tract irritation and CNS depression. Studies in laboratory animals indicate evidence of respiratory tract hyperplasia, and adverse effects on the liver, kidney and adrenal glands following high level exposure. The relevance of these findings to humans is not clear at this time. Findings from lifetime laboratory rodent inhalation studies were as follows: In F344/N rats: an increased incidence of renal carcinomas and adenomas, respiratory epithelial adenomas, and interstitial cell adenomas of the testes. In B6C3F1 mice: an increased incidence of carcinomas and adenomas of the bronchi and lung, liver neoplasms, hemangiosarcomas of the spleen, and adenomas of the thyroid.

1,2,4-TRIMETHYLBENZENE: The following information pertains to a mixture of C9 aromatic hydrocarbons, over 40% of which was composed of 1,2,4-trimethylbenzene. A developmental inhalation study was conducted in laboratory mice. Increased implantation losses, reduced fetal weights, delayed ossification and an increased incidence of cleft palate were observed at the highest exposure level (1,500 ppm). This exposure level was extremely toxic to pregnant female mice (44% mortality). Reduced fetal body weights were also observed at 500 ppm. A multi-generation reproduction inhalation study was conducted in laboratory rats. Reductions in pup weights, pup weight gain, litter size, and pup survival were observed at 1,500 ppm, an exposure level at which significant maternal toxicity was observed. Reduced pup weight gain was also observed at 500 ppm. Embryotoxicity has been reported in studies of laboratory animals. Adverse effects included increased implantation losses, reduced fetal weights, delayed ossification and an increased incidence of cleft palate.<n><n>

ETHYLBENZENE: Findings from a 2-year inhalation study in rodents conducted by NTP were as follows: Effects were observed only at the highest exposure level (750 ppm). At this level the incidence of renal tumors was elevated in male rats (tubular carcinomas) and female rats (tubular adenomas). The incidence of tumors was also elevated in male mice (alveolar and bronchiolar carcinomas) and female mice (hepatocellular carcinomas). IARC has classified ethyl benzene as "possibly carcinogenic to humans" (Group 2B). Studies in laboratory animals indicate some evidence of post-implantation deaths following high levels of maternal exposure. The relevance of these findings to humans is not clear at this time. Studies in laboratory animals indicate limited evidence of renal malformations, resorptions, and developmental delays following high levels of maternal exposure with evidence of maternal toxicity. The relevance of these findings to humans is not clear at this time. Studies in laboratory animals have demonstrated evidence of ototoxicity (hearing loss) following exposure levels as low as 300 ppm for 5 days. Studies in laboratory animals

indicate some evidence of adverse effects on the liver, kidney, thyroid, and pituitary gland.

	NAPHTHALENE: Severe jaundice, neurotoxicity (kernicterus) and fatalities have been reported in young children and infants as a result of hemolytic anemia from overexposure to naphthalene. Persons with glucose 6-phosphate dehydrogenase (G6PD) deficiency are more prone to the hemolytic effects of naphthalene. Adverse effects on the kidney have been reported in persons overexposed to naphthalene but these effects are believed to be a consequence of hemolytic anemia, and not a direct effect. Hemolytic anemia has been observed in laboratory animals exposed to naphthalene. Laboratory rodents exposed to naphthalene vapor for 2 years (lifetime studies) developed non-neoplastic and neoplastic tumors and inflammatory lesions of the nasal and respiratory tract. Cataracts and other adverse effects on the eye have been observed in laboratory animals exposed to high levels of naphthalene. Findings from a large number of bacterial and mammalian cell mutation assays have been negative. A few studies have shown chromosomal effects (elevated levels of Sister Chromatid Exchange or chromosomal aberrations) in vitro. Naphthalene has been classified as Possibly Carcinogenic to Humans (2B) by IARC, based on findings from studies in laboratory animals.
	CARBON MONOXIDE: is a chemical asphyxiant with no warning properties (such as odor). At 400-500 ppm for 1 hour headache and dyspnea may occur. If activity is increased, symptoms of overexposure may include nausea, irritability, increased respiration, tinnitus, sweating, chest pain, confusion, impaired judgement, dizziness, weakness, drowsiness, ataxia, irregular heart beat, cyanosis and pallor. Levels in excess of 1000 ppm can result in collapse, loss of conciousness, respiratory failure and death. Extremely high concentrations (12,800 ppm) can cause immediate unconsciousness and death in 1-3 minutes. Repeated anoxia can lead to central nervous system damage and peripheral neuropathy, with loss of sensation in the fingers, amnesia, and mental deterioration and possible congestive heart failure. Damage may also occur to the fetus, lung, liver, kidney, spleen, cardiovascular system and other organs.
	WHOLLY-VAPORIZED UNLEADED GASOLINE: Lifetime exposure to wholly vaporized unleaded gasoline produced an increased incidence of liver tumors in female mice exposed to the highest exposure concentration (2056 ppm) and α -2 urinary globulin-mediated kidney tumors in male rats. No exposure-related tumors were observed in male mice or female rats. The male-specific rat kidney tumors are not considered relevant to human health. Mice receiving lifetime repeated skin application of various petroleum naphthas exhibited an irritation-dependent increased incidence of skin tumors. Additional studies suggest that these tumors occur through a mechanism that may not be relevant to human health. Epidemiological data from over 18,000 petroleum marketing and distribution workers showed no increased risk of leukemia, multiple myeloma, or kidney cancer resulting from gasoline exposure. Unleaded gasoline has been identified as possibly carcinogenic to humans (2B) by the International Agency for Research on Cancer (IARC).
	COMBUSTION ENGINE EXHAUST: Chronic inhalation studies of gasoline engine exhaust in mice, rats and hamsters did not produce any carcinogenic effects. Condensates/extracts of gasoline engine exhaust produced an increase in tumors compared to controls when testing by skin painting, subcutaneous injection, intratracheal instillation or implantation into the lungs. Gasoline exhaust has been classified as possibly carcinogenic to humans (2B) by the International Agency for Research on Cancer (IARC).
Adverse effects related to the physic	cal, chemical and toxicological characteristics
Signs and Symptoms	Irritating to the skin and mucous membranes. Symptoms may include redness, itching, and inflammation. May cause nausea, vomiting, diarrhea, and signs of nervous system depression: headache, drowsiness, dizziness, loss of coordination, disorientation and fatigue. Aspiration hazard. May cause coughing, chest pains, shortness of breath, pulmonary edema and/or chemical pneumonitis. Prolonged or repeated exposure may cause damage to organs. Repeated or prolonged skin contact may cause drying, reddening, itching and cracking.
Sensitization	Not expected to be a skin or respiratory sensitizer.

Mutagenic effects

May cause genetic defects.

May cause cancer.

Carcinogenicity

Cancer designations are listed in the table below

Name	ACGIH (Class)	IARC (Class)	NTP	OSHA
Gasoline 86290-81-5	Confirmed animal carcinogen (A3)	Possible human carcinogen (2B)	Not Listed	Not Listed
Heptane (mixed isomers) 142-82-5	Not Listed	Not Listed	Not Listed	Not Listed
Butane (mixed isomers) 106-97-8	Not Listed	Not Listed	Not Listed	Not Listed
Pentane (mixed isomers) 78-78-4	Not Listed	Not Listed	Not Listed	Not Listed
Hexane Isomers (other than n-Hexane) 107-83-5	Not Listed	Not Listed	Not Listed	Not Listed
Toluene 108-88-3	Not Classifiable (A4)	Not Classifiable (3)	Not Listed	Not Listed
Xylene (mixed isomers) 1330-20-7	Not classifiable (A4)	Not classifiable (3)	Not Listed	Not Listed
Benzene 71-43-2	Confirmed human carcinogen (A1)	Carcinogenic to humans (1)	Known to be human carcinogen	Known carcinogen
n-Hexane 110-54-3	Not Listed	Not Listed	Not Listed	Not Listed
Cumene 98-82-8	Not listed	Possible human carcinogen (2B)	Reasonably anticipated to be a human carcinogen	Not listed
1,2,4 Trimethylbenzene 95-63-6	Not Listed	Not Listed	Not Listed	Not Listed
Ethylbenzene 100-41-4	Confirmed animal carcinogen (A3)	Possible human carcinogen (2B)	Not Listed	Not Listed
Cyclohexane 110-82-7	Not Listed	Not Listed	Not Listed	Not Listed
Octane 111-65-9	Not Listed	Not Listed	Not Listed	Not Listed
1,2,3-Trimethylbenzene 526-73-8	Not Listed	Not Listed	Not Listed	Not Listed
Naphthalene 91-20-3	Confirmed animal carcinogen (A3)	Possible human carcinogen (2B)	Reasonably anticipated to be a human carcinogen	Not Listed

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity (STOT) - single exposure

Blood. Blood-forming organs. Immune system.

Respiratory system. Central nervous system.

Specific Target Organ Toxicity (STOT) - repeated exposure

Aspiration hazard

May be fatal if swallowed or vomited and enters airways.

12. ECOLOGICAL INFORMATION

Ecotoxicity

This product should be considered toxic to aquatic organisms, with the potential to cause long lasting adverse effects in the aquatic environment.

Name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Gasoline	72-hr EC50 = 56 mg/l	96-hr LC50 = 11 mg/l	-	48-hr LC50 = 7.6 mg/l
86290-81-5	Algae	Rainbow trout (static)		Daphnia magna
Heptane (mixed isomers)	-	96-hr LC50 = 375 mg/L	-	-
142-82-5		Tilapia		
Butane (mixed isomers)	-	-	-	-

106-97-8				
Pentane (mixed isomers)	-	96-hr LC50 = 3.1 mg/L	-	48-hr EC50 = >1 - <10 mg/L
78-78-4		Rainbow trout		Daphnia magna
Hexane Isomers (other than	-	-	-	-
n-Hexane)				
107-83-5				
Toluene	72-hr EC50 = 12.5 mg/l	96-hr LC50 <= 10 mg/l	-	48-hr EC50 = 5.46-9.83 mg/l
108-88-3	Algae	Rainbow trout		Daphnia magna
	-			48-hr EC50 = 11.5 mg/l
				Daphnia magna (Static)
Xylene (mixed isomers)	72-hr EC50 = 11 mg/l	96-hr LC50 = 8 mg/l	-	48-hr LC50 = 3.82 mg/l
1330-20-7	Algae	Rainbow trout		Daphnia magna
Benzene	72-hr EC50 = 29 mg/l	96-hr LC50 = 5.3 mg/l	-	48-hr EC50 = 8.76-15.6 mg/l
71-43-2	Algae	Rainbow trout		Daphnia magna (Static)
		(flow-through)		,
n-Hexane	-	96-hr LC50 = 2.5 mg/l	-	-
110-54-3		Fathead minnow		
Cumene	72-hr EC50 = 2.6 mg/l	96-hr LC50 = 6.04-6.61 mg/l	-	48-hr EC50 = 7.9-14.1 mg/l
98-82-8	Algae	Fathead minnow		Daphnia magna (static)
		(Flow-through)		
		96-hr LC50 = 2.7 mg/l		
		Rainbow trout (semi-static)		
1,2,4 Trimethylbenzene	-	96-hr LC50 = 7.19-8.28 mg/l	-	48-hr EC50 = 6.14 mg/L
95-63-6		Fathead minnow		Daphnia magna
		(flow-through)		
Ethylbenzene	72-hr EC50 = 1.7-7.6 mg/l	96-hr LC50 = 4 mg/L	-	48-hr EC50 = 1-4 mg/L
100-41-4	Algae	Rainbow trout		Daphnia magna
Cyclohexane	72-hr EC50 = 500 mg/l	96-hr LC50 = 3.96-5.18 mg/l	-	48-hr EC50 = 1.7-3.5 mg/L
110-82-7	Algae	Fathead minnow		Bay shrimp
Octane	-	-	-	48-hr LC50 = 0.38 mg/l
111-65-9				Daphnia magna
1,2,3-Trimethylbenzene	-	96-hr LC50 = 7.72 mg/l	-	-
526-73-8		Fathead Minnow		
		(flow-through)		
Naphthalene	-	96-hr LC50 = 0.91-2.82 mg/l	-	48-hr LC50 = 1.6 mg/l
91-20-3		Rainbow trout (static)		Daphnia magna
		96-hr LC50 = 1.99 mg/l		
		Fathead minnow (static)		

Persistence and degradability	Expected to be inherently biodegradable. The presence of ethanol in this product may impede the biodegradation of benzene, toluene, ethylbenzene and xylene in groundwater, resulting in elongated plumes of these constituents.
Bioaccumulation	Has the potential to bioaccumulate.
Mobility in soil	May partition into air, soil and water.
Other adverse effects	No information available.

13. DISPOSAL CONSIDERATIONS

Description of Waste Residues

This material may be a flammable liquid waste.

Safe Handling of Wastes

Handle in accordance with applicable local, state, and federal regulations. Use personal protection measures as required. Use appropriate grounding and bonding practices. Use only non-sparking tools. Do not expose to heat, open flames, strong oxidizers or other sources of ignition. No smoking.

Disposal of Wastes / Methods of Disposal

The user is responsible for determining if any discarded material is a hazardous waste (40 CFR 262.11). Dispose of in accordance with federal, state and local regulations.

Methods of Contaminated Packaging Disposal

Empty containers should be completely drained and then discarded or recycled, if possible. Do not cut, drill, grind or weld on empty containers since explosive residues may be present. Dispose of in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT (49 CFR 172.101):	
UN Proper Shipping Name:	Gasoline
UN/Identification No:	UN 1203
Class:	3
Packing Group:	II
TDG (Canada):	
UN Proper Shipping Name:	Gasoline
UN/Identification No:	UN 1203
Transport Hazard Class(es):	3
Packing Group:	II

15. REGULATORY INFORMATION

US Federal Regulatory Information:

US TSCA Chemical Inventory Section 8(b):

This product and/or its components are listed on the TSCA Chemical Inventory.

EPA Superfund Amendment & Reauthorization Act (SARA):

SARA Section 302:

This product does not contain any component(s) included on EPA's Extremely Hazardous Substance (EHS) List.

Name	CERCLA/SARA - Section 302 Extremely Hazardous Substances and TPQs
Gasoline	NA
Heptane (mixed isomers)	NA
Butane (mixed isomers)	NA
Pentane (mixed isomers)	NA
Hexane Isomers (other than n-Hexane)	NA
Toluene	NA
Xylene (mixed isomers)	NA
Benzene	NA
n-Hexane	NA
Cumene	NA
1,2,4 Trimethylbenzene	NA
Ethylbenzene	NA
Cyclohexane	NA
Octane	NA
1,2,3-Trimethylbenzene	NA
Naphthalene	NA

SARA Section 304:

This product may contain component(s) identified either as an EHS or a CERCLA Hazardous substance which in case of a spill or release may be subject to SARA reporting requirements:

Name	Hazardous Substances RQs
Gasoline	NA
Heptane (mixed isomers)	NA
Butane (mixed isomers)	NA
Pentane (mixed isomers)	NA
Hexane Isomers (other than n-Hexane)	NA
Toluene	1000 lb final RQ
	454 kg final RQ

Xylene (mixed isomers)	100
Benzene	10
n-Hexane	5000
Cumene	5000
1,2,4 Trimethylbenzene	NA
Ethylbenzene	1000
Cyclohexane	1000
Octane	NA
1,2,3-Trimethylbenzene	NA
Naphthalene	100 lb final RQ
	45.4 kg final RQ

SARA Section 311/312:

The following EPA hazard categories apply to this product:

Acute Health Hazard Chronic Health Hazard Fire Hazard

SARA Section 313:

This product may contain component(s), which if in exceedance of the de minimus threshold, may be subject to the reporting requirements of SARA Title III Section 313 Toxic Release Reporting (Form R).

Name	CERCLA/SARA 313 Emission reporting:
Gasoline	None
Heptane (mixed isomers)	None
Butane (mixed isomers)	None
Pentane (mixed isomers)	None
Hexane Isomers (other than n-Hexane)	None
Toluene	1.0 % de minimis concentration
Xylene (mixed isomers)	1.0 % de minimis concentration
Benzene	0.1 % de minimis concentration
n-Hexane	1.0 % de minimis concentration
Cumene	1.0 % de minimis concentration
1,2,4 Trimethylbenzene	1.0 % de minimis concentration
Ethylbenzene	0.1 % de minimis concentration
Cyclohexane	1.0 % de minimis concentration
Octane	None
1,2,3-Trimethylbenzene	None
Naphthalene	0.1 % de minimis concentration

Not Listed Not Listed SN 0957 Present Present Not Listed Not Listed Not Listed Not Listed Not Listed Not Listed

State and Community Right-To-Know Regulations:

The following component(s) of this material are identified on the regulatory lists below:

Gasoline

Louisiana Right-To-Know:
California Proposition 65:
New Jersey Right-To-Know:
Pennsylvania Right-To-Know:
Massachusetts Right-To Know:
Florida Substance List:
Rhode Island Right-To-Know:
Michigan Critical Materials Register List:
Massachusetts Extraordinarily Hazardous Substances:
California - Regulated Carcinogens:
Pennsylvania RTK - Special Hazardous
Substances:
New Jersey - Special Hazardous Substances:
New Jersey - Environmental Hazardous
Substances List:

Carcinogen; Flammable - third degree

SN 0957 TPQ: 10000 lb (Under N.J.A.C. 7:1G, environmental hazardous substances in mixtures such as gasoline or new and used petroleum oil may be reported under these categories)

Illinois - Toxic Air Contaminants: New York - Reporting of Releases Part 597 -List of Hazardous Substances: Heptane (mixed isomers) Louisiana Right-To-Know: California Proposition 65: New Jersey Right-To-Know: Pennsylvania Right-To-Know: Massachusetts Right-To Know: Florida Substance List: Rhode Island Right-To-Know: Michigan Critical Materials Register List: Massachusetts Extraordinarily Hazardous Substances: California - Regulated Carcinogens: Pennsylvania RTK - Special Hazardous Substances: New Jersey - Special Hazardous Substances: New Jersey - Environmental Hazardous Substances List: Illinois - Toxic Air Contaminants: New York - Reporting of Releases Part 597 -List of Hazardous Substances: Butane (mixed isomers) Louisiana Right-To-Know: California Proposition 65: New Jersey Right-To-Know: Pennsylvania Right-To-Know: Massachusetts Right-To Know: Florida Substance List: Rhode Island Right-To-Know: Michigan Critical Materials Register List: Massachusetts Extraordinarily Hazardous Substances: California - Regulated Carcinogens: Pennsylvania RTK - Special Hazardous Substances: New Jersey - Special Hazardous Substances: New Jersey - Environmental Hazardous Substances List: Illinois - Toxic Air Contaminants: New York - Reporting of Releases Part 597 -List of Hazardous Substances: Pentane (mixed isomers) Louisiana Right-To-Know: California Proposition 65: New Jersev Right-To-Know: Pennsylvania Right-To-Know: Massachusetts Right-To Know: Florida Substance List: Rhode Island Right-To-Know: Michigan Critical Materials Register List: Massachusetts Extraordinarily Hazardous Substances: California - Regulated Carcinogens: Pennsylvania RTK - Special Hazardous Substances: New Jersey - Special Hazardous Substances: New Jersey - Environmental Hazardous Substances List: Illinois - Toxic Air Contaminants: New York - Reporting of Releases Part 597 -List of Hazardous Substances: Hexane Isomers (other than n-Hexane)

Not Listed Not Listed Not Listed SN 1339 Present Present Not Listed Toxic: Flammable Not Listed Not Listed Not Listed Not Listed Flammable - third degree Not Listed Not Listed Not Listed Not Listed Not Listed SN 0273 Present Present Not Listed Toxic: Flammable Not Listed Not Listed Not Listed Not Listed Flammable - fourth degree SN 0273 TPQ: 500 lb Not Listed Not Listed Not Listed Not Listed SN 1064 Present Present Not Listed Not Listed Not Listed Not Listed Not Listed Not Listed Flammable - fourth degree SN 1064 TPQ: 500 lb Not Listed Not Listed

Present

Louisiana Right-To-Know: California Proposition 65: New Jersey Right-To-Know: Pennsylvania Right-To-Know: Massachusetts Right-To Know: Florida Substance List: Rhode Island Right-To-Know: Michigan Critical Materials Register List: Massachusetts Extraordinarily Hazardous Substances: California - Regulated Carcinogens: Pennsylvania RTK - Special Hazardous Substances: New Jersey - Special Hazardous Substances: New Jersey - Environmental Hazardous Substances List: Illinois - Toxic Air Contaminants: New York - Reporting of Releases Part 597 -List of Hazardous Substances: Toluene Louisiana Right-To-Know: California Proposition 65: New Jersey Right-To-Know: Pennsylvania Right-To-Know: Massachusetts Right-To Know: Florida Substance List: Rhode Island Right-To-Know: Michigan Critical Materials Register List: Massachusetts Extraordinarily Hazardous Substances: California - Regulated Carcinogens: Pennsylvania RTK - Special Hazardous Substances: New Jersey - Special Hazardous Substances: New Jersey - Environmental Hazardous Substances List: Illinois - Toxic Air Contaminants: New York - Reporting of Releases Part 597 -List of Hazardous Substances: Xylene (mixed isomers) Louisiana Right-To-Know: California Proposition 65: New Jersey Right-To-Know: Pennsylvania Right-To-Know: Massachusetts Right-To Know: Florida Substance List: Rhode Island Right-To-Know: Michigan Critical Materials Register List: Massachusetts Extraordinarily Hazardous Substances: California - Regulated Carcinogens: Pennsylvania RTK - Special Hazardous Substances: New Jersey - Special Hazardous Substances: New Jersey - Environmental Hazardous Substances List: Illinois - Toxic Air Contaminants: New York - Reporting of Releases Part 597 -List of Hazardous Substances: Benzene Louisiana Right-To-Know: California Proposition 65:

Not Listed Not Listed SN 1285 Present Present Not Listed Not Listed Not Listed Not Listed Not Listed Not Listed Flammable - third degree Not Listed Not Listed Not Listed Not Listed Developmental toxicity, initial date 1/1/91 Female reproductive toxicity, initial date 8/7/09 SN 1866 Environmental hazard Present Not Listed Toxic (skin); Flammable (skin) 100 lb Annual usage threshold Not Listed Not Listed Not Listed Flammable - third degree; Teratogen SN 1866 TPQ: 500 lb Present 1000 lb RQ (air); 1 lb RQ (land/water) Not Listed Not Listed SN 2014 Environmental hazard Present Not Listed Toxic (skin); Flammable (skin) 100 lb Annual usage threshold all isomers Not Listed Not Listed Not Listed Flammable - third degree SN 2014 TPQ: 500 lb Present 1000 lb RQ (air); 1 lb RQ (land/water)

Not Listed Carcinogen, initial date 2/27/87 Developmental toxicity, initial date 12/26/97

New Jersey Right-To-Know: Pennsylvania Right-To-Know: Massachusetts Right-To Know: Florida Substance List: Rhode Island Right-To-Know: Michigan Critical Materials Register List: Massachusetts Extraordinarily Hazardous Substances: California - Regulated Carcinogens: Pennsylvania RTK - Special Hazardous Substances: New Jersey - Special Hazardous Substances: New Jersey - Environmental Hazardous Substances List: Illinois - Toxic Air Contaminants: New York - Reporting of Releases Part 597 -List of Hazardous Substances: n-Hexane Louisiana Right-To-Know: California Proposition 65: New Jersey Right-To-Know: Pennsylvania Right-To-Know: Massachusetts Right-To Know: Florida Substance List: Rhode Island Right-To-Know: Michigan Critical Materials Register List: Massachusetts Extraordinarily Hazardous Substances: California - Regulated Carcinogens: Pennsylvania RTK - Special Hazardous Substances: New Jersey - Special Hazardous Substances: New Jersey - Environmental Hazardous Substances List: Illinois - Toxic Air Contaminants: New York - Reporting of Releases Part 597 -List of Hazardous Substances: Cumene Louisiana Right-To-Know: California Proposition 65: New Jersey Right-To-Know: Pennsylvania Right-To-Know: Massachusetts Right-To Know: Florida Substance List: Rhode Island Right-To-Know: Michigan Critical Materials Register List: Massachusetts Extraordinarily Hazardous Substances: California - Regulated Carcinogens: Pennsylvania RTK - Special Hazardous Substances: New Jersey - Special Hazardous Substances: New Jersey - Environmental Hazardous Substances List: Illinois - Toxic Air Contaminants: New York - Reporting of Releases Part 597 -List of Hazardous Substances: 1,2,4 Trimethylbenzene Louisiana Right-To-Know: California Proposition 65: New Jersey Right-To-Know: Pennsylvania Right-To-Know: Massachusetts Right-To Know:

Male reproductive toxicity, initial date 12/26/97 SN 0197 Environmental hazard; Special hazardous substance Carcinogen; Extraordinarily hazardous Not Listed Toxic (skin); Flammable (skin); Carcinogen (skin) 100 lb Annual usage threshold Carcinogen; Extraordinarily hazardous Not Listed Present Carcinogen; Flammable - third degree; Mutagen SN 0197 TPQ: 500 lb Present 10 lb RQ (air); 1 lb RQ (land/water) Not Listed Not Listed SN 1340 Present Present Not Listed Toxic; Flammable Not Listed Not Listed Not Listed Not Listed Flammable - third degree SN 1340 TPQ: 500 lb Present 1 lb RQ (air); 1 lb RQ (land/water) Not Listed Carcinogen, initial date 4/6/10 SN 0542 Environmental hazard Present Not Listed Toxic (skin); Flammable (skin) Not Listed Not Listed Not Listed Not Listed Flammable - third degree SN 0542 TPQ: 500 lb Present 5000 lb RQ (air); 1 lb RQ (land/water) Not Listed Not Listed SN 1929 Present Present

Florida Substance List: Not Listed Rhode Island Right-To-Know: Toxic Michigan Critical Materials Register List: Not Listed Massachusetts Extraordinarily Hazardous Substances: Not Listed California - Regulated Carcinogens: Not Listed Pennsylvania RTK - Special Hazardous Not Listed Substances: New Jersey - Special Hazardous Substances: Not Listed New Jersey - Environmental Hazardous Not Listed Substances List: Illinois - Toxic Air Contaminants: Present New York - Reporting of Releases Part 597 -Not Listed List of Hazardous Substances: Ethylbenzene Louisiana Right-To-Know: Not Listed California Proposition 65: New Jersey Right-To-Know: SN 0851 Pennsylvania Right-To-Know: Massachusetts Right-To Know: Present Florida Substance List: Not Listed Rhode Island Right-To-Know: Michigan Critical Materials Register List: Not Listed Massachusetts Extraordinarily Hazardous Substances: Not Listed California - Regulated Carcinogens: Not Listed Pennsylvania RTK - Special Hazardous Not Listed Substances: New Jersey - Special Hazardous Substances: New Jersey - Environmental Hazardous Substances List: Illinois - Toxic Air Contaminants: Present New York - Reporting of Releases Part 597 -List of Hazardous Substances: Cyclohexane Louisiana Right-To-Know: Not Listed California Proposition 65: Not Listed New Jersey Right-To-Know: SN 0565 Pennsylvania Right-To-Know: Present Massachusetts Right-To Know: Florida Substance List: Not Listed Rhode Island Right-To-Know: Michigan Critical Materials Register List: Not Listed Massachusetts Extraordinarily Hazardous Substances: Not Listed California - Regulated Carcinogens: Not Listed Pennsylvania RTK - Special Hazardous Not Listed Substances: New Jersey - Special Hazardous Substances: New Jersey - Environmental Hazardous Substances List: Illinois - Toxic Air Contaminants: Not Listed New York - Reporting of Releases Part 597 -List of Hazardous Substances: Octane Louisiana Right-To-Know: Not Listed California Proposition 65: Not Listed New Jersey Right-To-Know: SN 1434 Pennsylvania Right-To-Know: Present Massachusetts Right-To Know: Present Florida Substance List: Not Listed Rhode Island Right-To-Know: Michigan Critical Materials Register List: Not Listed Massachusetts Extraordinarily Hazardous Substances: Not Listed

Carcinogen, initial date 6/11/04 Environmental hazard Toxic; Flammable Carcinogen; flammable - Third degree SN 0851 TPQ: 500 lb 1000 lb RQ (air); 1 lb RQ (land/water) Environmental hazard Toxic; Flammable Flammable - third degree SN 0565 TPQ: 500 lb 1000 lb RQ (air); 1 lb RQ (land/water) Toxic; Flammable

	California - Regulated Carcinogens: Pennsylvania RTK - Special Hazardous	Not Listed Not Listed
	Substances: New Jersey - Special Hazardous Substances: New Jersey - Environmental Hazardous	Flammable - third degree Not Listed
	Substances List: Illinois - Toxic Air Contaminants: New York - Reporting of Releases Part 597 -	Not Listed Not Listed
	List of Hazardous Substances:	
1,2	,3-Trimethylbenzene	NI 211 2 1
	Louisiana Right-To-Know:	Not Listed
	California Proposition 65:	NOT LISTED
	New Jersey Right-To-Khow.	SIN 1929 Drecent
	Massachusotte Pight To Know:	Present
	Florida Substance List:	Not Listed
	Rhode Island Right-To-Know	Toxic
	Michigan Critical Materials Register List	Not Listed
	Massachusetts Extraordinarily Hazardous Substances:	Not Listed
	California - Regulated Carcinogens:	Not Listed
	Pennsylvania RTK - Special Hazardous	Not Listed
	Substances:	
	New Jersey - Special Hazardous Substances:	Not Listed
	New Jersey - Environmental Hazardous	Not Listed
	Substances List:	
	Illinois - Toxic Air Contaminants:	Present
	New York - Reporting of Releases Part 597 -	Not Listed
	List of Hazardous Substances:	
Na	phthalene	
	Louisiana Right-To-Know:	Not Listed
	California Proposition 65:	Carcinogen, initial date 4/19/02
	New Jersey Right-To-Know:	SN 1322 SN 3758
	Pennsylvania Right-To-Know:	Environmental nazard Present (particulate)
	Massachusetts Right-To Know:	Present
	Florida Substance List. Phode Island Pight To Know:	Not Listed
	Michigan Critical Materiale Projector Liet:	Not Listod
	Massachusetts Extraordinarily Hazardous Substances:	Not Listed
	California - Regulated Carcinogens:	Not Listed
	Pennsylvania RTK - Special Hazardous	Not Listed
	Substances:	
	New Jersey - Special Hazardous Substances:	Carcinogen
	New Jersey - Environmental Hazardous	SN 1322 TPQ: 500 lb (Reportable at the de minimis quantity of
	Substances List:	>0.1%)
	Illinois - Toxic Air Contaminants:	Present
	New York - Reporting of Releases Part 597 -	100 lb RQ (air); 1 lb RQ (land/water)
	List of Hazardous Substances:	
_		

Canada DSL/NDSL Inventory:

This product and/or its components are listed either on the Domestic Substances List (DSL) or are exempt.

Canadian Regulatory Information:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all of the information required by those regulations.

Name	Canada - WHMIS: Classifications of Substances:	Canada - WHMIS: Ingredient Disclosure:
Gasoline	B2,D2A,D2B	0.1%
Heptane (mixed isomers)	B2,D2B	1%
Butane (mixed isomers)	A,B1	1%
Pentane (mixed isomers)	B2	1%

Hexane Isomers (other than n-Hexane)	B2	1%
Toluene	B2,D2A,D2B	0.1%
Xylene (mixed isomers)	B2,D2A,D2B	m-, o-isomers 1.0%; p-isomer 0.1%
Benzene	B2,D2A,D2B	0.1%
n-Hexane	B2,D2A,D2B	1%
Cumene	B2,D2A	0.1%
1,2,4 Trimethylbenzene	B3,D2B	1%
Ethylbenzene	B2,D2A,D2B	0.1%
Cyclohexane	B2,D2B	1%
Octane	B2,D2B	1%
1,2,3-Trimethylbenzene	B3	1%
Naphthalene	B4,D2A	0.1%



Note:

Not applicable.

16. OTHER INFORMATION

Prepared By

Revision Notes

Revision Date Previous Publish Date Revised Sections Toxicology and Product Safety

03/19/2018 11/06/2017 The following sections (§) have been updated: 2. HAZARD IDENTIFICATION 3. COMPOSITION/INFORMATION ON INGREDIENTS 4. FIRST AID MEASURES 11. TOXICOLOGICAL INFORMATION

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is intended as guidance for safe handling, use, processing, storage, transportation, accidental release, clean-up and disposal and is not considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SAFETY DATA SHEET

CITGO CITGARD® 600 Engine Oil, SAE 15W-40



GHS product identifier	: CITGO CITGARD® 600 Engine Oil, SAE 15W-40
Synonyms	: Heavy duty motor oil
Material uses	: Heavy Duty Engine Oil
Code	: 622615001
Supplier's details	: CITGO Petroleum Corporation P.O. Box 4689 Houston, TX 77210 sdsvend@citgo.com
Emergency telephone number (with hours of operation)	: Technical Contact: (800) 248-4684 Medical Emergency: (832) 486-4700 CHEMTREC Emergency: (800) 424-9300 (United States Only)

Section 2. Hazards identification

OSHA/HCS status	: While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.
Classification of the substance or mixture	: Not classified.
GHS label elements	
Signal word	: No signal word.
Hazard statements	: No known significant effects or critical hazards.
Precautionary statements	
General	: Avoid contact with eyes, skin and clothing. Thoroughly wash exposed areas and clothing with soap and water. IF IN EYES: Rinse cautiously with water for several minutes. IF SWALLOWED: Do not induce vomiting. If you feel unwell, seek medical attention and show the label when possible. Keep out of reach of children.
Prevention	: Not applicable.
Response	: Not applicable.
Storage	: Not applicable.
Disposal	: Not applicable.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Heavy duty motor oil

CAS number/other identifiers

CAS number

: Not applicable.





Section 3. Composition/information on ingredients

Ingredient name	%	CAS number
Distillates (petroleum), hydrotreated heavy paraffinic Distillates (petroleum), solvent-refined heavy paraffinic Distillates (petroleum), solvent-dewaxed heavy paraffinic reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl) propionate	≥75 - ≤90 ≤5 ≤3 ≤3	64742-54-7 64741-88-4 64742-65-0 125643-61-0

Any concentration shown as a range is to protect confidentiality or is due to process variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	: Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Potential acute health	<u>n effects</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs	/symptoms
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Indication of immediat	<u>e medical attention and special treatment needed, if necessary</u>
Nuclear the scheme test and	

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediate 	iately if large
	quantities have been ingested or inhaled.	
One selfter the stress sets		

- **Specific treatments** : Treat symptomatically and supportively.
- **Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide sulfur oxides phosphorus oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures		
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containment and cleaning up		
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe hand	ling					
Protective measures	ection 8).					
Advice on general occupational hygiene	: Eating, d handled, drinking entering measure	rinking and smoking should stored and processed. Wo and smoking. Remove con eating areas. See also Sec s.	be prohibited in area rkers should wash ha taminated clothing ar tion 8 for additional in	as where this n ands and face nd protective e nformation on	naterial is before ea quipment hygiene	ting, before
Date of issue/Date of revision	: 4/9/2018	Date of previous issue	: 11/14/2017	Version	: 1.01	3/11

Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.
	Bulk Storage Conditions: Maintain all storage tanks in accordance with applicable regulations. Use necessary controls to monitor tank inventories. Inspect all storage tanks on a periodic basis. Test tanks and associated piping for tightness. Maintain the automatic leak detection devices to assure proper working condition.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated heavy paraffinic	ACGIH TLV (United States, 3/2016). TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction OSHA PEL (United States, 6/2016). TWA: 5 mg/m ³ 8 hours. NIOSH REL (United States, 10/2013). TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist
Distillates (petroleum), solvent-refined heavy paraffinic	ACGIH TLV (United States, 3/2016). TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction OSHA PEL (United States, 6/2016). TWA: 5 mg/m ³ 8 hours. NIOSH REL (United States, 10/2013). TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist
Distillates (petroleum), solvent-dewaxed heavy paraffinic	ACGIH TLV (United States, 3/2016). TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction OSHA PEL (United States, 6/2016). TWA: 5 mg/m ³ 8 hours. NIOSH REL (United States, 10/2013). TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist

Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, vapor controls, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection meas	ures	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 8. Exposure controls/personal protection

Eye/face protection	: Safety glasses equipped with side shields are recommended as minimum protection in industrial settings. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If inhalation hazards exist, a full-face respirator may be required instead.
Skin protection	
Hand protection	: Chemical-resistant gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Avoid skin contact with liquid. Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Leather boots are not protective for liquid contact.
Respiratory protection	: Avoid inhalation of gases, vapors, mists or dusts. Use a properly fitted, air-purifying or supplied-air respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance		
Physical state	:	Liquid.
Color	1	Amber.
Odor	:	Mild petroleum odor
рН	1	Not available.
Boiling point	:	Not available.
Flash point	:	Open cup: 235°C (455°F) [Cleveland.]
Evaporation rate	:	<1 (butyl acetate = 1)
Lower and upper explosive (flammable) limits	:	Not available.
Vapor pressure	1	<0.0013 kPa (<0.01 mm Hg) [room temperature]
Vapor density	1	Not available.
Relative density	:	0.87
Density lbs/gal	1	7.28 lbs/gal
Density gm/cm ³	:	Not available.
Gravity, °API	:	30.8
Solubility	:	Insoluble in the following materials: cold water.
Flow time (ISO 2431)	:	Not available.
Viscosity	:	Kinematic (40°C (104°F)): 1.16 cm²/s (116 cSt)
Viscosity SUS	:	Estimated 537 SUS @104 F

Section 10. Stability and reactivity

: 4/9/2018

Date of issue/Date of revision

Reactivity	:	Not expected to be Explosive, Self-Reactive, Self-Heating, or an Organic Peroxide under US GHS Definition(s).
Chemical stability	:	The product is stable.
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.

Date of previous issue

:11/14/2017

Version : 1.01

Section 10. Stability and reactivity

Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition	: Under normal conc

Hazardous decomposition : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), hydrotreated heavy paraffinic Distillates (petroleum)	LD50 Oral	Rat Rabbit	>5000 mg/kg	-
solvent-refined heavy paraffinic				
Distillatos (notrolours)	LD50 Oral	Rat	5000 mg/kg	-
solvent-dewaxed heavy	LD50 Dermai	Raddil	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Irritation/Corrosion	Distillates (petroleum), hydrotic highly refined oils are reported to Effects from single and short-term oil mists well above applicable w reaction, lipoid granuloma formar studies involving exposures to lo current work place exposure leve Distillates (petroleum), solvent from highly refined oils are report animals. Effects from single and of mineral oil mists well above applicable with a sub-acute studies involving exposure from highly refined oils are report animals. Effects from single and of mineral oil mists well above applicable with a sub-acute studies involving exposure from highly refined oils are report animals. Effects from single and of mineral oil mists well above applicable with a sub-acute studies involving exposure from highly refined oils are report animals. Effects from single and of mineral oil mists well above applicable were characterized by necrosis a effects (cellular hypertrophy) followere characterized by necrosis a effects on prothrombin index were Chronic studies did not find carcinal sub-acute studie	have low acute a m repeated exposi- orkplace exposur- tion and lipoid pne- wer concentration els produced no si t-refined heavy p - ted to have low ac short-term repea- oplicable workplace nuloma formation sures to lower con- e levels produced t-dewaxed heavy - ted to have low ac short-term repea- oplicable workplace applicable workplace to have low ac short-term repea- oplicable workplace applicable workplace short-term repea- oplicable workplace applicable workplace short-term repea- oplicable workplace applicable workplace applicable workplace to have low ac short-term repea- oplicable workplace applicable	aminic: Mineral off and sub-acute toxici sures to high concer- e levels include lung eumonia. In acute a is of mineral oil mis- ignificant toxicologic paraffinic: Mineral of cute and sub-acute ted exposures to his e exposure levels i and lipoid pneumor- ncentrations of mine- no significant toxico paraffinic: Mineral cute and sub-acute ted exposure levels i and lipoid pneumor- ncentrations of mine- ted exposures to his e exposure levels i and lipoid pneumor- ncentrations of mine- no significant toxico di-tert-butyl-4-hydr nenols have been as stration to rats. The es of 250 mg/kg/da ver this effect is not i rats or mice.	ties in animals. ntrations of mineral g inflammatory and sub-acute ts at or near cal effects. bil mists derived toxicities in gh concentrations nclude lung hia. In acute and eral oil mists at or ological effects. I oil mists derived toxicities in gh concentrations nclude lung hia. In acute and eral oil mists at or ological effects. I oil mists at or ological effects. I oil mists at or ological effects. I oil mists at or ological effects. roxyphenyl) ssociated with liver ese liver effects by or higher. Also, a seen in all studies.

Not available.

Skin Eyes Respiratory Sensitization Not available.

- : No additional information.
- : No additional information.
- : No additional information.

Date of issue/Date of revision

Section 11. Toxicological information

Section 11. TOXICO	Jiogica		nation	
Skin	: No additional information.			
Respiratory	: No additional information.			
<u>Mutagenicity</u>				
Not available.				
Conclusion/Summary	: No addi	ional inform	nation.	
Carcinogenicity				
Not available.				
Conclusion/Summany	Distillat	ac (natrala	um) solvent refined heavy pareffinie: In long term studies (up to	
conclusion/Summary	two vea	s) no carcir	nogenic effects have been reported in any animal species tested.	
Classification	, ,	-,		
Product/ingredient name	OSHA	IARC	NTP	
	-	4	-	
solvent-refined heavy paraffinic				
Reproductive toxicity				
Not available.				
Conclusion/Summary	: No addit	ional inform	nation.	
Teratogenicity				
Not available.				
Conclusion/Summary	: No addit	ional inform	nation.	
Specific target organ toxicit	v (sinale e)	(posure)		
Not available.		,		
Specific target organ toxicit	ty (repeated	<u>exposure</u>		
Not available.				
Aspiration hazard				
Not available.				
Information on the likely routes of exposure	: Not avai	lable.		
Potential acute health effects	<u>i</u>			
Eye contact	: No knov	n significar/	nt effects or critical hazards.	
Inhalation	: No known significant effects or critical hazards.			
Skin contact	: No known significant effects or critical hazards.			
Ingestion	: No known significant effects or critical hazards.			
Symptoms related to the phy	<u>sical, chem</u>	ical and to	xicological characteristics	
Eye contact	: No spec	ific data.		
Inhalation	: No specific data.			
Skin contact	: No specific data.			
Ingestion	: No spec	ific data.		
Delayed and immediate effect	ts and also	<u>chronic ef</u>	fects from short and long term exposure	
Short term exposure				
Potential immediate effects	: Not avai	lable.		
Potential delayed effects	: Not avai	lable.		

Date of issue/Date of revision

: 4/9/2018

Date of previous issue

sue : 11/14/2017

Version : 1.01

7/11

Section 11. Toxicological information

<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	<u>ects</u>
Not available.	
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Section 12. Ecological information

Toxicity

Not available.

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Distillates (petroleum), solvent-refined heavy paraffinic	3.9 to 6	-	high
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl- 4-hydroxyphenyl) propionate	9.2	260	low

Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

Oil: The product(s) represented by this SDS is (are) regulated as "oil" under 49 CFR Part 130. Shipments by rail or highway in packaging having a capacity of 3500 gallons or more or in a quantity greater 42,000 gallons are subject to these requirements. In addition, mixtures containing 10% or more of this product may be subject to these requirements.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

```
Transport in bulk according : Not available.
to Annex II of MARPOL and
the IBC Code
```

Section 15. Regulatory information

U.S. Federal regulations United States inventory (TSCA 8b): All components are listed or exempted. Clean Water Act (CWA) 307: Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts; toluene; benzene Clean Water Act (CWA) 311: fumaric acid; ethylenediamine; toluene; vinyl acetate; benzene This material is classified as an oil under Section 311 of the Clean Water Act (CWA) and the Oil Pollution Act of 1990 (OPA). Discharges or spills which produce a visible sheen on waters of the United States, their adjoining shorelines, or into conduits leading to surface waters must be reported to the EPA's National Response Center at (800) 424-8802.

SARA 302/304

Composition/information on ingredients

			SARA 302 TPQ		SARA 30	SARA 304 RQ	
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)	
ethylenediamine vinyl acetate	<0.1 <0.0001	Yes. Yes.	10000 1000	1337.1 129	5000 5000	668.5 644.8	
SARA 304 RQ	: 42151407.9 lbs / 19136	739.2 kg [58	310795 gal	/ 21996251.91	1		

SARA 311/312

Classification : Not applicable.

Composition/information on ingredients

No products were found.

Section 15. Regulatory information

State regulations

Massachusetts	: None of the components are listed.
New York	: None of the components are listed.
New Jersey	: None of the components are listed.
Pennsylvania	: None of the components are listed.

California Prop. 65 Clear and Reasonable Warnings (2018)

▲ WARNING: This product can expose you to Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Toluene, Ethylene Glycol, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ingredient name	%	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
toluene	<0.1	No.	Yes.	-	Yes.
benzene	trace	Yes.	Yes.	Yes.	Yes.
ethanediol	<0.1	NO.	Yes.	-	-
nternational regulations					
WHMIS (Canada)	Not contr	olled under W	HMIS (Canada).		
<u>nventory list</u>					
United States	All comp	onents are liste	ed or exempted.		
Australia	All compo	onents are liste	ed or exempted.		
Canada	All compo	onents are liste	ed or exempted.		
China :	Not deter	Not determined.			
Europe	All compo	All components are listed or exempted.			
Japan :	Japan inventory (ENCS): Not determined. Japan inventory (ISHL): Not determined.				
Malaysia	Not deter	Not determined.			
New Zealand	All compo	All components are listed or exempted.			
Philippines :	Not deter	Not determined.			
Republic of Korea :	All compo	All components are listed or exempted.			
Taiwan	All compo	All components are listed or exempted.			
Thailand :	Not deter	mined.			
Turkey	Not deter	mined.			
Viet Nam :	Not deter	mined.			

Section 16. Other information

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Section 16. Other information

Procedure used to derive t	e classification		
	Classific	ation	Justification
Not classified.			
History			
Date of printing	: 4/24/2018		
Date of issue/Date of revision	: 4/9/2018		
Date of previous issue	: 11/14/2017		
Version	: 1.01		
Key to abbreviations	: ATE = Acute BCF = Bioca GHS = Glob IATA = Inter IBC = Intern IMDG = Inter LogPow = Ic MARPOL = as modified UN = United	e Toxicity Estimate oncentration Factor pally Harmonized System of Classification a rnational Air Transport Association nediate Bulk Container ernational Maritime Dangerous Goods ogarithm of the octanol/water partition coeff International Convention for the Prevention by the Protocol of 1978. ("Marpol" = marine d Nations	and Labelling of Chemicals ricient n of Pollution From Ships, 1973 e pollution)
References	: Not availabl	e.	

Indicates information that has changed from previously issued version.

Notice to reader

THE INFORMATION IN THIS SAFETY DATA SHEET (SDS) WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED REGARDING ITS CORRECTNESS OR ACCURACY. SOME INFORMATION PRESENTED AND CONCLUSIONS DRAWN HEREIN ARE FROM SOURCES OTHER THAN DIRECT TEST DATA ON THE SUBSTANCE ITSELF. THIS SDS WAS PREPARED AND IS TO BE USED ONLY FOR THIS PRODUCT. IF THE PRODUCT IS USED AS A COMPONENT IN ANOTHER PRODUCT, THIS SDS INFORMATION MAY NOT BE APPLICABLE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE OR APPLICATION.

THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE, AND/OR DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR ANY LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.

CITGO is a registered trademark of CITGO Petroleum Corporation

SAFETY DATA SHEET

CITGO No. 2 Diesel Fuel, All Grades, Low Sulfur

Section 1. Identification

GHS product identifier	: CITGO No. 2 Diesel Fuel, All Grades, Low Sulfur
Chemical name	: Fuels, diesel, No 2
Synonyms	 No. 2-D Grade Diesel Fuel Oil (defined by ASTM D-975); Treated or Refined Diesel Fuel No. 2; Grade 2 Distillate Fuel; Hydrodesulfurized Middle Distillate; C9-C16 Petroleum Hydrocarbons
Material uses	: Fuel.
Code	: Various
Supplier's details	: CITGO Petroleum Corporation P.O. Box 4689 Houston, TX 77210 sdsvend@citgo.com
Emergency telephone number (with hours of operation)	: Technical Contact: (800) 248-4684 Medical Emergency: (832) 486-4700 CHEMTREC Emergency: (800) 424-9300 (United States Only)

Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	 FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2B CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS)) - Category 2 ASPIRATION HAZARD - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 2

GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	 Flammable liquid and vapor. Harmful if inhaled. Causes skin and eye irritation. Suspected of causing cancer. May be fatal if swallowed and enters airways. May cause damage to organs through prolonged or repeated exposure. (central nervous system (CNS)) Toxic to aquatic life with long lasting effects.
Precautionary statements	
General	: Diesel engine exhaust can cause upper respiratory tract irritation and reversible pulmonary effects. Long-term exposure to diesel engine exhaust may cause cancer. Do not syphon by mouth.



Section 2. Hazards identification

Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Do not breathe vapor. Wash hands thoroughly after handling.
Response	: Collect spillage. Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	: Store locked up. Store in a well-ventilated place. Keep cool.
Disposal	 Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and receiving equipment. These alone may be insufficient to remove static electricity. Do not taste or swallow. Wash thoroughly after handling.
Hazards not otherwise classified	: Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor may cause flash fire or explosion. Causes digestive tract burns. Prolonged or repeated contact may dry skin and cause irritation.

Section 3. Composition/information on ingredients

Substance/mixture	:	Substance
Chemical name	:	Fuels, diesel, No 2
Other means of identification	:	No. 2-D Grade Diesel Fuel Oil (defined by ASTM D-975); Treated or Refined Diesel Fuel No. 2; Grade 2 Distillate Fuel; Hydrodesulfurized Middle Distillate; C9-C16 Petroleum Hydrocarbons

CAS number/other identifiers

CAS number : 68476-34-6		
Ingredient name	%	CAS number
Benzene, trimethyl-	1 - 5	25551-13-7
Naphthalene	0.5 - 1.5	91-20-3
biphenyl	0.5 - 1.5	92-52-4
Cumene	0.5 - 1.5	98-82-8
Xylene	0.5 - 1.5	1330-20-7
Ethylbenzene	0.5 - 1.5	100-41-4

* = Various ** = Mixture *** = Proprietary

Any concentration shown as a range is to protect confidentiality or is due to process variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed		
Potential acute health effects		
Eye contact	: Causes eye irritation.	
Inhalation	: Harmful if inhaled.	
Skin contact	: Causes skin irritation. Defatting to the skin.	
Ingestion	: Corrosive to the digestive tract. Causes burns. May be fatal if swallowed and enters airways.	
Over-exposure signs/symptoms		
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness	
Inhalation	: Repeated or prolonged overexposure to solvents can cause brain or other nervous system damage. The symptoms can include the loss of memory, the loss of intellectual capacity and the loss of coordination.	
Skin contact	: Adverse symptoms may include the following: irritation redness dryness cracking	
Ingestion	: Adverse symptoms may include the following: stomach pains nausea or vomiting	
Indication of immediate medic	al attention and special treatment needed, if necessary	
Notes to physician	: If ingested, this material presents a significant aspiration and chemical pneumonitis hazard. Induction of emesis is not recommended. Consider activated charcoal and/or gastric lavage. If patient is obtunded, protect the airway by cuffed endotracheal intubation or by placement of the body in a Trendelenburg and left lateral decubitus position.	
Specific treatments	: Treat symptomatically and supportively.	

 Date of issue/Date of revision
 : 7/31/2018
 Date of previous issue
 : 4/16/2018
 Vers
Section 4. First aid measures

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that gas or vapor is still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use caution when applying carbon dioxide in confined spaces. SMALL FIRE: Steam, CO ₂ , dry chemical or inert gas (e.g., nitrogen). LARGE FIRE: Use foam, water fog or water spray. Water fog and spray are effective in cooling containers and adjacent structures. However, water can cause frothing and/or may not extinguish the fire. Water can be used to cool the external walls of vessels to prevent excessive pressure, ignition or explosion.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static accumulation may be significantly increased by the presence of small quantities of water or other contaminants. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide Diesel engine exhaust
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures					
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.				
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".				

Section 6. Accidental release measures

Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Restrict flow velocity according to API 2003 (2008), NFPA 77 (2007), and Laurence Britton, "Avoiding Static Ignition Hazards in Chemical Operations". To reduce potential for static discharge, ensure that all equipment is properly grounded and bonded and meets appropriate electrical classification requirements. Non equilibrium conditions may increase the fire hazard associated with this product. Always bond receiving containers to the fill pipe before and during loading. Always confirm that receiving container is properly grounded. Bonding and grounding alone may be inadequate to eliminate fire and explosion hazards. Carefully review operations that may increase the risks such as tank and container filling, tank cleaning, sampling, gauging, loading, filtering, mixing, agitation, etc. In addition to bonding and grounding, efforts to mitigate the hazards may include, but are not limited to, ventilation, inerting and/or reduction of transfer velocities. Always keep nozzle in contact with the container throughout the loading process. Do NOT fill any portable container in or on a vehicle. Special precautions, such as reduced loading rates and increased monitoring, must be observed during "switch loading" operations (i.e., loading this material in tanks or shipping compartments that previously contained a dissimilar product). Advice on general Eating, drinking and smoking should be prohibited in areas where this material is occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use. Bulk Storage Conditions: Maintain all storage tanks in accordance with applicable regulations. Use necessary controls to monitor tank inventories. Inspect all storage tanks on a periodic basis. Test tanks and associated piping for tightness. Maintain the automatic leak detection devices to assure proper working condition
	Head spaces in tanks and other containers may contain a mixture of air and vapor in the flammable range. Vapor may be ignited by static discharge. Storage area must meet OSHA requirements and applicable fire codes. Additional information regarding the design and control of hazards associated with the handling and storage of flammable and combustible liquids may be found in professional and industrial documents including, but not limited to, the National Fire Protection Association (NFPA) publications NFPA 30 ("Flammable and Combustible Liquid Code"), NFPA 77 ("Recommended Practice on Static Electricity") and the American Petroleum Institute (API) Recommended Practice 2003, ("Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents").

Section 8. Exposure controls/personal protection

Occupational exposure li	<u>mits</u>			
Fuels, diesel, No 2			ACGIH TLV (Ur Absorbed thro TWA: 100 mg/ hydrocarbons) 8 hydrocarbons	nited States, 2/2010). ugh skin. /m³, (measured as total 3 hours. Form: Total
Benzene, trimethyl-			ACGIH TLV (Ur TWA: 25 ppm TWA: 123 mg/	nited States, 3/2017). 8 hours. /m³ 8 hours
Naphthalene			ACGIH TLV (Ur through skin. STEL: 15 ppm ACGIH TLV (Ur Absorbed thro TWA: 10 ppm TWA: 52 mg/n NIOSH REL (Ur	nited States). Absorbed 15 minutes. nited States, 3/2017). ugh skin. 8 hours. n ³ 8 hours. nited States, 10/2016).
			TWA: 10 ppm TWA: 50 mg/n STEL: 15 ppm STEL: 75 mg/r OSHA PEL (Un TWA: 10 ppm TWA: 50 mg/n	10 hours. n ³ 10 hours. 15 minutes. n ³ 15 minutes. ited States, 6/2016). 8 hours. n ³ 8 hours.
biphenyl			OSHA PEL Z2 (TWA: 0.2 ppm ACGIH TLV (Ur TWA: 0.2 ppm TWA: 1.3 mg/r NIOSH REL (Ur TWA: 1 mg/m ³ TWA: 0.2 ppm OSHA PEL (Un TWA: 0.2 ppm TWA: 1 mg/m ³	(United States). a 8 hours. nited States, 3/2017). a 8 hours. m ³ 8 hours. nited States, 10/2016). ³ 10 hours. a 10 hours. bited States, 6/2016). a 8 hours. ³ 8 hours.
Date of issue/Date of revision	: 7/31/2018	Date of previous issue	: 4/16/2018	Version :4

Date of issue/Date of revision

Control parameters

Section 8. Exposure controls/personal protection

Cumene	NIOSH REL (United States, 10/2016). Absorbed through skin. TWA: 50 ppm 10 hours. TWA: 245 mg/m ³ 10 hours. ACGIH TLV (United States, 3/2017). TWA: 50 ppm 8 hours. OSHA PEL (United States, 6/2016). Absorbed through skin. TWA: 50 ppm 8 hours
	TWA: 245 mg/m ³ 8 hours.
Xylene	ACGIH TLV (United States, 3/2017). TWA: 100 ppm 8 hours. TWA: 434 mg/m ³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 651 mg/m ³ 15 minutes. OSHA PEL (United States, 6/2016). TWA: 100 ppm 8 hours. TWA: 435 mg/m ³ 8 hours.
Ethylbenzene	ACGIH TLV (United States, 3/2017). TWA: 20 ppm 8 hours. NIOSH REL (United States, 10/2016). TWA: 100 ppm 10 hours. TWA: 435 mg/m ³ 10 hours. STEL: 125 ppm 15 minutes. STEL: 545 mg/m ³ 15 minutes. OSHA PEL (United States, 6/2016). TWA: 100 ppm 8 hours. TWA: 435 mg/m ³ 8 hours.

Appropriate engineering controls	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, vapor controls, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measure	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	Safety glasses equipped with side shields are recommended as minimum protection in ndustrial settings. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If inhalation hazards exist, a full-face respirator may be required nstead.
Skin protection	

Section 8. Exposure controls/personal protection

Hand protection	: Avoid skin contact with liquid. Chemical-resistant gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Recommended: Heavy duty, industrial grade chemically resistant gloves constructed of nitrile, neoprene, polyethylene, fluoroelastomer rubber or polyvinyl chloride as approved by glove manufacturer. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Leather gloves are not protective for liquid contact.
Body protection	: Avoid skin contact with liquid. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Avoid skin contact with liquid. Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Leather boots are not protective for liquid contact.
Respiratory protection	: Avoid inhalation of gases, vapors, mists or dusts. Use a properly fitted, air-purifying or supplied-air respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If an air purifying respirator is appropriate, use one equipped with cartridges rated for organic vapors.

Section 9. Physical and chemical properties

<u>Appearance</u>		
Physical state	:	Liquid.
Color	:	Not available.
Odor	:	Characteristic.
рН	:	Not available.
Melting point	:	-30 to -18°C (-22 to -0.4°F)
Boiling point	:	282 to 338°C (539.6 to 640.4°F)
Flash point	:	Closed cup: ≥52°C (≥125.6°F) [Pensky-Martens.]
Evaporation rate	:	<1 (butyl acetate = 1)
Lower and upper explosive (flammable) limits	:	Lower: 0.6% Upper: 6.5%
Vapor pressure	:	0.27 kPa (2 mm Hg) [room temperature]
Vapor density	:	5 [Air = 1]
Relative density	:	0.84
Density Ibs/gal	:	Estimated 7 lbs/gal
Density gm/cm ³	:	0.87 to 0.95 g/cm ³
Gravity, °API	:	Estimated 37 @ 60 F
Solubility	:	Very slightly soluble in the following materials: cold water.
Solubility in water	:	0.005 g/l
Partition coefficient: n- octanol/water	:	>3.3
Auto-ignition temperature	:	254 to 285°C (489.2 to 545°F)
Flow time (ISO 2431)	:	Not available.
Viscosity	:	Kinematic (room temperature): 0.03 cm ² /s (3 cSt)
Conductivity	;	<50 picosiemens/meter (unadditized)

Section 10. Stability and reactivity

Reactivity	: Not expected to be Explosive, Self-Reactive, Self-Heating, or an Organic Peroxide under US GHS Definition(s).
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas. Do not store with strong oxidizing agents.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Benzene, trimethyl-	LD50 Oral	Rat	8970 mg/kg	-
Naphthalene	LD50 Oral	Rat	490 mg/kg	-
biphenyl	LD50 Dermal	Rabbit	>5010 mg/kg	-
	LD50 Oral	Rat	2140 mg/kg	-
Cumene	LC50 Inhalation Vapor	Mouse	10 g/m³	7 hours
	LD50 Dermal	Rabbit	12300 uL/kg	-
	LD50 Oral	Rat	2.9 g/kg	-
	LD50 Oral	Rat	4000 mg/kg	-
Xylene	LC50 Inhalation Vapor	Rat	5000 ppm	4 hours
	LC50 Inhalation Vapor	Rat	6700 ppm	4 hours
	LD50 Oral	Mouse	2119 mg/kg	-
	LD50 Oral	Rat	4300 mg/kg	-
	LD50 Oral	Rat	4300 mg/kg	-
Ethylbenzene	LD50 Dermal	Rabbit	>5000 mg/kg	-
-	LD50 Oral	Rat	3500 mg/kg	-

Conclusion/Summary : No additional information.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Benzene, trimethyl-	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
Naphthalene	Skin - Mild irritant	Rabbit	-	495 milligrams	-
biphenyl	Eyes - Mild irritant	Rabbit	-	100 milligrams	-
	Skin - Severe irritant	Rabbit	-	24 hours 500 microliters	-
Cumene	Eyes - Mild irritant	Rabbit	-	86 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 10 milligrams	-
Xylene	Skin - Mild irritant	Rat	-	8 hours 60 microliters	-
Date of issue/Date of revision	: 7/31/2018 Date of prev	vious issue	: 4/16/2018	Version	:4 9/1

Section 11. Toxicological information

	J - J	-			
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Moderate irritant	Rabbit	-	100 Percent	-
Ethylbenzene	Skin - Mild irritant	Rabbit	-	24 hours 15	-
				milligrams	
Skin	: No additional information).			
Eyes	: No additional information	1.			
Respiratory	: No additional information	1.			
Sensitization					
Not available.					
Skin	: No additional information	1.			
Respiratory	: No additional information	1.			
<u>Mutagenicity</u>					
Not available.					
Conclusion/Summary	: No additional information	1.			
Carcinogenicity					
Not available.					
Conclusion/Summary	: Diesel exhaust particul mice exposed to unflitere epidemiological studies h workers and bladder can to diesel engine exhaust	ate: Lung tum ed diesel fuel e nave identified cer in bus and NTP has de	or and lymph exhaust in ch increase inc truck driver termined that	nomas were identifie ronic inhalation stud idences of lung can s possibly associate t exposure to diesel	d in rats and lies. Further, cer in US railroad d with exposure exhaust

Classification

Product/ingredient name	OSHA	IARC	NTP
Fuels, diesel, No 2	-	3	-
Diesel exhaust particulate	-	1	Reasonably anticipated to be a human carcinogen.
Naphthalene	-	2B	Reasonably anticipated to be a human carcinogen.
Cumene	-	2B	Reasonably anticipated to be a human carcinogen.
Xylene	-	3	-
Ethylbenzene	-	2B	-

diesel exhaust as a potential carcinogen.

particulates, a complex mixture of combustion products of diesel fuel, is reasonably anticipated to be a human carcinogen. In addition, NIOSH has identified complete

Reproductive toxicity

Not available.

Conclusion/Summary : No additional information.

Teratogenicity

Not available.

Conclusion/Summary : No additional information.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Benzene, trimethyl-	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
biphenyl	Category 3	Not applicable.	Respiratory tract irritation
Cumene	Category 3	Not applicable.	Respiratory tract irritation
Ethylbenzene	Category 3	Not applicable.	Respiratory tract irritation
Date of issue/Date of revision : 7/31/2018	Date of previous issue : 4/1	16/2018	Version : 4 10

Section 11. Toxicological information

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Benzene, trimethyl-	Category 2	Not determined	central nervous system (CNS)
Xylene	Category 2	Not determined	hearing organs

Aspiration hazard

Name	Result
Benzene, trimethyl-	ASPIRATION HAZARD - Category 1
Cumene	ASPIRATION HAZARD - Category 1
Ethylbenzene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure	1	Routes of entry	anticipated: Dermal,	Inhalation.				
Potential acute health effects	<u>s</u>							
Eye contact	:	Causes eye irrit	ation.					
Inhalation	:	Harmful if inhal	ed.					
Skin contact	:	Causes skin irri	tation. Defatting to t	he skin.				
Ingestion	:	Corrosive to the airways.	e digestive tract. Cau	ises burns.	May be fatal if	swallowe	d and enter	S
Symptoms related to the phy	ysic	al, chemical an	d toxicological cha	racteristics	<u>.</u>			
Eye contact	:	Adverse sympto pain or irritation watering redness	oms may include the	following:				
Inhalation	:	Repeated or pro system damage capacity and the	blonged overexposure. The symptoms ca loss of coordination	re to solvent n include th n.	s can cause bra e loss of memo	ain or othe ry, the los	er nervous ss of intelled	ctual
Skin contact	:	Adverse sympto irritation redness dryness cracking	oms may include the	following:				
Ingestion	:	Adverse sympto stomach pains nausea or vomi	oms may include the ting	following:				
Delayed and immediate effe	<u>cts</u>	and also chroni	c effects from shor	t and long	<u>term exposure</u>	Ŀ		
Short term exposure								
Potential immediate effects	-	Not available.						
Potential delayed effects	1	Not available.						
Long term exposure								
Potential immediate effects	-	Not available.						
Potential delayed effects	:	Not available.						
Potential chronic health eff	ect	5						
Not available.								
General	:	May cause dam	age to organs throug	gh prolonge	d or repeated e	xposure.		
Carcinogenicity	:	Suspected of ca exposure.	ausing cancer. Risk	of cancer d	epends on dura	tion and I	evel of	
Mutagenicity	:	No known signi	ficant effects or critic	al hazards.				
Date of issue/Date of revision	: 7	/31/2018 🛛	ate of previous issue	: 4/16/20)18	Version	: 4	11/17

Section 11. Toxicological information

Teratogenicity Developmental effects Fertility effects

- : No known significant effects or critical hazards.
- : No known significant effects or critical hazards.
 - : No known significant effects or critical hazards.

Section 12. Ecological information

<u>Toxicity</u>			
Product/ingredient name	Result	Species	Exposure
Benzene, trimethyl-	Acute LC50 5600 µg/l Marine water	Crustaceans - Palaemonetes	48 hours
Naphthalene	Acute EC50 1.6 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 2350 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
	Acute LC50 213 µg/l Fresh water	Fish - Melanotaenia fluviatilis - Larvae	96 hours
	Chronic NOEC 0.5 mg/l Marine water	Crustaceans - Uca pugnax - Adult	3 weeks
	Chronic NOEC 1.5 mg/l Fresh water	Fish - Oreochromis mossambicus	60 days
biphenyl	Acute LC50 360 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 1450 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NOEC 0.17 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	21 days
	Chronic NOEC 0.229 mg/l Fresh water	Fish - Oncorhynchus mykiss	87 days
Cumene	Acute EC50 2600 μg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 7400 μg/l Fresh water	Crustaceans - Artemia sp Nauplii	48 hours
	Acute EC50 10600 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 2700 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
Xylene	Acute EC50 90 mg/l Fresh water	Crustaceans - Cypris subglobosa	48 hours
	Acute LC50 8.5 ppm Marine water	Crustaceans - Palaemonetes pugio - Adult	48 hours
	Acute LC50 8500 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
	Acute LC50 15700 μg/l Fresh water	Fish - Lepomis macrochirus - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute LC50 19000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 13400 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 16940 µg/l Fresh water	Fish - Carassius auratus	96 hours
Ethylbenzene	Acute EC50 4600 μg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 3600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 6530 µg/l Fresh water	Crustaceans - Artemia sp Nauplii	48 hours
	Acute EC50 2930 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 4200 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours

Conclusion/Summary : Not available.

Persistence and degradability

Not available.

Conclusion/Summary : Not available.

Section 12. Ecological information

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Fuels, diesel, No 2	>3.3	-	low
Benzene, trimethyl-	3.4 to 3.8	-	low
Naphthalene	3.4	36.5 to 168	low
biphenyl	4.008	1900	high
Cumene	3.55	35.48	low
Xylene	3.12	8.1 to 25.9	low
Ethylbenzene	3.6	-	low

Mobility in soil

Soil/water partition	1	Not available.
coefficient (Koc)		

Other adverse effects	: No known significant effects or critical hazards.
-----------------------	---

Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
RCRA classification	· D001 D018

Section 14. Transport information

	DOT Classification	IMDG	ΙΑΤΑ
UN number	NA1993	UN1202	UN1202
UN proper shipping name	Diesel Fuel	DIESEL FUEL	Diesel Fuel
Transport hazard class(es)	3	3	3
Packing group	III	III	Ш
Environmental hazards	No.	No.	No.

Additional information

Section 14. Transport information

DOT Classification	his product may be re-classified as "Combustible Liquid," unless transported by vessel r aircraft. Non-bulk packages (less than or equal to 119 gal) of combustible liquids are ot regulated as hazardous materials in package sizes less than the product reportable uantity. Reportable quantity 11223.3 lbs / 5095.4 kg [1479.2 gal / 5599.3 L]. Package sizes hipped in quantities less than the product reportable quantity are not subject to the RQ reportable quantity) transportation requirements. Imited quantity Yes. Packaging instruction Exceptions: 150. Non-bulk: 203. Bulk: 242. Quantity limitation Passenger aircraft/rail: 60 L. Cargo aircraft: 220 L. Special provisions 144, B1, IB3, T4, TP1, TP29 Remarks 49 CFR 173.150 (f)(1) states that a flammable liquid with a flash point at or	
	bove 38°C (100°F) that does not meet the definition of any other hazard class may be eclassed as a combustible liquid. This provision does not apply to transportation by essel or aircraft except where other means of transportation is impracticable.	
TDG Classification	roduct classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3).	
IMDG	imergency schedules F-E, S-E Special provisions 363	
ΙΑΤΑ	<u>Juantity limitation</u> Passenger and Cargo Aircraft: 60 L. Packaging instructions: 355. Cargo Aircraft Only: 220 L. Packaging instructions: 366. Limited Quantities - Passenger Aircraft: 10 L. Packaging instructions: Y344. Special provisions	٢
Special precautions for user	ransport within user's premises: always transport in closed containers that are pright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	;
Transport in bulk according to Annex II of MARPOL and the IBC Code	lot available.	

Section 15. Regulatory information

U.S. Federal regulations	 United States inventory (TSCA 8b): All components are listed or exempted. Clean Water Act (CWA) 307: naphthalene; ethylbenzene; toluene; benzene Clean Water Act (CWA) 311: naphthalene; xylene; ethylbenzene; toluene; benzene This material is classified as an oil under Section 311 of the Clean Water Act (CWA) and the Oil Pollution Act of 1990 (OPA). Discharges or spills which produce a visible sheen on waters of the United States, their adjoining shorelines, or into conduits leading to surface waters must be reported to the EPA's National Response Center at (800) 424-8802.
<u>SARA 302/304</u>	
Composition/information	<u>n on ingredients</u>
SARA 304 RQ	: Not applicable.
<u>SARA 311/312</u>	
Classification	 FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2B CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS)) - Category 2 ASPIRATION HAZARD - Category 1 HNOC - Corrosive to digestive tract HNOC - Static-accumulating flammable liquid

Composition	/information	on ingredien	ts

Date of issue/Date of revision	: 7/31/2018	Date of previous issue	: 4/16/2018	Version : 4	14/17

Section 15. Regulatory information

Name	%	Classification
Fuels, diesel, No 2 Diesel exhaust particulate Benzene, trimethyl-	>99 1 - 5 1 - 5	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2B CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS)) - Category 2 ASPIRATION HAZARD - Category 1 HNOC - Corrosive to digestive tract HNOC - Static-accumulating flammable liquid CARCINOGENICITY (inhalation) - Category 2 FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS)) - Category 2 ASPIRATION HAZARD - Category 1
Naphthalene	0.5 - 1.5	FLAMMABLE SOLIDS - Category 2 ACUTE TOXICITY (oral) - Category 4 CARCINOGENICITY - Category 2
biphenyl	0.5 - 1.5	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
Cumene	0.5 - 1.5	FLAMMABLE LIQUIDS - Category 3 EYE IRRITATION - Category 2A CARCINOGENICITY (inhalation) - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 ASPIRATION HAZARD - Category 1
Xylene	0.5 - 1.5	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (hearing organs) - Category 2
Ethylbenzene	0.5 - 1.5	FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A CARCINOGENICITY (inhalation) - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 ASPIRATION HAZARD - Category 1

<u>SARA 313</u>

	Product name	CAS number	%
Form R - Reporting	naphthalene	91-20-3	<1
requirements	ethylbenzene	100-41-4	<1
Supplier notification	naphthalene	91-20-3	<1
	ethylbenzene	100-41-4	<1

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts

: The following components are listed: ethyltoluene; trimethylbenzene

Date of issue/Date of revision	: 7/31/2018	Date of previous issue	: 4/16/2018	Version : 4	15/17

Section 15. Regulatory information

New York	1	The following components are listed: Naphthalene; Cumene; Benzene, 1-methylethyl-; Ethylbenzene
New Jersey	:	The following components are listed: ETHYLTOLUENES; BENZENE, ETHYLMETHYL-; TRIMETHYL BENZENE (mixed isomers); BENZENE, TRIMETHYL-; NAPHTHALENE; MOTH FLAKES; cumene; ethylbenzene
Pennsylvania	:	The following components are listed: ethyltoluene; trimethylbenzene; NAPHTHALENE; cumene; ethylbenzene

California Prop. 65 Clear and Reasonable Warnings (2018)

▲ WARNING: This product can expose you to Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Diesel exhaust particulate, Naphthalene, Cumene, Ethylbenzene, which are known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause cancer, and roluene, which is known to the State of California to cause cancer.

Ingredient name	%	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Diesel exhaust particulate	<3	Yes.	No.	-	-
naphthalene	<1	Yes.	No.	Yes.	-
cumene	<1	Yes.	No.	-	-
ethylbenzene	<1	Yes.	No.	Yes.	-
toluene	<0.1	No.	Yes.	-	Yes.
benzene	<0.1	Yes.	Yes.	Yes.	Yes.

International regulations

Inventory list

United States	:	All components are listed or exempted.
Australia	÷	All components are listed or exempted.
Canada	1	All components are listed or exempted.
China	:	All components are listed or exempted.
Europe	:	All components are listed or exempted.
Japan	:	Japan inventory (ENCS): All components are listed or exempted. Japan inventory (ISHL): Not determined.
Malaysia	:	Not determined.
New Zealand	1	All components are listed or exempted.
Philippines	:	All components are listed or exempted.
Republic of Korea	1	All components are listed or exempted.
Taiwan	:	Not determined.
Thailand	:	Not determined.
Turkey	:	Not determined.
Viet Nam	:	Not determined.

Section 16. Other information

National Fire Protection Association (U.S.A.)

2	Flammability
Health 10	Instability/Reactivity
	Special

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Section 16. Other information

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Procedure used to derive the classification

Justification
Expert judgment
Calculation method
Expert judgment
Expert judgment

HISTORY	
Date of printing	: 7/31/2018
Date of issue/Date of revision	: 7/31/2018
Date of previous issue	: 4/16/2018
Version	: 4
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations
References	· Not available

References

Indicates information that has changed from previously issued version.

Notice to reader

THE INFORMATION IN THIS SAFETY DATA SHEET (SDS) WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED REGARDING ITS CORRECTNESS OR ACCURACY. SOME INFORMATION PRESENTED AND CONCLUSIONS DRAWN HEREIN ARE FROM SOURCES OTHER THAN DIRECT TEST DATA ON THE SUBSTANCE ITSELF. THIS SDS WAS PREPARED AND IS TO BE USED ONLY FOR THIS PRODUCT. IF THE PRODUCT IS USED AS A COMPONENT IN ANOTHER PRODUCT, THIS SDS INFORMATION MAY NOT BE APPLICABLE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE OR APPLICATION.

THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE, AND/OR DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR ANY LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.

CITGO is a registered trademark of CITGO Petroleum Corporation



SAFETY DATA SHEET

1. Identification

Product identifier	Solder-Safe 97/3 Lead-Free Solder
Other means of identification	
SDS number	WC007
Recommended use	Solder.
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/I	Distributor information
Manufacturer/Supplier	Worthington Cylinder Corporation
Address	200 Old Wilson Bridge Road
	Columbus, OH 43085
	United States
Email:	cylinders@worthingtonindustries.com
Telephone Number:	866-928-2657
CHEMTREC - 24 HOURS:	
Within US and Canada	800-424-9300
Outside US and Canada	+1 703-741-5970 (collect calls accepted)
2. Hazard(s) identification	
	N1-A standard

Physical hazards	Not classified.
Health hazards	Not classified.
OSHA defined hazards	Not classified.
Label elements	
Hazard symbol	None.
Signal word	None.
Hazard statement	None.
Precautionary statement	
Prevention	Observe good industrial hygiene practices.
Response	Wash thoroughly after handling.
Storage	Store away from incompatible materials.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
Hazard(s) not otherwise classified (HNOC)	Molten material will produce thermal burns.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Tin	7440-31-5	90 - 100
Copper	7440-50-8	1 - 10

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Immediately remove from further exposure. Get immediate medical assistance. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. Give supplemental oxygen, if available. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

Skin contact	Remove contaminated clothes and rinse skin thoroughly with water for at least 15 minutes. If skin rash or an allergic skin reaction develops, get medical attention.
Eye contact	Rinse immediately with plenty of water for at least 15 minutes. Remove any contact lenses. Get medical attention if irritation develops or persists.
Ingestion	Immediately rinse mouth and drink a cupful of water. Never give anything by mouth to a victim who is unconscious or is having convulsions. Only induce vomiting at the instruction of medical personnel. Get medical attention immediately.
Most important symptoms/effects, acute and delayed	Dust and fumes may irritate eyes, skin and upper respiratory tract. Contact with molten material may cause thermal burns.
Indication of immediate medical attention and special treatment needed	Treat symptomatically. Exposure may aggravate pre-existing respiratory disorders. Symptoms may be delayed.
General information	Show this safety data sheet to the doctor in attendance.
5. Fire-fighting measures	
Suitable extinguishing media	Extinguish with foam, carbon dioxide or dry powder.
Unsuitable extinguishing media	Do not use water or halogenated extinguishing media.
Specific hazards arising from the chemical	Fire or high temperatures create: Metal oxides.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do it without risk.
General fire hazards	Solid metal is not flammable; however, finely divided metallic dust or powder may form an explosive mixture with air.
6. Accidental release meas	ures
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Avoid inhalation of dust from the spilled material. Wear protective clothing as described in Section 8 of this SDS. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
Methods and materials for containment and cleaning up	Stop leak if you can do so without risk. Local authorities should be advised if significant spillages cannot be contained.
	For a dry material spill, use a HEPA (high efficiency particle air) vacuum to collect material and place in a sealable container for disposal. Avoid dust formation. Recover and recycle, if practical. Keep out of water supplies and sewers.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not contaminate water. If release occurs in the U.S. and is reportable under CERCLA Section 103, notify the National Response Center at (800)424-8802 (USA) or (202)426-2675 (USA).
7. Handling and storage	
Precautions for safe handling	Wear appropriate personal protective equipment (See Section 8). Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Avoid inhalation of dust and fumes. Avoid contact with skin and eyes. Do not get this material on clothing. Do not eat, drink or smoke when using the product. Wash thoroughly after handling. Avoid release to the environment.
	Any surface that comes in contact with molten metal must be preheated or specially coated and rust free. Inadvertent contaminants to product such as moisture, ice, snow, grease, or oil can cause an explosion when charged to a molten metal bath or metal furnace (preheating metal will remove moisture from product).
Conditions for safe storage, including any incompatibilities	Store in tightly closed original container in a dry, cool and well-ventilated place. Store in a closed container away from incompatible materials. Keep out of reach of children. Keep away from food, drink and animal feedingstuffs.

11

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Copper (CAS 7440-50-8)	PEL	1 mg/m3	Dust and mist.
		0.1 mg/m3	Fume.
Tin (CAS 7440-31-5)	PEL	2 mg/m3	
ACGIH			
Components	Туре	Value	Form
Copper (CAS 7440-50-8)	TWA	1 mg/m3	Dust and mist.
US ACCIH Threshold Limit V	عميراه	0.2 mg/m3	Fume.
Componente	Type	Value	
		2 mg/m3	
Tin (CAS 7440-31-5)		2 mg/m3	
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
Copper (CAS 7440-50-8)	TWA	1 mg/m3	Dust and mist.
Tin (CAS 7440-31-5)	TWA	2 mg/m3	
Biological limit values	No biological exposure limits noted for	or the ingredient(s).	
Exposure guide <mark>line</mark> s	No exposure standards allocated.		
Appropriate engineering controls	Provide adequate ventilation. Observinhalation of dust. Keep melting/soldar generation of fume. Shower, hand an recommended.	re Occupational Exposure Limits ering temperatures as low as po nd eye washing facilities near th	s and minimize the risk of ossible to minimize the e workplace are
Individual protection measures, s	uch as personal protective equipm	ient	
Eye/face protection	Wear safety glasses with side shields material.	s (or goggles). Wear a face shie	ld when working with molten
Skin protection			
Hand protection	Wear protective gloves (i.e. latex, niti	rile, neoprene).	
Other	Chemical resistant clothing is recomm	mended.	
Respiratory protection	Use a respirator when local exhaust of OEL. In a confined space a supplied protective equipment should be in ac 1910.134; or in Canada with CSA Stathere is a risk of exposure to dust/function	or ventilation is not adequate to I respirator may be required. Se cordance with OSHA General I andard Z94.4. Use a NIOSH/MS ne at levels exceeding the expo	ection and use of respiratory ndustry Standard 29 CFR SHA approved respirator if isure limits.
Thermal hazards	Heat resistant/insulated gloves and o	lothing are recommended wher	n working with molten material.
General hygiene considerations	Always observe good personal hygie and before eating, drinking, and/or sr equipment to remove contaminants.	ne measures, such as washing moking. Routinely wash work cl	after handling the material othing and protective
9. Physical and chemical p	roperties		-
Appearance	Silver to silver-gray metallic metal.		
Physical state	Solid.		
Form	Wire.		
Color	Silver to gray.		
Odor	Odorless.		
Odor threshold	Not available.		
рН	Not available.		
Melting point/freezing point	441 - 482 °F (227.22 - 250 °C)		
Initial boiling point and boiling range	Not available.		
Flash point	Not available.		
Evaporation rate	Not available.		

Solder-Safe 97/3 Lead-Free Solder 908003 Version #: 01 Revision date: - Issue date: 28-May-2015

Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	7.38
Solubility(ies)	
Solubility (water)	Not soluble
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.

10. Stability and reactivity

Reactivity	The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Contact with incompatible materials. Avoid molten metal contact with water.
Incompatible materials	Chlorine. Turpentine. Magnesium. Acetylene Gas.
Hazardous decomposition products	Toxic metal oxides are emitted when heated above the melting point.

11. Toxicological information

Information on likely routes of exposure

이야 한 것 같아? 승규가 가지 않는 것 같아? 그 같은 것은 것 같아 것 같아 가지 않는 것 같아 ㅠㅠ 것	
Inhalation	Elevated temperatures or mechanical action may form dust and fumes which may be irritating to the mucous membranes and respiratory tract.
Skin contact	Dust may irritate skin.
Eye contact	Elevated temperatures or mechanical action may form dust and fumes which may be irritating to the eyes.
Ingestion	May cause discomfort if swallowed.
Symptoms related to the physical, chemical and toxicological characteristics	Elevated temperatures or mechanical action may form dust and fumes which may be irritating to the eye, mucous membranes and respiratory tract. Contact with molten material may cause thermal burns.
Information on toxicological effe	cts
Acute toxicity	High concentrations of freshly formed fumes/dusts of metal oxides can produce symptoms of metal fume fever. When heated, the vapors/fumes given off may cause respiratory tract irritation. Overexposure of Tin can cause irritation of the eyes, skin, mucous membranes, and respiratory system. Acute overexposure to Copper dust/fume can cause irritation of the eyes, nose, throat, and skin and under severe fume overexposure can cause metal fume fever with flu-like symptoms such as sweet metal taste, dry throat, coughing, fever and chills, tight chest, dyspnea, headache, blurred vision, back pain, nausea, vomiting, fatigue. Symptoms usually disappear within 24 hours. Copper may cause skin and hair discoloration. Inhalation of copper dusts may change the gums and mucous lining of the mouth which is generally attributable to localized tissue effect rather than general toxicity.
Skin corrosion/irritation	Dust may irritate skin.
Serious eye damage/eye irritation	Elevated temperatures or mechanical action may form dust and fumes which may be irritating to the eye.
Respiratory or skin sensitization	
Respiratory sensitization	No sensitizing effects known.

Skin sensitization	No sensitizing effects known.
Germ cell mutagenicity	No data available.
Carcinogenicity	Not classifiable as to carcinogenicity to humans.
OSHA Specifically Regulated Not listed.	Substances (29 CFR 1910.1001-1050)
Reproductive toxicity	No data available.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not relevant, due to the form of the product.
Chronic effects	Prolonged and repeated overexposure to dust and fumes can lead to benign pneumoconiosis (stannosis). Overexposure to Tin can result in benign pneumoconiosis (stannous). This form of pneumoconiosis produces progressive x-ray changes of the lungs as long as exposure exists, but there is no distinctive fibrosis, no evidence of disability and no special complicating factors.
Further information	No other specific acute or chronic health impact noted.
12. Ecological information	

Ecotoxicity	Alloys in massive forms present a limited hazard for the environment.
Persistence and degradability	The product is not biodegradable.
Bioaccumulative potential	No data available.
Mobility in soil	Alloys in massive forms are not mobile in the environment.
Other adverse effects	None expected.

13. Disposal considerations

Disposal instructions	Dispose in accordance with all applicable regulations.	
Hazardous waste code	Not regulated.	
Waste from residues / unused products	Dispose of in accordance with local regulations. Scrapped material should be sent for refining to recover precious metal content. Solid metal and alloys in the form of particles may be reactive. Its hazardous characteristics, including fire and explosion, should be determined prior to disposal.	
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied.	

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

US federal regulations Under some use conditions, this material may be considered to be hazardous in accordance with OSHA 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, 3	Subpt. D)
Not regulated.	
OSHA Specifically Regulated Substances (29 CFR 19	10.1001-1050)
Not listed.	
CERCLA Hazardous Substance List (40 CFR 302.4)	
Copper (CAS 7440-50-8)	LISTED

Superfund Amendments and F	Reauthorization Act of 1986	(SARA)		
Hazard categories	Delayed Hazard - No			
70°	Fire Hazard - No			
	Pressure Hazard - No			
	Reactivity Hazard - No			
SARA 302 Extremely haza	rdous substance	12		
Not listed.	17 .			
SARA 311/312 Hazardous chemical	No			
SARA 313 (TRI reporting)				
Chemical name		CAS number	% by wt.	
Copper		7440-50-8	1 - 10	
Other federal regulations				
Clean Air Act (CAA) Section	on 112 Hazardous Air Pollut	ants (HAPs) List		
Not regulated. Clean Air Act (CAA) Section	on 112(r) Accidental Release	e Prevention (40 CFR	68.130)	
Not regulated.				
Safe Drinking Water Act (SDWA)	Not regulated.			
US state regulations	This product does not cor defects or other reproduct	itain a chemical known tive harm.	to the State of Californ	nia to cause cancer, birth
US. Massachusetts R	FK - Substance List			
Copper (CAS 7440	-50-8)			
Tin (CAS 7440-31-	5)			
US. New Jersey Work	er and Community Right-to-	Know Act		
Copper (CAS 7440	-50-8) 5)			
US. Pennsylvania Wo	ker and Community Right-t	o-Know Law		
Copper (CAS 7440	-50-8)			
Tin (CAS 7440-31-	5)			
US. Rhode Island RTK				
Copper (CAS 7440	-50-8)			
US. California Proposition Not Listed.	65			
International Inventories				
Country(s) or region	Inventory name			On inventory (yes/no)*
Australia	Australian Inventory of Ch	nemical Substances (Al	ICS)	Yes
Canada	Domestic Substances Lis	t (DSL)		Yes
Canada	Non-Domestic Substance	s List (NDSL)		No
China	Inventory of Existing Cher	mical Substances in Ch	nina (IECSC)	Yes
Europe	European Inventory of Ex Substances (EINECS)	isting Commercial Che	mical	Yes
Europe	European List of Notified	Chemical Substances	(ELINCS)	No
Japan	Inventory of Existing and	New Chemical Substar	nces (ENCS)	No
Korea	Existing Chemicals List (E	ECL)		Yes
New Zealand	New Zealand Inventory			Yes
Philippines	Philippine Inventory of Ch (PICCS)	emicals and Chemical	Substances	Yes
United States & Puerto Ricc	Toxic Substances Contro	Act (TSCA) Inventory		Yes
*A "Yes" indicates this product A "No" indicates that one or mo country(s).	complies with the inventory requi are components of the product are	rements administered by e not listed or exempt fron	the governing country(s). n listing on the inventory a	administered by the governing
16. Other information, in	cluding date of prepar	ation or last revis	ion	

Issue date 28-May-2015 Revision date Solder-Safe 97/3 Lead-Free Solder 908003 Version #: 01 Revision date: Issue date: 28-May-2015

01 HMIS® is a registered trade and service mark of the NPCA. Health: 1 Flammability: 0 Physical hazard: 0 ACGIH EPA: AQUIRE database NLM: Hazardous Substances Data Base US. IARC Monographs on Occupational Exposures to Chemical Agents HSDB® - Hazardous Substances Data Bank IARC Monographs. Overall Evaluation of Carcinogenicity

Disclaimer

National Toxicology Program (NTP) Report on Carcinogens ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices All information in this Material Safety Data Sheet is believed to be accurate and reliable. However, no guarantee or warranty of any kind is made with regard to the accuracy of information or the suitability of the recommendations contained herein. It is the user's responsibility to assess the safety and toxicity of this product under their own conditions of use and to comply with all applicable laws and regulations.

Version # Further information HMIS® ratings

NFPA ratings

References

	Safety Data Sheet (SDS)
Section 1.	Identification
Product iden	tifier: White PVC Pipe

Trade names and Synonyms: N/A

Recommended Uses: Pipes and fittings for water supply, irrigation, sewerage, drainage, industrial process piping Telecommunications and electrical conduit.

Restrictions on Use: None

Company Identification: Cresline-West Inc. 600 Cross Pointe Blvd. Evansville, IN 47715 Telephone (General): 812-428-9300 Emergengcy Telephone: 812-428-9300

Section 2. Hazard Indentification

This product is not classified as hazardous under the U.S. Occupational Safety and Health Administration Hazard Communication Standard (HCS), 29 C.F.R. 1910.1200. PVC pipe, a finished product, is not a hazardous chemical under normal conditions of use and is categorized as an article. While an SDS is not required under the HCS, this document is being provided as a courtesy to our customers.

Section 3. Composition/Information on Ingredients

Composition and Form manufactured rigid solid tubes of various dimensions for plumbing and water distribution as described in Section 1.

Titanium Dioxide CAS: 13463-67-7 Weight: 0-5% Polyvinyl Chloride CAS: 9002-86-2 Weight: >80%

Silica, crystalline CAS: 14808-60-7 Weight: < .1%

Section 4. First-Aid Measures

EYE CONTACT: No effects anticipated under normal conditions of use. Particles generated by mechanical cutting, grinding or sanding can cause mechanical irritation. Immediately flush with large amounts of water, occasionally lifting the upper and lower eyelids to remove particles. Consult a physician if pain or irritation persists.

CREJLINE-WEST, INC.

Safety Data Sheet (SDS)

SKIN CONTACT: No effects anticipated under normal conditions of use. Cool skin rapidly if contacted with molten polymer. Obtain medical attention for thermal burns or skin irritation.

INHALATION: The product is not expected to present an inhalation hazard unless mechanically chipped or pulverized or if melted during fire. If dust or fumes are inhaled, remove to fresh air.

SWALLOWING: No adverse health effects expected from ingestion.

Description of the most important symptoms or effects, and any symptoms that are acute or delayed: none known.

Recommendations for immediate medical care and special treatment needed, when necessary: none known

Section 5. Fire-Fighting Measures

PVC PIPE DOES NOT PRESENT A FIRE OR EXPLOSION HAZARD UNDER NORMAL CONDITIONS OF USE. ALTHOUGH PVC PIPE WILL NOT SUPPORT COMBUSTION, IT WILL BURN, RELEASING HYDROGEN CHLORIDE GAS, DETECTABLE BY ITS PUNGENT ODOR.

SPECIAL FIRE FIGHTING PROCEDURES: Evacuate enclosed areas. Confined areas require selfcontained breathing apparatus. Extinguish using dry chemical, carbon dioxide, foam or water fog or spray equipment.

Section 6. Accidental Release Measures

Minor Spills Collect products and bundle or secure safely. If necessary, isolate area to prevent damage to /destruction of products by vehicles etc. Broken parts may be sharp and eye protection and glove are recommended.

Major Spills Isolate area as necessary to prevent further damage. Collect products and bundle or secure safely. Broken product and parts may have sharp edges and eye protection and gloves are recommended.

Section 7. Handling and Storage

PVC pipes presents no inhalation, ingestion or contact hazards. Cutting and grinding PVC pipe may release nuisance dust particles which are non-toxic. Care should be taken to avoid inhaling dust. Use any methods that keep dust to a minimum. General storage procedures are acceptable.

Section 8. Exposure Controls/Personal Protection

Exposure Controls No exposure controls are necessary as products are inert and all ingredients are encapsulated within the polymer matrix and are believed to present no hazard under conditions of normal use and good occupational work practice.

Personal Protection: Eye Glasses are recommended when handling pipe and especially when working pipes mechanically, sawing etc.

Hands/Feet Safety footwear and gloves.

Engineering Controls Appropriate controls for safe working when handling and mechanically working e.g. sawing.

Section 9. Physical and Chemical Properties

- Appearance (physical state, color, etc.); Solid white pipe and fittings. Color of pipes varies upon application (e.g. white, grey, blue, yellow, green).
- Upper/lower flammability or explosive limits; Not applicable
- Odor; Not available
- Vapor pressure; Not applicable
- Odor threshold; Not available
- Vapor density; Not applicable
- pH; Not applicable
- Relative density; Not Applicable
- Melting point/freezing point; Not Applicable
- Solubility(ies); insoluble in water
- Initial boiling point and boiling range; Not applicable
- Flash point; Not applicable
- Evaporation rate; Not applicable
- Flammability (solid, gas); will burn in contact with flame
- Partition coefficient: n-octanol/water; Not applicable
- Auto-ignition temperature; Not available
- Decomposition temperature; Not available
- Viscosity. Not applicable

Section 10. Stability and Reactivity

Reactivity

Stable at normal temperatures and pressures.

Chemical stability

Stable under normal storage conditions.

Other

- HAZARDOUS DECOMPOSITION PRODUCTS: Hydrogen chloride, benzene, carbon monoxide, carbon dioxide, aromatic and aliphatic hydrocarbons, and other gases could be released in fire.
- Incompatible materials: Do not store with oxidising agents.

CREJLINE-WEST, INC. Safety Data Sheet (SDS)

Section 11. Toxicological Information

No toxicological data were found for this product. The effects reported are those anticipated based on the components of this product.

POTENTIAL ROUTES OF EXPOSURE: Exposure under ordianry use conditions to hazardous chemicals is not anticipated. Inhalation of dust from mechanical cutting, sanding or grinding may occur. **SIGNS, SYMPTOMS, AND TOXIC EFFECTS OF OVEREXPOSURE:** Exposure to high concentrations of dust of this product may cause irritation of the respiratory tract with cough, difficulty breathing, dryness of the throat, or eye irritation.

ANIMAL TOXICITY DATA: No data found

REPRODUCTIVE EFFECTS: No data were found regarding reproductive effects in humans or animals of any component of this product.

MUTAGENICITY DATA: No mutagenicity data were found for any component of this product. **DESIGNATION AS POTENTIAL CARCINOGEN:** IARC designates PVC homopolymer as Group 3, "not classifiable as to its carcinogencity in humans," and titanium dioxide as Group 2B, "Possibly carcinogenic to humans"."

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: No data were found regarding this issue. INTERACTIONS WITH CHEMICALS THAT ENHANCE TOXICITY: No data were found regarding this issue.

Section 12. Ecological Information

No Data were found regarding adverse ecological impacts of this product.

Section 13. Disposal Considerations

Recycle where possible. Refer to state/territory environmental protection agency/authority. Normally suitable for disposal as general waste land fill.

Section 14. Transportation Information

Not Regulated.

Section 15. Regulatory Information

This plastic PVC pipe is an article and, therefore, exposure to titanium dioxide or silica is unlikely because the substances are inextricably bound in the plastic matrix. It is unlikely that titanium dioxide or silica will contribute to workplace exposures under normal conditions of use. While there is a possibility that mechanical cutting, sanding or grinding the product copuld produce respirable particles, it is not clear that the titanium dioxide or silica would be found as unbound particles of respirable size. Users must determine if respirable particles are produced in their operations. If so, then the appropriate Prop 65 warning language is as follows:

California's Proposition 65

WARNING: This product can expose you to chemicals including titanium dioxide, which are known to the State of California to cause cancer. For more information go to <u>www.P65Warnings.ca.gov</u>.

Please note that Prop 65 only requires the identification of one chemical per endpoint in the warning.

Section 16. Other Information

8/20/2018



SAFETY DATA SHEET

Section 1 – Product & Company Identification

Product Name: RIDGID Nu-Clear Thread Cutting Oil (Canada)

Product Catalog No.: 11461, 11481, 41575, 41585, 42513, 70835

Recommended Use: Thread Cutting

Restrictions on Use: Industrial use only

Company Information:

North America Ridge Tool Company 400 Clark Street Elyria, Ohio 44035-6001 1-800-519-3456 (8:00 am – 5:00 pm EST, M-F) Emergency Telephone call 9-1-1 or local emergency number www.RIDGID.com

Issue Date: May 2, 2018

I

Revision:



	Section 2 – Hazards Identification	
Hazard Classification	This product is classified as not hazardous per Canada Hazardous Product Regulations (WHMIS 2015)	
Label Elements		
Hazard Symbol:	No symbol	
Signal Word:	No signal word.	
Hazard Statement:	Not applicable	
Precautionary Statements	Not applicable	
Other hazards which do not result in GHS classification:	None.	

Section 3 – Composition / Information On Ingredients

Mixtures

Chemical Identity	Common name and synonyms	CAS number	Content in percent (%)*
Mineral oil	Mineral oil,	Trade Secret	30 - 60%
Paraffin oils	Paraffin oils,	Trade Secret	30 - 60%
Vegetable oil	Vegetable oil,	Trade Secret	1 - 5%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition Comments: This product does not contain silicone or chlorinated additives.

Section 4 – First Aid Measures

Ingestion:	Rinse mouth thoroughly. Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting.
Inhalation:	Move to fresh air. Call a POISON CENTER/doctor if you feel unwell.
Skin Contact:	Remove contaminated clothing and shoes. Wash contact areas with soap and water. If skin irritation occurs: Get medical advice/attention.



Eye contact:	Flush thoroughly with water. If irritation occurs, get medical assistance. Continue to rinse for at least 15 minutes.	
Most important symptoms/effec	ts, acute and delayed	
Symptoms:	No data available.	
Hazards:	No data available.	
Indication of immediate medical	attention and special treatment needed	
Treatment:	Get medical attention if symptoms occur.	
Se	ction 5 – Fire Fighting Measures	
General Fire Hazards:	No unusual fire or explosion hazards noted.	
Suitable (and unsuitable) exting	uishing media	
Suitable extinguishing media:	Water spray, fog, CO2, dry chemical, or regular foam. Use fire- extinguishing media appropriate for surrounding materials.	
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.	
Specific hazards arising from the chemical:	Heat may cause the containers to explode. During fire, gases hazardous to health may be formed.	
Special protective equipment an	d precautions for firefighters	
Special fire fighting procedures:	No data available.	
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.	
Sect	tion 6 – Accidental Release Measures	
Personal precautions, protective equipment and emergency procedures:	See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away. Ensure adequate ventilation.	

3

up:

Methods and material for



Environmental Precautions:	Avoid release to the environment. Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.
Se	ection 7 – Handling And Storage
Precautions for safe handling:	Observe good industrial hygiene practices. Wear appropriate personal protective equipment. Do not expose to intense heat as product may expand and pressurize container.
Conditions for safe storage, including any incompatibilities:	Store in original tightly closed container. Avoid contact with oxidizing agents. Store away from incompatible materials. Shelf Life: 720 Days

Section 8 – Exposure Controls / Personal Protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure Limit Values	Source
Mineral oil - Mist.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Mineral oil - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Mineral oil - Mist.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011)
	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011)
Paraffin oils - Mist.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Paraffin oils - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011)

	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011)
Paraffin oils - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Paraffin oils - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Vegetable oil - Mist.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Vegetable oil - Respirable mist.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Vegetable oil - Mist.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Vegetable oil - Mist.	8 HR ACL	10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	8 HR ACL	10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	15 MIN ACL	20 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	15 MIN ACL	20 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
Vegetable oil - Mist.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011)

Appropriate Engineering Controls

No data available.

Individual protection measures, such as personal protective equipment

General information:	Use personal protective equipment as required.		
Eye/face protection:	Wear safety glasses with side shields (or goggles).		
Skin Protection Hand Protection:	No data available.		
Other:	Wear protective clothing appropriate for the risk of exposure. Be aware of other hazards such as rotating parts. Contact health and safety professional or manufacturer for specific information.		
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from supervisor on the company's respiratory protection standards.		
Hygiene measures:	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.		



Section 9 – Physical And Chemical Properties

Appearance

Physical state: Form: Color: Odor: Odor threshold: pH: Melting point/freezing point: Initial boiling point and boiling range: Flash Point: Evaporation rate: Flammability (solid, gas): Upper/lower limit on flammability or explosive limits Flammability limit - upper (%): Flammability limit - lower (%): Explosive limit - upper (%): **Explosive limit - lower (%):** Vapor pressure:

Vapor density: Density: Relative density: Solubility(ies) Solubility in water: Solubility (other): Partition coefficient (n-octanol/water):

Auto-ignition temperature: Decomposition temperature:

Viscosity:

Other information VOC:

Liquid No data available. Yellow Mild petroleum/solvent No data available. No data available. No data available. 196.11 °C No data available. No data available.

No data available. No data available. No data available. No data available. No data available.

No data available. No data available. 0.878

Insoluble No data available. No data available.

No data available. No data available.

43 mm2/s (40 °C, Measured)

1.1 % (Method 24) 9.4 g/l (ASTM E 1868-10)



Section 10 – Stability And Reactivity		
Reactivity:	Not reactive during normal use.	
Chemical Stability:	Material is stable under normal conditions.	
Possibility of hazardous reactions:	None under normal conditions.	
Conditions to avoid:	Avoid heat or contamination.	
Incompatible Materials:	No data available.	
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.	

Section 11 – Toxicological Information

Information on likely routes of exposure

Inhalation: Inhalation is the primary route of exposure. In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.

Skin Contact: Prolonged skin contact may cause redness and irritation.

Eye contact: Eye contact is possible and should be avoided.

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
-------------	--------------------

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Not classified for acute toxicity based on available data.



Dermal Product:	
	Not classified for acute toxicity based on available data.
Inhalation Product:	Not classified for acute toxicity based on available data.
Delayed and immediate efference of the second secon	ects, including chronic effects from short- and long-term exposure No data available.
Skin Corrosion/Irritation Product:	No data available.
Serious Eye Damage/Eye Ir Product:	ritation No data available.
Respiratory or Skin Sensitia Product:	zation No data available.
Carcinogenicity Product:	No data available.
US. National Toxicology Pro No carcinogenic ACGIH Carcinogen List:	ogram (NTP) Report on Carcinogens: ; components identified
No carcinogenic	; components identified
Germ Cell Mutagenicity	
In vitro Product:	No data available.
In vivo Product:	No data available.
Reproductive toxicity Product:	No data available.
Other effects: Specific Target Organ To Product:	No data available. 5xicity - Single Exposure No data available.
Specific Target Organ To Product:	oxicity - Repeated Exposure No data available.
Aspiration Hazard Product:	
	No data available.



Section 12 – Ecological Information

Ecotoxicity:				
Acute hazards to the aquatic environment:				
Fish Product:	No data available.			
Aquatic Invertebrates Product:	No data available.			
Chronic hazards to the aquatic environment:				
Fish Product:	No data available.			
Aquatic Invertebrates Product:	No data available.			
Toxicity to Aquatic Plants Product:	No data available.			
Persistence and Degradability				
Biodegradation Product:	No data available.			
BOD/COD Ratio Product:	No data available.			
Bioaccumulative potential				
Bioconcentration Factor (I Product:	BCF) No data available.			
Partition Coefficient n-octanol / water (log Kow) Product: No data available.				
Mobility in soil: Other adverse effects:	No data available. No data available.			


Section 13 – Disposal Consideration		
Disposal instructions:	Discharge, treatment, or disposal may be subject to national, state, or local laws. Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must be applied.	
Contaminated Packaging:	Empty containers should be taken to an approved waste handling site for recycling or disposal.	

Section 14 – Transportation Information

TDG

Not regulated.

IMDG

Not regulated.

ΙΑΤΑ

Not regulated.

Section 15 – Regulatory Information

Canada Federal Regul List of Toxic Substance Not Regulated	ations es (CEPA, Schedule 1)	
Export Control List (C Not Regulated	EPA 1999, Schedule 3)	
National Pollutant Rela Canada. National I Reporting Require NPRI PT5	ease Inventory (NPRI) Pollutant Release Inventory ments Not Regulated	(NPRI) Substances, Part 5, VOCs with Additional
Canada. National I NPRI	Pollutant Release Inventory Not Regulated	(NPRI) (Schedule 1, Parts 1-4)
Greenhouse Gases		

Not Regulated



Section 16 – Other Information

Prepared by: Ridge Tool Company (Operating Standard 6-102)

RIDGE TOOL BELIEVES THE STATEMENTS, TECHNICAL INFORMATION AND RECOM-MENDATIONS CONTAINED HEREIN ARE RELIABLE BUT THEY ARE GIVEN WITHOUT WARRANTY OR GUARANTEE OF ANY KIND, EXPRESSED OR IMPLIED, AND WE ASSUME NO RESPONSIBILITY FOR ANY LOSS, DAMAGE OR EXPENSE, DIRECT OR CONSEQUENTIAL, ARISING OUT OF THEIR USE.



FICHE SANTÉ/SÉCURITÉ

1 – Identification du produit et du fournisseur

Produit: RIDGID Nu-Clear Thread Cutting Oil (Canada)

Réf. catalogue: 11461, 11481, 41575, 41585, 42513, 70835

Emploi recommandé: Filetage mécanique

Restrictions d'utilisation: Usage industriel seulement

Fournisseur:

North America Ridge Tool Company 400 Clark Street Elyria, Ohio 44035-6001 1-800-519-3456 (Etats-Unis) (du lundi au vendredi de 8h à 17h EST) Téléphone d'urgence: composer le 9-1-1 ou appeler les services d'urgences appropriés www.RIDGID.com

Date de publication: le 2 mai 2018

Révision



	2 – Identification des risques	
Classe de Danger	Ce produit est classé non dangereux selon le Règlement sur les produits dangereux du Canada (SIMDUT 2015)	
Éléments d'Étiquetage		
Symbole de Danger:	Aucun symbole	
Mention d'Avertissement:	Aucun mot indicateur.	
Mention de Danger:	Non applicable	
Conseils de Prudence	Non applicable	
Autres dangers ne donnant pas lieu à classement selon le SGH:	Aucun(e).	

3 – Composition du produit et renseignements sur ses ingrédients

Mélanges

Identité Chimique	Nom commun et synonymes	Numéro CAS	Teneur en pourcentage (%)*
Mineral oil	Mineral oil,	Secret industriel	30 - 60%
Paraffin oils	Paraffin oils,	Secret industriel	30 - 60%
Vegetable oil	Vegetable oil,	Secret industriel	1 - 5%

* Toutes les concentrations sont exprimées en pourcentage pondéral sauf si le composant est un gaz. Les concentrations de gaz sont exprimées en pourcentage volumique.

Remarques sur la Composition:

Ce produit ne contient pas de silicone ou d'additifs chlorés.



	4 – Premiers soins			
Ingestion:	Rincer soigneusement la bouche. Appeler un CENTRE ANTIPOISON/un médecin en cas de malaise. NE PAS faire vomir.			
Inhalation:	Transporter à l'air frais. Appeler un CENTRE ANTIPOISON/un médecin en cas de malaise.			
Contact avec la Peau:	Enlever les vêtements et les chaussures contaminés. Laver les zones de contact à l'eau et au savon. En cas d'irritation cutanée: consulter un médecin.			
Contact oculaire:	Rincer avec soin à l'eau. En cas d'irritation, consulter un médecin. Continuer à rincer pendant au moins 15 minutes.			
Symptômes/effets les plus impo	rtants, aigus et différés			
Symptômes:	Aucune information disponible.			
Dangers:	Aucune information disponible.			
Indication d'un besoin médical i	mmédiat et traitement spécial requis			
Traitement:	Consulter un médecin en cas de symptômes.			

5 – Lutte contre les incendies

Dangers d'Incendie Généraux: Aucun risque exceptionnel d'incendie et d'explosion.

Moyens d'extinction appropriés (et inappropriés)

Moyens d'extinction appropriés:	Eau pulvérisée, brouillard, CO2, agent chimique sec ou mousse standard. Choisir le moyen d'extinction de l'incendie en tenant compte d'autres produits chimiques éventuels.
Moyens d'extinction inappropriés:	Ne pas lutter contre l'incendie au jet d'eau pour ne pas propager les flammes.
Dangers spécifiques dus au produit chimique:	La chaleur peut provoquer l'explosion des récipients. En cas d'incendie, des gaz dangereux pour la santé peuvent se former.
Équinament de protection ané	sial et présoutions nour les nompiers

Équipement de protection spécial et précautions pour les pompiers

Procédures spéciales de	Aucune information disponible.
lutte contre l'incendie:	



Équipement de protection spécial pour le personnel préposé à la lutte contre le feu: Les pompiers doivent porter un équipement de protection standard, notamment vêtement ignifuge, casque à masque facial, gants, bottes en caoutchouc et, dans les espaces clos, un appareil respiratoire autonome.

6 – Lutte contre les déversements accidentels

Précautions individuelles, équipement de protection et procédures d'urgence:	Voir l'équipement de protection individuelle à la Section 8. Ne pas toucher les récipients endommagés ou le produit déversé à moins de porter les vêtements de protection appropriés. Maintenir à distance le personnel non autorisé. Assurer une ventilation adéquate.
Méthodes et matériel de confinement et de nettoyage:	Absorber le produit avec du sable ou un autre absorbant inerte. Arrêter le débit de matière, si ceci est sans risque.
Précautions pour la Protection de l'Environnement:	Éviter le rejet dans l'environnement. Ne pas contaminer les sources d'eau ou les égouts. Endiguer la fuite ou le déversement si cela peut être fait sans danger.

7 – Manipulation et stockage

Précautions à prendre pour une manipulation sans danger:	Se conformer aux bonnes pratiques d'hygiène industrielle. Porter un équipement de protection personnelle approprié. N'exposez pas à la chaleur intense comme le produit peut développer et pressuriser le récipient.
Conditions d'un stockage sûr, y compris d'éventuelles incompatibilités:	Conserver dans le récipient d'origine hermétiquement fermé. Éviter tout contact avec des agents comburants. Conserver à l'écart des matières incompatibles. Durée de conservation: 720 jours



8 – Risques d'exposition et protection individuelle

Paramètres de Contrôle

Valeurs Limites d'Exposition Professionnelle

Identité Chimique	Туре	Valeurs Limites d'Exposition	Source
Mineral oil - Brouillard	TWA	1 mg/m3	Canada. Colombie-Britannique VLE's. (Valeurs limite d'exposition pour les substances chimiques, Réglementation sur la santé et sécurité au travail 296/97, et ses modifications. (05 2013)
Mineral oil - Fraction inhalable.	TWA	5 mg/m3	Canada. Ontario VLE's. (Contrôle de l'exposition aux agents biologiques ou chimiques) (06 2015)
	TWA	5 mg/m3	Canada. Ontario VLE's. (Contrôle de l'exposition aux agents biologiques ou chimiques) (06 2015)
Mineral oil - Brouillard	STEL		Canada. VLEs du Québec, (Ministère du Travail. Règlement sur la qualité du milieu de travail) (11 2011)
	TWA	5 mg/m3	Canada. VLEs du Québec, (Ministère du Travail. Règlement sur la qualité du milieu de travail) (11 2011)
Paraffin oils - Brouillard	TWA	1 mg/m3	Canada. Colombie-Britannique VLE's. (Valeurs limite d'exposition pour les substances chimiques, Réglementation sur la santé et sécurité au travail 296/97, et ses modifications. (05 2013)
	TWA	0.2 mg/m3	Canada. Colombie-Britannique VLE's. (Valeurs limite d'exposition pour les substances chimiques, Réglementation sur la santé et sécurité au travail 296/97, et ses modifications. (05 2013)
Paraffin oils - Brouillard	TWA	5 mg/m3	Canada. VLEs du Québec, (Ministère du Travail. Règlement sur la qualité du milieu de travail) (11 2011)
	STEL	10 mg/m3	Canada. VLEs du Québec, (Ministère du Travail. Règlement sur la qualité du milieu de travail) (11 2011)
Paraffin oils - Fraction inhalable.	TWA	5 mg/m3	Canada. Ontario VLE's. (Contrôle de l'exposition aux agents biologiques ou chimiques) (06 2015)
	TWA	5 mg/m3	Canada. Ontario VLE's. (Contrôle de l'exposition aux agents biologiques ou chimiques) (06 2015)
Paraffin oils - Fraction inhalable.	TWA	5 mg/m3	Les Etats-Unis. Valeurs de Limite de Seuil d'ACGIH (03 2014)
Vegetable oil - Brouillard	TWA	10 mg/m3	Canada. Colombie-Britannique VLE's. (Valeurs limite d'exposition pour les substances chimiques, Réglementation sur la santé et sécurité au travail 296/97, et ses modifications. (09 2011)
Vegetable oil - Brouillard respirable.	TWA	3 mg/m3	Canada. Colombie-Britannique VLE's. (Valeurs limite d'exposition pour les substances chimiques, Réglementation sur la santé et sécurité au travail 296/97, et ses modifications. (09 2011)
Vegetable oil - Brouillard	TWA	10 mg/m3	Canada. Ontario VLE's. (Contrôle de l'exposition aux agents biologiques ou chimigues) (11 2010)



Vegetable oil - Brouillard	8 HR ACL	10 mg/m3	Canada. OEL de la Saskatchewan (Règlement sur la santé et la sécurité au travail, 1996, tableau 21) (05 2009)
	8 HR ACL	10 mg/m3	Canada. OEL de la Saskatchewan (Règlement sur la santé et la sécurité au travail, 1996, tableau 21) (05 2009)
	15 MIN ACL	20 mg/m3	Canada. OEL de la Saskatchewan (Règlement sur la santé et la sécurité au travail, 1996, tableau 21) (05 2009)
	15 MIN ACL	20 mg/m3	Canada. OEL de la Saskatchewan (Règlement sur la santé et la sécurité au travail, 1996, tableau 21) (05 2009)
Vegetable oil - Brouillard	TWA	10 mg/m3	Canada. VLEs du Québec, (Ministère du Travail. Règlement sur la qualité du milieu de travail) (11 2011)

Contrôles Techniques Appropriés Aucune information disponible.

Mesures de protection individuelle, telles que les équipements de protection individuelle

Informations générales:	Utiliser l'équipement de protection individuel requis.	
Protection des yeux/du visage:	Porter des lunettes de sécurité à écrans latéraux ou des lunettes étanches.	
Protection de la Peau Protection des Mains:	Aucune information disponible.	
Autres:	Porter des vêtements de protection appropriés au risque d'exposition. Soyez conscient des autres dangers tels que les pièces en rotation. Contacter un professionnel de la santé et de la sécurité ou un fabricant pour obtenir des informations spécifiques.	
Protection Respiratoire:	En cas de ventilation insuffisante, porter un appareil respiratoire approprié. Demander l'avis du superviseur sur les normes de protection respiratoire de la société.	
Mesures d'hygiène:	Toujours adopter de bonnes pratiques d'hygiène personnelle, telles que lavage après manipulation de la substance et avant de manger, de boire ou de fumer. Laver régulièrement la tenue de travail pour éliminer les contaminants. Mettre au rebut les chaussures qui ne peuvent pas être lavées.	

9 – Caractéristiques physiques et chimiques

Aspect	
État:	Liquide
Forme:	Aucune information disponible.
Couleur:	Jaune
Odeur:	Légère, Pétrole/solvant
Seuil de perception de l'odeur:	Aucune information disponible.



pH:	Aucune information disponible.	
Point de fusion/point de congélation:	Aucune information disponible.	
Température d'ébullition initiale et intervalle d'ébullition:	Aucune information disponible.	
Point d'éclair:	196.11 °C	
Taux d'évaporation:	Aucune information disponible.	
Inflammabilité (solide, gaz):	Aucune information disponible.	
Limites supérieures/inférieures d'inflammabilité ou d'ex	plosivité	
Limites d'inflammabilité - supérieure (%):	Aucune information disponible.	
Limites d'inflammabilité - inférieure (%):	Aucune information disponible.	
Limites d'explosivité - supérieure (%) :	Aucune information disponible.	
Limites d'explosivité - inférieure (%):	Aucune information disponible.	
Pression de vapeur:	Aucune information disponible.	
Densité de vapeur:	Aucune information disponible.	
Densité:	Aucune information disponible.	
Densité relative:	0.878	
Solubilités		
Solubilité dans l'eau:	Insoluble	
Solubilité (autre):	Aucune information disponible.	
Coefficient de partition (n-octanol/eau):	Aucune information disponible.	
Température d'auto-inflammation:	Aucune information disponible.	
Température de décomposition:	Aucune information disponible.	
Viscosité:	43 mm2/s (40 °C, Mesurée)	
AUTRES INFORMATIONS		
VOC:	1.1 % (Method 24) 9.4 g/l (ASTM E 1868-10)	

10 – Stabilité et réactivité	
Réactivité:	Non réactif pendant l'utilisation normale.
Stabilité Chimique:	Ce produit est stable dans des conditions normales.
Possibilité de Réactions Dangereuses:	Aucun(e)(s) dans les conditions normales.
Conditions à Éviter:	Éviter tout chauffage ou contamination.



Matières Incompatibles:	Aucune information disponible.
Produits de Décomposition Dangereux:	La décomposition thermique ou la combustion peut libérer des oxydes de carbone et d'autres gaz ou vapeurs toxiques.
	11 – Données toxicologiques
Informations sur les voies d'ex Inhalation:	position probables L'inhalation est la principale voie d'exposition. À concentration élevée, les vapeurs, émanations ou brouillards peuvent être irritants pour le nez, la gorge et les muqueuses.
Contact avec la Peau:	Le contact prolongé avec la peau peut entraîner des rougeurs et de l'irritation.
Contact oculaire:	Le contact oculaire est possible ; il doit être évité.
Ingestion:	Peut être ingéré par accident. L'ingestion peut provoquer irritation et malaises.
Symptômes liés aux caractérist	iques physiques, chimiques et toxicologiques
Inhalation:	Aucune information disponible.
Contact avec la Peau:	Aucune information disponible.
Contact oculaire:	Aucune information disponible.
Ingestion:	Aucune information disponible.
Informations sur les effets toxic	cologiques
Toxicité aiguë (répertorier to	utes les voies d'exposition possibles)
Ingestion Produit:	Non classé comme présentant une toxicité aiguë d'après les données disponibles.
Contact avec la peau Produit:	Non classé comme présentant une toxicité aiguë d'après les données disponibles.
Inhalation Produit:	Non classé comme présentant une toxicité aiguë d'après les données disponibles.
Effets différés et immédiats, et Produit:	effets chroniques d'une exposition de courte et de longue durée Aucune information disponible.



Corrosion ou Irritation de la Pea	J
Produit:	Aucune information disponible.
Blessure ou Irritation Grave des	Yeux
Produit:	Aucune information disponible.
Sensibilisation Respiratoire ou C	Cutanée
Produit:	Aucune information disponible.
Cancérogénicité Produit:	Aucune information disponible.
Monographies du CIRC sur l'éva	luation des risques de cancérogénicité pour l'homme:
Aucun composant car	ncérigène identifié
États-Unis. Rapport du NTP (Nat	ional Toxicilogy Program) sur les cancérogènes :
Aucun composant car	ncérigène identifié
Liste des cancérogènes de l'ACC	GIH:
Aucun composant car	ncérigène identifié
Mutagénicité des Cellules Germi	nales
In vitro Produit:	Aucune information disponible.
In vivo Produit:	Aucune information disponible.
Toxicité pour la reproduction Produit:	Aucune information disponible.
Toxicité Spécifique au Niveau de	l'Organe Cible- Exposition Unique
Produit:	Aucune information disponible.
Toxicité Spécifique au Niveau de	l'Organe Cible- Expositions répétées
Produit:	Aucune information disponible.
Risque d'Aspiration Produit:	Aucune information disponible.
Autres effets:	Aucune information disponible.

RIDGII

	12 – Données écologiques		
,			
Écotoxicité:			
Risques aigus pour l'envire	onnement aquatique:		
Poisson Produit:	Aucune information disponible.		
Invertébrés Aquatiques Produit:	Aucune information disponible.		
Risques chroniques pour l	'environnement aquatique:		
Poisson Produit:	Aucune information disponible.		
Invertébrés Aquatiques Produit:	Aucune information disponible.		
Toxicité pour les plantes aquatiquesProduit:Aucune information disponible.			
Persistance et Dégradabilité			
Biodégradation			
Produit:	Aucune information disponible.		
Rapport DBO/DCO Produit:	Aucune information disponible.		
Potentiel de Bioaccumulation			
Facteur de Bioconcentration (BCF)Produit:Aucune information disponible.			
Coefficient de Partage n-octanol/eau (log Kow)Produit:Aucune information disponible.			
Mobilité dans le Sol: Autres Effets Néfastes:	Aucune information disponible. Aucune information disponible.		



Instructions pour l'élimination: Le rejet, le traitement et l'élimination peuvent être soumis à des lois nationales, régionales ou locales. Éliminer les déchets dans une installe de traitement et d'élimination des déchets appropriée conformément au lois et aux réglementations en vigueur et en fonction des caractéristique du produit au moment de l'élimination. C'est la responsabilité de l'utilisa de produit ou du propriétaire pour déterminer au moment de la dispositi qui se perdent les règlements doivent être appliqués. Emballages Contaminés: Les conteneurs vides doivent être acheminés vers un site agréé pour le traitement des déchets à des fins de recyclage ou d'élimination. 14 – Transport TDG Non réglementé. IMDG Non réglementé. IATA Non réglementé. IATA Non réglementé. Liste des substances toxiques (LCPE, Annexe 1) Non réglementé Liste des substances d'exportation contrôlée (LCPE 1999, Annexe 3) Non réglementé Inventaire national des rejets de polluants (INRP) Canada Substances de l'Inventaire national des rejets de polluants (INRP), partie 5, COV's faisant r'objet d'une déclaration plus détaillée NPRI PT5 NPRI		13 – Recyclage
Emballages Contaminés: Les conteneurs vides doivent être acheminés vers un site agréé pour le traitement des déchets à des fins de recyclage ou d'élimination. 14 – Transport	Instructions pour l'élimination:	Le rejet, le traitement et l'élimination peuvent être soumis à des lois nationales, régionales ou locales. Éliminer les déchets dans une installation de traitement et d'élimination des déchets appropriée conformément aux lois et aux réglementations en vigueur et en fonction des caractéristiques du produit au moment de l'élimination. C'est la responsabilité de l'utilisateu de produit ou du propriétaire pour déterminer au moment de la disposition qui se perdent les règlements doivent être appliqués.
14 – Transport TDG Non réglementé. IMDG Non réglementé. IATA Non réglementé. IATA Non réglementé. IATA Mon réglementé. IST – Réglementation Mon réglementé. Liste des substances toxiques (LCPE, Annexe 1) Non réglementé Non réglementé Liste des substances d'exportation contrôlée (LCPE 1999, Annexe 3) Non réglementé Inventaire national des rejets de polluants (INRP) Canada Substances de l'Inventaire national des rejets de polluants (INRP), partie 5, COV's faisant l'objet d'une déclaration plus détaillée NPRI PT5 Non réglementé Canada. Loi canadienne sur la protection de l'environnement (CEPA). Inventaire national des rejets de polluants (INRP) (Gaz.Can. Partie I, 135:12, 940) NPRI Non réglementé	Emballages Contaminés:	Les conteneurs vides doivent être acheminés vers un site agréé pour le traitement des déchets à des fins de recyclage ou d'élimination.
TDG Non réglementé. IMDG Non réglementé. IATA Non réglementé.		14 – Transport
IMDG Non réglementé. IATA Non réglementé. ISTA Son réglementé. Sequementations fédérales du Canada Liste des substances toxiques (LCPE, Annexe 1) Non réglementé Liste des substances d'exportation contrôlée (LCPE 1999, Annexe 3) Non réglementé Inventaire national des rejets de polluants (INRP) Canada Substances de l'Inventaire national des rejets de polluants (INRP), partie 5, COV's faisant l'objet d'une déclaration plus détaillée NPRI PT5 Non réglementé Canada. Loi canadienne sur la protection de l'environnement (CEPA). Inventaire national des rejets de polluants (INRP) Non réglementé NPRI Non réglementé	TDG Non réglementé.	
IATA Non réglementé.	IMDG Non réglementé.	
15 – Réglementation Réglementations fédérales du Canada Liste des substances toxiques (LCPE, Annexe 1) Non réglementé Non réglementé Liste des substances d'exportation contrôlée (LCPE 1999, Annexe 3) Non réglementé Non réglementé Inventaire national des rejets de polluants (INRP) Canada Substances de l'Inventaire national des rejets de polluants (INRP), partie 5, COV's faisant l'objet d'une déclaration plus détaillée NPRI PT5 Non réglementé Canada. Loi canadienne sur la protection de l'environnement (CEPA). Inventaire national des rejets de polluants (INRP) (Gaz.Can. Partie I, 135:12, 940) NPRI Non réglementé	IATA Non réglementé.	
Réglementations fédérales du Canada Liste des substances toxiques (LCPE, Annexe 1) Non réglementé Liste des substances d'exportation contrôlée (LCPE 1999, Annexe 3) Non réglementé Inventaire national des rejets de polluants (INRP) Canada Substances de l'Inventaire national des rejets de polluants (INRP), partie 5, COV's faisant l'objet d'une déclaration plus détaillée NPRI PT5 Non réglementé Canada. Loi canadienne sur la protection de l'environnement (CEPA). Inventaire national des rejets de polluants (INRP) (Gaz.Can. Partie I, 135:12, 940) NPRI Non réglementé		15 – Réglementation
Liste des substances d'exportation contrôlée (LCPE 1999, Annexe 3) Non réglementé Inventaire national des rejets de polluants (INRP) Canada Substances de l'Inventaire national des rejets de polluants (INRP), partie 5, COV's faisant l'objet d'une déclaration plus détaillée NPRI PT5 Non réglementé Canada. Loi canadienne sur la protection de l'environnement (CEPA). Inventaire national des rejets de polluants (INRP) (Gaz.Can. Partie I, 135:12, 940) NPRI Non réglementé	Réglementations fédérales du C Liste des substances toxiques (Non réglementé	anada LCPE, Annexe 1)
Inventaire national des rejets de polluants (INRP) Canada Substances de l'Inventaire national des rejets de polluants (INRP), partie 5, COV's faisant l'objet d'une déclaration plus détaillée NPRI PT5 Non réglementé Canada. Loi canadienne sur la protection de l'environnement (CEPA). Inventaire national des rejets de polluants (INRP) (Gaz.Can. Partie I, 135:12, 940) NPRI Non réglementé	Liste des substances d'exportat Non réglementé	ion contrôlée (LCPE 1999, Annexe 3)
Canada. Loi canadienne sur la protection de l'environnement (CEPA). Inventaire national des rejets de polluants (INRP) (Gaz.Can. Partie I, 135:12, 940) NPRI Non réglementé	Inventaire national des rejets de Canada Substances de l'Inve l'objet d'une déclaration plus NPRI PT5	polluants (INRP) entaire national des rejets de polluants (INRP), partie 5, COV's faisant s détaillée Non réglementé
-	Canada. Loi canadienne sur la rejets de polluants (INRP) (Ga NPRI No	a protection de l'environnement (CEPA). Inventaire national des z.Can. Partie I, 135:12, 940) on réglementé

Non réglementé



-

Produit: RIDGID Nu-Clear Thread Cutting Oil (Canada)

	16 – Renseignements divers
Rédaction :	Ridge Tool Company (OPSTD 6-102)
Date de publication : Dernière révision :	le 2 mai 2018 le 10 mai 2017

Quoi que la société Ridge Tool estime que les affirmations, informations techniques et recommandations ci-présentes sont dignes de confiance, celles-ci ne sont données qu'à titre indicatif, sans aucune garantie expresse ou implicite, et ne sauraient engager la responsabilité civile de la société en cas de pertes, dommages et intérêts, voire frais directs ou indirects relevant de leur application.



SAFETY DATA SHEET

1. Identification

Product identifier	Hercules Glug
Other means of identification	
Product code	7319E
Synonyms	Part Numbers: 20410, 20412, 20413, 20415
Recommended use	Drain Opener.
Recommended restrictions	None known.
Manufacturer/Importer/Supplie	r/Distributor information
Company Name	HCC Holdings, Inc. an Oatey Affiliate
Address	4700 West 160th Street
	Cleveland, OH 44135
Telephone	216-267-7100
E-mail	info@oatey.com
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)
Emergency First Aid	1-877-740-5015
Contact person	MSDS Coordinator

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Skin corrosion/irritation	Category 1A
	Serious eye damage/eye irritation	Category 1
OSHA defined hazards	Not classified.	

Label elements



Signal word	Danger
Hazard statement	Causes severe skin burns and eye damage.
Precautionary statement	
Prevention	Do not breathe dust or mists. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%	
Sodium hydroxide	1310-73-2	95-100	
Other components below reportable levels		1	
Hercules Glug		:	SDS US
925649 Version #: 01 Revision date: - Issue date: 22-April-2015			1/7

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures	
Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.

6. Accidental release measures

General fire hazards

o. Accidental release meat	
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

No unusual fire or explosion hazards noted.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Sodium hydroxide (CAS 1310-73-2)	PEL	2 mg/m3	
US. ACGIH Threshold Limit \	/alues		
Components	Туре	Value	
Sodium hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3	
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	
Sodium hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3	
Biological limit values	No biological exposure limits noted for the ingredient(s).		
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.		
Individual protection measures, s	such as personal protective equipm	nent	
Eye/face protection	Wear safety glasses with side shields (or goggles) and a face shield.		
Skin protection			
Hand protection	Wear appropriate chemical resistant gloves.		
Other	Wear appropriate chemical resistant clothing.		
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.		
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.		
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.		

9. Physical and chemical properties

Appearance		
Physical state	Solid.	
Form	Flakes.	
Color	Not available.	
Odor	None.	
Odor threshold	Not available.	
рН	13 - 14 (1% Solution)	
Melting point/freezing point	Not available.	
Initial boiling point and boiling range	Not determined	
Flash point	> 212.0 °F (> 100.0 °C)	
Evaporation rate	Not available.	
Flammability (solid, gas)	Not available.	
Upper/lower flammability or explosive limits		
Flammability limit - lower (%)	Not available.	
Flammability limit - upper (%)	Not available.	
Explosive limit - lower (%)	Not available.	
Explosive limit - upper (%)	Not available.	

Vapor pressure	Not available.
Vapor density	Not available.
Relative density	> 2.13
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
VOC (Weight %)	0 g/l

10. Stability and reactivity

Reactivity	Reacts violently with strong acids. This product may react with oxidizing agents.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Do not mix with other chemicals. Contact with incompatible materials.
Incompatible materials	Strong acids. Acids. Oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause irritation to the respiratory system. Prolonged inhalation may be harmful.
Skin contact	Causes severe skin burns.
Eye contact	Causes serious eye damage.
Ingestion	Causes digestive tract burns.
Symptoms related to the physical, chemical and toxicological characteristics	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Information on toxicological effects

Acute toxicity

Product	Species	Test Results
Hercules Glug (CAS Mixture)		
Acute		
Dermal		
LD50	Rabbit	1350 mg/kg
Oral		
LD50	Rat	140 mg/kg
* Estimates for product may b	e based on additional component data not shown.	
Skin corrosion/irritation	Causes severe skin burns and eye damage.	
Serious eye damage/eye irritation	Causes serious eye damage.	
Respiratory or skin sensitization	n	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT	
UN	number
UN	proper ship

	UN number	UN1823	
	UN proper shipping name	Sodium hydroxide, solid	
	Transport hazard class(es)		
	Class	8	
	Subsidiary risk	-	
	Label(s)	8	
	Packing group	11	
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.	
	Special provisions	IB8, IP2, IP4, T3, TP33	
	Packaging exceptions	154	
	Packaging non bulk	212	
	Packaging bulk	240	
ΙΑΤ	A		
	UN number	UN1823	
	UN proper shipping name	Sodium hydroxide, solid	
	Transport hazard class(es)		
	Class	8	
	Subsidiary risk	-	
	Packing group	11	
	Environmental hazards	No.	
	ERG Code	8L	
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.	
IMC	G		
	UN number	UN1823	
	UN proper shipping name	SODIUM HYDROXIDE, SOLID	

Transport hazard class(es) Class Subsidiary risk Packing group Environmental hazards Marine pollutant EmS Special precautions for user Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code 15. Regulatory information	8 - II No. F-A, S-B Read safety instructions, SDS and emergency p Not applicable. This product is a "Hazardous Chemical" as defi	procedures before handling. ned by the OSHA Hazard Communication		
	Standard, 29 CFR 1910.1200.			
TSCA Section 12(b) Export N	otification (40 CFR 707, Subpt. D)			
OSHA Specifically Regulated	Substances (29 CFR 1910.1001-1050)			
Not listed.				
CERCLA Hazardous Substar	ce List (40 CFR 302.4)			
Sodium hydroxide (CAS 1	USIED			
Hazard categories	Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - Yes			
SARA 302 Extremely hazard	ous substance			
Not listed.				
SARA 311/312 Hazardous chemical	No			
SARA 313 (TRI reporting) Not regulated.				
Other federal regulations				
Clean Air Act (CAA) Section Not regulated. Clean Air Act (CAA) Section	Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Not regulated. Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)			
Not regulated.				
Safe Drinking Water Act (SDWA)	Not regulated.			
US state regulations				
US. Massachusetts RTK - Su	bstance List			
Sodium hydroxide (CAS 1 US. New Jersey Worker and	Sodium hydroxide (CAS 1310-73-2) US. New Jersey Worker and Community Right-to-Know Act			
Sodium hydroxide (CAS 1 US. Pennsylvania Worker an	Sodium hydroxide (CAS 1310-73-2) US. Pennsylvania Worker and Community Right-to-Know Law			
Sodium hydroxide (CAS 1 US. Rhode Island RTK	310-73-2)			
Sodium hydroxide (CAS 1	310-73-2)			
US. California Proposition 66 California Safe Drinking W any chemicals currently lis	US. California Proposition 65 California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.			
International Inventories				
Country(s) or region Australia	Inventory name Australian Inventory of Chemical Substances (A	AICS) On inventory (yes/no)*		

Hercules Glug

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	22-April-2015
Revision date	-
Version #	01
HMIS® ratings	Health: 3 Flammability: 0 Physical hazard: 1

NFPA ratings



Disclaimer

HCC Holdings Inc. an Oatey Affiliate cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.



SAFETY DATA SHEET

1. Identification

Product identifier	Oatey 95/5 Lead Free Solder (Plumbing, Acid or Rosin Core)		
Other means of identification			
SDS number	1600E		
Synonyms	Part Numbers: 22004, 22018, 22025, 22017, 53026, 53181, 53027, 53189, 53171, 53173, 53175, 53177, 53190, 29031, 53170, 53172, 53174, 53176		
Recommended use	Joining Copper Pipes. Joining Copper Tubing.		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplier/Distributor information			
Company Name	Oatey Co.		
Address	4700 West 160th St.		
	Cleveland, OH 44135		
Telephone	216-267-7100		
E-mail	info@oatey.com		
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)		
Emergency First Aid	1-877-740-5015		
Contact person	MSDS Coordinator		

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Not classified.	
Environmental hazards	Hazardous to the aquatic environment, long-term hazard	Category 3
OSHA defined hazards	Not classified.	
Label elements		
Hazard symbol	None.	
Signal word	None.	
Hazard statement	Harmful to aquatic life with long lasting effects.	
Precautionary statement		
Prevention	Avoid release to the environment.	
Response	Wash hands after handling.	
Storage	Store away from incompatible materials.	
Disposal	Dispose of contents/container in accordance w	ith local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.	

3. Composition/information on ingredients

Chemical name	CAS number	%
Tin	7440-31-5	60-100
Antimony	7440-36-0	3-7

4. First-aid measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
Skin contact	Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. If ingestion of a large amount does occur, call a poison control center immediately.

Most important symptoms/effects, acute and delayed Indication of immediate medical attention and special treatment needed General information

Provide general supportive measures and treat symptomatically.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Dry sand. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Use water spray to cool unopened containers.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Stop the flow of material, if this is without risk. Dike far ahead of spill for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.
7. Handling and storage	
Precautions for safe handling	Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. Use care in handling/storage.
	Other is a single blick the share dependence. Other success from income with the materials (see Opention 40)

Conditions for safe storage, including any incompatibilities Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Antimony (CAS 7440-36-0)	PEL	0.5 mg/m3	
Tin (CAS 7440-31-5)	PEL	2 mg/m3	
US. ACGIH Threshold Limit Values	S		
Components	Туре	Value	
Antimony (CAS 7440-36-0)	TWA	0.5 mg/m3	
Tin (CAS 7440-31-5)	TWA	2 mg/m3	
US. NIOSH: Pocket Guide to Chen	nical Hazards		
Components	Туре	Value	
Antimony (CAS 7440-36-0)	TWA	0.5 mg/m3	
Tin (CAS 7440-31-5)	TWA	2 mg/m3	

Biological limit values	No biological exposure limits noted for the ingredient(s).		
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.		
Individual protection measures,	such as personal protective equipment		
Eye/face protection	Wear safety glasses with side shields (or goggles).		
Skin protection			
Hand protection	Wear appropriate chemical resistant gloves.		
Other	Wear suitable protective clothing.		
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.		
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.		
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.		

9. Physical and chemical properties

Appearance	
Physical state	Solid.
Form	Solid. Wire.
Color	Silver.
Odor	None.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	450 - 464 °F (232.22 - 240 °C)
Initial boiling point and boiling range	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	9 - 11
Solubility(ies)	
Solubility (water)	Not soluble.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
VOC (Weight %)	0
10. Stability and reactivity	

Reactivity

Chemical stability

The product is stable and non-reactive under normal conditions of use, storage and transport. Material is stable under normal conditions.

Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.

Information on toxicological effects

Acute toxicity	Not available.		
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.		
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.		
Respiratory or skin sensitization			
Respiratory sensitization	Not available.		
Skin sensitization	This product is not expected to cause skin sensitization.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.		
OSHA Specifically Regulated	l Substances (29 CFR 1910.1001-1050)		
Not listed.			
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.		
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not available.		
Chronic effects	Prolonged inhalation may be harmful.		
12. Ecological information			
Ecotoxicity	Harmful to aquatic life with long lasting effects.		
Persistence and degradability	No data is available on the degradability of this product.		

Persistence and degradability	No data is available on the degradability of this product.		
Bioaccumulative potential	No data available.		
Mobility in soil	No data available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.				
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)					
Not regulated. OSHA Specifically Regulate	d Substances (29 CFR 1910.1	001-1050)			
CERCLA Hazardous Substa	nce List (40 CFR 302.4)				
Antimony (CAS 7440-36-0) LISTED					
Superfund Amendments and Reauthorization Act of 1986 (SARA)					
Hazard categories	Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No	,			
SARA 302 Extremely hazard Not listed.	ous substance				
SARA 311/312 Hazardous chemical	No				
SARA 313 (TRI reporting) Chemical name		CAS number	% by wt.		
Antimony		7440-36-0	3-7		
Other federal regulations					
Clean Air Act (CAA) Section	112 Hazardous Air Pollutant	s (HAPs) List			
Antimony (CAS 7440-36- Clean Air Act (CAA) Section	0) 112(r) Accidental Release Pr	evention (40 CFR 68	.130)		
Not regulated.					
(SDWA)	Not regulated.				
US state regulations					
US. Massachusetts RTK - Si	ubstance List				
Antimony (CAS 7440-36-0) Tin (CAS 7440-31-5)					
US. New Jersey Worker and Community Right-to-Know Act					
US. New Jersey Worker and	Community Right-to-Know A	Act			
US. New Jersey Worker and Antimony (CAS 7440-36-0 Tin (CAS 7440-31-5)	Community Right-to-Know A	Act			
US. New Jersey Worker and Antimony (CAS 7440-36- Tin (CAS 7440-31-5) US. Pennsylvania Worker ar	Community Right-to-Know A	Act 7 Law			
US. New Jersey Worker and Antimony (CAS 7440-36-(Tin (CAS 7440-31-5) US. Pennsylvania Worker ar Antimony (CAS 7440-36-(Tip (CAS 7440-31-5))	Community Right-to-Know A D) Ind Community Right-to-Know D)	Act r Law			
US. New Jersey Worker and Antimony (CAS 7440-36- Tin (CAS 7440-31-5) US. Pennsylvania Worker ar Antimony (CAS 7440-36- Tin (CAS 7440-31-5) US. Rhode Island RTK	Community Right-to-Know A D) ad Community Right-to-Know D)	Act / Law			

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

Toxic Substances Control Act (TSCA) Inventory United States & Puerto Rico

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	17-December-2014
Revision date	-
Version #	01
HMIS® ratings	Health: 0 Flammability: 0 Physical hazard: 0
Disclaimer	Oatey Co. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.



SAFETY DATA SHEET

1. Identification

Oates	Purnle	Primor-	MSE List	d for DVC	and CDVC
Valey	Fuiple	Finner-	NOF LISU	ed for PVC	and CPVC

Product identifier	Oatey Purple Primer- NSF Listed for PVC and CPVC				
Other means of identification					
Product code	1402E				
Synonyms	Part Numbers: 30755(TV), 30756(TV), 30757(TV), 30758, 30759, 30927				
Recommended use	Joining PVC Pipes	(<i>m</i> = = = = = = = = = = = = = = = = = = =			
Recommended restrictions	None known.				
Manufacturer/Importer/Supplier/	Distributor information				
Company Name	Oatev Co				
Address	4700 West 160th St				
	Cleveland, OH 44135				
Telephone	216-267-7100				
E-mail	info@oatey.com				
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)				
Emergency First Aid	1-877-740-5015				
Contact person	MSDS Coordinator				
2 Hozord(a) identification					
2. Hazard(s) identification	_				
Physical hazards	Flammable liquids	Category 2			
Health hazards	Acute toxicity, oral	Category 4			
	Skin corrosion/irritation	Category 2			
	Serious eye damage/eye irritation	Category 2A			
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation			
	Specific target organ toxicity, single exposure	Category 3 narcotic effects			
	Aspiration hazard	Category 1			
OSHA defined hazards	Not classified.				
Label elements					
Signal word	Danger				
Hazard statement	Highly flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness.				
Precautionary statement					
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective dotting/eventilated area.				
Response	If swallowed: Immediately call a poison center/doctor. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in haled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. Rinse mouth. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.				

Storage

Disposal

Hazard(s) not otherwise classified (HNOC) Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May form explosive peroxides. Contains a chemical classified by the US EPA as a suspected possible carcinogen.

Supplemental information

Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Acetone	67-64-1	25-40
Cyclohexanone	108-94-1	25-40
Furan, Tetrahydro-	109-99-9	15-30
Methyl ethyl ketone	78-93-3	15-30

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.	
Skin contact	Take off immediately all contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.	
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.	
Ingestion	Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.	
Most important symptoms/effects, acute and delayed	Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Skin irritation. May cause redness and pain.	
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.	
General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.	
5. Fire-fighting measures		
Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.	
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.	
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.	
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.	
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.	
General fire hazards	Highly flammable liquid and vapor. This product contains tetrahydrofuran that may form explosive organic peroxide when exposed to air or light or with age.	

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water.
	Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
Cyclohexanone (CAS 108-94-1)	PEL	200 mg/m3	
Constant Contract Contract		50 ppm	
Furan, Tetrahydro- (CAS 109-99-9)	PEL	590 mg/m3	
,		200 ppm	
Methyl ethyl ketone (CAS 78-93-3)	PEL	590 mg/m3	
n an		200 ppm	
US. ACGIH Threshold Limit Valu	es		
Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
Cyclohexanone (CAS 108-94-1)	STEL	50 ppm	
tat usbitus (active inc. so.es	TWA	20 ppm	
Furan, Tetrahydro- (CAS 109-99-9)	STEL	100 ppm	

Oatey Purple Primer- NSF Listed for PVC and CPVC

926733 Version #: 01 Revision date: - Issue date: 27-May-2015

US. ACGIH Threshold Limit Values

Components	Туре	Value	
Norden en e	TWA	50 ppm	
Methyl ethyl ketone (CAS 78-93-3)	STEL	300 ppm	
2	TWA	200 ppm	
US. NIOSH: Pocket Guide to Che	mical Hazards	2. T	
Components	Туре	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
		250 ppm	
Cyclohexanone (CAS 108-94-1)	TWA	100 mg/m3	
		25 ppm	
Furan, Tetrahydro- (CAS 109-99-9)	STEL	735 mg/m3	
		250 ppm	
	TWA	590 mg/m3	
		200 ppm	
Methyl ethyl ketone (CAS 78-93-3)	STEL	885 mg/m3	
		300 ppm	
	TWA	590 mg/m3	
		200 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time	
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*	
Cyclohexanone (CAS 108-94-1)	80 mg/l	1,2-Cyclohexan ediol, with hydrolysis	Urine	*	
	8 mg/l	Cyclohexanol, with hydrolysis	Urine	*	
Furan, Tetrahydro- (CAS 109-99-9)	2 mg/l	Tetrahydrofura n	Urine	*	
Methyl ethyl ketone (CAS 78-93-3)	2 mg/l	MEK	Urine	*	

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Sk	n designation	
Cyclohexanone (CAS 108-94-1)		Can be absorbed through the skin.
US - Minnesota Haz Subs	: Skin designation applies	in 2 de provincien de la contra mandada.
Cyclohexanone (CAS	108-94-1)	Skin designation applies.
US - Tennessee OELs: S	kin designation	
Cyclohexanone (CAS	108-94-1)	Can be absorbed through the skin.
US ACGIH Threshold Lin	it Values: Skin designation	
Cyclohexanone (CAS 108-94-1)		Can be absorbed through the skin.
Furan, Tetrahydro- (CAS 109-99-9)		Can be absorbed through the skin.
US. NIOSH: Pocket Guide	e to Chemical Hazards	
Cyclohexanone (CAS 108-94-1)		Can be absorbed through the skin.
Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency	

shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

Face shield is recommended. Wear safety glasses with side shields (or goggles).

	Skin protection	
Hand protection		Wear appropriate chemical resistant gloves.
	Other	Wear appropriate chemical resistant clothing.
	Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
	Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Gen con	eral hygiene siderations	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Translucent liquid.
Color	Purple
Odor	Solvent.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	151 °F (66.11 °C)
Flash point	14.0 - 23.0 °F (-10.05.0 °C)
Evaporation rate	5.5 - 8
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	1.8
Flammability limit - upper (%)	11.8
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	145 mm Hg @ 20 C
Vapor density	2.5
Relative density	0.84 +/- 0.02 @20°C
Solubility(ies)	
Solubility (water)	Negligible
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Bulk density	7 lb/gal
VOC (Weight %)	505 g/l SQACMD Method 24
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Ammonia. Amines. Isocyanates. Caustics.

Oatey Purple Primer- NSF Listed for PVC and CPVC 926733 Version #: 01 Revision date: - Issue date: 27-May-2015

11. Toxicological information

Information on likely routes of exposure

Inhalation	May be fatal if swallowed and enters airways. Headache. Nausea, vomiting. May cause irritation to the respiratory system. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Prolonged inhalation may be harmful.	
Skin contact	Causes skin irritation.	
Eye contact	Causes serious eye irritation.	
Ingestion	May be fatal if swallowed and enters airways. Harmful if swallowed. Harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.	
Symptoms related to the physical, chemical and toxicological characteristics	Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.	

Information on toxicological effects

Acute toxicity	May be fatal if swallowed and enters airways. Narcotic effects. May cause respiratory irritation.		
Components Species Test Re		Test Results	
Acetone (CAS 67-64-1)			
Acute			
Dermal			
LD50	Rabbit	20 ml/kg	
Inhalation			
LC50	Rat	50 mg/l, 8 Hours	
Oral			
LD50	Rat	5800 mg/kg	
Cyclohexanone (CAS 108-94-1)			
Acute			
Dermal			
LD50	Rabbit	948 mg/kg	
Inhalation			
LC50	Rat	8000 ppm, 4 hours	
Oral			
LD50	Rat	1540 mg/kg	
* Estimates for product may	be based on additional component data	a not shown.	
Skin corrosion/irritation Causes skin irritation.			
Serious eye damage/eye irritation	Causes serious eye irritation.	auses serious eye irritation.	
Respiratory or skin sensitizatio	n		
Respiratory sensitization	Not available.		
Skin sensitization	This product is not expected to cause skin sensitization.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	In 2012 USEPA Integrated Risk Info lifetime study on THF conducted by mice developed liver tumors while n results. Because the carcinogenic m either tumor, the EPA determined th assessment of carcinogenic potentia data in aggregate indicate that there exposure to THF by all routes of exp	n 2012 USEPA Integrated Risk Information System (IRIS) reviewed a two species inhalation ifetime study on THF conducted by NTP (1998). Male rats developed renal tumors and female nice developed liver tumors while neither the female rats nor the male mice showed similar results. Because the carcinogenic mechanisms could not be identified clearly in either species for either tumor, the EPA determined that the male rat and female mouse findings are relevant to the assessment of carcinogenic potential in humans. Therefore, the IRIS review concludes that these data in aggregate indicate that there is "suggestive evidence of carcinogenic potential" following	
IARC Monographs, Overall	Evaluation of Carcinogenicity		

Cyclohexanone (CAS 108-94-1)

CSHA Specifically Regulate	d Substances (29 CFR 1910.1001-1050)
Not listed.	() = 1
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Narcotic effects. May cause drowsiness and dizziness. Respiratory tract irritation.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	May be fatal if swallowed and enters airways.
Chronic effects	Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.		
Components		Species	Test Results
Acetone (CAS 67-64-1)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	> 100 mg/l, 96 hours
Cyclohexanone (CAS 108-94-1)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	481 - 578 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Estimates for product may be	based on additional component data not snown.		
Persistence and degradability	No data is available on the degradability of this product.		
Bioaccumulative potential	No data available.		
Partition coefficient n-octand	ol / water (log Kow)		
Acetone (CAS 67-64-1)	-0.24		
Cyclohexanone (CAS 108-94-	0.81		
Furan, Tetrahydro- (CAS 109-9)9-9) 0.46		
Methyl ethyl ketone (CAS 78-9	3-3) 0.29		
Mobility in soil	No data available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		
13. Disposal consideration	S		
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.		
Local disposal regulations	Dispose in accordance with all applicable regulations.		
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.		
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).		

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DO	T	
	UN number	UN1993
	UN proper shipping name	Flammable liquids, n.o.s. (Methyl ethyl ketone RQ = 26274 LBS, Acetone RQ = 13130 LBS)
	Transport hazard class(es)	
	Class	3
	Subsidiary risk	a.
	Label(s)	3
	Packing group	П

Oatey Purple Primer- NSF Listed for PVC and CPVC 926733 Version #: 01 Revision date: - Issue date: 27-May-2015

Special precautions for user	r Read safety instructions, SDS and emergency procedures before handling.		
Special provisions	IB2, T7, TP1, TP8, TP28		
Packaging exceptions	150		
Packaging non bulk	202		
Packaging bulk	242		
IATA			
UN number	UN1993		
UN proper shipping name	Flammable liquid, n.o.s. (Methyl ethyl ketone, Acetone)		
Transport hazard class(es)			
Class	3		
Subsidiary risk	<u>19</u>		
Packing group	11		
Environmental hazards	No.		
ERG Code	3H		
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.		
IMDG			
UN number	UN1993		
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (Methyl ethyl ketone, Acetone)		
Transport hazard class(es)			
Class	3		
Subsidiary risk	•		
Packing group	1		
Environmental hazards			
Marine pollutant	No.		
EmS	F-E, S-E		
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.		
Transport in bulk according to	Not available.		
Annex II of MARPOL 73/78 and			
the IBC Code			
15. Regulatory information			
	The second s		
US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910,1200.		
	All components are on the U.S. EPA TSCA Inventory List.		
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)			
Not regulated.			
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)			
Not listed.	м. х .		

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)	LISTED
Cyclohexanone (CAS 108-94-1)	LISTED
Furan, Tetrahydro- (CAS 109-99-9)	LISTED
Methyl ethyl ketone (CAS 78-93-3)	LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard - Yes
	Delayed Hazard - No
	Fire Hazard - Yes
	Pressure Hazard - No
	Reactivity Hazard - No
SARA 302 Extremely ha	zardous substance

Not listed.

1.22

SARA 311/312 Hazardous No chemical

SARA 313 (TRI reporting) Not regulated.

Other federal regulations Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Not regulated. Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) Not regulated. Safe Drinking Water Act Not regulated. (SDWA) Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and **Chemical Code Number** Acetone (CAS 67-64-1) 6532 Methyl ethyl ketone (CAS 78-93-3) 6714 Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c)) Acetone (CAS 67-64-1) 35 %WV Methyl ethyl ketone (CAS 78-93-3) 35 %WV **DEA Exempt Chemical Mixtures Code Number** Acetone (CAS 67-64-1) 6532 Methyl ethyl ketone (CAS 78-93-3) 6714 US state regulations US. Massachusetts RTK - Substance List Acetone (CAS 67-64-1) Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS 109-99-9) Methyl ethyl ketone (CAS 78-93-3) US. New Jersey Worker and Community Right-to-Know Act Acetone (CAS 67-64-1) Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS 109-99-9) Methyl ethyl ketone (CAS 78-93-3) US. Pennsylvania Worker and Community Right-to-Know Law Acetone (CAS 67-64-1) Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS 109-99-9) Methyl ethyl ketone (CAS 78-93-3) **US. Rhode Island RTK** Acetone (CAS 67-64-1) Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS 109-99-9) Methyl ethyl ketone (CAS 78-93-3) US. California Proposition 65 California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. International Inventories Country(s) or region Inventory name On inventory (yes/no)* Canada Domestic Substances List (DSL) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes *A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s). 16. Other information, including date of preparation or last revision Issue date 27-May-2015 **Revision date** Version # 01

HMIS® ratings

Health: 2

Flammability: 3 Physical hazard: 0


Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Oatey Co. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.

SAFETY DATA SHEET

SDS 0011

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION ______ HMIS CODES PRODUCT NAME Health 1 RectorSeal No. 5 Flammability 2 Reactivity 0 PRODUCT CODES PPI В 25112, 25191, 25271, 25300, 25431, 25551, 25552, 25631, 25633, 25780, 25790, 25793 CHEMICAL FAMILY Organic USE Pipe Thread Sealant EMERGENCY TELEPHONE NO. MANUFACTURER'S NAME Chemtrec 24 Hours The RectorSeal Corporation 2601 Spenwick Drive (800)424-9300 USA (703) 527-3887 International Houston, Texas 77055 USA TECHNICAL SERVICE TELEPHONE NO. DATE OF VALIDATION January 23, 2015 (800)231-3345 or (713)263-8001 DATE OF PREPARATION January 9, 2013 _____ Section 2 -- HAZARDS IDENTIFICATION ______ EMERGENCY OVERVIEW OSHA Hazards Combustable TARGET ORGANS Not Classified GHS CLASSIFICATION PHYSICAL HAZARDS Combustable liquid (Category 4) HEALTH HAZARDS Acute Toxicity: Oral: Not Classified Dermal: Not Classified Inhalation: Not Classified Skin Corrosion/Irritation: Not Classified Serious Eye Damage/Eye Irritation: Not Classified Skin Sensitization: Not Classified Respiratory Sensitization: Not Classified Germ Cell Mutagenicity: Not Classified Carcinogenicity: See Section 11 Reproductive Toxicology: Not Classified Target Organ Systemic Toxicity - Single Exposure: Not Classified Target Organ Systemic Toxicity - Repeated Exposure: Not Classified Aspiration Toxicity: Not Classified _____ GHS Label elements, including precautionary statements Pictogram: Harmful / Irritant Signal Word: Warning

Hazard Statements H303 - May be harmful if swallowed. H313 - May be harmful in contact with skin. H335 + H336 - May cause respiratory irritation, and drowsiness or dizziness. Precautionary Statements P102 - Keep out of reach of children. P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking P240 - Ground/Bond container and receiving equipment P261 - Avoid breathing dust/fume/gas/mist/vapors/spray P262 - Do not get in eyes, on skin, or on clothing. P264 - Wash hands thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P362 - Take off contaminated clothing and wash before reuse. EUH066 - Repeated exposure may cause skin dryness or cracking Precautionary Statements - EU No. 1272/2008 _____ SUMMARY OF ACUTE HAZARDS Irritation to eyes, nose and throat; drowsiness, narcosis, tremors and other CNS effects at high concentration. ROUTE OF EXPOSURE, SIGNS AND SYMPTOMS INHALATION Nasal and respiratory irritation, dizziness, narcosis, headache, nausea, CNS depression and unconsciousness. EYE CONTACT Watering, blurred vision, inflammation and irritation which can result in corneal injury. SKIN CONTACT Irritation, dermatitis. INGESTION Nausea, vomiting; CNS depression; irritation of gastrointestinal tract, liver and peritoneal wall; lung congestion. SUMMARY OF CHRONIC HAZARDS Skin irritation and dermatitis. Possible liver and kidney damage. MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE Individuals with pre-existing or chronic diseases of the eyes, skin, respiratory system, cardiovascular system, gastrointestinal system, liver or kidneys may have increased susceptibility to excessive exposures. _____ Section 3 -- COMPOSITION/INFORMATION ON INGREDIENTS _____ INGREDIENT: Diacetone Alcohol PERCENTAGE BY WEIGHT: 20-30 CAS NUMBER: 123-42-2 EC# : 204-626-7 Section 4 -- FIRST AID MEASURES _____ If overcome by exposure, remove victim to fresh air If INHALED: immediately. Give oxygen or artificial respiration as needed. Obtain emergency medical attention. Prompt action is essential. Wash with soap and water. If irritation occurs, seek If on SKIN: medical attention.

```
If in EYES: Flush eyes with large amounts of water for 15 minutes.
```

9/6/2018 https://www.rectorseal.com/web-media/RectorSeal-No-5.html Get medical attention. If SWALLOWED: If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person. Section 5 -- FIRE FIGHTING MEASURES _____ EXTINGUSING MEDIA Foam, dry chemical, carbon dioxide or water fog. SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus (SCBA) and other protective clothing. Hazardous decomposition products possible (see Section 10). UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustible - moderate flash point. Vapors heavier than air and may travel along the ground or to low spots at considerable distances to a source of ignition resulting in potential flashback. Burning liquid may float on water. Heat may build up pressure and rupture containers. _____ Section 6 -- ACCIDENTAL RELEASE MEASURES _____ STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Use absorbent materials to prevent footing hazard and to contain. Ventilate area with natural or explosion-proof, forced air ventilation. Avoid flushing into sewers, drains, waterways, and soil. Wear protective clothing and respiratory protection during cleanup. _____ Section 7 -- HANDLING AND STORAGE PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep container closed and upright when not in use. Do not store near heat, sparks, or open flames. OTHER PRECAUTIONS: Avoid prolonged or repeated contact with skin or clothing. Empty containers may contain residues; treat as if full and observe all products precautions. Do not reuse empty containers. KEEP OUT OF REACH OF CHILDREN. ______ Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION INGREDIENT UNITS Diacetone Alcohol ACGIH TLV 50 ppm OSHA PEL 50 ppm RESPIRATORY PROTECTION (SPECIFY TYPE): In confined poorly ventilated areas, use NIOSH/MSHA approved air purifying or supplied air purifying or supplied air respirators. VENTILATION - LOCAL EXHAUST: Acceptable SPECIAL: Explosion-proof equipment. MECHANICAL (GENERAL): Preferable OTHER: N/A PROTECTIVE GLOVES: Wear rubber gloves. EYE PROTECTION: Chemical splash goggles (ANSI Z-87.1 or equivalent) OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Coveralls recommended. WORK/HYGIENIC PRACTICES: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area. Launder contaminated clothing before reuse. _____

Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT:	322 F (161 C) @ 760mm Hg
SPECIFIC GRAVITY (H20 = 1):	1.38
VAPOR PRESSURE (mm Hg):	U.3 @ 68 F (20 C) N/A
VAPOR DENSITY (AIR = 1):	1.1
EVAPORATION RATE (ETHYL ACETATE = 1):	0.14
APPEARANCE/ODOR:	Yellow Paste/Mild Odor
SOLUBILITY IN WATER:	23%
VOLATILE ORGANIC COMPOUNDS (VOC) Content	
(Theoretical Percentage By Weight):	23% or (317 g/L)
Flash POINT	150 F (65 C) SETA CC
LOWER EXPLOSION LIMIT	N/D
UPPER EXPLOSION LIMIT	N/D ====================================
Section 10 STABILITY AND	REACTIVITY
STABILITY: Stable	
CONDITIONS TO AVOID: Heat, sparks, op	en flames, and strong oxidizing.
Temperatures above 500 F (260 C).	
INCOMPATIBILITY (MATERIALS TO AVOID):	Gaseous oxygen, strong oxidizing
materials, molten alkali metals.	
HAZARDOUS DECOMPOSITION PRODUCTS: CO,	CO2 and fragmented hydrocarbons.
HAZARDOUS POLYMERIZATION: Will not oc	cur.
Section 11 TOXICOLOGY IN	======================================
CHRONIC HEALTH HAZARDS No ingredients in this product is an	n IARC, NTP or OSHA Lister carcinogen.
TOXICOLOGY DATA	
Ingredient Name	
Diacetone Alcohol	
Oral-Rat LD	50:4000 mg/kg
Inhalation-Human TC	Lo: 100 ppm
Section 12 Ecological In:	formation
ECOLOGICAL DATA	
Diacetone Alcohol	
Food Chain Concentrat	tion Potential N/A
WATERFOWL TOXICITY	N/A
BOD	N/A
AQUATIC TOXICITY	N/A
Section 13 DISPOSAL CONS	IDERATIONS
Waste Classification: Non-regulated so	DIIG WASTE
Waste from this product is not consider	red hazardous as defined under the
Resource Conservation and Recovery Ad	ct (RCRA) 40 CFR 261. Dispose of in
accordance with Federal, State, and I	Local regulation regarding pollution.
Section 14 TRANSPORTATION	N INFORMATION

DOT: OCEAN (IMDG): AIR (IATA): WHMIS (CANADA	Non-Regulated Non-Regulated Non-Regulated): Non-Regulated	
Se	ction 15 REGULATOR	Y INFORMATION
REGULATORY DA Ingredient Na	TA me 	
Diacetone A	SARA 313 TSCA Inventory CERCLA RQ RCRA Code	N/A Yes N/A N/A
Se	ction 16 OTHER INF	======================================
This docum Standard (29	ent is prepared pursu CFR 1910.1200). The	ant to the OSHA Hazard Communication information herein is given in good faith.

but no warranty, expressed or implied is made. Consult RectorSeal for further information: (713) 263-8001



SAFETY DATA SHEET

SDS ID NO.: Revision Date 0127MAR019 03/19/2018

1. IDENTIFICATION Product Name: Marathon Petroleum Gasoline - All Grades Gasoline: Regular Unleaded Gasoline: Conventional Regular Unleaded Gasoline: Mid Synonym: Grade Unleaded Gasoline: Conventional Mid Grade Unleaded Gasoline: Premium Unleaded Gasoline: Conventional Premium Unleaded Gasoline: Sub-Octane Gasoline: Regular RBOB; Super RBOB; Premium RBOB; RBOB; Reformulated Blend Stock For Oxygenated Blending; 84 Octane Gasoline; CBOB; Premium CBOB; Conventional Blend Stock for Oxygenate Blending; Recreational Gasoline; Recreational Gasoline; Recreational Unleaded Gasoline; 89 Recreational Gasoline; Brand 89 Recreational Gasoline; 7.0 Max RVP 89 Recreational Gasoline; BR 7.0 Max RVP 89 Recreational Gasoline; 90 Recreational Gasoline; 90 Marina Gasoline; Brand 91 Recreational Gasoline; 91 Recreational Gasoline; 91 Marina Gasoline; 90 Octane Midgrade Gasoline with No Ethanol; 0125MAR019; 0126MAR019; 0134MAR019; 0313MAR019; 0314MAR019 **Product Code:** 0127MAR019 **Chemical Family:** Complex Hydrocarbon Substance **Recommended Use:** Fuel. **Restrictions on Use:** All others.

Manufacturer, Importer, or Responsible Party Name and Address: MARATHON PETROLEUM COMPANY LP 539 South Main Street Findlay, OH 45840

SDS information (M-F, 8-5 PM EST): 1-419-421-3070

Emergency Telephone (24/7):

CHEMTREC: 1-800-424-9300 CCN#: 13740

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 1
Skin corrosion/irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Acute aquatic toxicity	Category 2
Chronic aquatic toxicity	Category 2

Hazards Not Otherwise Classified (HNOC)

Static accumulating flammable liquid

Label elements

EMERGENCY OVERVIEW

Danger

EXTREMELY FLAMMABLE LIQUID AND VAPOR May accumulate electrostatic charge and ignite or explode May be fatal if swallowed and enters airways Causes skin irritation May cause respiratory irritation May cause drowsiness or dizziness May cause genetic defects May cause cancer Suspected of damaging fertility or the unborn child Causes damage to organs (blood, blood-forming organs, immune system) through prolonged or repeated exposure Toxic to aquatic life with long lasting effects Appearance Clear yellow liquid Physical State Liquid Odor Hydrocarbon

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof electrical/ventilating/lighting/equipment Use only non-sparking tools. Take action to prevent static discharges Do not eat, drink or smoke when using this product Do not breathe mist/vapors/spray Use only outdoors or in a well-ventilated area Wear protective gloves/protective clothing/eye protection/face protection Wash hands and any possibly exposed skin thoroughly after handling Avoid release to the environment

Precautionary Statements - Response

IF exposed, concerned or you feel unwell: Get medical attention IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower If skin irritation occurs: Get medical attention Wash contaminated clothing before reuse IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor if you feel unwell IF SWALLOWED: Immediately call a POISON CENTER or doctor Do NOT induce vomiting In case of fire: Use water spray, fog or regular foam for extinction Collect spillage

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed Keep cool Store locked up

Precautionary Statements - Disposal

Dispose of contents/container at an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Gasoline is a complex combination of hydrocarbons consisting of paraffins, cycloparaffins, aromatic and olefinic hydrocarbons having molecular chains ranging in length from four to ten carbons. May contain small amounts of dye and other additives (>0.02%) which are not considered hazardous at the concentrations used.

Composition Information:

Name	CAS Number	% Concentration
Gasoline	86290-81-5	100
Heptane (mixed isomers)	142-82-5	2.5-26
Butane (mixed isomers)	106-97-8	0.5-19
Pentane (mixed isomers)	78-78-4	6.5-19
Hexane Isomers (other than n-Hexane)	107-83-5	2-12
Toluene	108-88-3	3-9.5
Xylene (mixed isomers)	1330-20-7	3.5-9.5
Benzene	71-43-2	0.1-4.9
n-Hexane	110-54-3	0.1-4.5
Cumene	98-82-8	0-4
1,2,4 Trimethylbenzene	95-63-6	1-4
Ethylbenzene	100-41-4	0.5-2.5
Cyclohexane	110-82-7	0-1.5
Octane	111-65-9	0-1.5
1,2,3-Trimethylbenzene	526-73-8	0-1
Naphthalene	91-20-3	0.1-0.5

Benzene concentration is percent by volume. All other concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume.

4. FIRST AID MEASURES

First Aid Measures

General Advice:	In case of accident or if you feel unwell, seek medical advice immediately (show directions for use or safety data sheet if possible).
Inhalation:	Remove to fresh air. If not breathing, institute rescue breathing. If breathing is difficult, ensure airway is clear, give oxygen and continue to monitor. If heart has stopped, immediately begin cardiopulmonary resuscitation (CPR). Keep affected person warm and at rest. If symptoms occur get medical attention.
Skin Contact:	Immediately wash exposed skin with plenty of soap and water while removing contaminated clothing and shoes. May be absorbed through the skin in harmful amounts. Get medical attention if irritation persists. Any injection injury from high pressure equipment should be evaluated immediately by a physician as potentially serious (See NOTES TO PHYSICIAN).
	Place contaminated clothing in closed container until cleaned or discarded. If clothing is to be laundered, inform the person performing the operation of contaminant's hazardous properties. Destroy contaminated, non-chemical resistant footwear.
Eye Contact:	Flush immediately with large amounts of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Gently remove contacts while flushing. Get medical attention if irritation persists.

Ingestion:	Do not induce vomiting because of danger of aspirating liquid into lungs, causing serious damage and chemical pneumonitis. If spontaneous vomiting occurs, keep head below hips, or if patient is lying down, turn body and head to side to prevent aspiration and monitor for breathing difficulty. Never give anything by mouth to an unconscious person. Keep affected person warm and at rest. GET IMMEDIATE MEDICAL ATTENTION.
Most important signs and symptom	s, both short-term and delayed with overexposure
Adverse Effects:	Irritating to the skin and mucous membranes. Symptoms may include redness, itching, and inflammation. May cause nausea, vomiting, diarrhea, and signs of nervous system depression: headache, drowsiness, dizziness, loss of coordination, disorientation and fatigue. Aspiration hazard. May cause coughing, chest pains, shortness of breath, pulmonary edema and/or chemical pneumonitis. Prolonged or repeated exposure may cause adverse effects on blood, blood-forming organs, and immune system. Repeated or prolonged skin contact may cause drying, reddening, itching and cracking.
Indication of any immediate medica	I attention and special treatment needed
Notes To Physician:	INHALATION: This material (or a component) sensitizes the myocardium to the effects of sympathomimetic amines. Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in individuals exposed to this material. Administration of sympathomimetic drugs should be avoided.
	SKIN: Leaks or accidents involving high-pressure equipment may inject a stream of material through the skin and initially produce an injury that may not appear serious. Only a small puncture wound may appear on the skin surface but, without proper treatment and depending on the nature, original pressure, volume, and location of the injected material, can compromise blood supply to an affected body part. Prompt surgical debridement of the wound may be necessary to prevent irreversible loss of function and/or the affected body part. High pressure injection injuries may be SERIOUS SURGICAL EMERGENCIES.
	INGESTION: This material represents a significant aspiration and chemical pneumonitis hazard. Induction of emesis is not recommended.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

For small fires, Class B fire extinguishing media such as CO2, dry chemical, foam (AFFF/ATC) or water spray can be used. For large fires, water spray, fog or foam (AFFF/ATC) can be used. Firefighting should be attempted only by those who are adequately trained and equipped with proper protective equipment.

Unsuitable extinguishing media

Do not use straight water streams to avoid spreading fire.

Specific hazards arising from the chemical

This product has been determined to be an extremely flammable liquid per the OSHA Hazard Communication Standard and should be handled accordingly. May accumulate electrostatic charge and ignite or explode. Vapors may travel along the ground or be moved by ventilation and ignited by many sources such as pilot lights, sparks, electric motors, static discharge, or other ignition sources at locations distant from material handling. Flashback can occur along vapor trail. For additional fire related information, see NFPA 30 or the Emergency Response Guidebook 128.

Hazardous combustion products

Smoke, carbon monoxide, and other products of incomplete combustion.

Explosion data Sensitivity to Mechanical Impact No. Sensitivity to Static Discharge Yes.

Special protective equipment and precautions for firefighters

Firefighters should wear full protective clothing and positive-pressure self-contained breathing apparatus (SCBA) with a full

face-piece, as appropriate. Avoid using straight water streams. Water may be ineffective in extinguishing low flash point fires, but can be used to cool exposed surfaces. Avoid excessive water spray application. Water spray and foam (AFFF/ATC) must be applied carefully to avoid frothing and from as far a distance as possible. Keep run-off water out of sewers and water sources.

Additional firefighting tactics

FIRES INVOLVING TANKS OR CAR/TRAILER LOADS: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Cool containers with flooding quantities of water until well after the fire is out. Do not direct water at source of leak or safety devices; icing may occur. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. ALWAYS stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles: if this is impossible, withdraw from area and let fire burn.

EVACUATION: Consider initial downwind evacuation for at least 1000 feet. If tank, rail car or tank truck is involved in a fire, ISOLATE for 5280 feet (1 mile) in all directions; also, consider initial evacuation of 5280 feet (1 mile) in all directions.

<u>NFPA</u>	Health 1	Flammability 3	Instability 0	Special Hazard -	
	6. A			6	
Personal precaution	ons:	Keep public away. Isolate and evacuate area. Shut off source if safe to do so. Eliminate all ignition sources.			
Protective equipm	ent:	Use personal protection measures	as recommended in Se	ection 8.	
Emergency procee	dures:	Advise authorities and National Response Center (800-424-8802) if the product has entered a water course or sewer. Notify local health and pollution control agencies, if appropriate.			
Environmental pre	ecautions:	Avoid release to the environment. Avoid subsoil penetration. Ethanol in gasoline phase seperates in contact with water. Monitor downstream for dissolved ethanol or other appropriate indicators.			
Methods and mate containment:	erials for	Contain liquid with sand or soil. Prevent spilled material from entering storm drains, sewers, and open waterways.			
Methods and mate up:	erials for cleaning	Use suitable absorbent materials s liquids. Recover and return free pr ensure all equipment is grounded	such as vermiculite, sar oduct to proper contain and bonded. Use only r	nd, or clay to clean up residual ers. When recovering free liquids non-sparking tools.	
		7. HANDLING AND	STORAGE		
Safe Handling Pre	cautions:	NEVER SIPHON THIS PRODUCT practices. Static accumulating flam to eliminate the hazard from static oxidizers or other sources of ignitic ventilation. Flashback may occur a tools. Avoid contact with skin, eye Use only with adequate ventilation personal protection measures as r hygiene including removal of soile not cut, drill, grind or weld on emp to applicable EPA, OSHA, NFPA a	[•] BY MOUTH. Use approximable liquid. Bonding a electricity. Do not expo on. Vapors may travel a along vapor trails. No sr s and clothing. Avoid br . Avoid repeated and pr ecommended in Sectio d clothing and prompt v ty containers since expl and consistent state and	ropriate grounding and bonding and grounding may be insufficient se to heat, open flames, strong long the ground or be moved by noking. Use only non-sparking eathing fumes, gas, or vapors. rolonged skin contact. Use n 8. Exercise good personal vashing with soap and water. Do osive residues may remain. Refer d local requirements.	
		Hydrocarbons are basically non-co- charged during mixing, filtering, pu- operations. If this charge reaches the vapors of flammable liquids. S from process equipment operating ingress of air into vacuum equipment presence of obvious ignition source	onductors of electricity a imping at high flow rate a sufficiently high level oudden release of hot of under elevated temper ent may result in ignition es. Nozzle spouts mus	and can become electrostatically s or loading and transfer , sparks can form that may ignite rganic chemical vapors or mists rature and pressure, or sudden n of vapors or mists without the t be kept in contact with the	

containers or tank during the entire filling operation.

Portable containers should never be filled while in or on a motor vehicle or marine craft. Containers should be placed on the ground. Static electric discharge can ignite fuel vapors when filling non-grounded containers or vehicles on trailers. The nozzle spout must be kept in contact with the container before and during the entire filling operation. Use only approved containers.

A buildup of static electricity can occur upon re-entry into a vehicle during fueling especially in cold or dry climate conditions. The charge is generated by the action of dissimilar fabrics (i.e., clothing and upholstery) rubbing across each other as a person enters/exits the vehicle. A flash fire can result from this discharge if sufficient flammable vapors are present. Therefore, do not get back in your vehicle while refueling.

Cellular phones and other electronic devices may have the potential to emit electrical charges (sparks). Sparks in potentially explosive atmospheres (including fueling areas such as gas stations) could cause an explosion if sufficient flammable vapors are present. Therefore, turn off cellular phones and other electronic devices when working in potentially explosive atmospheres or keep devices inside your vehicle during refueling.

High-pressure injection of any material through the skin is a serious medical emergency even though the small entrance wound at the injection site may not initially appear serious. These injection injuries can occur from high-pressure equipment such as paint spray or grease or guns, fuel injectors, or pinhole leaks in hoses or hydraulic lines and should all be considered serious. High pressure injection injuries may be SERIOUS SURGICAL EMERGENCIES (See First Aid Section 4).

Storage Conditions:Store in properly closed containers that are appropriately labeled and in a cool,
well-ventilated area. Do not store near an open flame, heat or other sources of ignition.

Incompatible Materials

Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	ACGIH TLV	OSHA PELS:	OSHA - Vacated PELs	NIOSH IDLH
Gasoline 86290-81-5	300 ppm TWA 500 ppm STEL	-	300 ppm TWA 900 mg/m ³ TWA 500 ppm STEL 1500 mg/m ³ STEL	-
Heptane (mixed isomers) 142-82-5	400 ppm TWA 500 ppm STEL	TWA: 500 ppm TWA: 2000 mg/m³	400 ppm TWA 1600 mg/m ³ TWA 500 ppm STEL 2000 mg/m ³ STEL	750 ppm
Butane (mixed isomers) 106-97-8	1000 ppm STEL	-	800 ppm TWA 1900 mg/m³ TWA	-
Pentane (mixed isomers) 78-78-4	1000 ppm TWA	-	-	-
Hexane Isomers (other than n-Hexane) 107-83-5	500 ppm TWA 1000 ppm STEL	-	500 ppm TWA 1800 mg/m³ TWA 1000 ppm STEL 3600 mg/m³ STEL	-
Toluene 108-88-3	20 ppm TWA	TWA: 200 ppm Ceiling: 300 ppm	100 ppm TWA 375 mg/m³ TWA 150 ppm STEL 560 mg/m³ STEL	500 ppm
Xylene (mixed isomers) 1330-20-7	100 ppm TWA 150 ppm STEL	TWA: 100 ppm TWA: 435 mg/m³	100 ppm TWA 435 mg/m³ TWA 150 ppm STEL 655 mg/m³ STEL	900 ppm
Benzene 71-43-2	0.5 ppm TWA 2.5 ppm STEL	TWA: 10 ppm (applies to industry segments exempt	25 ppm Ceiling 1 ppm TWA	500 ppm

	Skin - potential significant contribution to overall exposure by the cutaneous route	from the benzene standard) TWA: 1 ppm STEL: 5 ppm (see 29 CFR 1910.1028)	5 ppm STEL	
n-Hexane 110-54-3	50 ppm TWA Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 500 ppm TWA: 1800 mg/m³	50 ppm TWA 180 mg/m³ TWA	1100 ppm
Cumene 98-82-8	50 ppm TWA	TWA: 50 ppm TWA: 245 mg/m ³ Skin	50 ppm TWA 245 mg/m³ TWA Limit applies to skin	900 ppm
1,2,4 Trimethylbenzene 95-63-6	25 ppm TWA	-	25 ppm TWA 125 mg/m³ TWA	-
Ethylbenzene 100-41-4	20 ppm TWA	TWA: 100 ppm TWA: 435 mg/m ³	100 ppm TWA 435 mg/m³ TWA 125 ppm STEL 545 mg/m³ STEL	800 ppm
Cyclohexane 110-82-7	100 ppm TWA	TWA: 300 ppm TWA: 1050 mg/m ³	300 ppm TWA 1050 mg/m³ TWA	1300 ppm
Octane 111-65-9	300 ppm TWA	TWA: 500 ppm TWA: 2350 mg/m ³	300 ppm TWA 1450 mg/m³ TWA 375 ppm STEL 1800 mg/m³ STEL	1000 ppm
1,2,3-Trimethylbenzene 526-73-8	25 ppm TWA	-	25 ppm TWA 125 mg/m³ TWA	-
Naphthalene 91-20-3	10 ppm TWA Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 10 ppm TWA: 50 mg/m³	10 ppm TWA 50 mg/m³ TWA 15 ppm STEL 75 mg/m³ STEL	250 ppm
Notes:	The manufacturer 1989 air contamin were vacated in 19	has voluntarily elected to ants standard in its SDS 992.	o provide exposure limits s, even though certain of	contained in OSHA's those exposure limits
Engineering measures:	Local or general e ventilation. Use m	xhaust required in an en- echanical ventilation equ	closed area or when ther ipment that is explosion-	e is inadequate proof.
Personal protective equipme	<u>nt</u>			
Eye protection:	Use goggles or fac	ce-shield if the potential f	or splashing exists.	
Skin and body protection:	Use nitrile rubber, suitability is based specific advice on	Viton® or PVA gloves fo on workplace conditions glove selection and brea	r repeated or prolonged s and usage. Contact the akthrough times.	skin exposure. Glove glove manufacturer for
Respiratory protection:	Use a NIOSH approved organic vapor chemical cartridge or supplied air respirators when there is the potential for airborne exposures to exceed permissible exposure limits or if excessive vapors are generated. Observe respirator assigned protection factors (APFs) criteria cited in federal OSHA 29 CFR 1910.134. Self-contained breathing apparatus should be used for fire fighting.			
Hygiene measures:	Handle in accorda skin, eyes and clo	nce with good industrial thing.	hygiene and safety pract	ice. Avoid contact with

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties		
Physical State	Liquid	
Appearance	Clear yellow liquid	
Color	Yellow	

Odor Odor Threshold	Hydrocarbon No data available.
<u>Property</u> Melting Point / Freezing Point Initial Boiling Point / Boiling Range Flash Point Evaporation Rate	Values (Method) No data available. 24-210 °C / 75-410 °F (ASTM D86) -43 °C / -45 °F No data available.
Flammability (solid, gas)	Not applicable.
Upper Flammability Limit:	7.6
Explosion limits:	No data available.
Vapor Pressure	5.5-15 psi (ASTM D4814)
vapor Density Specific Gravity / Relative Density	3-4 0.70-0.76
Water Solubility	No data available.
Solubility in other solvents	No data available.
Partition Coefficient	2.13-4.5 No data available
pH:	Not applicable
Autoignition Temperature	280 °C / 536 °F
Kinematic Viscosity	No data available. No data available
Explosive Properties	No data available.
VOC Content (%)	100%
Density Bulk Density	No data available.
Durk Density	

10. STABILITY AND REACTIVITY

Reactivity	The product is non-reactive under normal conditions.
Chemical stability	The material is stable at 70°F (21°C), 760 mmHg pressure.
Possibility of hazardous reactions	None under normal processing.
Hazardous polymerization	Will not occur.
Conditions to avoid	Excessive heat, sources of ignition, open flame.
Incompatible Materials	Strong oxidizing agents.
Hazardous decomposition products	None known under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Potential short-term adverse effects from overexposures

Inhalation	May cause irritation of respiratory tract. May cause drowsiness or dizziness. Breathing high concentrations of this material in a confined space or by intentional abuse can cause irregular heartbeats which can cause death.
Eye contact	Exposure to vapor or contact with liquid may cause mild eye irritation, including tearing, stinging, and redness.
Skin contact	Irritating to skin. Effects may become more serious with repeated or prolonged contact. May be absorbed through the skin in harmful amounts.
Ingestion	May be fatal if swallowed or vomited and enters airways. May cause irritation of the mouth,

throat and gastrointestinal tract.

Acute toxicological data

Name	Oral LD50	Dermal LD50	Inhalation LC50
Gasoline 86290-81-5	14000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
Heptane (mixed isomers) 142-82-5	-	3000 mg/kg (Rabbit)	103 g/m³ (Rat) 4 h
Butane (mixed isomers) 106-97-8	-	-	658 mg/L (Rat) 4 h
Pentane (mixed isomers) 78-78-4	-	-	450 mg/L (Mouse) 2 h
Hexane Isomers (other than n-Hexane) 107-83-5	> 5000 mg/kg (Rat)	-	-
Toluene 108-88-3	> 2000 mg/kg (Rat)	8390 mg/kg (Rabbit)	12.5 mg/L (Rat) 4 h
Xylene (mixed isomers) 1330-20-7	> 2000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.04 mg/L (Rat) 4 h
Benzene 71-43-2	> 2000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	> 20 mg/l (Rat) 4 h
n-Hexane 110-54-3	15000 mg/kg (Rat)	3000 mg/kg (Rabbit)	48000 ppm (Rat) 4 h
Cumene 98-82-8	> 2000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 20 mg/L (Rat) 6 h
1,2,4 Trimethylbenzene 95-63-6	3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	18,000 mg/m³ (Rat) 4 h
Ethylbenzene 100-41-4	> 2000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	17.2 mg/L (Rat) 4 h
Cyclohexane 110-82-7	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	13.9 mg/L (Rat) 4 h
Octane 111-65-9	-	-	118 g/m³ (Rat) 4 h
1,2,3-Trimethylbenzene 526-73-8	-	-	-
Naphthalene 91-20-3	490 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 340 mg/m³ (Rat) 1 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

NAPHTHAS: In a large epidemiological study on over 15,000 employees at several petroleum refineries and amongst residents located near these refineries, no increased risk of kidney cancer was observed in association with gasoline exposures (a similar material). In a similar study, no increased risk of kidney cancer was observed among petroleum refinery workers, but there was a slight trend in the incidence of kidney cancers among service station employees, especially after a 30-year latency period. Altered mental state, drowsiness, peripheral motor neuropathy, irreversible brain damage (so-called Petrol Sniffer's Encephalopathy), delirium, seizures, and sudden death have been reported from repeated overexposure to some hydrocarbon solvents, naphthas, and gasoline.

ISOPARAFFINS: Studies in laboratory animals have shown that long-term exposure to similar materials (isoparaffins) can cause kidney damage and kidney cancer in male laboratory rats. However, in-depth research indicates that these findings are unique to the male rat, and that these effects are not relevant to humans.

C9 AROMATIC HYDROCARBONS: A developmental inhalation study was conducted in laboratory mice. Increased implantation losses, reduced fetal weights, delayed ossification and an increased incidence of cleft palate were observed at the highest exposure level (1,500 ppm). This exposure level was extremely toxic to pregnant female mice (44% mortality). Reduced fetal body weights were also observed at 500 ppm. A multi-generation reproduction inhalation study was conducted in laboratory rats. Reductions in pup weights, pup weight gain, litter size, and pup survival were observed at

1,500 ppm, an exposure level at which significant maternal toxicity was observed. Reduced pup weight gain was also observed at 500 ppm.

BUTANES: Studies in laboratory animals indicate exposure to extremely high levels of butanes (1-10 or higher vol.% in air) may cause cardiac arrhythmias (irregular heartbeats) which may be serious or fatal.

PENTANES: Studies of pentane isomers in laboratory animals indicate exposure to extremely high levels (roughly 10 vol.%) may induce cardiac arrhythmias (irregular heartbeats) which may be serious or fatal.

TOLUENE: Case studies of persons abusing toluene suggest isolated incidences of adverse effects on the fetus including birth defects. Abuse of toluene at high concentrations (e.g., glue sniffing and solvent abuse) has been associated with adverse effects on the liver, kidney and nervous system, and can cause CNS depression, cardiac arrhythmias, and death. Studies of workers indicate longterm exposure may be related to impaired color vision and hearing. Some studies of workers suggest longterm exposure may be related to neurobehavioral and cognitive changes. Some of these effects have been observed in laboratory animals following repeated exposure to high levels of toluene. Several studies of workers suggest longterm exposure may be related to small increases in spontaneous abortions and changes in some gonadotropic hormones. However, the weight of evidence does not indicate toluene is a reproductive hazard to humans. Studies in laboratory animals indicate some changes in reproductive organs following high levels of exposure, but no significant effects on mating performance or reproduction were observed. Case studies of persons abusing toluene suggest isolated incidences of adverse effects on the fetus including birth defects. Findings in laboratory animals have been largely negative. Positive findings include small increases in minor skeletal and visceral malformations and developmental delays following very high levels of maternal exposure. Studies of workers indicate long-term exposure may be related to effects on the liver, kidney and blood, but these appear to be limited to changes in serum enzymes and decreased leukocyte counts. Adverse effects on the liver, kidney, thymus and nervous system were observed in animal studies following very high levels of exposure. The relevance of these findings to humans is not clear at this time.

XYLENES, ALL ISOMERS: Overexposure to xylene may cause upper respiratory tract irritation, headache, cyanosis, blood serum changes, nervous system damage and narcosis. Effects may be increased by the use of alcoholic beverages. Evidence of liver and kidney impairment were reported in workers recovering from a gross overexposure. Effects from Prolonged or Repeated Exposure: Impaired neurological function was reported in workers exposed to solvents including xylene. Studies in laboratory animals have shown evidence of impaired hearing following high levels of exposure. Studies in laboratory animals suggest some changes in reproductive organs following high levels of exposure but no significant effects on reproduction were observed. Studies in laboratory animals indicate skeletal and visceral malformations, developmental delays, and increased fetal resorptions following extremely high levels of maternal exposure with evidence of maternal toxicity. The relevance of these observations to humans is not clear at this time. Adverse effects on the liver, kidney, bone marrow (changes in blood cell parameters) were observed in laboratory animals following high levels of exposure. The relevance of these observations to humans is not clear at this time.

BENZENE: Studies of workers exposed to benzene show clear evidence that overexposure can cause cancer and other diseases of the blood forming organs including Acute Myelogenous Leukemia (AML), and Aplastic Anemia (AA), an often fatal disease. Some studies suggest overexposure to benzene may also be associated with Myelodysplastic Syndrome (MDS). Findings from a case control study of workers exposed to benzene was reported during the 2009 Benzene Symposium in Munich included an increase in Acute Myeloid Leukemias and Non-Hodgkins Lymphoid Neoplasms (NHLN) of the subtype follicular lymphoma (FL) in some occupational categories. Some studies of workers exposed to benzene have shown an association with increased rates of chromosome aberrations in circulating lymphocytes. One study of women workers exposed to benzene suggested a weak association with irregular menstruation. However, other studies of

workers exposed to benzene have not demonstrated clear evidence of an effect on fertility or reproductive outcome in humans. Benzene can cross the placenta and affect the developing fetus. Cases of AA have been reported in the offspring of persons severely overexposed to benzene. Studies in laboratory animals indicate that prolonged, repeated exposure to high levels of benzene vapor can cause bone marrow suppression and cancer in multiple organ systems. Studies in laboratory animals show evidence of adverse effects on male reproductive organs following high levels of exposure but no significant effects on reproduction have been observed. Embryotoxicity has been reported in studies of laboratory animals but effects were limited to reduced fetal weight and minor skeletal variations. Benzene has been classified as a proven human carcinogen by OSHA and a Group 1 (Carcinogenic to Humans) material by IARC. The current proposed IARC classification for benzene is summarized as follows: Sufficient evidence for Acute Myeloid Leukemia; limited evidence for Acute Lymphatic Leukemia, Chronic Lymphatic Leukemia, Non-Hodgkin Lymphoma, and Multiple Myeloma.

N-HEXANE: Long-term or repeated exposure to n-hexane can cause peripheral nerve damage. Initial symptoms are numbness of the fingers and toes. Also, motor weakness can occur in the digits, but may also involve muscles of the arms, thighs and forearms. The onset of these symptoms may be delayed for several months to a year after the beginning of exposure. Testicular atrophy and partial to full loss of the germ cell line were observed in sub-chronic high-dose inhalation studies of laboratory rodents. These effects appeared irreversible. Rodent reproduction studies have shown evidence of reduced fetal weight but no frank malformations.

CUMENE: Overexposure to cumene may cause upper respiratory tract irritation and CNS depression. Studies in laboratory animals indicate evidence of respiratory tract hyperplasia, and adverse effects on the liver, kidney and adrenal glands following high level exposure. The relevance of these findings to humans is not clear at this time. Findings from lifetime laboratory rodent inhalation studies were as follows: In F344/N rats: an increased incidence of renal carcinomas and adenomas, respiratory epithelial adenomas, and interstitial cell adenomas of the testes. In B6C3F1 mice: an increased incidence of carcinomas and adenomas of the bronchi and lung, liver neoplasms, hemangiosarcomas of the spleen, and adenomas of the thyroid.

1,2,4-TRIMETHYLBENZENE: The following information pertains to a mixture of C9 aromatic hydrocarbons, over 40% of which was composed of 1,2,4-trimethylbenzene. A developmental inhalation study was conducted in laboratory mice. Increased implantation losses, reduced fetal weights, delayed ossification and an increased incidence of cleft palate were observed at the highest exposure level (1,500 ppm). This exposure level was extremely toxic to pregnant female mice (44% mortality). Reduced fetal body weights were also observed at 500 ppm. A multi-generation reproduction inhalation study was conducted in laboratory rats. Reductions in pup weights, pup weight gain, litter size, and pup survival were observed at 1,500 ppm, an exposure level at which significant maternal toxicity was observed. Reduced pup weight gain was also observed at 500 ppm. Embryotoxicity has been reported in studies of laboratory animals. Adverse effects included increased implantation losses, reduced fetal weights, delayed ossification and an increased incidence of cleft palate.<n><n>

ETHYLBENZENE: Findings from a 2-year inhalation study in rodents conducted by NTP were as follows: Effects were observed only at the highest exposure level (750 ppm). At this level the incidence of renal tumors was elevated in male rats (tubular carcinomas) and female rats (tubular adenomas). The incidence of tumors was also elevated in male mice (alveolar and bronchiolar carcinomas) and female mice (hepatocellular carcinomas). IARC has classified ethyl benzene as "possibly carcinogenic to humans" (Group 2B). Studies in laboratory animals indicate some evidence of post-implantation deaths following high levels of maternal exposure. The relevance of these findings to humans is not clear at this time. Studies in laboratory animals indicate limited evidence of renal malformations, resorptions, and developmental delays following high levels of maternal exposure with evidence of maternal toxicity. The relevance of these findings to humans is not clear at this time. Studies in laboratory animals have demonstrated evidence of ototoxicity (hearing loss) following exposure levels as low as 300 ppm for 5 days. Studies in laboratory animals

indicate some evidence of adverse effects on the liver, kidney, thyroid, and pituitary gland.

	NAPHTHALENE: Severe jaundice, neurotoxicity (kernicterus) and fatalities have been reported in young children and infants as a result of hemolytic anemia from overexposure to naphthalene. Persons with glucose 6-phosphate dehydrogenase (G6PD) deficiency are more prone to the hemolytic effects of naphthalene. Adverse effects on the kidney have been reported in persons overexposed to naphthalene but these effects are believed to be a consequence of hemolytic anemia, and not a direct effect. Hemolytic anemia has been observed in laboratory animals exposed to naphthalene. Laboratory rodents exposed to naphthalene vapor for 2 years (lifetime studies) developed non-neoplastic and neoplastic tumors and inflammatory lesions of the nasal and respiratory tract. Cataracts and other adverse effects on the eye have been observed in laboratory animals exposed to high levels of naphthalene. Findings from a large number of bacterial and mammalian cell mutation assays have been negative. A few studies have shown chromosomal effects (elevated levels of Sister Chromatid Exchange or chromosomal aberrations) in vitro. Naphthalene has been classified as Possibly Carcinogenic to Humans (2B) by IARC, based on findings from studies in laboratory animals.
	CARBON MONOXIDE: is a chemical asphyxiant with no warning properties (such as odor). At 400-500 ppm for 1 hour headache and dyspnea may occur. If activity is increased, symptoms of overexposure may include nausea, irritability, increased respiration, tinnitus, sweating, chest pain, confusion, impaired judgement, dizziness, weakness, drowsiness, ataxia, irregular heart beat, cyanosis and pallor. Levels in excess of 1000 ppm can result in collapse, loss of conciousness, respiratory failure and death. Extremely high concentrations (12,800 ppm) can cause immediate unconsciousness and death in 1-3 minutes. Repeated anoxia can lead to central nervous system damage and peripheral neuropathy, with loss of sensation in the fingers, amnesia, and mental deterioration and possible congestive heart failure. Damage may also occur to the fetus, lung, liver, kidney, spleen, cardiovascular system and other organs.
	WHOLLY-VAPORIZED UNLEADED GASOLINE: Lifetime exposure to wholly vaporized unleaded gasoline produced an increased incidence of liver tumors in female mice exposed to the highest exposure concentration (2056 ppm) and α -2 urinary globulin-mediated kidney tumors in male rats. No exposure-related tumors were observed in male mice or female rats. The male-specific rat kidney tumors are not considered relevant to human health. Mice receiving lifetime repeated skin application of various petroleum naphthas exhibited an irritation-dependent increased incidence of skin tumors. Additional studies suggest that these tumors occur through a mechanism that may not be relevant to human health. Epidemiological data from over 18,000 petroleum marketing and distribution workers showed no increased risk of leukemia, multiple myeloma, or kidney cancer resulting from gasoline exposure. Unleaded gasoline has been identified as possibly carcinogenic to humans (2B) by the International Agency for Research on Cancer (IARC).
	COMBUSTION ENGINE EXHAUST: Chronic inhalation studies of gasoline engine exhaust in mice, rats and hamsters did not produce any carcinogenic effects. Condensates/extracts of gasoline engine exhaust produced an increase in tumors compared to controls when testing by skin painting, subcutaneous injection, intratracheal instillation or implantation into the lungs. Gasoline exhaust has been classified as possibly carcinogenic to humans (2B) by the International Agency for Research on Cancer (IARC).
Adverse effects related to the physic	cal, chemical and toxicological characteristics
Signs and Symptoms	Irritating to the skin and mucous membranes. Symptoms may include redness, itching, and inflammation. May cause nausea, vomiting, diarrhea, and signs of nervous system depression: headache, drowsiness, dizziness, loss of coordination, disorientation and fatigue. Aspiration hazard. May cause coughing, chest pains, shortness of breath, pulmonary edema and/or chemical pneumonitis. Prolonged or repeated exposure may cause damage to organs. Repeated or prolonged skin contact may cause drying, reddening, itching and cracking.
Sensitization	Not expected to be a skin or respiratory sensitizer.

Mutagenic effects

May cause genetic defects.

May cause cancer.

Carcinogenicity

Cancer designations are listed in the table below

Name	ACGIH (Class)	IARC (Class)	NTP	OSHA
Gasoline 86290-81-5	Confirmed animal carcinogen (A3)	Possible human carcinogen (2B)	Not Listed	Not Listed
Heptane (mixed isomers) 142-82-5	Not Listed	Not Listed	Not Listed	Not Listed
Butane (mixed isomers) 106-97-8	Not Listed	Not Listed	Not Listed	Not Listed
Pentane (mixed isomers) 78-78-4	Not Listed	Not Listed	Not Listed	Not Listed
Hexane Isomers (other than n-Hexane) 107-83-5	Not Listed	Not Listed	Not Listed	Not Listed
Toluene 108-88-3	Not Classifiable (A4)	Not Classifiable (3)	Not Listed	Not Listed
Xylene (mixed isomers) 1330-20-7	Not classifiable (A4)	Not classifiable (3)	Not Listed	Not Listed
Benzene 71-43-2	Confirmed human carcinogen (A1)	Carcinogenic to humans (1)	Known to be human carcinogen	Known carcinogen
n-Hexane 110-54-3	Not Listed	Not Listed	Not Listed	Not Listed
Cumene 98-82-8	Not listed	Possible human carcinogen (2B)	Reasonably anticipated to be a human carcinogen	Not listed
1,2,4 Trimethylbenzene 95-63-6	Not Listed	Not Listed	Not Listed	Not Listed
Ethylbenzene 100-41-4	Confirmed animal carcinogen (A3)	Possible human carcinogen (2B)	Not Listed	Not Listed
Cyclohexane 110-82-7	Not Listed	Not Listed	Not Listed	Not Listed
Octane 111-65-9	Not Listed	Not Listed	Not Listed	Not Listed
1,2,3-Trimethylbenzene 526-73-8	Not Listed	Not Listed	Not Listed	Not Listed
Naphthalene 91-20-3	Confirmed animal carcinogen (A3)	Possible human carcinogen (2B)	Reasonably anticipated to be a human carcinogen	Not Listed

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity (STOT) - single exposure

Blood. Blood-forming organs. Immune system.

Respiratory system. Central nervous system.

Specific Target Organ Toxicity (STOT) - repeated exposure

Aspiration hazard

May be fatal if swallowed or vomited and enters airways.

12. ECOLOGICAL INFORMATION

Ecotoxicity

This product should be considered toxic to aquatic organisms, with the potential to cause long lasting adverse effects in the aquatic environment.

Name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Gasoline	72-hr EC50 = 56 mg/l	96-hr LC50 = 11 mg/l	-	48-hr LC50 = 7.6 mg/l
86290-81-5	Algae	Rainbow trout (static)		Daphnia magna
Heptane (mixed isomers)	-	96-hr LC50 = 375 mg/L	-	-
142-82-5		Tilapia		
Butane (mixed isomers)	-	-	-	-

106-97-8				
Pentane (mixed isomers)	-	96-hr LC50 = 3.1 mg/L	-	48-hr EC50 = >1 - <10 mg/L
78-78-4		Rainbow trout		Daphnia magna
Hexane Isomers (other than	-	-	-	-
n-Hexane)				
107-83-5				
Toluene	72-hr EC50 = 12.5 mg/l	96-hr LC50 <= 10 mg/l	-	48-hr EC50 = 5.46-9.83 mg/l
108-88-3	Algae	Rainbow trout		Daphnia magna
	-			48-hr EC50 = 11.5 mg/l
				Daphnia magna (Static)
Xylene (mixed isomers)	72-hr EC50 = 11 mg/l	96-hr LC50 = 8 mg/l	-	48-hr LC50 = 3.82 mg/l
1330-20-7	Algae	Rainbow trout		Daphnia magna
Benzene	72-hr EC50 = 29 mg/l	96-hr LC50 = 5.3 mg/l	-	48-hr EC50 = 8.76-15.6 mg/l
71-43-2	Algae	Rainbow trout		Daphnia magna (Static)
		(flow-through)		,
n-Hexane	-	96-hr LC50 = 2.5 mg/l	-	-
110-54-3		Fathead minnow		
Cumene	72-hr EC50 = 2.6 mg/l	96-hr LC50 = 6.04-6.61 mg/l	-	48-hr EC50 = 7.9-14.1 mg/l
98-82-8	Algae	Fathead minnow		Daphnia magna (static)
		(Flow-through)		
		96-hr LC50 = 2.7 mg/l		
		Rainbow trout (semi-static)		
1,2,4 Trimethylbenzene	-	96-hr LC50 = 7.19-8.28 mg/l	-	48-hr EC50 = 6.14 mg/L
95-63-6		Fathead minnow		Daphnia magna
		(flow-through)		
Ethylbenzene	72-hr EC50 = 1.7-7.6 mg/l	96-hr LC50 = 4 mg/L	-	48-hr EC50 = 1-4 mg/L
100-41-4	Algae	Rainbow trout		Daphnia magna
Cyclohexane	72-hr EC50 = 500 mg/l	96-hr LC50 = 3.96-5.18 mg/l	-	48-hr EC50 = 1.7-3.5 mg/L
110-82-7	Algae	Fathead minnow		Bay shrimp
Octane	-	-	-	48-hr LC50 = 0.38 mg/l
111-65-9				Daphnia magna
1,2,3-Trimethylbenzene	-	96-hr LC50 = 7.72 mg/l	-	-
526-73-8		Fathead Minnow		
		(flow-through)		
Naphthalene	-	96-hr LC50 = 0.91-2.82 mg/l	-	48-hr LC50 = 1.6 mg/l
91-20-3		Rainbow trout (static)		Daphnia magna
		96-hr LC50 = 1.99 mg/l		
		Fathead minnow (static)		

Persistence and degradability	Expected to be inherently biodegradable. The presence of ethanol in this product may impede the biodegradation of benzene, toluene, ethylbenzene and xylene in groundwater, resulting in elongated plumes of these constituents.
Bioaccumulation	Has the potential to bioaccumulate.
Mobility in soil	May partition into air, soil and water.
Other adverse effects	No information available.

13. DISPOSAL CONSIDERATIONS

Description of Waste Residues

This material may be a flammable liquid waste.

Safe Handling of Wastes

Handle in accordance with applicable local, state, and federal regulations. Use personal protection measures as required. Use appropriate grounding and bonding practices. Use only non-sparking tools. Do not expose to heat, open flames, strong oxidizers or other sources of ignition. No smoking.

Disposal of Wastes / Methods of Disposal

The user is responsible for determining if any discarded material is a hazardous waste (40 CFR 262.11). Dispose of in accordance with federal, state and local regulations.

Methods of Contaminated Packaging Disposal

Empty containers should be completely drained and then discarded or recycled, if possible. Do not cut, drill, grind or weld on empty containers since explosive residues may be present. Dispose of in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT (49 CFR 172.101):	
UN Proper Shipping Name:	Gasoline
UN/Identification No:	UN 1203
Class:	3
Packing Group:	II
TDG (Canada):	
UN Proper Shipping Name:	Gasoline
UN/Identification No:	UN 1203
Transport Hazard Class(es):	3
Packing Group:	II

15. REGULATORY INFORMATION

US Federal Regulatory Information:

US TSCA Chemical Inventory Section 8(b):

This product and/or its components are listed on the TSCA Chemical Inventory.

EPA Superfund Amendment & Reauthorization Act (SARA):

SARA Section 302:

This product does not contain any component(s) included on EPA's Extremely Hazardous Substance (EHS) List.

Name	CERCLA/SARA - Section 302 Extremely Hazardous Substances and TPQs
Gasoline	NA
Heptane (mixed isomers)	NA
Butane (mixed isomers)	NA
Pentane (mixed isomers)	NA
Hexane Isomers (other than n-Hexane)	NA
Toluene	NA
Xylene (mixed isomers)	NA
Benzene	NA
n-Hexane	NA
Cumene	NA
1,2,4 Trimethylbenzene	NA
Ethylbenzene	NA
Cyclohexane	NA
Octane	NA
1,2,3-Trimethylbenzene	NA
Naphthalene	NA

SARA Section 304:

This product may contain component(s) identified either as an EHS or a CERCLA Hazardous substance which in case of a spill or release may be subject to SARA reporting requirements:

Name	Hazardous Substances RQs
Gasoline	NA
Heptane (mixed isomers)	NA
Butane (mixed isomers)	NA
Pentane (mixed isomers)	NA
Hexane Isomers (other than n-Hexane)	NA
Toluene	1000 lb final RQ
	454 kg final RQ

Xylene (mixed isomers)	100
Benzene	10
n-Hexane	5000
Cumene	5000
1,2,4 Trimethylbenzene	NA
Ethylbenzene	1000
Cyclohexane	1000
Octane	NA
1,2,3-Trimethylbenzene	NA
Naphthalene	100 lb final RQ
	45.4 kg final RQ

SARA Section 311/312:

The following EPA hazard categories apply to this product:

Acute Health Hazard Chronic Health Hazard Fire Hazard

SARA Section 313:

This product may contain component(s), which if in exceedance of the de minimus threshold, may be subject to the reporting requirements of SARA Title III Section 313 Toxic Release Reporting (Form R).

Name	CERCLA/SARA 313 Emission reporting:
Gasoline	None
Heptane (mixed isomers)	None
Butane (mixed isomers)	None
Pentane (mixed isomers)	None
Hexane Isomers (other than n-Hexane)	None
Toluene	1.0 % de minimis concentration
Xylene (mixed isomers)	1.0 % de minimis concentration
Benzene	0.1 % de minimis concentration
n-Hexane	1.0 % de minimis concentration
Cumene	1.0 % de minimis concentration
1,2,4 Trimethylbenzene	1.0 % de minimis concentration
Ethylbenzene	0.1 % de minimis concentration
Cyclohexane	1.0 % de minimis concentration
Octane	None
1,2,3-Trimethylbenzene	None
Naphthalene	0.1 % de minimis concentration

Not Listed Not Listed SN 0957 Present Present Not Listed Not Listed Not Listed Not Listed Not Listed Not Listed

State and Community Right-To-Know Regulations:

The following component(s) of this material are identified on the regulatory lists below:

Gasoline

Louisiana Right-To-Know:
California Proposition 65:
New Jersey Right-To-Know:
Pennsylvania Right-To-Know:
Massachusetts Right-To Know:
Florida Substance List:
Rhode Island Right-To-Know:
Michigan Critical Materials Register List:
Massachusetts Extraordinarily Hazardous Substances:
California - Regulated Carcinogens:
Pennsylvania RTK - Special Hazardous
Substances:
New Jersey - Special Hazardous Substances:
New Jersey - Environmental Hazardous
Substances List:

Carcinogen; Flammable - third degree

SN 0957 TPQ: 10000 lb (Under N.J.A.C. 7:1G, environmental hazardous substances in mixtures such as gasoline or new and used petroleum oil may be reported under these categories)

Illinois - Toxic Air Contaminants: New York - Reporting of Releases Part 597 -List of Hazardous Substances: Heptane (mixed isomers) Louisiana Right-To-Know: California Proposition 65: New Jersey Right-To-Know: Pennsylvania Right-To-Know: Massachusetts Right-To Know: Florida Substance List: Rhode Island Right-To-Know: Michigan Critical Materials Register List: Massachusetts Extraordinarily Hazardous Substances: California - Regulated Carcinogens: Pennsylvania RTK - Special Hazardous Substances: New Jersey - Special Hazardous Substances: New Jersey - Environmental Hazardous Substances List: Illinois - Toxic Air Contaminants: New York - Reporting of Releases Part 597 -List of Hazardous Substances: Butane (mixed isomers) Louisiana Right-To-Know: California Proposition 65: New Jersey Right-To-Know: Pennsylvania Right-To-Know: Massachusetts Right-To Know: Florida Substance List: Rhode Island Right-To-Know: Michigan Critical Materials Register List: Massachusetts Extraordinarily Hazardous Substances: California - Regulated Carcinogens: Pennsylvania RTK - Special Hazardous Substances: New Jersey - Special Hazardous Substances: New Jersey - Environmental Hazardous Substances List: Illinois - Toxic Air Contaminants: New York - Reporting of Releases Part 597 -List of Hazardous Substances: Pentane (mixed isomers) Louisiana Right-To-Know: California Proposition 65: New Jersev Right-To-Know: Pennsylvania Right-To-Know: Massachusetts Right-To Know: Florida Substance List: Rhode Island Right-To-Know: Michigan Critical Materials Register List: Massachusetts Extraordinarily Hazardous Substances: California - Regulated Carcinogens: Pennsylvania RTK - Special Hazardous Substances: New Jersey - Special Hazardous Substances: New Jersey - Environmental Hazardous Substances List: Illinois - Toxic Air Contaminants: New York - Reporting of Releases Part 597 -List of Hazardous Substances: Hexane Isomers (other than n-Hexane)

Not Listed Not Listed Not Listed SN 1339 Present Present Not Listed Toxic: Flammable Not Listed Not Listed Not Listed Not Listed Flammable - third degree Not Listed Not Listed Not Listed Not Listed Not Listed SN 0273 Present Present Not Listed Toxic: Flammable Not Listed Not Listed Not Listed Not Listed Flammable - fourth degree SN 0273 TPQ: 500 lb Not Listed Not Listed Not Listed Not Listed SN 1064 Present Present Not Listed Not Listed Not Listed Not Listed Not Listed Not Listed Flammable - fourth degree SN 1064 TPQ: 500 lb Not Listed Not Listed

Present

Louisiana Right-To-Know: California Proposition 65: New Jersey Right-To-Know: Pennsylvania Right-To-Know: Massachusetts Right-To Know: Florida Substance List: Rhode Island Right-To-Know: Michigan Critical Materials Register List: Massachusetts Extraordinarily Hazardous Substances: California - Regulated Carcinogens: Pennsylvania RTK - Special Hazardous Substances: New Jersey - Special Hazardous Substances: New Jersey - Environmental Hazardous Substances List: Illinois - Toxic Air Contaminants: New York - Reporting of Releases Part 597 -List of Hazardous Substances: Toluene Louisiana Right-To-Know: California Proposition 65: New Jersey Right-To-Know: Pennsylvania Right-To-Know: Massachusetts Right-To Know: Florida Substance List: Rhode Island Right-To-Know: Michigan Critical Materials Register List: Massachusetts Extraordinarily Hazardous Substances: California - Regulated Carcinogens: Pennsylvania RTK - Special Hazardous Substances: New Jersey - Special Hazardous Substances: New Jersey - Environmental Hazardous Substances List: Illinois - Toxic Air Contaminants: New York - Reporting of Releases Part 597 -List of Hazardous Substances: Xylene (mixed isomers) Louisiana Right-To-Know: California Proposition 65: New Jersey Right-To-Know: Pennsylvania Right-To-Know: Massachusetts Right-To Know: Florida Substance List: Rhode Island Right-To-Know: Michigan Critical Materials Register List: Massachusetts Extraordinarily Hazardous Substances: California - Regulated Carcinogens: Pennsylvania RTK - Special Hazardous Substances: New Jersey - Special Hazardous Substances: New Jersey - Environmental Hazardous Substances List: Illinois - Toxic Air Contaminants: New York - Reporting of Releases Part 597 -List of Hazardous Substances: Benzene Louisiana Right-To-Know: California Proposition 65:

Not Listed Not Listed SN 1285 Present Present Not Listed Not Listed Not Listed Not Listed Not Listed Not Listed Flammable - third degree Not Listed Not Listed Not Listed Not Listed Developmental toxicity, initial date 1/1/91 Female reproductive toxicity, initial date 8/7/09 SN 1866 Environmental hazard Present Not Listed Toxic (skin); Flammable (skin) 100 lb Annual usage threshold Not Listed Not Listed Not Listed Flammable - third degree; Teratogen SN 1866 TPQ: 500 lb Present 1000 lb RQ (air); 1 lb RQ (land/water) Not Listed Not Listed SN 2014 Environmental hazard Present Not Listed Toxic (skin); Flammable (skin) 100 lb Annual usage threshold all isomers Not Listed Not Listed Not Listed Flammable - third degree SN 2014 TPQ: 500 lb Present 1000 lb RQ (air); 1 lb RQ (land/water)

Not Listed Carcinogen, initial date 2/27/87 Developmental toxicity, initial date 12/26/97

New Jersey Right-To-Know: Pennsylvania Right-To-Know: Massachusetts Right-To Know: Florida Substance List: Rhode Island Right-To-Know: Michigan Critical Materials Register List: Massachusetts Extraordinarily Hazardous Substances: California - Regulated Carcinogens: Pennsylvania RTK - Special Hazardous Substances: New Jersey - Special Hazardous Substances: New Jersey - Environmental Hazardous Substances List: Illinois - Toxic Air Contaminants: New York - Reporting of Releases Part 597 -List of Hazardous Substances: n-Hexane Louisiana Right-To-Know: California Proposition 65: New Jersey Right-To-Know: Pennsylvania Right-To-Know: Massachusetts Right-To Know: Florida Substance List: Rhode Island Right-To-Know: Michigan Critical Materials Register List: Massachusetts Extraordinarily Hazardous Substances: California - Regulated Carcinogens: Pennsylvania RTK - Special Hazardous Substances: New Jersey - Special Hazardous Substances: New Jersey - Environmental Hazardous Substances List: Illinois - Toxic Air Contaminants: New York - Reporting of Releases Part 597 -List of Hazardous Substances: Cumene Louisiana Right-To-Know: California Proposition 65: New Jersey Right-To-Know: Pennsylvania Right-To-Know: Massachusetts Right-To Know: Florida Substance List: Rhode Island Right-To-Know: Michigan Critical Materials Register List: Massachusetts Extraordinarily Hazardous Substances: California - Regulated Carcinogens: Pennsylvania RTK - Special Hazardous Substances: New Jersey - Special Hazardous Substances: New Jersey - Environmental Hazardous Substances List: Illinois - Toxic Air Contaminants: New York - Reporting of Releases Part 597 -List of Hazardous Substances: 1,2,4 Trimethylbenzene Louisiana Right-To-Know: California Proposition 65: New Jersey Right-To-Know: Pennsylvania Right-To-Know: Massachusetts Right-To Know:

Male reproductive toxicity, initial date 12/26/97 SN 0197 Environmental hazard; Special hazardous substance Carcinogen; Extraordinarily hazardous Not Listed Toxic (skin); Flammable (skin); Carcinogen (skin) 100 lb Annual usage threshold Carcinogen; Extraordinarily hazardous Not Listed Present Carcinogen; Flammable - third degree; Mutagen SN 0197 TPQ: 500 lb Present 10 lb RQ (air); 1 lb RQ (land/water) Not Listed Not Listed SN 1340 Present Present Not Listed Toxic; Flammable Not Listed Not Listed Not Listed Not Listed Flammable - third degree SN 1340 TPQ: 500 lb Present 1 lb RQ (air); 1 lb RQ (land/water) Not Listed Carcinogen, initial date 4/6/10 SN 0542 Environmental hazard Present Not Listed Toxic (skin); Flammable (skin) Not Listed Not Listed Not Listed Not Listed Flammable - third degree SN 0542 TPQ: 500 lb Present 5000 lb RQ (air); 1 lb RQ (land/water) Not Listed Not Listed SN 1929 Present Present

Florida Substance List: Not Listed Rhode Island Right-To-Know: Toxic Michigan Critical Materials Register List: Not Listed Massachusetts Extraordinarily Hazardous Substances: Not Listed California - Regulated Carcinogens: Not Listed Pennsylvania RTK - Special Hazardous Not Listed Substances: New Jersey - Special Hazardous Substances: Not Listed New Jersey - Environmental Hazardous Not Listed Substances List: Illinois - Toxic Air Contaminants: Present New York - Reporting of Releases Part 597 -Not Listed List of Hazardous Substances: Ethylbenzene Louisiana Right-To-Know: Not Listed California Proposition 65: New Jersey Right-To-Know: SN 0851 Pennsylvania Right-To-Know: Massachusetts Right-To Know: Present Florida Substance List: Not Listed Rhode Island Right-To-Know: Michigan Critical Materials Register List: Not Listed Massachusetts Extraordinarily Hazardous Substances: Not Listed California - Regulated Carcinogens: Not Listed Pennsylvania RTK - Special Hazardous Not Listed Substances: New Jersey - Special Hazardous Substances: New Jersey - Environmental Hazardous Substances List: Illinois - Toxic Air Contaminants: Present New York - Reporting of Releases Part 597 -List of Hazardous Substances: Cyclohexane Louisiana Right-To-Know: Not Listed California Proposition 65: Not Listed New Jersey Right-To-Know: SN 0565 Pennsylvania Right-To-Know: Present Massachusetts Right-To Know: Florida Substance List: Not Listed Rhode Island Right-To-Know: Michigan Critical Materials Register List: Not Listed Massachusetts Extraordinarily Hazardous Substances: Not Listed California - Regulated Carcinogens: Not Listed Pennsylvania RTK - Special Hazardous Not Listed Substances: New Jersey - Special Hazardous Substances: New Jersey - Environmental Hazardous Substances List: Illinois - Toxic Air Contaminants: Not Listed New York - Reporting of Releases Part 597 -List of Hazardous Substances: Octane Louisiana Right-To-Know: Not Listed California Proposition 65: Not Listed New Jersey Right-To-Know: SN 1434 Pennsylvania Right-To-Know: Present Massachusetts Right-To Know: Present Florida Substance List: Not Listed Rhode Island Right-To-Know: Michigan Critical Materials Register List: Not Listed Massachusetts Extraordinarily Hazardous Substances: Not Listed

Carcinogen, initial date 6/11/04 Environmental hazard Toxic; Flammable Carcinogen; flammable - Third degree SN 0851 TPQ: 500 lb 1000 lb RQ (air); 1 lb RQ (land/water) Environmental hazard Toxic; Flammable Flammable - third degree SN 0565 TPQ: 500 lb 1000 lb RQ (air); 1 lb RQ (land/water) Toxic; Flammable

	California - Regulated Carcinogens: Pennsylvania RTK - Special Hazardous	Not Listed Not Listed
	Substances: New Jersey - Special Hazardous Substances: New Jersey - Environmental Hazardous	Flammable - third degree Not Listed
	Substances List: Illinois - Toxic Air Contaminants: New York - Reporting of Releases Part 597 -	Not Listed Not Listed
	List of Hazardous Substances:	
1,2	,3-Trimethylbenzene	NI 211 2 1
	Louisiana Right-To-Know:	Not Listed
	California Proposition 65:	NOT LISTED
	New Jersey Right-To-Khow.	SIN 1929 Drecent
	Massachusotte Pight To Know:	Present
	Florida Substance List:	Not Listed
	Rhode Island Right-To-Know	Toxic
	Michigan Critical Materials Register List	Not Listed
	Massachusetts Extraordinarily Hazardous Substances:	Not Listed
	California - Regulated Carcinogens:	Not Listed
	Pennsylvania RTK - Special Hazardous	Not Listed
	Substances:	
	New Jersey - Special Hazardous Substances:	Not Listed
	New Jersey - Environmental Hazardous	Not Listed
	Substances List:	
	Illinois - Toxic Air Contaminants:	Present
	New York - Reporting of Releases Part 597 -	Not Listed
	List of Hazardous Substances:	
Na	phthalene	
	Louisiana Right-To-Know:	Not Listed
	California Proposition 65:	Carcinogen, initial date 4/19/02
	New Jersey Right-To-Know:	SN 1322 SN 3758
	Pennsylvania Right-To-Know:	Environmental nazard Present (particulate)
	Massachusetts Right-To Know:	Present
	Florida Substance List. Phode Island Pight To Know:	Not Listed
	Michigan Critical Materiale Projector Liet:	Not Listod
	Massachusetts Extraordinarily Hazardous Substances:	Not Listed
	California - Regulated Carcinogens:	Not Listed
	Pennsylvania RTK - Special Hazardous	Not Listed
	Substances:	
	New Jersey - Special Hazardous Substances:	Carcinogen
	New Jersey - Environmental Hazardous	SN 1322 TPQ: 500 lb (Reportable at the de minimis quantity of
	Substances List:	>0.1%)
	Illinois - Toxic Air Contaminants:	Present
	New York - Reporting of Releases Part 597 -	100 lb RQ (air); 1 lb RQ (land/water)
	List of Hazardous Substances:	
_		

Canada DSL/NDSL Inventory:

This product and/or its components are listed either on the Domestic Substances List (DSL) or are exempt.

Canadian Regulatory Information:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all of the information required by those regulations.

Name	Canada - WHMIS: Classifications of Substances:	Canada - WHMIS: Ingredient Disclosure:
Gasoline	B2,D2A,D2B	0.1%
Heptane (mixed isomers)	B2,D2B	1%
Butane (mixed isomers)	A,B1	1%
Pentane (mixed isomers)	B2	1%

Hexane Isomers (other than n-Hexane)	B2	1%
Toluene	B2,D2A,D2B	0.1%
Xylene (mixed isomers)	B2,D2A,D2B	m-, o-isomers 1.0%; p-isomer 0.1%
Benzene	B2,D2A,D2B	0.1%
n-Hexane	B2,D2A,D2B	1%
Cumene	B2,D2A	0.1%
1,2,4 Trimethylbenzene	B3,D2B	1%
Ethylbenzene	B2,D2A,D2B	0.1%
Cyclohexane	B2,D2B	1%
Octane	B2,D2B	1%
1,2,3-Trimethylbenzene	B3	1%
Naphthalene	B4,D2A	0.1%



Note:

Not applicable.

16. OTHER INFORMATION

Prepared By

Revision Notes

Revision Date Previous Publish Date Revised Sections Toxicology and Product Safety

03/19/2018 11/06/2017 The following sections (§) have been updated: 2. HAZARD IDENTIFICATION 3. COMPOSITION/INFORMATION ON INGREDIENTS 4. FIRST AID MEASURES 11. TOXICOLOGICAL INFORMATION

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is intended as guidance for safe handling, use, processing, storage, transportation, accidental release, clean-up and disposal and is not considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SAFETY DATA SHEET

CITGO CITGARD® 600 Engine Oil, SAE 15W-40



GHS product identifier	: CITGO CITGARD® 600 Engine Oil, SAE 15W-40
Synonyms	: Heavy duty motor oil
Material uses	: Heavy Duty Engine Oil
Code	: 622615001
Supplier's details	: CITGO Petroleum Corporation P.O. Box 4689 Houston, TX 77210 sdsvend@citgo.com
Emergency telephone number (with hours of operation)	: Technical Contact: (800) 248-4684 Medical Emergency: (832) 486-4700 CHEMTREC Emergency: (800) 424-9300 (United States Only)

Section 2. Hazards identification

OSHA/HCS status	: While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.
Classification of the substance or mixture	: Not classified.
GHS label elements	
Signal word	: No signal word.
Hazard statements	: No known significant effects or critical hazards.
Precautionary statements	
General	: Avoid contact with eyes, skin and clothing. Thoroughly wash exposed areas and clothing with soap and water. IF IN EYES: Rinse cautiously with water for several minutes. IF SWALLOWED: Do not induce vomiting. If you feel unwell, seek medical attention and show the label when possible. Keep out of reach of children.
Prevention	: Not applicable.
Response	: Not applicable.
Storage	: Not applicable.
Disposal	: Not applicable.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Heavy duty motor oil

CAS number/other identifiers

CAS number

: Not applicable.





Section 3. Composition/information on ingredients

Ingredient name	%	CAS number
Distillates (petroleum), hydrotreated heavy paraffinic Distillates (petroleum), solvent-refined heavy paraffinic Distillates (petroleum), solvent-dewaxed heavy paraffinic reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl) propionate	≥75 - ≤90 ≤5 ≤3 ≤3	64742-54-7 64741-88-4 64742-65-0 125643-61-0

Any concentration shown as a range is to protect confidentiality or is due to process variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	: Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Potential acute health	n effects
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs	/symptoms
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Indication of immediat	<u>e medical attention and special treatment needed, if necessary</u>
Nuclear the scheme test and	

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediate 	iately if large
	quantities have been ingested or inhaled.	
One selfter the stress sets		

- **Specific treatments** : Treat symptomatically and supportively.
- **Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide sulfur oxides phosphorus oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protect	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	nta	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe hand	ling					
Protective measures	: Put on a	opropriate personal protecti	ve equipment (see Se	ection 8).		
Advice on general occupational hygiene	: Eating, d handled, drinking entering measure	Lating, drinking and smoking should be prohibited in areas where this material is nandled, stored and processed. Workers should wash hands and face before eating, frinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.				
Date of issue/Date of revision	: 4/9/2018	Date of previous issue	: 11/14/2017	Version	: 1.01	3/11

Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.
	Bulk Storage Conditions: Maintain all storage tanks in accordance with applicable regulations. Use necessary controls to monitor tank inventories. Inspect all storage tanks on a periodic basis. Test tanks and associated piping for tightness. Maintain the automatic leak detection devices to assure proper working condition.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated heavy paraffinic	ACGIH TLV (United States, 3/2016). TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction OSHA PEL (United States, 6/2016). TWA: 5 mg/m ³ 8 hours. NIOSH REL (United States, 10/2013). TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist
Distillates (petroleum), solvent-refined heavy paraffinic	ACGIH TLV (United States, 3/2016). TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction OSHA PEL (United States, 6/2016). TWA: 5 mg/m ³ 8 hours. NIOSH REL (United States, 10/2013). TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist
Distillates (petroleum), solvent-dewaxed heavy paraffinic	ACGIH TLV (United States, 3/2016). TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction OSHA PEL (United States, 6/2016). TWA: 5 mg/m ³ 8 hours. NIOSH REL (United States, 10/2013). TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist

Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, vapor controls, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection meas	ures	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 8. Exposure controls/personal protection

Eye/face protection	: Safety glasses equipped with side shields are recommended as minimum protection in industrial settings. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If inhalation hazards exist, a full-face respirator may be required instead.
Skin protection	
Hand protection	: Chemical-resistant gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Avoid skin contact with liquid. Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Leather boots are not protective for liquid contact.
Respiratory protection	: Avoid inhalation of gases, vapors, mists or dusts. Use a properly fitted, air-purifying or supplied-air respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance		
Physical state	:	Liquid.
Color	1	Amber.
Odor	:	Mild petroleum odor
рН	1	Not available.
Boiling point	:	Not available.
Flash point	:	Open cup: 235°C (455°F) [Cleveland.]
Evaporation rate	:	<1 (butyl acetate = 1)
Lower and upper explosive (flammable) limits	:	Not available.
Vapor pressure	1	<0.0013 kPa (<0.01 mm Hg) [room temperature]
Vapor density	1	Not available.
Relative density	:	0.87
Density lbs/gal	1	7.28 lbs/gal
Density gm/cm ³	:	Not available.
Gravity, °API	:	30.8
Solubility	:	Insoluble in the following materials: cold water.
Flow time (ISO 2431)	:	Not available.
Viscosity	:	Kinematic (40°C (104°F)): 1.16 cm²/s (116 cSt)
Viscosity SUS	:	Estimated 537 SUS @104 F

Section 10. Stability and reactivity

: 4/9/2018

Date of issue/Date of revision

Reactivity	:	Not expected to be Explosive, Self-Reactive, Self-Heating, or an Organic Peroxide under US GHS Definition(s).
Chemical stability	:	The product is stable.
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.

Date of previous issue

:11/14/2017

Version : 1.01

Section 10. Stability and reactivity

Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition	: Under normal conc

Hazardous decomposition : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), hydrotreated heavy paraffinic Distillates (petroleum)	LD50 Oral	Rat Rabbit	>5000 mg/kg	-
solvent-refined heavy paraffinic				
Distillatos (notrolours)	LD50 Oral	Rat	5000 mg/kg	-
solvent-dewaxed heavy	LD50 Dermai	Raddil	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Irritation/Corrosion	Distillates (petroleum), hydrotic highly refined oils are reported to Effects from single and short-term oil mists well above applicable w reaction, lipoid granuloma formar studies involving exposures to lo current work place exposure leve Distillates (petroleum), solvent from highly refined oils are report animals. Effects from single and of mineral oil mists well above applicable with a sub-acute studies involving exposure from highly refined oils are report animals. Effects from single and of mineral oil mists well above applicable with a sub-acute studies involving exposure from highly refined oils are report animals. Effects from single and of mineral oil mists well above applicable with a sub-acute studies involving exposure from highly refined oils are report animals. Effects from single and of mineral oil mists well above applicable with a sub-acute studies involving exposure from highly refined oils are report animals. Effects from single and of mineral oil mists well above applicable were characterized by necrosis a effects (cellular hypertrophy) followere characterized by necrosis a effects on prothrombin index were Chronic studies did not find carcies.	have low acute a m repeated exposi- orkplace exposur- tion and lipoid pne- wer concentration els produced no si t-refined heavy p - ted to have low ac short-term repea- oplicable workplace nuloma formation sures to lower con- e levels produced t-dewaxed heavy - ted to have low ac short-term repea- oplicable workplace applicable workplace to have low ac short-term repea- oplicable workplace applicable workplace short-term repea- oplicable workplace applicable workplace short-term repea- oplicable workplace applicable workplace	aminic: Mineral off and sub-acute toxici sures to high concer- e levels include lung eumonia. In acute a is of mineral oil mis- ignificant toxicologic paraffinic: Mineral of cute and sub-acute ted exposures to his e exposure levels i and lipoid pneumor- ncentrations of mine- no significant toxico paraffinic: Mineral cute and sub-acute ted exposure levels i and lipoid pneumor- ncentrations of mine- ted exposures to his e exposure levels i and lipoid pneumor- ncentrations of mine- no significant toxico di-tert-butyl-4-hydi- nenols have been as stration to rats. The es of 250 mg/kg/da ver this effect is not i rats or mice.	ties in animals. ntrations of mineral g inflammatory and sub-acute ts at or near cal effects. bil mists derived toxicities in gh concentrations nclude lung hia. In acute and eral oil mists at or ological effects. I oil mists derived toxicities in gh concentrations nclude lung hia. In acute and eral oil mists at or ological effects. I oil mists at or ological effects. I oil mists at or ological effects. I oil mists at or ological effects. roxyphenyl) ssociated with liver ese liver effects by or higher. Also, a seen in all studies.

Not available.

Skin Eyes Respiratory Sensitization Not available.

- : No additional information.
- : No additional information.
- : No additional information.

Date of issue/Date of revision

Section 11. Toxicological information

Section 11. TOXICO	Jiogica		nation
Skin	: No additional information.		
Respiratory	: No additional information.		
<u>Mutagenicity</u>			
Not available.			
Conclusion/Summary	: No addi	ional inform	nation.
Carcinogenicity			
Not available.			
Conclusion/Summany	Distillat	ac (natrala	um) solvent refined heavy pareffinie: In long term studies (up to
conclusion/Summary	two vea	s) no carcir	nogenic effects have been reported in any animal species tested.
Classification	, ,	-,	
Product/ingredient name	OSHA	IARC	NTP
	-	4	-
solvent-refined heavy paraffinic			
Reproductive toxicity			
Not available.			
Conclusion/Summary	: No addit	ional inform	nation.
Teratogenicity			
Not available.			
Conclusion/Summary	: No addit	ional inform	nation.
Specific target organ toxicit	v (sinale e)	(posure)	
Not available.		,	
Specific target organ toxicit	ty (repeated	<u>exposure</u>	
Not available.			
Aspiration hazard			
Not available.			
Information on the likely routes of exposure	: Not avai	lable.	
Potential acute health effects	<u>i</u>		
Eye contact	: No knov	n significar/	nt effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.		
Skin contact	: No known significant effects or critical hazards.		
Ingestion	: No known significant effects or critical hazards.		
Symptoms related to the phy	<u>sical, chem</u>	ical and to	xicological characteristics
Eye contact	: No spec	ific data.	
Inhalation	: No spec	ific data.	
Skin contact	: No spec	ific data.	
Ingestion	: No spec	ific data.	
Delayed and immediate effect	ts and also	<u>chronic ef</u>	fects from short and long term exposure
Short term exposure			
Potential immediate effects	: Not avai	lable.	
Potential delayed effects	: Not avai	lable.	

Date of issue/Date of revision

: 4/9/2018

Date of previous issue

sue : 11/14/2017

Version : 1.01

7/11

Section 11. Toxicological information

<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	ects
Not available.	
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Section 12. Ecological information

Toxicity

Not available.

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Distillates (petroleum), solvent-refined heavy paraffinic	3.9 to 6	-	high
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl- 4-hydroxyphenyl) propionate	9.2	260	low

Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Section 14. Transport information

	DOT Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

Oil: The product(s) represented by this SDS is (are) regulated as "oil" under 49 CFR Part 130. Shipments by rail or highway in packaging having a capacity of 3500 gallons or more or in a quantity greater 42,000 gallons are subject to these requirements. In addition, mixtures containing 10% or more of this product may be subject to these requirements.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

```
Transport in bulk according : Not available.
to Annex II of MARPOL and
the IBC Code
```

Section 15. Regulatory information

U.S. Federal regulations United States inventory (TSCA 8b): All components are listed or exempted. Clean Water Act (CWA) 307: Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts; toluene; benzene Clean Water Act (CWA) 311: fumaric acid; ethylenediamine; toluene; vinyl acetate; benzene This material is classified as an oil under Section 311 of the Clean Water Act (CWA) and the Oil Pollution Act of 1990 (OPA). Discharges or spills which produce a visible sheen on waters of the United States, their adjoining shorelines, or into conduits leading to surface waters must be reported to the EPA's National Response Center at (800) 424-8802.

SARA 302/304

Composition/information on ingredients

			SARA 30	2 TPQ	SARA 30)4 RQ
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
ethylenediamine vinyl acetate	<0.1 <0.0001	Yes. Yes.	10000 1000	1337.1 129	5000 5000	668.5 644.8
SARA 304 RQ	: 42151407.9 lbs / 19136	739.2 kg [58	310795 gal	/ 21996251.91	1	

SARA 311/312

Classification : Not applicable.

Composition/information on ingredients

No products were found.

Section 15. Regulatory information

State regulations

Massachusetts	: None of the components are listed.
New York	: None of the components are listed.
New Jersey	: None of the components are listed.
Pennsylvania	: None of the components are listed.

California Prop. 65 Clear and Reasonable Warnings (2018)

▲ WARNING: This product can expose you to Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Toluene, Ethylene Glycol, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ingredient name	%	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
toluene	<0.1	No.	Yes.	-	Yes.
benzene	trace	Yes.	Yes.	Yes.	Yes.
ethanediol	<0.1	NO.	Yes.	-	-
nternational regulations					
WHMIS (Canada)	Not contr	olled under W	HMIS (Canada).		
<u>nventory list</u>					
United States	All comp	onents are liste	ed or exempted.		
Australia	All compo	onents are liste	ed or exempted.		
Canada	All compo	onents are liste	ed or exempted.		
China :	Not deter	lot determined.			
Europe	All compo	onents are liste	ed or exempted.		
Japan :	Japan in Japan in	ventory (ENC ventory (ISHI	S) : Not determined:): Not determined.	Ι.	
Malaysia	Not deter	mined.			
New Zealand	All compo	onents are liste	ed or exempted.		
Philippines :	Not deter	mined.			
Republic of Korea :	All compo	onents are liste	ed or exempted.		
Taiwan	All compo	onents are liste	ed or exempted.		
Thailand :	Not deter	mined.			
Turkey	Not deter	mined.			
Viet Nam :	Not deter	mined.			

Section 16. Other information

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Section 16. Other information

Procedure used to derive the classification				
	Classific	ation	Justification	
Not classified.				
History				
Date of printing	: 4/24/2018			
Date of issue/Date of revision	: 4/9/2018			
Date of previous issue	: 11/14/2017			
Version	: 1.01			
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)			
References	: Not availabl	e.		

Indicates information that has changed from previously issued version.

Notice to reader

THE INFORMATION IN THIS SAFETY DATA SHEET (SDS) WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED REGARDING ITS CORRECTNESS OR ACCURACY. SOME INFORMATION PRESENTED AND CONCLUSIONS DRAWN HEREIN ARE FROM SOURCES OTHER THAN DIRECT TEST DATA ON THE SUBSTANCE ITSELF. THIS SDS WAS PREPARED AND IS TO BE USED ONLY FOR THIS PRODUCT. IF THE PRODUCT IS USED AS A COMPONENT IN ANOTHER PRODUCT, THIS SDS INFORMATION MAY NOT BE APPLICABLE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE OR APPLICATION.

THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE, AND/OR DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR ANY LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.

CITGO is a registered trademark of CITGO Petroleum Corporation

SAFETY DATA SHEET

CITGO No. 2 Diesel Fuel, All Grades, Low Sulfur

Section 1. Identification

GHS product identifier	: CITGO No. 2 Diesel Fuel, All Grades, Low Sulfur
Chemical name	: Fuels, diesel, No 2
Synonyms	 No. 2-D Grade Diesel Fuel Oil (defined by ASTM D-975); Treated or Refined Diesel Fuel No. 2; Grade 2 Distillate Fuel; Hydrodesulfurized Middle Distillate; C9-C16 Petroleum Hydrocarbons
Material uses	: Fuel.
Code	: Various
Supplier's details	: CITGO Petroleum Corporation P.O. Box 4689 Houston, TX 77210 sdsvend@citgo.com
Emergency telephone number (with hours of operation)	: Technical Contact: (800) 248-4684 Medical Emergency: (832) 486-4700 CHEMTREC Emergency: (800) 424-9300 (United States Only)

Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	 FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2B CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS)) - Category 2 ASPIRATION HAZARD - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 2

GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	 Flammable liquid and vapor. Harmful if inhaled. Causes skin and eye irritation. Suspected of causing cancer. May be fatal if swallowed and enters airways. May cause damage to organs through prolonged or repeated exposure. (central nervous system (CNS)) Toxic to aquatic life with long lasting effects.
Precautionary statements	
General	: Diesel engine exhaust can cause upper respiratory tract irritation and reversible pulmonary effects. Long-term exposure to diesel engine exhaust may cause cancer. Do not syphon by mouth.



Section 2. Hazards identification

Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Do not breathe vapor. Wash hands thoroughly after handling.
Response	: Collect spillage. Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	: Store locked up. Store in a well-ventilated place. Keep cool.
Disposal	 Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and receiving equipment. These alone may be insufficient to remove static electricity. Do not taste or swallow. Wash thoroughly after handling.
Hazards not otherwise classified	: Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor may cause flash fire or explosion. Causes digestive tract burns. Prolonged or repeated contact may dry skin and cause irritation.

Section 3. Composition/information on ingredients

Substance/mixture	:	Substance
Chemical name	:	Fuels, diesel, No 2
Other means of identification	:	No. 2-D Grade Diesel Fuel Oil (defined by ASTM D-975); Treated or Refined Diesel Fuel No. 2; Grade 2 Distillate Fuel; Hydrodesulfurized Middle Distillate; C9-C16 Petroleum Hydrocarbons

CAS number/other identifiers

CAS number : 68476-34-6		
Ingredient name	%	CAS number
Benzene, trimethyl-	1 - 5	25551-13-7
Naphthalene	0.5 - 1.5	91-20-3
biphenyl	0.5 - 1.5	92-52-4
Cumene	0.5 - 1.5	98-82-8
Xylene	0.5 - 1.5	1330-20-7
Ethylbenzene	0.5 - 1.5	100-41-4

* = Various ** = Mixture *** = Proprietary

Any concentration shown as a range is to protect confidentiality or is due to process variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effe	ects, acute and delayed		
Potential acute health effects			
Eye contact	: Causes eye irritation.		
Inhalation	Harmful if inhaled.		
Skin contact	: Causes skin irritation. Defatting to the skin.		
Ingestion	Corrosive to the digestive tract. Causes burns. May be fatal if swallowed and enters airways.		
Over-exposure signs/sympto	<u>ms</u>		
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness		
Inhalation	Repeated or prolonged overexposure to solvents can cause brain or other nervous system damage. The symptoms can include the loss of memory, the loss of intellectual capacity and the loss of coordination.		
Skin contact	: Adverse symptoms may include the following: irritation redness dryness cracking		
Ingestion	: Adverse symptoms may include the following: stomach pains nausea or vomiting		
Indication of immediate medic	al attention and special treatment needed, if necessary		
Notes to physician	: If ingested, this material presents a significant aspiration and chemical pneumonitis hazard. Induction of emesis is not recommended. Consider activated charcoal and/or gastric lavage. If patient is obtunded, protect the airway by cuffed endotracheal intubation or by placement of the body in a Trendelenburg and left lateral decubitus position.		
Specific treatments	: Treat symptomatically and supportively.		

 Date of issue/Date of revision
 : 7/31/2018
 Date of previous issue
 : 4/16/2018
 Vers

Section 4. First aid measures

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that gas or vapor is still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use caution when applying carbon dioxide in confined spaces. SMALL FIRE: Steam, CO ₂ , dry chemical or inert gas (e.g., nitrogen). LARGE FIRE: Use foam, water fog or water spray. Water fog and spray are effective in cooling containers and adjacent structures. However, water can cause frothing and/or may not extinguish the fire. Water can be used to cool the external walls of vessels to prevent excessive pressure, ignition or explosion.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static accumulation may be significantly increased by the presence of small quantities of water or other contaminants. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide Diesel engine exhaust
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures		
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.	
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	

Section 6. Accidental release measures

Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Restrict flow velocity according to API 2003 (2008), NFPA 77 (2007), and Laurence Britton, "Avoiding Static Ignition Hazards in Chemical Operations". To reduce potential for static discharge, ensure that all equipment is properly grounded and bonded and meets appropriate electrical classification requirements. Non equilibrium conditions may increase the fire hazard associated with this product. Always bond receiving containers to the fill pipe before and during loading. Always confirm that receiving container is properly grounded. Bonding and grounding alone may be inadequate to eliminate fire and explosion hazards. Carefully review operations that may increase the risks such as tank and container filling, tank cleaning, sampling, gauging, loading, filtering, mixing, agitation, etc. In addition to bonding and grounding, efforts to mitigate the hazards may include, but are not limited to, ventilation, inerting and/or reduction of transfer velocities. Always keep nozzle in contact with the container throughout the loading process. Do NOT fill any portable container in or on a vehicle. Special precautions, such as reduced loading rates and increased monitoring, must be observed during "switch loading" operations (i.e., loading this material in tanks or shipping compartments that previously contained a dissimilar product). Advice on general Eating, drinking and smoking should be prohibited in areas where this material is occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use. Bulk Storage Conditions: Maintain all storage tanks in accordance with applicable regulations. Use necessary controls to monitor tank inventories. Inspect all storage tanks on a periodic basis. Test tanks and associated piping for tightness. Maintain the automatic leak detection devices to assure proper working condition
	Head spaces in tanks and other containers may contain a mixture of air and vapor in the flammable range. Vapor may be ignited by static discharge. Storage area must meet OSHA requirements and applicable fire codes. Additional information regarding the design and control of hazards associated with the handling and storage of flammable and combustible liquids may be found in professional and industrial documents including, but not limited to, the National Fire Protection Association (NFPA) publications NFPA 30 ("Flammable and Combustible Liquid Code"), NFPA 77 ("Recommended Practice on Static Electricity") and the American Petroleum Institute (API) Recommended Practice 2003, ("Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents").

Section 8. Exposure controls/personal protection

Occupational exposure li	<u>mits</u>			
Fuels, diesel, No 2			ACGIH TLV (Ur Absorbed thro TWA: 100 mg/ hydrocarbons) 8 hydrocarbons	nited States, 2/2010). ugh skin. /m³, (measured as total 3 hours. Form: Total
Benzene, trimethyl-			ACGIH TLV (Ur TWA: 25 ppm TWA: 123 mg/	nited States, 3/2017). 8 hours. /m³ 8 hours
Naphthalene			ACGIH TLV (Ur through skin. STEL: 15 ppm ACGIH TLV (Ur Absorbed thro TWA: 10 ppm TWA: 52 mg/n NIOSH REL (Ur	nited States). Absorbed 15 minutes. nited States, 3/2017). ugh skin. 8 hours. n ³ 8 hours. nited States, 10/2016).
			TWA: 10 ppm TWA: 50 mg/n STEL: 15 ppm STEL: 75 mg/r OSHA PEL (Un TWA: 10 ppm TWA: 50 mg/n	10 hours. n ³ 10 hours. 15 minutes. n ³ 15 minutes. ited States, 6/2016). 8 hours. n ³ 8 hours.
biphenyl			OSHA PEL Z2 (TWA: 0.2 ppm ACGIH TLV (Ur TWA: 0.2 ppm TWA: 1.3 mg/r NIOSH REL (Ur TWA: 1 mg/m ³ TWA: 0.2 ppm OSHA PEL (Un TWA: 0.2 ppm TWA: 1 mg/m ³	(United States). a 8 hours. nited States, 3/2017). a 8 hours. m ³ 8 hours. nited States, 10/2016). ³ 10 hours. a 10 hours. bited States, 6/2016). a 8 hours. ³ 8 hours.
Date of issue/Date of revision	: 7/31/2018	Date of previous issue	: 4/16/2018	Version :4

Date of issue/Date of revision

Control parameters

Section 8. Exposure controls/personal protection

Cumene	NIOSH REL (United States, 10/2016). Absorbed through skin. TWA: 50 ppm 10 hours. TWA: 245 mg/m ³ 10 hours. ACGIH TLV (United States, 3/2017). TWA: 50 ppm 8 hours. OSHA PEL (United States, 6/2016). Absorbed through skin. TWA: 50 ppm 8 hours
	TWA: 245 mg/m ³ 8 hours.
Xylene	ACGIH TLV (United States, 3/2017). TWA: 100 ppm 8 hours. TWA: 434 mg/m ³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 651 mg/m ³ 15 minutes. OSHA PEL (United States, 6/2016). TWA: 100 ppm 8 hours. TWA: 435 mg/m ³ 8 hours.
Ethylbenzene	ACGIH TLV (United States, 3/2017). TWA: 20 ppm 8 hours. NIOSH REL (United States, 10/2016). TWA: 100 ppm 10 hours. TWA: 435 mg/m ³ 10 hours. STEL: 125 ppm 15 minutes. STEL: 545 mg/m ³ 15 minutes. OSHA PEL (United States, 6/2016). TWA: 100 ppm 8 hours. TWA: 435 mg/m ³ 8 hours.

Appropriate engineering controls	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, vapor controls, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measure	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	Safety glasses equipped with side shields are recommended as minimum protection in ndustrial settings. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If inhalation hazards exist, a full-face respirator may be required nstead.
Skin protection	

Section 8. Exposure controls/personal protection

Hand protection	: Avoid skin contact with liquid. Chemical-resistant gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Recommended: Heavy duty, industrial grade chemically resistant gloves constructed of nitrile, neoprene, polyethylene, fluoroelastomer rubber or polyvinyl chloride as approved by glove manufacturer. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Leather gloves are not protective for liquid contact.
Body protection	: Avoid skin contact with liquid. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Avoid skin contact with liquid. Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Leather boots are not protective for liquid contact.
Respiratory protection	: Avoid inhalation of gases, vapors, mists or dusts. Use a properly fitted, air-purifying or supplied-air respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If an air purifying respirator is appropriate, use one equipped with cartridges rated for organic vapors.

Section 9. Physical and chemical properties

<u>Appearance</u>		
Physical state	:	Liquid.
Color	:	Not available.
Odor	:	Characteristic.
рН	:	Not available.
Melting point	:	-30 to -18°C (-22 to -0.4°F)
Boiling point	:	282 to 338°C (539.6 to 640.4°F)
Flash point	:	Closed cup: ≥52°C (≥125.6°F) [Pensky-Martens.]
Evaporation rate	:	<1 (butyl acetate = 1)
Lower and upper explosive (flammable) limits	:	Lower: 0.6% Upper: 6.5%
Vapor pressure	:	0.27 kPa (2 mm Hg) [room temperature]
Vapor density	:	5 [Air = 1]
Relative density	:	0.84
Density Ibs/gal	:	Estimated 7 lbs/gal
Density gm/cm ³	:	0.87 to 0.95 g/cm ³
Gravity, °API	:	Estimated 37 @ 60 F
Solubility	:	Very slightly soluble in the following materials: cold water.
Solubility in water	:	0.005 g/l
Partition coefficient: n- octanol/water	:	>3.3
Auto-ignition temperature	:	254 to 285°C (489.2 to 545°F)
Flow time (ISO 2431)	:	Not available.
Viscosity	:	Kinematic (room temperature): 0.03 cm ² /s (3 cSt)
Conductivity	;	<50 picosiemens/meter (unadditized)

Section 10. Stability and reactivity

Reactivity	: Not expected to be Explosive, Self-Reactive, Self-Heating, or an Organic Peroxide under US GHS Definition(s).
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas. Do not store with strong oxidizing agents.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Benzene, trimethyl-	LD50 Oral	Rat	8970 mg/kg	-
Naphthalene	LD50 Oral	Rat	490 mg/kg	-
biphenyl	LD50 Dermal	Rabbit	>5010 mg/kg	-
	LD50 Oral	Rat	2140 mg/kg	-
Cumene	LC50 Inhalation Vapor	Mouse	10 g/m³	7 hours
	LD50 Dermal	Rabbit	12300 uL/kg	-
	LD50 Oral	Rat	2.9 g/kg	-
	LD50 Oral	Rat	4000 mg/kg	-
Xylene	LC50 Inhalation Vapor	Rat	5000 ppm	4 hours
	LC50 Inhalation Vapor	Rat	6700 ppm	4 hours
	LD50 Oral	Mouse	2119 mg/kg	-
	LD50 Oral	Rat	4300 mg/kg	-
	LD50 Oral	Rat	4300 mg/kg	-
Ethylbenzene	LD50 Dermal	Rabbit	>5000 mg/kg	-
-	LD50 Oral	Rat	3500 mg/kg	-

Conclusion/Summary : No additional information.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Benzene, trimethyl-	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
Naphthalene	Skin - Mild irritant	Rabbit	-	495 milligrams	-
biphenyl	Eyes - Mild irritant	Rabbit	-	100 milligrams	-
	Skin - Severe irritant	Rabbit	-	24 hours 500 microliters	-
Cumene	Eyes - Mild irritant	Rabbit	-	86 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 10 milligrams	-
Xylene	Skin - Mild irritant	Rat	-	8 hours 60 microliters	-
Date of issue/Date of revision	: 7/31/2018 Date of prev	vious issue	: 4/16/2018	Version	:4 9/1

Section 11. Toxicological information

	J - J	-			
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Moderate irritant	Rabbit	-	100 Percent	-
Ethylbenzene	Skin - Mild irritant	Rabbit	-	24 hours 15	-
				milligrams	
Skin	: No additional information).			
Eyes	: No additional information	1.			
Respiratory	: No additional information	1.			
Sensitization					
Not available.					
Skin	: No additional information	1.			
Respiratory	: No additional information	1.			
<u>Mutagenicity</u>					
Not available.					
Conclusion/Summary	: No additional information	1.			
Carcinogenicity					
Not available.					
Conclusion/Summary	: Diesel exhaust particul mice exposed to unflitere epidemiological studies h workers and bladder can to diesel engine exhaust	ate: Lung tum ed diesel fuel e nave identified cer in bus and NTP has de	or and lymph exhaust in ch increase inc truck driver termined that	nomas were identifie ronic inhalation stud idences of lung can s possibly associate t exposure to diesel	d in rats and lies. Further, cer in US railroad d with exposure exhaust

Classification

Product/ingredient name	OSHA	IARC	NTP
Fuels, diesel, No 2	-	3	-
Diesel exhaust particulate	-	1	Reasonably anticipated to be a human carcinogen.
Naphthalene	-	2B	Reasonably anticipated to be a human carcinogen.
Cumene	-	2B	Reasonably anticipated to be a human carcinogen.
Xylene	-	3	-
Ethylbenzene	-	2B	-

diesel exhaust as a potential carcinogen.

particulates, a complex mixture of combustion products of diesel fuel, is reasonably anticipated to be a human carcinogen. In addition, NIOSH has identified complete

Reproductive toxicity

Not available.

Conclusion/Summary : No additional information.

Teratogenicity

Not available.

Conclusion/Summary : No additional information.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Benzene, trimethyl-	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
biphenyl	Category 3	Not applicable.	Respiratory tract irritation
Cumene	Category 3	Not applicable.	Respiratory tract irritation
Ethylbenzene	Category 3	Not applicable.	Respiratory tract irritation
Date of issue/Date of revision : 7/31/2018	Date of previous issue : 4/1	16/2018	Version : 4 10

Section 11. Toxicological information

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Benzene, trimethyl-	Category 2	Not determined	central nervous system (CNS)
Xylene	Category 2	Not determined	hearing organs

Aspiration hazard

Name	Result
Benzene, trimethyl-	ASPIRATION HAZARD - Category 1
Cumene	ASPIRATION HAZARD - Category 1
Ethylbenzene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure	1	Routes of entry	anticipated: Dermal,	Inhalation.				
Potential acute health effects	<u>s</u>							
Eye contact	:	Causes eye irrit	ation.					
Inhalation	:	Harmful if inhal	ed.					
Skin contact	:	Causes skin irri	tation. Defatting to t	he skin.				
Ingestion	:	Corrosive to the airways.	corrosive to the digestive tract. Causes burns. May be fatal if swallowed and enters irways.					
Symptoms related to the phy	ysic	al, chemical an	d toxicological cha	racteristics	<u>.</u>			
Eye contact	:	Adverse sympto pain or irritation watering redness	oms may include the	following:				
Inhalation	:	Repeated or pro system damage capacity and the	blonged overexposure. The symptoms ca loss of coordination	re to solvent n include th n.	s can cause bra e loss of memo	ain or othe ry, the los	er nervous ss of intelled	ctual
Skin contact	:	Adverse sympto irritation redness dryness cracking	oms may include the	following:				
Ingestion	:	Adverse sympto stomach pains nausea or vomi	oms may include the ting	following:				
Delayed and immediate effe	<u>cts</u>	and also chroni	c effects from shor	t and long	<u>term exposure</u>	1		
Short term exposure								
Potential immediate effects	-	Not available.						
Potential delayed effects	1	Not available.						
Long term exposure								
Potential immediate effects	-	Not available.						
Potential delayed effects	:	Not available.						
Potential chronic health eff	ect	5						
Not available.								
General	:	May cause dam	age to organs throug	gh prolonge	d or repeated e	xposure.		
Carcinogenicity	:	Suspected of ca exposure.	ausing cancer. Risk	of cancer d	epends on dura	tion and I	evel of	
Mutagenicity	:	No known signi	ficant effects or critic	al hazards.				
Date of issue/Date of revision	: 7	/31/2018 🛛	ate of previous issue	: 4/16/20)18	Version	: 4	11/17

Section 11. Toxicological information

Teratogenicity Developmental effects Fertility effects

- : No known significant effects or critical hazards.
- : No known significant effects or critical hazards.
 - : No known significant effects or critical hazards.

Section 12. Ecological information

<u>Toxicity</u>			
Product/ingredient name	Result	Species	Exposure
Benzene, trimethyl-	Acute LC50 5600 µg/l Marine water	Crustaceans - Palaemonetes	48 hours
Naphthalene	Acute EC50 1.6 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 2350 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
	Acute LC50 213 µg/l Fresh water	Fish - Melanotaenia fluviatilis - Larvae	96 hours
	Chronic NOEC 0.5 mg/l Marine water	Crustaceans - Uca pugnax - Adult	3 weeks
	Chronic NOEC 1.5 mg/l Fresh water	Fish - Oreochromis mossambicus	60 days
biphenyl	Acute LC50 360 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 1450 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NOEC 0.17 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	21 days
	Chronic NOEC 0.229 mg/l Fresh water	Fish - Oncorhynchus mykiss	87 days
Cumene	Acute EC50 2600 μg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 7400 μg/l Fresh water	Crustaceans - Artemia sp Nauplii	48 hours
	Acute EC50 10600 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 2700 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
Xylene	Acute EC50 90 mg/l Fresh water	Crustaceans - Cypris subglobosa	48 hours
	Acute LC50 8.5 ppm Marine water	Crustaceans - Palaemonetes pugio - Adult	48 hours
	Acute LC50 8500 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
	Acute LC50 15700 μg/l Fresh water	Fish - Lepomis macrochirus - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute LC50 19000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 13400 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 16940 µg/l Fresh water	Fish - Carassius auratus	96 hours
Ethylbenzene	Acute EC50 4600 μg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 3600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 6530 µg/l Fresh water	Crustaceans - Artemia sp Nauplii	48 hours
	Acute EC50 2930 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 4200 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours

Conclusion/Summary : Not available.

Persistence and degradability

Not available.

Conclusion/Summary : Not available.

Section 12. Ecological information

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Fuels, diesel, No 2	>3.3	-	low
Benzene, trimethyl-	3.4 to 3.8	-	low
Naphthalene	3.4	36.5 to 168	low
biphenyl	4.008	1900	high
Cumene	3.55	35.48	low
Xylene	3.12	8.1 to 25.9	low
Ethylbenzene	3.6	-	low

Mobility in soil

Soil/water partition	1	Not available.
coefficient (Koc)		

Other adverse effects	: No known significant effects or critical hazards.
-----------------------	---

Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
RCRA classification	· D001 D018

Section 14. Transport information

	DOT Classification	IMDG	ΙΑΤΑ
UN number	NA1993	UN1202	UN1202
UN proper shipping name	Diesel Fuel	DIESEL FUEL	Diesel Fuel
Transport hazard class(es)	3	3	3
Packing group	III	III	Ш
Environmental hazards	No.	No.	No.

Additional information

Section 14. Transport information

DOT Classification	his product may be re-classified as "Combustible Liquid," unless transported by vessel r aircraft. Non-bulk packages (less than or equal to 119 gal) of combustible liquids are ot regulated as hazardous materials in package sizes less than the product reportable uantity. Reportable quantity 11223.3 lbs / 5095.4 kg [1479.2 gal / 5599.3 L]. Package sizes hipped in quantities less than the product reportable quantity are not subject to the RQ reportable quantity) transportation requirements. Imited quantity Yes. Packaging instruction Exceptions: 150. Non-bulk: 203. Bulk: 242. Quantity limitation Passenger aircraft/rail: 60 L. Cargo aircraft: 220 L. Special provisions 144, B1, IB3, T4, TP1, TP29 Remarks 49 CFR 173.150 (f)(1) states that a flammable liquid with a flash point at or	
	bove 38°C (100°F) that does not meet the definition of any other hazard class may be eclassed as a combustible liquid. This provision does not apply to transportation by essel or aircraft except where other means of transportation is impracticable.	
TDG Classification	roduct classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3).	
IMDG	imergency schedules F-E, S-E Special provisions 363	
ΙΑΤΑ	<u>Juantity limitation</u> Passenger and Cargo Aircraft: 60 L. Packaging instructions: 355. Cargo Aircraft Only: 220 L. Packaging instructions: 366. Limited Quantities - Passenger Aircraft: 10 L. Packaging instructions: Y344. Special provisions	٢
Special precautions for user	ransport within user's premises: always transport in closed containers that are pright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	;
Transport in bulk according to Annex II of MARPOL and the IBC Code	lot available.	

Section 15. Regulatory information

U.S. Federal regulations	 United States inventory (TSCA 8b): All components are listed or exempted. Clean Water Act (CWA) 307: naphthalene; ethylbenzene; toluene; benzene Clean Water Act (CWA) 311: naphthalene; xylene; ethylbenzene; toluene; benzene This material is classified as an oil under Section 311 of the Clean Water Act (CWA) and the Oil Pollution Act of 1990 (OPA). Discharges or spills which produce a visible sheen on waters of the United States, their adjoining shorelines, or into conduits leading to surface waters must be reported to the EPA's National Response Center at (800) 424-8802.
<u>SARA 302/304</u>	
Composition/information	<u>n on ingredients</u>
SARA 304 RQ	: Not applicable.
<u>SARA 311/312</u>	
Classification	 FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2B CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS)) - Category 2 ASPIRATION HAZARD - Category 1 HNOC - Corrosive to digestive tract HNOC - Static-accumulating flammable liquid

Composition	/information	on ingredien	ts

Date of issue/Date of revision	: 7/31/2018	Date of previous issue	: 4/16/2018	Version : 4	14/17

Section 15. Regulatory information

Name	%	Classification
Fuels, diesel, No 2 Diesel exhaust particulate Benzene, trimethyl-	>99 1 - 5 1 - 5	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2B CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS)) - Category 2 ASPIRATION HAZARD - Category 1 HNOC - Corrosive to digestive tract HNOC - Static-accumulating flammable liquid CARCINOGENICITY (inhalation) - Category 2 FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS)) - Category 2 ASPIRATION HAZARD - Category 1
Naphthalene	0.5 - 1.5	FLAMMABLE SOLIDS - Category 2 ACUTE TOXICITY (oral) - Category 4 CARCINOGENICITY - Category 2
biphenyl	0.5 - 1.5	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
Cumene	0.5 - 1.5	FLAMMABLE LIQUIDS - Category 3 EYE IRRITATION - Category 2A CARCINOGENICITY (inhalation) - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 ASPIRATION HAZARD - Category 1
Xylene	0.5 - 1.5	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (hearing organs) - Category 2
Ethylbenzene	0.5 - 1.5	FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A CARCINOGENICITY (inhalation) - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 ASPIRATION HAZARD - Category 1

<u>SARA 313</u>

	Product name	CAS number	%
Form R - Reporting	naphthalene	91-20-3	<1
requirements	ethylbenzene	100-41-4	<1
Supplier notification	naphthalene	91-20-3	<1
	ethylbenzene	100-41-4	<1

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts

: The following components are listed: ethyltoluene; trimethylbenzene

Date of issue/Date of revision	: 7/31/2018	Date of previous issue	: 4/16/2018	Version : 4	15/17

Section 15. Regulatory information

New York	1	The following components are listed: Naphthalene; Cumene; Benzene, 1-methylethyl-; Ethylbenzene
New Jersey	:	The following components are listed: ETHYLTOLUENES; BENZENE, ETHYLMETHYL-; TRIMETHYL BENZENE (mixed isomers); BENZENE, TRIMETHYL-; NAPHTHALENE; MOTH FLAKES; cumene; ethylbenzene
Pennsylvania	:	The following components are listed: ethyltoluene; trimethylbenzene; NAPHTHALENE; cumene; ethylbenzene

California Prop. 65 Clear and Reasonable Warnings (2018)

▲ WARNING: This product can expose you to Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Diesel exhaust particulate, Naphthalene, Cumene, Ethylbenzene, which are known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause cancer, and roluene, which is known to the State of California to cause cancer.

Ingredient name	%	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Diesel exhaust particulate	<3	Yes.	No.	-	-
naphthalene	<1	Yes.	No.	Yes.	-
cumene	<1	Yes.	No.	-	-
ethylbenzene	<1	Yes.	No.	Yes.	-
toluene	<0.1	No.	Yes.	-	Yes.
benzene	<0.1	Yes.	Yes.	Yes.	Yes.

International regulations

Inventory list

United States	:	All components are listed or exempted.
Australia	÷	All components are listed or exempted.
Canada	1	All components are listed or exempted.
China	:	All components are listed or exempted.
Europe	:	All components are listed or exempted.
Japan	:	Japan inventory (ENCS): All components are listed or exempted. Japan inventory (ISHL): Not determined.
Malaysia	:	Not determined.
New Zealand	1	All components are listed or exempted.
Philippines	:	All components are listed or exempted.
Republic of Korea	1	All components are listed or exempted.
Taiwan	:	Not determined.
Thailand	:	Not determined.
Turkey	:	Not determined.
Viet Nam	:	Not determined.

Section 16. Other information

National Fire Protection Association (U.S.A.)

2	Flammability
Health 10	Instability/Reactivity
	Special

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Section 16. Other information

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Procedure used to derive the classification

Justification
Expert judgment
Calculation method
Expert judgment
Expert judgment

HISTORY	
Date of printing	: 7/31/2018
Date of issue/Date of revision	: 7/31/2018
Date of previous issue	: 4/16/2018
Version	: 4
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations
References	· Not available

References

Indicates information that has changed from previously issued version.

Notice to reader

THE INFORMATION IN THIS SAFETY DATA SHEET (SDS) WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED REGARDING ITS CORRECTNESS OR ACCURACY. SOME INFORMATION PRESENTED AND CONCLUSIONS DRAWN HEREIN ARE FROM SOURCES OTHER THAN DIRECT TEST DATA ON THE SUBSTANCE ITSELF. THIS SDS WAS PREPARED AND IS TO BE USED ONLY FOR THIS PRODUCT. IF THE PRODUCT IS USED AS A COMPONENT IN ANOTHER PRODUCT, THIS SDS INFORMATION MAY NOT BE APPLICABLE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE OR APPLICATION.

THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE, AND/OR DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR ANY LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.

CITGO is a registered trademark of CITGO Petroleum Corporation



SAFETY DATA SHEET

1. Identification

Product identifier	Solder-Safe 97/3 Lead-Free Solder
Other means of identification	
SDS number	WC007
Recommended use	Solder.
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/I	Distributor information
Manufacturer/Supplier	Worthington Cylinder Corporation
Address	200 Old Wilson Bridge Road
	Columbus, OH 43085
	United States
Email:	cylinders@worthingtonindustries.com
Telephone Number:	866-928-2657
CHEMTREC - 24 HOURS:	
Within US and Canada	800-424-9300
Outside US and Canada	+1 703-741-5970 (collect calls accepted)
2. Hazard(s) identification	
	N1-A standard

Physical hazards	Not classified.
Health hazards	Not classified.
OSHA defined hazards	Not classified.
Label elements	
Hazard symbol	None.
Signal word	None.
Hazard statement	None.
Precautionary statement	
Prevention	Observe good industrial hygiene practices.
Response	Wash thoroughly after handling.
Storage	Store away from incompatible materials.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
Hazard(s) not otherwise classified (HNOC)	Molten material will produce thermal burns.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Tin	7440-31-5	90 - 100
Copper	7440-50-8	1 - 10

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Immediately remove from further exposure. Get immediate medical assistance. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. Give supplemental oxygen, if available. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

Skin contact	Remove contaminated clothes and rinse skin thoroughly with water for at least 15 minutes. If skin rash or an allergic skin reaction develops, get medical attention.
Eye contact	Rinse immediately with plenty of water for at least 15 minutes. Remove any contact lenses. Get medical attention if irritation develops or persists.
Ingestion	Immediately rinse mouth and drink a cupful of water. Never give anything by mouth to a victim who is unconscious or is having convulsions. Only induce vomiting at the instruction of medical personnel. Get medical attention immediately.
Most important symptoms/effects, acute and delayed	Dust and fumes may irritate eyes, skin and upper respiratory tract. Contact with molten material may cause thermal burns.
Indication of immediate medical attention and special treatment needed	Treat symptomatically. Exposure may aggravate pre-existing respiratory disorders. Symptoms may be delayed.
General information	Show this safety data sheet to the doctor in attendance.
5. Fire-fighting measures	
Suitable extinguishing media	Extinguish with foam, carbon dioxide or dry powder.
Unsuitable extinguishing media	Do not use water or halogenated extinguishing media.
Specific hazards arising from the chemical	Fire or high temperatures create: Metal oxides.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do it without risk.
General fire hazards	Solid metal is not flammable; however, finely divided metallic dust or powder may form an explosive mixture with air.
6. Accidental release meas	ures
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Avoid inhalation of dust from the spilled material. Wear protective clothing as described in Section 8 of this SDS. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
Methods and materials for containment and cleaning up	Stop leak if you can do so without risk. Local authorities should be advised if significant spillages cannot be contained.
	For a dry material spill, use a HEPA (high efficiency particle air) vacuum to collect material and place in a sealable container for disposal. Avoid dust formation. Recover and recycle, if practical. Keep out of water supplies and sewers.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not contaminate water. If release occurs in the U.S. and is reportable under CERCLA Section 103, notify the National Response Center at (800)424-8802 (USA) or (202)426-2675 (USA).
7. Handling and storage	
Precautions for safe handling	Wear appropriate personal protective equipment (See Section 8). Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Avoid inhalation of dust and fumes. Avoid contact with skin and eyes. Do not get this material on clothing. Do not eat, drink or smoke when using the product. Wash thoroughly after handling. Avoid release to the environment.
	Any surface that comes in contact with molten metal must be preheated or specially coated and rust free. Inadvertent contaminants to product such as moisture, ice, snow, grease, or oil can cause an explosion when charged to a molten metal bath or metal furnace (preheating metal will remove moisture from product).
Conditions for safe storage, including any incompatibilities	Store in tightly closed original container in a dry, cool and well-ventilated place. Store in a closed container away from incompatible materials. Keep out of reach of children. Keep away from food, drink and animal feedingstuffs.

10

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Copper (CAS 7440-50-8)	PEL	1 mg/m3	Dust and mist.
		0.1 mg/m3	Fume.
Tin (CAS 7440-31-5)	PEL	2 mg/m3	
ACGIH			
Components	Туре	Value	Form
Copper (CAS 7440-50-8)	TWA	1 mg/m3	Dust and mist.
US ACCIH Threshold Limit V	عميراه	0.2 mg/m3	Fume.
Componente	Type	Value	
		2 mg/m3	
Tin (CAS 7440-31-5)		2 mg/m3	
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
Copper (CAS 7440-50-8)	TWA	1 mg/m3	Dust and mist.
Tin (CAS 7440-31-5)	TWA	2 mg/m3	
Biological limit values	No biological exposure limits noted for	or the ingredient(s).	
Exposure guide <mark>line</mark> s	No exposure standards allocated.		
Appropriate engineering controls	Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of dust. Keep melting/soldering temperatures as low as possible to minimize the generation of fume. Shower, hand and eye washing facilities near the workplace are recommended.		s and minimize the risk of ossible to minimize the e workplace are
Individual protection measures, s	uch as personal protective equipm	ient	
Eye/face protection	Wear safety glasses with side shields material.	s (or goggles). Wear a face shie	ld when working with molten
Skin protection			
Hand protection	Wear protective gloves (i.e. latex, niti	rile, neoprene).	
Other	Chemical resistant clothing is recomm	mended.	
Respiratory protection	Use a respirator when local exhaust of OEL. In a confined space a supplied protective equipment should be in ac 1910.134; or in Canada with CSA Stathere is a risk of exposure to dust/function	or ventilation is not adequate to I respirator may be required. Se cordance with OSHA General I andard Z94.4. Use a NIOSH/MS ne at levels exceeding the expo	ection and use of respiratory ndustry Standard 29 CFR SHA approved respirator if isure limits.
Thermal hazards	Heat resistant/insulated gloves and clothing are recommended when working with molten mater		n working with molten material.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.		
9. Physical and chemical p	roperties		-
Appearance	Silver to silver-gray metallic metal.		
Physical state	Solid.		
Form	Wire.		
Color	Silver to gray.		
Odor	Odorless.		
Odor threshold	Not available.		
рН	Not available.		
Melting point/freezing point	441 - 482 °F (227.22 - 250 °C)		
Initial boiling point and boiling range	Not available.		
Flash point	Not available.		
Evaporation rate	Not available.		

Solder-Safe 97/3 Lead-Free Solder 908003 Version #: 01 Revision date: - Issue date: 28-May-2015

Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	7.38
Solubility(ies)	
Solubility (water)	Not soluble
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.

10. Stability and reactivity

Reactivity	The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Contact with incompatible materials. Avoid molten metal contact with water.
Incompatible materials	Chlorine. Turpentine. Magnesium. Acetylene Gas.
Hazardous decomposition products	Toxic metal oxides are emitted when heated above the melting point.

11. Toxicological information

Information on likely routes of exposure

이야 한 것 같아? 승규가 가지 않는 것 같아? 그 같은 것은 것 같아 것 같아요. 그는 것 같아요 ㅠㅠ 것 ㅠㅠ ㅋ ㅋ ㅋ ㅋ ㅋ ㅋ ㅋ ㅋ ㅋ ㅋ ㅋ ㅋ ㅋ ㅋ ㅋ ㅋ	
Inhalation	Elevated temperatures or mechanical action may form dust and fumes which may be irritating to the mucous membranes and respiratory tract.
Skin contact	Dust may irritate skin.
Eye contact	Elevated temperatures or mechanical action may form dust and fumes which may be irritating to the eyes.
Ingestion	May cause discomfort if swallowed.
Symptoms related to the physical, chemical and toxicological characteristics	Elevated temperatures or mechanical action may form dust and fumes which may be irritating to the eye, mucous membranes and respiratory tract. Contact with molten material may cause thermal burns.
Information on toxicological effe	cts
Acute toxicity	High concentrations of freshly formed fumes/dusts of metal oxides can produce symptoms of metal fume fever. When heated, the vapors/fumes given off may cause respiratory tract irritation. Overexposure of Tin can cause irritation of the eyes, skin, mucous membranes, and respiratory system. Acute overexposure to Copper dust/fume can cause irritation of the eyes, nose, throat, and skin and under severe fume overexposure can cause metal fume fever with flu-like symptoms such as sweet metal taste, dry throat, coughing, fever and chills, tight chest, dyspnea, headache, blurred vision, back pain, nausea, vomiting, fatigue. Symptoms usually disappear within 24 hours. Copper may cause skin and hair discoloration. Inhalation of copper dusts may change the gums and mucous lining of the mouth which is generally attributable to localized tissue effect rather than general toxicity.
Skin corrosion/irritation	Dust may irritate skin.
Serious eye damage/eye irritation	Elevated temperatures or mechanical action may form dust and fumes which may be irritating to the eye.
Respiratory or skin sensitization	
Respiratory sensitization	No sensitizing effects known.

Skin sensitization	No sensitizing effects known.	
Germ cell mutagenicity	No data available.	
Carcinogenicity	Not classifiable as to carcinogenicity to humans.	
OSHA Specifically Regulated Not listed.	Substances (29 CFR 1910.1001-1050)	
Reproductive toxicity	No data available.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not relevant, due to the form of the product.	
Chronic effects	Prolonged and repeated overexposure to dust and fumes can lead to benign pneumoconiosis (stannosis). Overexposure to Tin can result in benign pneumoconiosis (stannous). This form of pneumoconiosis produces progressive x-ray changes of the lungs as long as exposure exists, but there is no distinctive fibrosis, no evidence of disability and no special complicating factors.	
Further information	No other specific acute or chronic health impact noted.	
12. Ecological information		

Ecotoxicity	Alloys in massive forms present a limited hazard for the environment.
Persistence and degradability	The product is not biodegradable.
Bioaccumulative potential	No data available.
Mobility in soil	Alloys in massive forms are not mobile in the environment.
Other adverse effects	None expected.

13. Disposal considerations

Disposal instructions	Dispose in accordance with all applicable regulations.	
Hazardous waste code	Not regulated.	
Waste from residues / unused products	Dispose of in accordance with local regulations. Scrapped material should be sent for refining to recover precious metal content. Solid metal and alloys in the form of particles may be reactive. Its hazardous characteristics, including fire and explosion, should be determined prior to disposal.	
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied.	

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

US federal regulations Under some use conditions, this material may be considered to be hazardous in accordance with OSHA 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, 3	Subpt. D)
Not regulated.	
OSHA Specifically Regulated Substances (29 CFR 19	10.1001-1050)
Not listed.	
CERCLA Hazardous Substance List (40 CFR 302.4)	
Copper (CAS 7440-50-8)	LISTED

Superfund Amendments and F	Reauthorization Act of 1986	(SARA)		
Hazard categories	Immediate Hazard - No Delaved Hazard - No			
70°	Fire Hazard - No			
	Pressure Hazard - No			
	Reactivity Hazard - No			
SARA 302 Extremely haza	rdous substance	82.		
Not listed.	17 .			
SARA 311/312 Hazardous chemical	No			
SARA 313 (TRI reporting)				
Chemical name		CAS number	% by wt.	
Copper		7440-50-8	1 - 10	
Other federal regulations				
Clean Air Act (CAA) Section	on 112 Hazardous Air Pollut	a <mark>nts (HAPs) List</mark>		
Not regulated. Clean Air Act (CAA) Section	on 112(r) Accidental Release	e Prevention (40 CFR	68.130)	
Not regulated.				
Safe Drinking Water Act (SDWA)	Not regulated.			
US state regulations	This product does not cor defects or other reproduct	itain a chemical known tive harm.	to the State of Californ	nia to cause cancer, birth
US. Massachusetts R	FK - Substance List			
Copper (CAS 7440	-50-8)			
Tin (CAS 7440-31-	5)			
US. New Jersey Work	er and Community Right-to-	-Know Act		
Copper (CAS 7440	-50-8)			
US. Pennsylvania Wo	rker and Community Right-t	o-Know Law		
Copper (CAS 7440	-50-8)			
Tin (CAS 7440-31-	5)			
US. Rhode Island RTK	C			
Copper (CAS 7440	-50-8)			
US. California Proposition Not Listed.	65			
International Inventories				
Country(s) or region	Inventory name			On inventory (yes/no)*
Australia	Australian Inventory of Ch	nemical Substances (A	ICS)	Yes
Canada	Domestic Substances Lis	t (DSL)		Yes
Canada	Non-Domestic Substance	s List (NDSL)		No
China	Inventory of Existing Cher	mical Substances in Ch	nina (IECSC)	Yes
Europe	European Inventory of Ex Substances (EINECS)	isting Commercial Che	emical	Yes
Europe	European List of Notified	Chemical Substances	(ELINCS)	No
Japan	Inventory of Existing and	New Chemical Substar	nces (ENCS)	No
Korea	Existing Chemicals List (E	ECL)		Yes
New Zealand	New Zealand Inventory			Yes
Philippines	Philippine Inventory of Ch (PICCS)	emicals and Chemical	Substances	Yes
United States & Puerto Ricc	Toxic Substances Contro	I Act (TSCA) Inventory		Yes
*A "Yes" indicates this product A "No" indicates that one or mo country(s).	complies with the inventory requi are components of the product are	rements administered by e not listed or exempt fror	the governing country(s). n listing on the inventory a	administered by the governing
16. Other information, in	cluding date of prepar	ation or last revis	ion	

Issue date 28-May-2015 Revision date Solder-Safe 97/3 Lead-Free Solder 908003 Version #: 01 Revision date: Issue date: 28-May-2015

01 HMIS® is a registered trade and service mark of the NPCA. Health: 1 Flammability: 0 Physical hazard: 0 ACGIH EPA: AQUIRE database NLM: Hazardous Substances Data Base US. IARC Monographs on Occupational Exposures to Chemical Agents HSDB® - Hazardous Substances Data Bank IARC Monographs. Overall Evaluation of Carcinogenicity

Disclaimer

National Toxicology Program (NTP) Report on Carcinogens ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices All information in this Material Safety Data Sheet is believed to be accurate and reliable. However, no guarantee or warranty of any kind is made with regard to the accuracy of information or the suitability of the recommendations contained herein. It is the user's responsibility to assess the safety and toxicity of this product under their own conditions of use and to comply with all applicable laws and regulations.

Version # Further information HMIS® ratings

NFPA ratings

References

	Safety Data Sheet (SDS)
Section 1.	Identification
Product iden	tifier: White PVC Pipe

Trade names and Synonyms: N/A

Recommended Uses: Pipes and fittings for water supply, irrigation, sewerage, drainage, industrial process piping Telecommunications and electrical conduit.

Restrictions on Use: None

Company Identification: Cresline-West Inc. 600 Cross Pointe Blvd. Evansville, IN 47715 Telephone (General): 812-428-9300 Emergengcy Telephone: 812-428-9300

Section 2. Hazard Indentification

This product is not classified as hazardous under the U.S. Occupational Safety and Health Administration Hazard Communication Standard (HCS), 29 C.F.R. 1910.1200. PVC pipe, a finished product, is not a hazardous chemical under normal conditions of use and is categorized as an article. While an SDS is not required under the HCS, this document is being provided as a courtesy to our customers.

Section 3. Composition/Information on Ingredients

Composition and Form manufactured rigid solid tubes of various dimensions for plumbing and water distribution as described in Section 1.

Titanium Dioxide CAS: 13463-67-7 Weight: 0-5% Polyvinyl Chloride CAS: 9002-86-2 Weight: >80%

Silica, crystalline CAS: 14808-60-7 Weight: < .1%

Section 4. First-Aid Measures

EYE CONTACT: No effects anticipated under normal conditions of use. Particles generated by mechanical cutting, grinding or sanding can cause mechanical irritation. Immediately flush with large amounts of water, occasionally lifting the upper and lower eyelids to remove particles. Consult a physician if pain or irritation persists.

CREJLINE-WEST, INC.

Safety Data Sheet (SDS)

SKIN CONTACT: No effects anticipated under normal conditions of use. Cool skin rapidly if contacted with molten polymer. Obtain medical attention for thermal burns or skin irritation.

INHALATION: The product is not expected to present an inhalation hazard unless mechanically chipped or pulverized or if melted during fire. If dust or fumes are inhaled, remove to fresh air.

SWALLOWING: No adverse health effects expected from ingestion.

Description of the most important symptoms or effects, and any symptoms that are acute or delayed: none known.

Recommendations for immediate medical care and special treatment needed, when necessary: none known

Section 5. Fire-Fighting Measures

PVC PIPE DOES NOT PRESENT A FIRE OR EXPLOSION HAZARD UNDER NORMAL CONDITIONS OF USE. ALTHOUGH PVC PIPE WILL NOT SUPPORT COMBUSTION, IT WILL BURN, RELEASING HYDROGEN CHLORIDE GAS, DETECTABLE BY ITS PUNGENT ODOR.

SPECIAL FIRE FIGHTING PROCEDURES: Evacuate enclosed areas. Confined areas require selfcontained breathing apparatus. Extinguish using dry chemical, carbon dioxide, foam or water fog or spray equipment.

Section 6. Accidental Release Measures

Minor Spills Collect products and bundle or secure safely. If necessary, isolate area to prevent damage to /destruction of products by vehicles etc. Broken parts may be sharp and eye protection and glove are recommended.

Major Spills Isolate area as necessary to prevent further damage. Collect products and bundle or secure safely. Broken product and parts may have sharp edges and eye protection and gloves are recommended.

Section 7. Handling and Storage

PVC pipes presents no inhalation, ingestion or contact hazards. Cutting and grinding PVC pipe may release nuisance dust particles which are non-toxic. Care should be taken to avoid inhaling dust. Use any methods that keep dust to a minimum. General storage procedures are acceptable.

Section 8. Exposure Controls/Personal Protection

Exposure Controls No exposure controls are necessary as products are inert and all ingredients are encapsulated within the polymer matrix and are believed to present no hazard under conditions of normal use and good occupational work practice.

Personal Protection: Eye Glasses are recommended when handling pipe and especially when working pipes mechanically, sawing etc.

Hands/Feet Safety footwear and gloves.

Engineering Controls Appropriate controls for safe working when handling and mechanically working e.g. sawing.

Section 9. Physical and Chemical Properties

- Appearance (physical state, color, etc.); Solid white pipe and fittings. Color of pipes varies upon application (e.g. white, grey, blue, yellow, green).
- Upper/lower flammability or explosive limits; Not applicable
- Odor; Not available
- Vapor pressure; Not applicable
- Odor threshold; Not available
- Vapor density; Not applicable
- pH; Not applicable
- Relative density; Not Applicable
- Melting point/freezing point; Not Applicable
- Solubility(ies); insoluble in water
- Initial boiling point and boiling range; Not applicable
- Flash point; Not applicable
- Evaporation rate; Not applicable
- Flammability (solid, gas); will burn in contact with flame
- Partition coefficient: n-octanol/water; Not applicable
- Auto-ignition temperature; Not available
- Decomposition temperature; Not available
- Viscosity. Not applicable

Section 10. Stability and Reactivity

Reactivity

Stable at normal temperatures and pressures.

Chemical stability

Stable under normal storage conditions.

Other

- HAZARDOUS DECOMPOSITION PRODUCTS: Hydrogen chloride, benzene, carbon monoxide, carbon dioxide, aromatic and aliphatic hydrocarbons, and other gases could be released in fire.
- Incompatible materials: Do not store with oxidising agents.

CREJLINE-WEST, INC. Safety Data Sheet (SDS)

Section 11. Toxicological Information

No toxicological data were found for this product. The effects reported are those anticipated based on the components of this product.

POTENTIAL ROUTES OF EXPOSURE: Exposure under ordianry use conditions to hazardous chemicals is not anticipated. Inhalation of dust from mechanical cutting, sanding or grinding may occur. **SIGNS, SYMPTOMS, AND TOXIC EFFECTS OF OVEREXPOSURE:** Exposure to high concentrations of dust of this product may cause irritation of the respiratory tract with cough, difficulty breathing, dryness of the throat, or eye irritation.

ANIMAL TOXICITY DATA: No data found

REPRODUCTIVE EFFECTS: No data were found regarding reproductive effects in humans or animals of any component of this product.

MUTAGENICITY DATA: No mutagenicity data were found for any component of this product. **DESIGNATION AS POTENTIAL CARCINOGEN:** IARC designates PVC homopolymer as Group 3, "not classifiable as to its carcinogencity in humans," and titanium dioxide as Group 2B, "Possibly carcinogenic to humans"."

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: No data were found regarding this issue. INTERACTIONS WITH CHEMICALS THAT ENHANCE TOXICITY: No data were found regarding this issue.

Section 12. Ecological Information

No Data were found regarding adverse ecological impacts of this product.

Section 13. Disposal Considerations

Recycle where possible. Refer to state/territory environmental protection agency/authority. Normally suitable for disposal as general waste land fill.

Section 14. Transportation Information

Not Regulated.

Section 15. Regulatory Information

This plastic PVC pipe is an article and, therefore, exposure to titanium dioxide or silica is unlikely because the substances are inextricably bound in the plastic matrix. It is unlikely that titanium dioxide or silica will contribute to workplace exposures under normal conditions of use. While there is a possibility that mechanical cutting, sanding or grinding the product copuld produce respirable particles, it is not clear that the titanium dioxide or silica would be found as unbound particles of respirable size. Users must determine if respirable particles are produced in their operations. If so, then the appropriate Prop 65 warning language is as follows:

California's Proposition 65

WARNING: This product can expose you to chemicals including titanium dioxide, which are known to the State of California to cause cancer. For more information go to <u>www.P65Warnings.ca.gov</u>.

Please note that Prop 65 only requires the identification of one chemical per endpoint in the warning.

Section 16. Other Information

8/20/2018



SAFETY DATA SHEET

Section 1 – Product & Company Identification

Product Name: RIDGID Nu-Clear Thread Cutting Oil (Canada)

Product Catalog No.: 11461, 11481, 41575, 41585, 42513, 70835

Recommended Use: Thread Cutting

Restrictions on Use: Industrial use only

Company Information:

North America Ridge Tool Company 400 Clark Street Elyria, Ohio 44035-6001 1-800-519-3456 (8:00 am – 5:00 pm EST, M-F) Emergency Telephone call 9-1-1 or local emergency number www.RIDGID.com

Issue Date: May 2, 2018

I

Revision:



Product Name: RIDGID Nu-Clear Thread Cutting Oil (Canada)

	Section 2 – Hazards Identification
Hazard Classification	This product is classified as not hazardous per Canada Hazardous Product Regulations (WHMIS 2015)
Label Elements	
Hazard Symbol:	No symbol
Signal Word:	No signal word.
Hazard Statement:	Not applicable
Precautionary Statements	Not applicable
Other hazards which do not result in GHS classification:	None.

Section 3 – Composition / Information On Ingredients

Mixtures

Chemical Identity	Common name and synonyms	CAS number	Content in percent (%)*
Mineral oil	Mineral oil,	Trade Secret	30 - 60%
Paraffin oils	Paraffin oils,	Trade Secret	30 - 60%
Vegetable oil	Vegetable oil,	Trade Secret	1 - 5%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition Comments: This product does not contain silicone or chlorinated additives.

Section 4 – First Aid Measures

Ingestion:	Rinse mouth thoroughly. Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting.
Inhalation:	Move to fresh air. Call a POISON CENTER/doctor if you feel unwell.
Skin Contact:	Remove contaminated clothing and shoes. Wash contact areas with soap and water. If skin irritation occurs: Get medical advice/attention.



Product Name: RIDGID Nu-Clear Thread Cutting Oil (Canada)

Eye contact:	Flush thoroughly with water. If irritation occurs, get medical assistance. Continue to rinse for at least 15 minutes.	
Most important symptoms/effec	ts, acute and delayed	
Symptoms:	No data available.	
Hazards:	No data available.	
Indication of immediate medical	attention and special treatment needed	
Treatment:	Get medical attention if symptoms occur.	
Se	ction 5 – Fire Fighting Measures	
General Fire Hazards:	No unusual fire or explosion hazards noted.	
Suitable (and unsuitable) exting	uishing media	
Suitable extinguishing media:	Water spray, fog, CO2, dry chemical, or regular foam. Use fire- extinguishing media appropriate for surrounding materials.	
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.	
Specific hazards arising from the chemical:	Heat may cause the containers to explode. During fire, gases hazardous to health may be formed.	
Special protective equipment an	d precautions for firefighters	
Special fire fighting procedures:	No data available.	
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.	
Sect	tion 6 – Accidental Release Measures	
Personal precautions, protective equipment and emergency procedures:	See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away. Ensure adequate ventilation.	

3

up:

Methods and material for


Environmental Precautions:	Avoid release to the environment. Do not contaminate water sources o sewer. Prevent further leakage or spillage if safe to do so.	
Se	ection 7 – Handling And Storage	
Precautions for safe handling:	Observe good industrial hygiene practices. Wear appropriate personal protective equipment. Do not expose to intense heat as product may expand and pressurize container.	
Conditions for safe storage, including any incompatibilities:	Store in original tightly closed container. Avoid contact with oxidizing agents. Store away from incompatible materials. Shelf Life: 720 Days	

Section 8 – Exposure Controls / Personal Protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure Limit Values	Source
Mineral oil - Mist.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Mineral oil - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Mineral oil - Mist.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011)
	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011)
Paraffin oils - Mist.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Paraffin oils - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011)

	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011)
Paraffin oils - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Paraffin oils - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Vegetable oil - Mist.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Vegetable oil - Respirable mist.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Vegetable oil - Mist.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Vegetable oil - Mist.	8 HR ACL	10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	8 HR ACL	10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	15 MIN ACL	20 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	15 MIN ACL	20 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
Vegetable oil - Mist.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011)

Appropriate Engineering Controls

No data available.

Individual protection measures, such as personal protective equipment

General information:	Use personal protective equipment as required.		
Eye/face protection:	Wear safety glasses with side shields (or goggles).		
Skin Protection Hand Protection:	No data available.		
Other:	Wear protective clothing appropriate for the risk of exposure. Be aware of other hazards such as rotating parts. Contact health and safety professional or manufacturer for specific information.		
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from supervisor on the company's respiratory protection standards.		
Hygiene measures:	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.		



Section 9 – Physical And Chemical Properties

Appearance

Physical state: Form: Color: Odor: Odor threshold: pH: Melting point/freezing point: Initial boiling point and boiling range: Flash Point: Evaporation rate: Flammability (solid, gas): Upper/lower limit on flammability or explosive limits Flammability limit - upper (%): Flammability limit - lower (%): Explosive limit - upper (%): **Explosive limit - lower (%):** Vapor pressure:

Vapor density: Density: Relative density: Solubility(ies) Solubility in water: Solubility (other): Partition coefficient (n-octanol/water):

Auto-ignition temperature: Decomposition temperature:

Viscosity:

Other information VOC:

Liquid No data available. Yellow Mild petroleum/solvent No data available. No data available. No data available. 196.11 °C No data available. No data available.

No data available. No data available. No data available. No data available. No data available.

No data available. No data available. 0.878

Insoluble No data available. No data available.

No data available. No data available.

43 mm2/s (40 °C, Measured)

1.1 % (Method 24) 9.4 g/l (ASTM E 1868-10)



Section 10 – Stability And Reactivity		
Reactivity:	Not reactive during normal use.	
Chemical Stability:	Material is stable under normal conditions.	
Possibility of hazardous reactions:	None under normal conditions.	
Conditions to avoid:	Avoid heat or contamination.	
Incompatible Materials:	No data available.	
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.	

Section 11 – Toxicological Information

Information on likely routes of exposure

Inhalation: Inhalation is the primary route of exposure. In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.

Skin Contact: Prolonged skin contact may cause redness and irritation.

Eye contact: Eye contact is possible and should be avoided.

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
-------------	--------------------

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Not classified for acute toxicity based on available data.



Dermal Product:	
	Not classified for acute toxicity based on available data.
Inhalation Product:	Not classified for acute toxicity based on available data.
Delayed and immediate efference of the second secon	ects, including chronic effects from short- and long-term exposure No data available.
Skin Corrosion/Irritation Product:	No data available.
Serious Eye Damage/Eye Ir Product:	ritation No data available.
Respiratory or Skin Sensitia Product:	zation No data available.
Carcinogenicity Product:	No data available.
US. National Toxicology Pro No carcinogenic ACGIH Carcinogen List:	ogram (NTP) Report on Carcinogens: ; components identified
No carcinogenic	; components identified
Germ Cell Mutagenicity	
In vitro Product:	No data available.
In vivo Product:	No data available.
Reproductive toxicity Product:	No data available.
Other effects: Specific Target Organ To Product:	No data available. 5xicity - Single Exposure No data available.
Specific Target Organ To Product:	oxicity - Repeated Exposure No data available.
Aspiration Hazard Product:	
	No data avallable.



Section 12 – Ecological Information

Ecotoxicity:			
Acute hazards to the aquatic environment:			
Fish Product:	No data available.		
Aquatic Invertebrates Product:	No data available.		
Chronic hazards to the aqua	atic environment:		
Fish Product:	No data available.		
Aquatic Invertebrates Product:	No data available.		
Toxicity to Aquatic Plants Product:	No data available.		
Persistence and Degradability			
Biodegradation Product:	No data available.		
BOD/COD Ratio Product:	No data available.		
Bioaccumulative potential			
Bioconcentration Factor (I Product:	BCF) No data available.		
Partition Coefficient n-octanol Product:	/ water (log Kow) No data available.		
Mobility in soil: Other adverse effects:	No data available. No data available.		



Section 13 – Disposal Consideration			
Disposal instructions:	Discharge, treatment, or disposal may be subject to national, state, or local laws. Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must be applied.		
Contaminated Packaging:	Empty containers should be taken to an approved waste handling site for recycling or disposal.		

Section 14 – Transportation Information

TDG

Not regulated.

IMDG

Not regulated.

ΙΑΤΑ

Not regulated.

Section 15 – Regulatory Information

Canada Federal Regul List of Toxic Substanc Not Regulated	ations es (CEPA, Schedule 1)	
Export Control List (C Not Regulated	EPA 1999, Schedule 3)	
National Pollutant Rela Canada. National I Reporting Require NPRI PT5	ease Inventory (NPRI) Pollutant Release Inventory ments Not Regulated	(NPRI) Substances, Part 5, VOCs with Additional
Canada. National I NPRI	Pollutant Release Inventory Not Regulated	(NPRI) (Schedule 1, Parts 1-4)
Greenhouse Gases		

Not Regulated



Section 16 – Other Information

Prepared by: Ridge Tool Company (Operating Standard 6-102)

RIDGE TOOL BELIEVES THE STATEMENTS, TECHNICAL INFORMATION AND RECOM-MENDATIONS CONTAINED HEREIN ARE RELIABLE BUT THEY ARE GIVEN WITHOUT WARRANTY OR GUARANTEE OF ANY KIND, EXPRESSED OR IMPLIED, AND WE ASSUME NO RESPONSIBILITY FOR ANY LOSS, DAMAGE OR EXPENSE, DIRECT OR CONSEQUENTIAL, ARISING OUT OF THEIR USE.



FICHE SANTÉ/SÉCURITÉ

1 – Identification du produit et du fournisseur

Produit: RIDGID Nu-Clear Thread Cutting Oil (Canada)

Réf. catalogue: 11461, 11481, 41575, 41585, 42513, 70835

Emploi recommandé: Filetage mécanique

Restrictions d'utilisation: Usage industriel seulement

Fournisseur:

North America Ridge Tool Company 400 Clark Street Elyria, Ohio 44035-6001 1-800-519-3456 (Etats-Unis) (du lundi au vendredi de 8h à 17h EST) Téléphone d'urgence: composer le 9-1-1 ou appeler les services d'urgences appropriés www.RIDGID.com

Date de publication: le 2 mai 2018

Révision



	2 – Identification des risques
Classe de Danger	Ce produit est classé non dangereux selon le Règlement sur les produits dangereux du Canada (SIMDUT 2015)
Éléments d'Étiquetage	
Symbole de Danger:	Aucun symbole
Mention d'Avertissement:	Aucun mot indicateur.
Mention de Danger:	Non applicable
Conseils de Prudence	Non applicable
Autres dangers ne donnant pas lieu à classement selon le SGH:	Aucun(e).

3 – Composition du produit et renseignements sur ses ingrédients

Mélanges

Identité Chimique	Nom commun et synonymes	Numéro CAS	Teneur en pourcentage (%)*
Mineral oil	Mineral oil,	Secret industriel	30 - 60%
Paraffin oils	Paraffin oils,	Secret industriel	30 - 60%
Vegetable oil	Vegetable oil,	Secret industriel	1 - 5%

* Toutes les concentrations sont exprimées en pourcentage pondéral sauf si le composant est un gaz. Les concentrations de gaz sont exprimées en pourcentage volumique.

Remarques sur la Composition:

Ce produit ne contient pas de silicone ou d'additifs chlorés.



4 – Premiers soins		
Ingestion:	Rincer soigneusement la bouche. Appeler un CENTRE ANTIPOISON/un médecin en cas de malaise. NE PAS faire vomir.	
Inhalation:	Transporter à l'air frais. Appeler un CENTRE ANTIPOISON/un médecin en cas de malaise.	
Contact avec la Peau:	Enlever les vêtements et les chaussures contaminés. Laver les zones de contact à l'eau et au savon. En cas d'irritation cutanée: consulter un médecin.	
Contact oculaire:	Rincer avec soin à l'eau. En cas d'irritation, consulter un médecin. Continuer à rincer pendant au moins 15 minutes.	
Symptômes/effets les plus impo	rtants, aigus et différés	
Symptômes:	Aucune information disponible.	
Dangers:	Aucune information disponible.	
Indication d'un besoin médical i	mmédiat et traitement spécial requis	
Traitement:	Consulter un médecin en cas de symptômes.	

5 – Lutte contre les incendies

Dangers d'Incendie Généraux: Aucun risque exceptionnel d'incendie et d'explosion.

Moyens d'extinction appropriés (et inappropriés)

Moyens d'extinction appropriés:	Eau pulvérisée, brouillard, CO2, agent chimique sec ou mousse standard. Choisir le moyen d'extinction de l'incendie en tenant compte d'autres produits chimiques éventuels.
Moyens d'extinction inappropriés:	Ne pas lutter contre l'incendie au jet d'eau pour ne pas propager les flammes.
Dangers spécifiques dus au produit chimique:	La chaleur peut provoquer l'explosion des récipients. En cas d'incendie, des gaz dangereux pour la santé peuvent se former.
Équipement de protection enérgiel et précentiene pour les permisere	

Équipement de protection spécial et précautions pour les pompiers

Procédures spéciales de	Aucune information disponible.
lutte contre l'incendie:	



Équipement de protection spécial pour le personnel préposé à la lutte contre le feu: Les pompiers doivent porter un équipement de protection standard, notamment vêtement ignifuge, casque à masque facial, gants, bottes en caoutchouc et, dans les espaces clos, un appareil respiratoire autonome.

6 – Lutte contre les déversements accidentels

Précautions individuelles, équipement de protection et procédures d'urgence:	Voir l'équipement de protection individuelle à la Section 8. Ne pas toucher les récipients endommagés ou le produit déversé à moins de porter les vêtements de protection appropriés. Maintenir à distance le personnel non autorisé. Assurer une ventilation adéquate.
Méthodes et matériel de confinement et de nettoyage:	Absorber le produit avec du sable ou un autre absorbant inerte. Arrêter le débit de matière, si ceci est sans risque.
Précautions pour la Protection de l'Environnement:	Éviter le rejet dans l'environnement. Ne pas contaminer les sources d'eau ou les égouts. Endiguer la fuite ou le déversement si cela peut être fait sans danger.

7 – Manipulation et stockage

Précautions à prendre pour une manipulation sans danger:	Se conformer aux bonnes pratiques d'hygiène industrielle. Porter un équipement de protection personnelle approprié. N'exposez pas à la chaleur intense comme le produit peut développer et pressuriser le récipient.
Conditions d'un stockage sûr, y compris d'éventuelles incompatibilités:	Conserver dans le récipient d'origine hermétiquement fermé. Éviter tout contact avec des agents comburants. Conserver à l'écart des matières incompatibles. Durée de conservation: 720 jours



8 – Risques d'exposition et protection individuelle

Paramètres de Contrôle

Valeurs Limites d'Exposition Professionnelle

Identité Chimique	Туре	Valeurs Limites d'Exposition	Source
Mineral oil - Brouillard	TWA	1 mg/m3	Canada. Colombie-Britannique VLE's. (Valeurs limite d'exposition pour les substances chimiques, Réglementation sur la santé et sécurité au travail 296/97, et ses modifications. (05 2013)
Mineral oil - Fraction inhalable.	TWA	5 mg/m3	Canada. Ontario VLE's. (Contrôle de l'exposition aux agents biologiques ou chimiques) (06 2015)
	TWA	5 mg/m3	Canada. Ontario VLE's. (Contrôle de l'exposition aux agents biologiques ou chimiques) (06 2015)
Mineral oil - Brouillard	STEL		Canada. VLEs du Québec, (Ministère du Travail. Règlement sur la qualité du milieu de travail) (11 2011)
	TWA	5 mg/m3	Canada. VLEs du Québec, (Ministère du Travail. Règlement sur la qualité du milieu de travail) (11 2011)
Paraffin oils - Brouillard	TWA	1 mg/m3	Canada. Colombie-Britannique VLE's. (Valeurs limite d'exposition pour les substances chimiques, Réglementation sur la santé et sécurité au travail 296/97, et ses modifications. (05 2013)
	TWA	0.2 mg/m3	Canada. Colombie-Britannique VLE's. (Valeurs limite d'exposition pour les substances chimiques, Réglementation sur la santé et sécurité au travail 296/97, et ses modifications. (05 2013)
Paraffin oils - Brouillard	TWA	5 mg/m3	Canada. VLEs du Québec, (Ministère du Travail. Règlement sur la qualité du milieu de travail) (11 2011)
	STEL	10 mg/m3	Canada. VLEs du Québec, (Ministère du Travail. Règlement sur la qualité du milieu de travail) (11 2011)
Paraffin oils - Fraction inhalable.	TWA	5 mg/m3	Canada. Ontario VLE's. (Contrôle de l'exposition aux agents biologiques ou chimiques) (06 2015)
	TWA	5 mg/m3	Canada. Ontario VLE's. (Contrôle de l'exposition aux agents biologiques ou chimiques) (06 2015)
Paraffin oils - Fraction inhalable.	TWA	5 mg/m3	Les Etats-Unis. Valeurs de Limite de Seuil d'ACGIH (03 2014)
Vegetable oil - Brouillard	TWA	10 mg/m3	Canada. Colombie-Britannique VLE's. (Valeurs limite d'exposition pour les substances chimiques, Réglementation sur la santé et sécurité au travail 296/97, et ses modifications. (09 2011)
Vegetable oil - Brouillard respirable.	TWA	3 mg/m3	Canada. Colombie-Britannique VLE's. (Valeurs limite d'exposition pour les substances chimiques, Réglementation sur la santé et sécurité au travail 296/97, et ses modifications. (09 2011)
Vegetable oil - Brouillard	TWA	10 mg/m3	Canada. Ontario VLE's. (Contrôle de l'exposition aux agents biologiques ou chimigues) (11 2010)



Vegetable oil - Brouillard	8 HR ACL	10 mg/m3	Canada. OEL de la Saskatchewan (Règlement sur la santé et la sécurité au travail, 1996, tableau 21) (05 2009)
	8 HR ACL	10 mg/m3	Canada. OEL de la Saskatchewan (Règlement sur la santé et la sécurité au travail, 1996, tableau 21) (05 2009)
	15 MIN ACL	20 mg/m3	Canada. OEL de la Saskatchewan (Règlement sur la santé et la sécurité au travail, 1996, tableau 21) (05 2009)
	15 MIN ACL	20 mg/m3	Canada. OEL de la Saskatchewan (Règlement sur la santé et la sécurité au travail, 1996, tableau 21) (05 2009)
Vegetable oil - Brouillard	TWA	10 mg/m3	Canada. VLEs du Québec, (Ministère du Travail. Règlement sur la qualité du milieu de travail) (11 2011)

Contrôles Techniques Appropriés Aucune information disponible.

Mesures de protection individuelle, telles que les équipements de protection individuelle

Informations générales:	Utiliser l'équipement de protection individuel requis.
Protection des yeux/du visage:	Porter des lunettes de sécurité à écrans latéraux ou des lunettes étanches.
Protection de la Peau Protection des Mains:	Aucune information disponible.
Autres:	Porter des vêtements de protection appropriés au risque d'exposition. Soyez conscient des autres dangers tels que les pièces en rotation. Contacter un professionnel de la santé et de la sécurité ou un fabricant pour obtenir des informations spécifiques.
Protection Respiratoire:	En cas de ventilation insuffisante, porter un appareil respiratoire approprié. Demander l'avis du superviseur sur les normes de protection respiratoire de la société.
Mesures d'hygiène:	Toujours adopter de bonnes pratiques d'hygiène personnelle, telles que lavage après manipulation de la substance et avant de manger, de boire ou de fumer. Laver régulièrement la tenue de travail pour éliminer les contaminants. Mettre au rebut les chaussures qui ne peuvent pas être lavées.

9 – Caractéristiques physiques et chimiques

Aspect	
État:	Liquide
Forme:	Aucune information disponible.
Couleur:	Jaune
Odeur:	Légère, Pétrole/solvant
Seuil de perception de l'odeur:	Aucune information disponible.



pH:	Aucune information disponible.
Point de fusion/point de congélation:	Aucune information disponible.
Température d'ébullition initiale et intervalle d'ébullition:	Aucune information disponible.
Point d'éclair:	196.11 °C
Taux d'évaporation:	Aucune information disponible.
Inflammabilité (solide, gaz):	Aucune information disponible.
Limites supérieures/inférieures d'inflammabilité ou d'ex	plosivité
Limites d'inflammabilité - supérieure (%):	Aucune information disponible.
Limites d'inflammabilité - inférieure (%):	Aucune information disponible.
Limites d'explosivité - supérieure (%) :	Aucune information disponible.
Limites d'explosivité - inférieure (%):	Aucune information disponible.
Pression de vapeur:	Aucune information disponible.
Densité de vapeur:	Aucune information disponible.
Densité:	Aucune information disponible.
Densité relative:	0.878
Solubilités	
Solubilité dans l'eau:	Insoluble
Solubilité (autre):	Aucune information disponible.
Coefficient de partition (n-octanol/eau):	Aucune information disponible.
Température d'auto-inflammation:	Aucune information disponible.
Température de décomposition:	Aucune information disponible.
Viscosité:	43 mm2/s (40 °C, Mesurée)
AUTRES INFORMATIONS	
VOC:	1.1 % (Method 24) 9.4 g/l (ASTM E 1868-10)

	10 – Stabilité et réactivité	
Réactivité:	Non réactif pendant l'utilisation normale.	
Stabilité Chimique:	Ce produit est stable dans des conditions normales.	
Possibilité de Réactions Dangereuses:	Aucun(e)(s) dans les conditions normales.	
Conditions à Éviter:	Éviter tout chauffage ou contamination.	



Matières Incompatibles:	Aucune information disponible.
Produits de Décomposition Dangereux:	La décomposition thermique ou la combustion peut libérer des oxydes de carbone et d'autres gaz ou vapeurs toxiques.
	11 – Données toxicologiques
Informations sur les voies d'ex Inhalation:	position probables L'inhalation est la principale voie d'exposition. À concentration élevée, les vapeurs, émanations ou brouillards peuvent être irritants pour le nez, la gorge et les muqueuses.
Contact avec la Peau:	Le contact prolongé avec la peau peut entraîner des rougeurs et de l'irritation.
Contact oculaire:	Le contact oculaire est possible ; il doit être évité.
Ingestion:	Peut être ingéré par accident. L'ingestion peut provoquer irritation et malaises.
Symptômes liés aux caractérist	iques physiques, chimiques et toxicologiques
Inhalation:	Aucune information disponible.
Contact avec la Peau:	Aucune information disponible.
Contact oculaire:	Aucune information disponible.
Ingestion:	Aucune information disponible.
Informations sur les effets toxic	cologiques
Toxicité aiguë (répertorier to	utes les voies d'exposition possibles)
Ingestion Produit:	Non classé comme présentant une toxicité aiguë d'après les données disponibles.
Contact avec la peau Produit:	Non classé comme présentant une toxicité aiguë d'après les données disponibles.
Inhalation Produit:	Non classé comme présentant une toxicité aiguë d'après les données disponibles.
Effets différés et immédiats, et Produit:	effets chroniques d'une exposition de courte et de longue durée Aucune information disponible.



Corrosion ou Irritation de la Pea	J		
Produit:	Aucune information disponible.		
Blessure ou Irritation Grave des	Yeux		
Produit:	Aucune information disponible.		
Sensibilisation Respiratoire ou C	Cutanée		
Produit:	Aucune information disponible.		
Cancérogénicité Produit:	Aucune information disponible.		
Monographies du CIRC sur l'éva	luation des risques de cancérogénicité pour l'homme:		
Aucun composant car	ncérigène identifié		
États-Unis. Rapport du NTP (Nat	ional Toxicilogy Program) sur les cancérogènes :		
Aucun composant car	ncérigène identifié		
Liste des cancérogènes de l'ACC	GIH:		
Aucun composant car	ncérigène identifié		
Mutagénicité des Cellules Germinales			
In vitro Produit:	Aucune information disponible.		
In vivo Produit:	Aucune information disponible.		
Toxicité pour la reproduction Produit:	Aucune information disponible.		
Toxicité Spécifique au Niveau de	l'Organe Cible- Exposition Unique		
Produit:	Aucune information disponible.		
Toxicité Spécifique au Niveau de	l'Organe Cible- Expositions répétées		
Produit:	Aucune information disponible.		
Risque d'Aspiration Produit:	Aucune information disponible.		
Autres effets:	Aucune information disponible.		

RIDGII

	12 – Données écologiques	
,		
Écotoxicité:		
Risques aigus pour l'envire	onnement aquatique:	
Poisson Produit:	Aucune information disponible.	
Invertébrés Aquatiques Produit:	Aucune information disponible.	
Risques chroniques pour l	'environnement aquatique:	
Poisson Produit:	Aucune information disponible.	
Invertébrés Aquatiques Produit:	Aucune information disponible.	
Toxicité pour les plantes aquatiques Produit: Aucune information disponible.		
Persistance et Dégradabilité		
Biodégradation		
Produit:	Aucune information disponible.	
Rapport DBO/DCO Produit:	Aucune information disponible.	
Potentiel de Bioaccumulation		
Facteur de Bioconcentration (BCF)Produit:Aucune information disponible.		
Coefficient de Partage n-octa Produit:	nol/eau (log Kow) Aucune information disponible.	
Mobilité dans le Sol: Autres Effets Néfastes:	Aucune information disponible. Aucune information disponible.	



Instructions pour l'élimination: Le rejet, le traitement et l'élimination peuvent être soumis à des lois nationales, régionales ou locales. Éliminer les déchets dans une installe de traitement et d'élimination des déchets appropriée conformément au lois et aux réglementations en vigueur et en fonction des caractéristique du produit au moment de l'élimination. C'est la responsabilité de l'utilisa de produit ou du propriétaire pour déterminer au moment de la dispositi qui se perdent les règlements doivent être appliqués. Emballages Contaminés: Les conteneurs vides doivent être acheminés vers un site agréé pour le traitement des déchets à des fins de recyclage ou d'élimination. 14 – Transport TDG Non réglementé. IMDG Non réglementé. IATA Non réglementé. IATA Non réglementé. Liste des substances toxiques (LCPE, Annexe 1) Non réglementé Liste des substances d'exportation contrôlée (LCPE 1999, Annexe 3) Non réglementé Inventaire national des rejets de polluants (INRP) Canada Substances de l'Inventaire national des rejets de polluants (INRP), partie 5, COV's faisant r'objet d'une déclaration plus détaillée NPRI PT5 NPRI		13 – Recyclage
Emballages Contaminés: Les conteneurs vides doivent être acheminés vers un site agréé pour le traitement des déchets à des fins de recyclage ou d'élimination. 14 – Transport	Instructions pour l'élimination:	Le rejet, le traitement et l'élimination peuvent être soumis à des lois nationales, régionales ou locales. Éliminer les déchets dans une installation de traitement et d'élimination des déchets appropriée conformément aux lois et aux réglementations en vigueur et en fonction des caractéristiques du produit au moment de l'élimination. C'est la responsabilité de l'utilisateu de produit ou du propriétaire pour déterminer au moment de la disposition qui se perdent les règlements doivent être appliqués.
14 – Transport TDG Non réglementé. IMDG Non réglementé. IATA Non réglementé. IATA Non réglementé. IATA Mon réglementé. IST – Réglementation Mon réglementé. Liste des substances toxiques (LCPE, Annexe 1) Non réglementé Non réglementé Liste des substances d'exportation contrôlée (LCPE 1999, Annexe 3) Non réglementé Inventaire national des rejets de polluants (INRP) Canada Substances de l'Inventaire national des rejets de polluants (INRP), partie 5, COV's faisant l'objet d'une déclaration plus détaillée NPRI PT5 Non réglementé Canada. Loi canadienne sur la protection de l'environnement (CEPA). Inventaire national des rejets de polluants (INRP) (Gaz.Can. Partie I, 135:12, 940) NPRI Non réglementé	Emballages Contaminés:	Les conteneurs vides doivent être acheminés vers un site agréé pour le traitement des déchets à des fins de recyclage ou d'élimination.
TDG Non réglementé. IMDG Non réglementé. IATA Non réglementé.		14 – Transport
IMDG Non réglementé. IATA Non réglementé. ISTA Son réglementé. Sequementations fédérales du Canada Liste des substances toxiques (LCPE, Annexe 1) Non réglementé Liste des substances d'exportation contrôlée (LCPE 1999, Annexe 3) Non réglementé Inventaire national des rejets de polluants (INRP) Canada Substances de l'Inventaire national des rejets de polluants (INRP), partie 5, COV's faisant l'objet d'une déclaration plus détaillée NPRI PT5 Non réglementé Canada. Loi canadienne sur la protection de l'environnement (CEPA). Inventaire national des rejets de polluants (INRP) Non réglementé NPRI Non réglementé	TDG Non réglementé.	
IATA Non réglementé.	IMDG Non réglementé.	
15 – Réglementation Réglementations fédérales du Canada Liste des substances toxiques (LCPE, Annexe 1) Non réglementé Non réglementé Liste des substances d'exportation contrôlée (LCPE 1999, Annexe 3) Non réglementé Non réglementé Inventaire national des rejets de polluants (INRP) Canada Substances de l'Inventaire national des rejets de polluants (INRP), partie 5, COV's faisant l'objet d'une déclaration plus détaillée NPRI PT5 Non réglementé Canada. Loi canadienne sur la protection de l'environnement (CEPA). Inventaire national des rejets de polluants (INRP) (Gaz.Can. Partie I, 135:12, 940) NPRI Non réglementé	IATA Non réglementé.	
Réglementations fédérales du Canada Liste des substances toxiques (LCPE, Annexe 1) Non réglementé Liste des substances d'exportation contrôlée (LCPE 1999, Annexe 3) Non réglementé Inventaire national des rejets de polluants (INRP) Canada Substances de l'Inventaire national des rejets de polluants (INRP), partie 5, COV's faisant l'objet d'une déclaration plus détaillée NPRI PT5 Non réglementé Canada. Loi canadienne sur la protection de l'environnement (CEPA). Inventaire national des rejets de polluants (INRP) (Gaz.Can. Partie I, 135:12, 940) NPRI Non réglementé		15 – Réglementation
Liste des substances d'exportation contrôlée (LCPE 1999, Annexe 3) Non réglementé Inventaire national des rejets de polluants (INRP) Canada Substances de l'Inventaire national des rejets de polluants (INRP), partie 5, COV's faisant l'objet d'une déclaration plus détaillée NPRI PT5 Non réglementé Canada. Loi canadienne sur la protection de l'environnement (CEPA). Inventaire national des rejets de polluants (INRP) (Gaz.Can. Partie I, 135:12, 940) NPRI Non réglementé	Réglementations fédérales du C Liste des substances toxiques (Non réglementé	anada LCPE, Annexe 1)
Inventaire national des rejets de polluants (INRP) Canada Substances de l'Inventaire national des rejets de polluants (INRP), partie 5, COV's faisant l'objet d'une déclaration plus détaillée NPRI PT5 Non réglementé Canada. Loi canadienne sur la protection de l'environnement (CEPA). Inventaire national des rejets de polluants (INRP) (Gaz.Can. Partie I, 135:12, 940) NPRI Non réglementé	Liste des substances d'exportat Non réglementé	ion contrôlée (LCPE 1999, Annexe 3)
Canada. Loi canadienne sur la protection de l'environnement (CEPA). Inventaire national des rejets de polluants (INRP) (Gaz.Can. Partie I, 135:12, 940) NPRI Non réglementé	Inventaire national des rejets de Canada Substances de l'Inve l'objet d'une déclaration plus NPRI PT5	polluants (INRP) entaire national des rejets de polluants (INRP), partie 5, COV's faisant s détaillée Non réglementé
-	Canada. Loi canadienne sur la rejets de polluants (INRP) (Ga NPRI No	a protection de l'environnement (CEPA). Inventaire national des z.Can. Partie I, 135:12, 940) on réglementé

Non réglementé



-

Produit: RIDGID Nu-Clear Thread Cutting Oil (Canada)

	16 – Renseignements divers	
Rédaction :	Ridge Tool Company (OPSTD 6-102)	
Date de publication : Dernière révision :	le 2 mai 2018 le 10 mai 2017	

Quoi que la société Ridge Tool estime que les affirmations, informations techniques et recommandations ci-présentes sont dignes de confiance, celles-ci ne sont données qu'à titre indicatif, sans aucune garantie expresse ou implicite, et ne sauraient engager la responsabilité civile de la société en cas de pertes, dommages et intérêts, voire frais directs ou indirects relevant de leur application.



SAFETY DATA SHEET

1. Identification

Product identifier	Hercules Glug		
Other means of identification			
Product code	7319E		
Synonyms	Part Numbers: 20410, 20412, 20413, 20415		
Recommended use	Drain Opener.		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplie	r/Distributor information		
Company Name	HCC Holdings, Inc. an Oatey Affiliate		
Address 4700 West 160th Street			
	Cleveland, OH 44135		
Telephone	216-267-7100		
E-mail	info@oatey.com		
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)		
Emergency First Aid	1-877-740-5015		
Contact person	MSDS Coordinator		

2. Hazard(s) identification

Physical hazards	Not classified.		
Health hazards	Skin corrosion/irritation	Category 1A	
	Serious eye damage/eye irritation	Category 1	
OSHA defined hazards	Not classified.		

Label elements



Signal word	Danger
Hazard statement	Causes severe skin burns and eye damage.
Precautionary statement	
Prevention	Do not breathe dust or mists. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%	
Sodium hydroxide	1310-73-2	95-100	
Other components below reportable levels		1	
Hercules Glug		:	SDS US
925649 Version #: 01 Revision date: - Issue date: 22-April-2015			1/7

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures	
Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.

6. Accidental release measures

General fire hazards

o. Accidental release meat	
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

No unusual fire or explosion hazards noted.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Sodium hydroxide (CAS 1310-73-2)	PEL	2 mg/m3	
US. ACGIH Threshold Limit \	/alues		
Components	Туре	Value	
Sodium hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3	
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	
Sodium hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3	
Biological limit values	No biological exposure limits noted for the ingredient(s).		
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.		
Individual protection measures, s	such as personal protective equipm	nent	
Eye/face protection	Wear safety glasses with side shields (or goggles) and a face shield.		
Skin protection			
Hand protection	Wear appropriate chemical resistant gloves.		
Other	Wear appropriate chemical resistant clothing.		
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.		
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.		
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.		

9. Physical and chemical properties

Appearance		
Physical state	Solid.	
Form	Flakes.	
Color	Not available.	
Odor	None.	
Odor threshold	Not available.	
рН	13 - 14 (1% Solution)	
Melting point/freezing point	Not available.	
Initial boiling point and boiling range	Not determined	
Flash point	> 212.0 °F (> 100.0 °C)	
Evaporation rate	Not available.	
Flammability (solid, gas)	Not available.	
Upper/lower flammability or explosive limits		
Flammability limit - lower (%)	Not available.	
Flammability limit - upper (%)	Not available.	
Explosive limit - lower (%)	Not available.	
Explosive limit - upper (%)	Not available.	

Vapor pressure	Not available.
Vapor density	Not available.
Relative density	> 2.13
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
VOC (Weight %)	0 g/l

10. Stability and reactivity

Reactivity	Reacts violently with strong acids. This product may react with oxidizing agents.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Do not mix with other chemicals. Contact with incompatible materials.
Incompatible materials	Strong acids. Acids. Oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause irritation to the respiratory system. Prolonged inhalation may be harmful.	
Skin contact	Causes severe skin burns.	
Eye contact	Causes serious eye damage.	
Ingestion	Causes digestive tract burns.	
Symptoms related to the physical, chemical and toxicological characteristics	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.	

Information on toxicological effects

Acute toxicity

Product	Species	Test Results
Hercules Glug (CAS Mixture)		
Acute		
Dermal		
LD50	Rabbit	1350 mg/kg
Oral		
LD50	Rat	140 mg/kg
* Estimates for product may b	e based on additional component data not shown.	
Skin corrosion/irritation	Causes severe skin burns and eye damage.	
Serious eye damage/eye Causes serious eye damage.		
Respiratory or skin sensitization	n	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT	
UN	number
UN	proper ship

	UN number	UN1823
	UN proper shipping name	Sodium hydroxide, solid
	Transport hazard class(es)	
	Class	8
	Subsidiary risk	-
	Label(s)	8
	Packing group	11
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
	Special provisions	IB8, IP2, IP4, T3, TP33
	Packaging exceptions	154
	Packaging non bulk	212
	Packaging bulk	240
ΙΑΤ	A	
	UN number	UN1823
	UN proper shipping name	Sodium hydroxide, solid
	Transport hazard class(es)	
	Class	8
	Subsidiary risk	-
	Packing group	11
	Environmental hazards	No.
	ERG Code	8L
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
IMC	G	
	UN number	UN1823
	UN proper shipping name	SODIUM HYDROXIDE, SOLID

Transport hazard class(es) Class Subsidiary risk Packing group Environmental hazards Marine pollutant EmS Special precautions for user Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code 15. Regulatory information	8 - II No. F-A, S-B Read safety instructions, SDS and emergency p Not applicable. This product is a "Hazardous Chemical" as defi	procedures before handling. ned by the OSHA Hazard Communication	
	Standard, 29 CFR 1910.1200.		
TSCA Section 12(b) Export N	otification (40 CFR 707, Subpt. D)		
OSHA Specifically Regulated	Substances (29 CFR 1910.1001-1050)		
Not listed.			
CERCLA Hazardous Substar	ce List (40 CFR 302.4)		
Sodium hydroxide (CAS 1	USIED		
Hazard categories	Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - Yes		
SARA 302 Extremely hazard	ous substance		
Not listed.			
SARA 311/312 Hazardous chemical	No		
SARA 313 (TRI reporting) Not regulated.			
Other federal regulations			
Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Not regulated. Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)			
Not regulated.			
Safe Drinking Water Act (SDWA)	Not regulated.		
US state regulations			
US. Massachusetts RTK - Su	US. Massachusetts RTK - Substance List		
Sodium hydroxide (CAS 1310-73-2) US. New Jersey Worker and Community Right-to-Know Act			
Sodium hydroxide (CAS 1 US. Pennsylvania Worker an	Sodium hydroxide (CAS 1310-73-2) US. Pennsylvania Worker and Community Right-to-Know Law		
Sodium hydroxide (CAS 1 US. Rhode Island RTK	310-73-2)		
Sodium hydroxide (CAS 1	310-73-2)		
US. California Proposition 66 California Safe Drinking W any chemicals currently lis	US. California Proposition 65 California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.		
International Inventories			
Country(s) or region Australia	Inventory name Australian Inventory of Chemical Substances (A	AICS) On inventory (yes/no)*	

Hercules Glug

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	22-April-2015
Revision date	-
Version #	01
HMIS® ratings	Health: 3 Flammability: 0 Physical hazard: 1

NFPA ratings



Disclaimer

HCC Holdings Inc. an Oatey Affiliate cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.



SAFETY DATA SHEET

1. Identification

Product identifier	Oatey 95/5 Lead Free Solder (Plumbing, Acid or Rosin Core)
Other means of identification	
SDS number	1600E
Synonyms	Part Numbers: 22004, 22018, 22025, 22017, 53026, 53181, 53027, 53189, 53171, 53173, 53175, 53177, 53190, 29031, 53170, 53172, 53174, 53176
Recommended use	Joining Copper Pipes. Joining Copper Tubing.
Recommended restrictions	None known.
Manufacturer/Importer/Supplie	er/Distributor information
Company Name	Oatey Co.
Address	4700 West 160th St.
	Cleveland, OH 44135
Telephone	216-267-7100
E-mail	info@oatey.com
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)
Emergency First Aid	1-877-740-5015
Contact person	MSDS Coordinator

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Not classified.	
Environmental hazards	Hazardous to the aquatic environment, long-term hazard	Category 3
OSHA defined hazards	Not classified.	
Label elements		
Hazard symbol	None.	
Signal word	None.	
Hazard statement	Harmful to aquatic life with long lasting effects.	
Precautionary statement		
Prevention	Avoid release to the environment.	
Response	Wash hands after handling.	
Storage	Store away from incompatible materials.	
Disposal	Dispose of contents/container in accordance w	ith local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.	

3. Composition/information on ingredients

Chemical name	CAS number	%
Tin	7440-31-5	60-100
Antimony	7440-36-0	3-7

4. First-aid measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
Skin contact	Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. If ingestion of a large amount does occur, call a poison control center immediately.

Most important symptoms/effects, acute and delayed Indication of immediate medical attention and special treatment needed General information

Provide general supportive measures and treat symptomatically.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Dry sand. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Use water spray to cool unopened containers.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Stop the flow of material, if this is without risk. Dike far ahead of spill for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.
7. Handling and storage	
Precautions for safe handling	Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. Use care in handling/storage.
	Others is a single of the black of a sector in an Others and the sector is a sector in the sector is the sector is a sector of the sector

Conditions for safe storage, including any incompatibilities Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Antimony (CAS 7440-36-0)	PEL	0.5 mg/m3	
Tin (CAS 7440-31-5)	PEL	2 mg/m3	
US. ACGIH Threshold Limit Values	S		
Components	Туре	Value	
Antimony (CAS 7440-36-0)	TWA	0.5 mg/m3	
Tin (CAS 7440-31-5)	TWA	2 mg/m3	
US. NIOSH: Pocket Guide to Chen	nical Hazards		
Components	Туре	Value	
Antimony (CAS 7440-36-0)	TWA	0.5 mg/m3	
Tin (CAS 7440-31-5)	TWA	2 mg/m3	

Biological limit values	No biological exposure limits noted for the ingredient(s).
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Individual protection measures,	such as personal protective equipment
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves.
Other	Wear suitable protective clothing.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	
Physical state	Solid.
Form	Solid. Wire.
Color	Silver.
Odor	None.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	450 - 464 °F (232.22 - 240 °C)
Initial boiling point and boiling range	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	9 - 11
Solubility(ies)	
Solubility (water)	Not soluble.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
VOC (Weight %)	0
10. Stability and reactivity	

Reactivity

Chemical stability

The product is stable and non-reactive under normal conditions of use, storage and transport. Material is stable under normal conditions.

Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.

Information on toxicological effects

Acute toxicity	Not available.
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not available.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
OSHA Specifically Regulated	l Substances (29 CFR 1910.1001-1050)
Not listed.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not available.
Chronic effects	Prolonged inhalation may be harmful.
12. Ecological information	
Ecotoxicity	Harmful to aquatic life with long lasting effects.
Persistence and degradability	No data is available on the degradability of this product.

Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according toNot applicable.Annex II of MARPOL 73/78 andthe IBC Code

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.			
TSCA Section 12(b) Export I	Notification (40 CFR 707, Sub	pt. D)		
Not regulated. OSHA Specifically Regulate	d Substances (29 CFR 1910.1	001-1050)		
CERCLA Hazardous Substa	nce List (40 CFR 302.4)			
Antimony (CAS 7440-36-	D)	LISTED		
Superfund Amendments and Re	authorization Act of 1986 (SA	RA)		
Hazard categories	Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No	,		
SARA 302 Extremely hazard Not listed.	ous substance			
SARA 311/312 Hazardous chemical	No			
SARA 313 (TRI reporting) Chemical name		CAS number	% by wt.	
Antimony		7440-36-0	3-7	
Other federal regulations				
Clean Air Act (CAA) Section	112 Hazardous Air Pollutant	s (HAPs) List		
Antimony (CAS 7440-36- Clean Air Act (CAA) Section	0) 112(r) Accidental Release Pr	evention (40 CFR 68	.130)	
Not regulated.				
(SDWA)	Not regulated.			
US state regulations				
US. Massachusetts RTK - Si	ubstance List			
Antimony (CAS 7440-36-0 Tin (CAS 7440-31-5)	D)			
US. New Jersey Worker and	Community Right-to-Know A	Act		
US. New Jersey Worker and Antimony (CAS 7440-36-0 Tin (CAS 7440-31-5)	Community Right-to-Know A	Act		
US. New Jersey Worker and Antimony (CAS 7440-36- Tin (CAS 7440-31-5) US. Pennsylvania Worker ar	Community Right-to-Know A	Act 7 Law		
US. New Jersey Worker and Antimony (CAS 7440-36-(Tin (CAS 7440-31-5) US. Pennsylvania Worker ar Antimony (CAS 7440-36-(Tip (CAS 7440-31-5))	Community Right-to-Know A D) Ind Community Right-to-Know D)	Act r Law		
US. New Jersey Worker and Antimony (CAS 7440-36- Tin (CAS 7440-31-5) US. Pennsylvania Worker ar Antimony (CAS 7440-36- Tin (CAS 7440-31-5) US. Rhode Island RTK	Community Right-to-Know A D) ad Community Right-to-Know D)	Act / Law		

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

Toxic Substances Control Act (TSCA) Inventory United States & Puerto Rico

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	17-December-2014
Revision date	-
Version #	01
HMIS® ratings	Health: 0 Flammability: 0 Physical hazard: 0
Disclaimer	Oatey Co. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.



SAFETY DATA SHEET

1. Identification

Oates	Purnle	Primor-	MSE List	d for DVC	and CDVC
Valey	Fuiple	Finner-	NOF LISU	ed for PVC	and CPVC

Product identifier	Oatey Purple Primer- NSF Listed for PVC and CPVC			
Other means of identification				
Product code	1402E			
Synonyms	Part Numbers: 30755(TV), 30756(TV), 30757(TV), 30758, 30759, 30927			
Recommended use	Joining PVC Pipes	(<i>m</i> = = = = = = = = = = = = = = = = = = =		
Recommended restrictions	None known.			
Manufacturer/Importer/Supplier/	Distributor information			
Company Name	Oatev Co			
Address	4700 West 160th St			
	Cleveland, OH 44135			
Telephone	216-267-7100			
E-mail	info@oatey.com			
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the U	S 1-703-527-3887)		
Emergency First Aid	1-877-740-5015			
Contact person	MSDS Coordinator			
2 Hozord(a) identification				
2. Hazard(s) identification	_			
Physical hazards	Flammable liquids	Category 2		
Health hazards	Acute toxicity, oral	Category 4		
	Skin corrosion/irritation	Category 2		
	Serious eye damage/eye irritation	Category 2A		
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation		
	Specific target organ toxicity, single exposure	Category 3 narcotic effects		
	Aspiration hazard	Category 1		
OSHA defined hazards	Not classified.			
Label elements				
Signal word	Danger			
Hazard statement	Highly flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness			
Precautionary statement				
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective disting/outparts and the protective gloves/protective protective protective protective for the protective protective protective for the protective protective protective protective for the protective pro			
Response	If swallowed: Immediately call a poison center/doctor. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. Rinse mouth. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish			

Storage

Disposal

Hazard(s) not otherwise classified (HNOC) Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May form explosive peroxides. Contains a chemical classified by the US EPA as a suspected possible carcinogen.

Supplemental information

Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%	
Acetone	67-64-1	25-40	
Cyclohexanone	108-94-1	25-40	
Furan, Tetrahydro-	109-99-9	15-30	
Methyl ethyl ketone	78-93-3	15-30	

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.
Most important symptoms/effects, acute and delayed	Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor. This product contains tetrahydrofuran that may form explosive organic peroxide when exposed to air or light or with age.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water.
	Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
Cyclohexanone (CAS 108-94-1)	PEL	200 mg/m3	
Constant Contract Contract		50 ppm	
Furan, Tetrahydro- (CAS 109-99-9)	PEL	590 mg/m3	
,		200 ppm	
Methyl ethyl ketone (CAS 78-93-3)	PEL	590 mg/m3	
n an		200 ppm	
US. ACGIH Threshold Limit Valu	es		
Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
Cyclohexanone (CAS 108-94-1)	STEL	50 ppm	
tat usbitus (active inc. so.∎s	TWA	20 ppm	
Furan, Tetrahydro- (CAS 109-99-9)	STEL	100 ppm	

Oatey Purple Primer- NSF Listed for PVC and CPVC

926733 Version #: 01 Revision date: - Issue date: 27-May-2015
US. ACGIH Threshold Limit Values

Components	Туре	Value	
Norden en e	TWA	50 ppm	
Methyl ethyl ketone (CAS 78-93-3)	STEL	300 ppm	
2	TWA	200 ppm	
US. NIOSH: Pocket Guide to Che	mical Hazards	2. T	
Components	Туре	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
		250 ppm	
Cyclohexanone (CAS 108-94-1)	TWA	100 mg/m3	
		25 ppm	
Furan, Tetrahydro- (CAS 109-99-9)	STEL	735 mg/m3	
		250 ppm	
	TWA	590 mg/m3	
		200 ppm	
Methyl ethyl ketone (CAS 78-93-3)	STEL	885 mg/m3	
		300 ppm	
	TWA	590 mg/m3	
		200 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time	
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*	
Cyclohexanone (CAS 108-94-1)	80 mg/l	1,2-Cyclohexan ediol, with hydrolysis	Urine	*	
	8 mg/l	Cyclohexanol, with hydrolysis	Urine	*	
Furan, Tetrahydro- (CAS 109-99-9)	2 mg/l	Tetrahydrofura n	Urine	*	
Methyl ethyl ketone (CAS 78-93-3)	2 mg/l	MEK	Urine	*	

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Sk	n designation		
Cyclohexanone (CAS 108-94-1)		Can be absorbed through the skin.	
US - Minnesota Haz Subs	: Skin designation applies	in 2 de provincien de la contra mandada.	
Cyclohexanone (CAS	108-94-1)	Skin designation applies.	
US - Tennessee OELs: S	kin designation		
Cyclohexanone (CAS	108-94-1)	Can be absorbed through the skin.	
US ACGIH Threshold Lin	it Values: Skin designation		
Cyclohexanone (CAS 108-94-1)		Can be absorbed through the skin.	
Furan, Tetrahydro- (CAS 109-99-9)		Can be absorbed through the skin.	
US. NIOSH: Pocket Guide	e to Chemical Hazards		
Cyclohexanone (CAS 108-94-1)		Can be absorbed through the skin.	
Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency		

shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

Face shield is recommended. Wear safety glasses with side shields (or goggles).

	Skin protection	
	Hand protection	Wear appropriate chemical resistant gloves.
	Other	Wear appropriate chemical resistant clothing.
	Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
	Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Gen con	eral hygiene siderations	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Translucent liquid.
Color	Purple
Odor	Solvent.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	151 °F (66.11 °C)
Flash point	14.0 - 23.0 °F (-10.05.0 °C)
Evaporation rate	5.5 - 8
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	1.8
Flammability limit - upper (%)	11.8
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	145 mm Hg @ 20 C
Vapor density	2.5
Relative density	0.84 +/- 0.02 @20°C
Solubility(ies)	
Solubility (water)	Negligible
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Bulk density	7 lb/gal
VOC (Weight %)	505 g/l SQACMD Method 24
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Ammonia. Amines. Isocyanates. Caustics.

Oatey Purple Primer- NSF Listed for PVC and CPVC 926733 Version #: 01 Revision date: - Issue date: 27-May-2015

11. Toxicological information

Information on likely routes of exposure

Inhalation	May be fatal if swallowed and enters airways. Headache. Nausea, vomiting. May cause irritation to the respiratory system. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	May be fatal if swallowed and enters airways. Harmful if swallowed. Harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Symptoms related to the physical, chemical and toxicological characteristics	Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects

Acute toxicity	May be fatal if swallowed and enters airways. Narcotic effects. May cause respiratory irritation.		
Components	Species	Test Results	
Acetone (CAS 67-64-1)			
Acute			
Dermal			
LD50	Rabbit	20 ml/kg	
Inhalation			
LC50	Rat	50 mg/l, 8 Hours	
Oral			
LD50	Rat	5800 mg/kg	
Cyclohexanone (CAS 108-94-1)			
Acute			
Dermal			
LD50	Rabbit	948 mg/kg	
Inhalation			
LC50	Rat	8000 ppm, 4 hours	
Oral			
LD50	Rat	1540 mg/kg	
* Estimates for product may	be based on additional component data	a not shown.	
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye irritation	Causes serious eye irritation.		
Respiratory or skin sensitizatio	n		
Respiratory sensitization	Not available.		
Skin sensitization	This product is not expected to cause	e skin sensitization.	
Germ cell mutagenicity	No data available to indicate produc mutagenic or genotoxic.	t or any components present at greater than 0.1% are	
Carcinogenicity In 2012 USEPA Integrated Risk Information System (IRIS) reviewed a two species inl lifetime study on THF conducted by NTP (1998). Male rats developed renal tumors ar mice developed liver tumors while neither the female rats nor the male mice showed s results. Because the carcinogenic mechanisms could not be identified clearly in either either tumor, the EPA determined that the male rat and female mouse findings are rel assessment of carcinogenic potential in humans. Therefore, the IRIS review conclude data in aggregate indicate that there is "suggestive evidence of carcinogenic potential		rmation System (IRIS) reviewed a two species inhalation NTP (1998). Male rats developed renal tumors and female either the female rats nor the male mice showed similar techanisms could not be identified clearly in either species for at the male rat and female mouse findings are relevant to the al in humans. Therefore, the IRIS review concludes that these is "suggestive evidence of carcinogenic potential" following	
IARC Monographs, Overall	Evaluation of Carcinogenicity		

Cyclohexanone (CAS 108-94-1)

CSHA Specifically Regulate	d Substances (29 CFR 1910.1001-1050)
Not listed.	() = 1
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Narcotic effects. May cause drowsiness and dizziness. Respiratory tract irritation.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	May be fatal if swallowed and enters airways.
Chronic effects	Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity	The product is possibility tha	s not classified as environmentally hazardo t large or frequent spills can have a harmfu	us. However, this does not exclude the I or damaging effect on the environment.
Components		Species	Test Results
Acetone (CAS 67-64-1)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	> 100 mg/l, 96 hours
Cyclohexanone (CAS 108-9	4-1)		
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	481 - 578 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Estimates for product may be	based on additional component data not snown.		
Persistence and degradability	No data is available on the degradability of this product.		
Bioaccumulative potential	No data available.		
Partition coefficient n-octand	ol / water (log Kow)		
Acetone (CAS 67-64-1)	-0.24		
Cyclohexanone (CAS 108-94-	0.81		
Furan, Tetrahydro- (CAS 109-9			
Methyl ethyl ketone (CAS 78-9	3-3) 0.29		
Mobility in soil	No data available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		
13. Disposal consideration	S		
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.		
Local disposal regulations	Dispose in accordance with all applicable regulations.		
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.		
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).		

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DO	T	
	UN number	UN1993
	UN proper shipping name	Flammable liquids, n.o.s. (Methyl ethyl ketone RQ = 26274 LBS, Acetone RQ = 13130 LBS)
	Transport hazard class(es)	
	Class	3
	Subsidiary risk	a.
	Label(s)	3
	Packing group	П

Oatey Purple Primer- NSF Listed for PVC and CPVC 926733 Version #: 01 Revision date: - Issue date: 27-May-2015

Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	IB2, T7, TP1, TP8, TP28
Packaging exceptions	150
Packaging non bulk	202
Packaging bulk	242
IATA	
UN number	UN1993
UN proper shipping name	Flammable liquid, n.o.s. (Methyl ethyl ketone, Acetone)
Transport hazard class(es)	
Class	3
Subsidiary risk	<u>19</u>
Packing group	11
Environmental hazards	No.
ERG Code	3H
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
IMDG	
UN number	UN1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (Methyl ethyl ketone, Acetone)
Transport hazard class(es)	
Class	3
Subsidiary risk	
Packing group	1
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to	Not available.
Annex II of MARPOL 73/78 and	
the IBC Code	
15. Regulatory information	
	The second s
US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910,1200.
	All components are on the U.S. EPA TSCA Inventory List.
TSCA Section 12(b) Export N	otification (40 CFR 707, Subpt. D)
Not regulated.	
OSHA Specifically Regulated	Substances (29 CFR 1910.1001-1050)
Not listed.	м. х .

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)	LISTED
Cyclohexanone (CAS 108-94-1)	LISTED
Furan, Tetrahydro- (CAS 109-99-9)	LISTED
Methyl ethyl ketone (CAS 78-93-3)	LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard - Yes
	Delayed Hazard - No
	Fire Hazard - Yes
	Pressure Hazard - No
	Reactivity Hazard - No
SARA 302 Extremely ha	zardous substance

Not listed.

1.22

SARA 311/312 Hazardous No chemical

SARA 313 (TRI reporting) Not regulated.

Other federal regulations Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Not regulated. Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) Not regulated. Safe Drinking Water Act Not regulated. (SDWA) Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and **Chemical Code Number** Acetone (CAS 67-64-1) 6532 Methyl ethyl ketone (CAS 78-93-3) 6714 Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c)) Acetone (CAS 67-64-1) 35 %WV Methyl ethyl ketone (CAS 78-93-3) 35 %WV **DEA Exempt Chemical Mixtures Code Number** Acetone (CAS 67-64-1) 6532 Methyl ethyl ketone (CAS 78-93-3) 6714 US state regulations US. Massachusetts RTK - Substance List Acetone (CAS 67-64-1) Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS 109-99-9) Methyl ethyl ketone (CAS 78-93-3) US. New Jersey Worker and Community Right-to-Know Act Acetone (CAS 67-64-1) Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS 109-99-9) Methyl ethyl ketone (CAS 78-93-3) US. Pennsylvania Worker and Community Right-to-Know Law Acetone (CAS 67-64-1) Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS 109-99-9) Methyl ethyl ketone (CAS 78-93-3) **US. Rhode Island RTK** Acetone (CAS 67-64-1) Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS 109-99-9) Methyl ethyl ketone (CAS 78-93-3) US. California Proposition 65 California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. International Inventories Country(s) or region Inventory name On inventory (yes/no)* Canada Domestic Substances List (DSL) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes *A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s). 16. Other information, including date of preparation or last revision Issue date 27-May-2015 **Revision date** Version # 01

HMIS® ratings

Health: 2

Flammability: 3 Physical hazard: 0



Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Oatey Co. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.

SAFETY DATA SHEET

SDS 0011

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION ______ HMIS CODES PRODUCT NAME Health 1 RectorSeal No. 5 Flammability 2 Reactivity 0 PRODUCT CODES PPI В 25112, 25191, 25271, 25300, 25431, 25551, 25552, 25631, 25633, 25780, 25790, 25793 CHEMICAL FAMILY Organic USE Pipe Thread Sealant EMERGENCY TELEPHONE NO. MANUFACTURER'S NAME Chemtrec 24 Hours The RectorSeal Corporation 2601 Spenwick Drive (800)424-9300 USA (703) 527-3887 International Houston, Texas 77055 USA TECHNICAL SERVICE TELEPHONE NO. DATE OF VALIDATION January 23, 2015 (800)231-3345 or (713)263-8001 DATE OF PREPARATION January 9, 2013 _____ Section 2 -- HAZARDS IDENTIFICATION ______ EMERGENCY OVERVIEW OSHA Hazards Combustable TARGET ORGANS Not Classified GHS CLASSIFICATION PHYSICAL HAZARDS Combustable liquid (Category 4) HEALTH HAZARDS Acute Toxicity: Oral: Not Classified Dermal: Not Classified Inhalation: Not Classified Skin Corrosion/Irritation: Not Classified Serious Eye Damage/Eye Irritation: Not Classified Skin Sensitization: Not Classified Respiratory Sensitization: Not Classified Germ Cell Mutagenicity: Not Classified Carcinogenicity: See Section 11 Reproductive Toxicology: Not Classified Target Organ Systemic Toxicity - Single Exposure: Not Classified Target Organ Systemic Toxicity - Repeated Exposure: Not Classified Aspiration Toxicity: Not Classified _____ GHS Label elements, including precautionary statements Pictogram: Harmful / Irritant Signal Word: Warning

Hazard Statements H303 - May be harmful if swallowed. H313 - May be harmful in contact with skin. H335 + H336 - May cause respiratory irritation, and drowsiness or dizziness. Precautionary Statements P102 - Keep out of reach of children. P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking P240 - Ground/Bond container and receiving equipment P261 - Avoid breathing dust/fume/gas/mist/vapors/spray P262 - Do not get in eyes, on skin, or on clothing. P264 - Wash hands thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P362 - Take off contaminated clothing and wash before reuse. EUH066 - Repeated exposure may cause skin dryness or cracking Precautionary Statements - EU No. 1272/2008 _____ SUMMARY OF ACUTE HAZARDS Irritation to eyes, nose and throat; drowsiness, narcosis, tremors and other CNS effects at high concentration. ROUTE OF EXPOSURE, SIGNS AND SYMPTOMS INHALATION Nasal and respiratory irritation, dizziness, narcosis, headache, nausea, CNS depression and unconsciousness. EYE CONTACT Watering, blurred vision, inflammation and irritation which can result in corneal injury. SKIN CONTACT Irritation, dermatitis. INGESTION Nausea, vomiting; CNS depression; irritation of gastrointestinal tract, liver and peritoneal wall; lung congestion. SUMMARY OF CHRONIC HAZARDS Skin irritation and dermatitis. Possible liver and kidney damage. MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE Individuals with pre-existing or chronic diseases of the eyes, skin, respiratory system, cardiovascular system, gastrointestinal system, liver or kidneys may have increased susceptibility to excessive exposures. _____ Section 3 -- COMPOSITION/INFORMATION ON INGREDIENTS _____ INGREDIENT: Diacetone Alcohol PERCENTAGE BY WEIGHT: 20-30 CAS NUMBER: 123-42-2 EC# : 204-626-7 Section 4 -- FIRST AID MEASURES _____ If overcome by exposure, remove victim to fresh air If INHALED: immediately. Give oxygen or artificial respiration as needed. Obtain emergency medical attention. Prompt action is essential. Wash with soap and water. If irritation occurs, seek If on SKIN: medical attention.

```
If in EYES: Flush eyes with large amounts of water for 15 minutes.
```

9/6/2018 https://www.rectorseal.com/web-media/RectorSeal-No-5.html Get medical attention. If SWALLOWED: If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person. Section 5 -- FIRE FIGHTING MEASURES _____ EXTINGUSING MEDIA Foam, dry chemical, carbon dioxide or water fog. SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus (SCBA) and other protective clothing. Hazardous decomposition products possible (see Section 10). UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustible - moderate flash point. Vapors heavier than air and may travel along the ground or to low spots at considerable distances to a source of ignition resulting in potential flashback. Burning liquid may float on water. Heat may build up pressure and rupture containers. _____ Section 6 -- ACCIDENTAL RELEASE MEASURES _____ STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Use absorbent materials to prevent footing hazard and to contain. Ventilate area with natural or explosion-proof, forced air ventilation. Avoid flushing into sewers, drains, waterways, and soil. Wear protective clothing and respiratory protection during cleanup. _____ Section 7 -- HANDLING AND STORAGE PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep container closed and upright when not in use. Do not store near heat, sparks, or open flames. OTHER PRECAUTIONS: Avoid prolonged or repeated contact with skin or clothing. Empty containers may contain residues; treat as if full and observe all products precautions. Do not reuse empty containers. KEEP OUT OF REACH OF CHILDREN. ______ Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION INGREDIENT UNITS Diacetone Alcohol ACGIH TLV 50 ppm OSHA PEL 50 ppm RESPIRATORY PROTECTION (SPECIFY TYPE): In confined poorly ventilated areas, use NIOSH/MSHA approved air purifying or supplied air purifying or supplied air respirators. VENTILATION - LOCAL EXHAUST: Acceptable SPECIAL: Explosion-proof equipment. MECHANICAL (GENERAL): Preferable OTHER: N/A PROTECTIVE GLOVES: Wear rubber gloves. EYE PROTECTION: Chemical splash goggles (ANSI Z-87.1 or equivalent) OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Coveralls recommended. WORK/HYGIENIC PRACTICES: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area. Launder contaminated clothing before reuse. _____

Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT:	322 F (161 C) @ 760mm Hg
SPECIFIC GRAVITY (H20 = 1):	1.38
VAPOR PRESSURE (mm Hg):	U.3 @ 68 F (20 C) N/A
VAPOR DENSITY (AIR = 1):	1.1
EVAPORATION RATE (ETHYL ACETATE = 1):	0.14
APPEARANCE/ODOR:	Yellow Paste/Mild Odor
SOLUBILITY IN WATER:	23%
VOLATILE ORGANIC COMPOUNDS (VOC) Content	
(Theoretical Percentage By Weight):	23% or (317 g/L)
Flash POINT	150 F (65 C) SETA CC
LOWER EXPLOSION LIMIT	N/D
UPPER EXPLOSION LIMIT	N/D ====================================
Section 10 STABILITY AND	REACTIVITY
STABILITY: Stable	
CONDITIONS TO AVOID: Heat, sparks, op	en flames, and strong oxidizing.
Temperatures above 500 F (260 C).	
INCOMPATIBILITY (MATERIALS TO AVOID):	Gaseous oxygen, strong oxidizing
materials, molten alkali metals.	
HAZARDOUS DECOMPOSITION PRODUCTS: CO,	CO2 and fragmented hydrocarbons.
HAZARDOUS POLYMERIZATION: Will not oc	cur.
Section 11 TOXICOLOGY IN	======================================
CHRONIC HEALTH HAZARDS No ingredients in this product is an	n IARC, NTP or OSHA Lister carcinogen.
TOXICOLOGY DATA	
Ingredient Name	
Diacetone Alcohol	
Oral-Rat LD	50:4000 mg/kg
Inhalation-Human TC	Lo: 100 ppm
Section 12 Ecological In:	formation
ECOLOGICAL DATA	
Diacetone Alcohol	
Food Chain Concentrat	tion Potential N/A
WATERFOWL TOXICITY	N/A
BOD	N/A
AQUATIC TOXICITY	N/A
Section 13 DISPOSAL CONS	IDERATIONS
Waste Classification: Non-regulated so	DIIG WASTE
Waste from this product is not consider	red hazardous as defined under the
Resource Conservation and Recovery Ad	ct (RCRA) 40 CFR 261. Dispose of in
accordance with Federal, State, and I	Local regulation regarding pollution.
Section 14 TRANSPORTATION	N INFORMATION

DOT: OCEAN (IMDG): AIR (IATA): WHMIS (CANADA	Non-Regulated Non-Regulated Non-Regulated): Non-Regulated	
Se	ction 15 REGULATOR	Y INFORMATION
REGULATORY DA Ingredient Na	TA me 	
Diacetone A	SARA 313 TSCA Inventory CERCLA RQ RCRA Code	N/A Yes N/A N/A
Se	ction 16 OTHER INF	======================================
This docum Standard (29	ent is prepared pursu CFR 1910.1200). The	ant to the OSHA Hazard Communication information herein is given in good faith.

but no warranty, expressed or implied is made. Consult RectorSeal for further information: (713) 263-8001



SAFETY DATA SHEET

1. Identification	
Product identifier	Oatey Clear Cutting Oil
Other means of identification	
Product code	
Synonyms	Part Numbers: 30200, 30201, 30202
Recommended use	Cutting oil for hand threaded or high speed thread cutting machines.
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/E	Distributor information
Company Name	Oatey Inc.
Address	4700 West 160th Street
	Cleveland, OH 44135
Telephone	216-267-7100
E-mail	info@oatey.com
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)
Emergency First Aid	1-877-740-5015
Contact person	MSDS Coordinator
2. Hazard(s) identification	
Physical hazards	Not Classified.
Health hazards	Not Classified
OSHA defined hazards	Not Classified.
Label elements	
Hazard symbol	None.
Signal word	None
Hazard statement	This product does not require any hazard statements.
Precautionary statement	
Prevention	This product does not require any precautionary statements.
Response	This product does not require any precautionary statements.
Storage	Not applicable.
Disposal	Not applicable.
Hazard(s) not otherwise classified (HNOC)	Used Oil may contain harmful impurities.

3. Composition/information on ingredients

Mixtures

Chemical name		CAS number	%	
Petroleum Hydrocarbon Mixture		Mixture	>95	-
4. First-aid measures				_
Inhalation	Remove victim to fresh air and keep at rest attention if symptoms occur.	t in a position comfortable f	or breathing. Get m	edical
Skin contact	Flush contaminated skin with plenty of wate medical attention if symptoms occur.	er. Remove contaminated	clothing and shoes.	Get
Eye contact	Immediately flush eyes with plenty of water Check for and remove any contact lenses.	r, occasionally lifting the up Get medical attention if irri	per and lower eyelic tation occurs.	ds.
Ingestion	Wash out mouth with water. Remove victim for breathing. If material has been swallowe quantities of water to drink. Do not induce v	n to fresh air and keep at re ed and the exposed persor vomiting unless directed to	est in a position com i is conscious, give s do so by medical	nfortable small
Oatev Clear Cutting Oil				SDS US

	personnel. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Ingestion may result in nausea, vomiting, and or diarrhea.
Indication of immediate medical attention and special treatment needed.	Immediate medical attention is not required.
General information	Note to physician, treat symptomatically.
5. Fire-fighting measures	
Suitable extinguishing media	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water in a jet.
Specific hazards arising from the chemical	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases, oxides of sulfur and phosphorous (smoke). Carbon monoxide.
Special protective equipment and precautions for firefighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Fire fighting equipment/instructions	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Use water spray to keep fire-exposed containers cool. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Specific methods	None

6. Accidental release measures

None

General fire hazards

Personal precautions, protective equipment and emergency procedures	Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel"
Methods and materials for containment and cleaning up	Large Spills: Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal. Small Spills: Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
7. Handling and storage	
Precautions for safe handling	Use local exhaust ventilation if there is risk of inhalation of vapors, mists or aerosols. Properly dispose of any contaminated rags or cleaning materials to prevent fires. Put on appropriate personal protective equipment (see section 8 of SDS). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on bygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.
8 Exposure controls/porcor	al protection

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components		Туре	Value	
Oil Mist, Mineral		TLV or PEL	5 mg/m3	
US OSHA Permissible Ex	oosure Limits			
Components		Туре	Value	
Biological limit values	Data Not available.			
Appropriate engineering controls	No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.			
Individual protection measures Eye/face protection	, such as personal prot Safety eyewear com indicates this is nece	ective equipment plying with an approved standard sho ssary to avoid exposure to liquid spla	ould be used when a risk assessment ashes, mists, gases or dusts.	
Skin protection		, , , , ,	, , , , ,	
Hand	Chemical-resistant, i all times when handl	mpervious gloves complying with an ing chemical products if a risk assess	approved standard should be worn at sment indicates this is necessary.	
Other	Appropriate footweat the task being perfor handling this product	r and any additional skin protection m med and the risks involved and shou t.	neasures should be selected based on Id be approved by a specialist before	
Respiratory protection Thermal hazards	Respiratory protection Use a properly fitted, particulate filter respirator complying with an approved standard if a rist assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Chermal hazards None.		g with an approved standard if a risk ion must be based on known or nd the safe working limits of the	
General hygiene considerations	Wash hands, forearr smoking and using the should be used to re not be allowed out or eyewash stations an	ns and face thoroughly after handling he lavatory and at the end of the work move potentially contaminated clothi f the workplace. Wash contaminated d safety showers are close to the wo	g chemical products, before eating, king period. Appropriate techniques ng. Contaminated work clothing should clothing before reusing. Ensure that rkstation location.	

9. Physical and chemical properties

Appearance	
Physical state	Liquid
Form	Liquid
Color	Amber
Odor	Slight hydrocarbon
Odor threshold	Not available.
рН	Not applicable
Melting point/freezing point	No data available.
Initial boiling point and boiling	Not determined
range	
Flash point	> 340 °F (> 171°C)
Upper/lower flammability or explose	sive limits
Flammability limit – lower (%)	Not available
Flammability limit – upper (%)	Not available
Explosive limit - lower (%)	Not available
Explosive limit - upper (%)	Not available
Vapor pressure	Not applicable
Vapor density	Not applicable
Relative density	0.91
Solubility(ies)	
Solubility (water)	Negligible
Partition coefficient	
(n-octanol/water)	>6 based on similar products
Auto-ignition temperature	Not applicable

Oatey Clear Cutting Oil SDS # Version #: 01 Revision date: Issue date: 12-May-2015

Decomposition temperature	Not available
Viscosity, kinematic	160 SUS at 100 F (typical)
Other information	
VOC (Weight %)	<1% by weight, < 10 g/L

10. Stability and reactivity

Reactivity	The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph
Chemical stability	The product is stable.
Possibility of hazardous reaction	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Extreme temperature and direct sunlight.
Incompatible materials	Strong Oxidizing Agents.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
11. Toxicological information	on

Information on likely routes of ex	cposure	
Inhalation	Mist from processing.	
Skin contact	Skin contact.	
Eye contact	Eye contact.	
Ingestion	No known significant effects or critical hazards.	
Symptoms related to the physical, chemical and toxicological characteristics	No specific data.	
Information on likely routes of ex Acute Toxicity	cposure	
Components	Species	Results

Skin corrosion/irritation Serious eye damage/eye irritation	May cause skin irritation after prolonged exposure. Prolonged exposure or repeated exposure without proper cleaning can clog pores of the skin. Expected to be slightly irritating.
Respiratory or skin sensitization Respiratory sensitization	Inhalation of vapors or mists may cause irritation to the respiratory system.
Skin sensitization	This product is not expected to cause skin irritation.
Germ cell mutagenicity	Not considered a mutagenic hazard
Carcinogenicity	No component of this product is identified as a probable, possible, or confirmed carcinogen by IARC, NTP, Monographs, or OSHA.
Reproductive toxicity	No known significant effects or critical hazards.
Specific target organ toxicity	
Single exposure Repeated exposure	Not expected to be a hazard. Not expected to be a hazard.
Aspiration Hazard	Contains Distillates (petroleum), hydrotreated – Which is a category 1 Aspiration Hazard. The likely hood of aspirating the product in this form is very low due to the high viscosity.
Chronic effects	Not Classified.
Further information	Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and may present risks to health and the environment on disposal. Used oil should be handled with caution and skin contact should be avoided when possible.

12. Ecological information

Ecotoxicity			
Product/ingredient name	Results	Species	Exposure
Petroleum Distillates			
	Acute LC50 2,900 µg/l Fresh water	Fish - Rainbow trout,Donaldson trou	it 96 h

Persistence and degradability	Not Available.
Bio accumulative potential	Not Available.
Mobility in soil	Liquid under most conditions. Floats on water. If it enters soil, it will adsorb to soil particles and will not be mobile.
Other adverse effects	No known significant effects of critical hazards.

13. Disposal considerations

Disposal instructions	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewere
Local disposal regulations	Not Applicable
Hazardous waste code	Not Applicable
14. Transportation information	tion
DOT .	Not Regulated
UN number	
UN Proper Shipping Name	
Transportation Hazard classes	
Packing group	
ΙΑΤΑ	Not Regulated
UN number	
UN Proper Shipping Name	
Transportation Hazard classes	
Packing group	
IMDG	Not Regulated
UN number	
UN Proper Shipping Name	
Transportation Hazard classes	
Packing group	
Environmental hazards	
Marine polluntant	
15. Regulatory information	
U.S. Federal regulations	TSCA 12(b) - Chemical export notification: None required. TSCA 5(a)2 - Final significant new use rules: Not listed TSCA 5(a)2 - Proposed significant new use rules: Not listed TSCA 5(e) - Substances consent order: Not listed
SARA 311/312	
Classification	Not applicable
US state regulations	
California Prop 65	This product does not contain a chemical known to the State of California to cause cancer, birth defects, or other reproductive harm.
Oatev Clear Cutting Oil	211 2 1 2

16. Other information, including date of preparation or last revision

Issue Date	12-May-2015
Revision Date	-
Version #	01
HMIS Rating	Health: 1 Flammability: 1 Physical Hazards: 0
Disclaimer	Oatey Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.



SAFETY DATA SHEET

1 Identification

Product identifier	Oatey CPVC Flowguard Gold UVI One-Step Yellow Cement		
Other means of identification			
Product code	1203E		
Synonyms	Part Numbers: 31910(TV), 31911(TV), 31912, 31913, 31914, 31656, 31657, 32200, 32201, 32202, 32203, 31660, 31661, 31662, 31663, 31917, 31918, 31919		
Recommended use	Joining CPVC Pipes		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplier/I	Distributor information		
Company Name	Oatey Co.		
Address	4700 West 160th St.		
	Cleveland, OH 44135		
Telephone	216-267-7100		
E-mail	info@oatey.com		
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the U	S 1-703-527-3887)	
Emergency First Aid	1-877-740-5015		
Contact person	MSDS Coordinator		
2. Hazard(s) identification			
Physical hazards	Flammable liquids	Category 2	
Health hazards	Acute toxicity, oral	Category 4	
	Skin corrosion/irritation	Category 2	
	Serious eye damage/eye irritation	Category 2A	
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation	
	Specific target organ toxicity, single exposure	Category 3 narcotic effects	
	Aspiration hazard	Category 1	
OSHA defined hazards	Not classified.		
Label elements			
Signal word	Danger		
Hazard statement	Highly flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness.		
Precautionary statement			
Prevention	Keep away from heat/sparks/open flames/hot	surfaces No smoking. Keep container tightly	

closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response	If swallowed: Immediately call a poison center/doctor. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. Rinse mouth. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May form explosive peroxides. Contains a chemical classified by the US EPA as a suspected possible carcinogen.

Supplemental information

Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Furan, Tetrahydro-	109-99-9	30-60
Methyl ethyl ketone	78-93-3	10-30
Ethene, chloro-, homopolymer, chlorinated	68648-82-8	10-20
Acetone	67-64-1	5-15
Cyclohexanone	108-94-1	5-15
Silica, amorphous, fumed	112945-52-5	1-5

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.
Most important symptoms/effects, acute and delayed	Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

the chemical

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor. This product contains tetrahydrofuran that may form explosive organic peroxide when exposed to air or light or with age.
6. Accidental release meas	sures
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water.
	Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
Cyclohexanone (CAS 108-94-1)	PEL	200 mg/m3	
,		50 ppm	
Furan, Tetrahydro- (CAS 109-99-9)	PEL	590 mg/m3	
,		200 ppm	
Methyl ethyl ketone (CAS 78-93-3)	PEL	590 mg/m3	
,		200 ppm	
US. OSHA Table Z-3 (29 CFR 1910	0.1000)		
Components	Туре	Value	
Silica, amorphous, fumed (CAS 112945-52-5)	TWA	0.8 mg/m3	

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Туре	Value	
		20 mppcf	
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
Cyclohexanone (CAS 108-94-1)	STEL	50 ppm	
	TWA	20 ppm	
Furan, Tetrahydro- (CAS 109-99-9)	STEL	100 ppm	
	TWA	50 ppm	
Methyl ethyl ketone (CAS 78-93-3)	STEL	300 ppm	
	TWA	200 ppm	
US. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Туре	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
		250 ppm	
Cyclohexanone (CAS 108-94-1)	TWA	100 mg/m3	
		25 ppm	
Furan, Tetrahydro- (CAS 109-99-9)	STEL	735 mg/m3	
		250 ppm	
	TWA	590 mg/m3	
		200 ppm	
Methyl ethyl ketone (CAS 78-93-3)	STEL	885 mg/m3	
		300 ppm	
	TWA	590 mg/m3	
		200 ppm	
Silica, amorphous, fumed (CAS 112945-52-5)	TWA	6 mg/m3	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
Cyclohexanone (CAS 108-94-1)	80 mg/l	1,2-Cyclohexan ediol, with hydrolysis	Urine	*
	8 mg/l	Cyclohexanol, with hydrolysis	Urine	*
Furan, Tetrahydro- (CAS 109-99-9)	2 mg/l	Tetrahydrofura n	Urine	*
Methyl ethyl ketone (CAS 78-93-3)	2 mg/l	MEK	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Cyclohexanone (CAS 108-94-1)

US - Minnesota Haz Subs: Skin designation applies Cyclohexanone (CAS 108-94-1) Can be absorbed through the skin.

Skin designation applies.

US - Tennessee OELs: Skin o	designation	
Cyclohexanone (CAS 108-94-1)		Can be absorbed through the skin.
US ACGIH Threshold Limit V	alues: Skin designation	
Cyclohexanone (CAS 108-94-1)		Can be absorbed through the skin.
Furan, Tetrahydro- (CAS 109-99-9)		Can be absorbed through the skin.
US. NIOSH: Pocket Guide to	Chemical Hazards	
Cyclohexanone (CAS 108-94-1)		Can be absorbed through the skin.
Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.	
Individual protection measures, s	such as personal protective ed	quipment
Eye/face protection	Face shield is recommended. Wear safety glasses with side shields (or goggles).	
Skin protection		
Hand protection	Wear appropriate chemical resistant gloves.	
Other	Wear appropriate chemical resistant clothing.	
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.	
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.	
General hygiene considerations	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.	

9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Translucent liquid.
Color	Yellow / Gold
Odor	Solvent.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling	151 °F (66.11 °C)
range	
Flash point	14.0 - 23.0 °F (-10.05.0 °C)
Evaporation rate	5.5 - 8
Flammability (solid, gas)	Not available.
Upper/lower flammability or expl	osive limits
Flammability limit - lower (%)	1.8
Flammability limit - lower (%) Flammability limit - upper (%)	1.8 11.8
Flammability limit - lower (%) Flammability limit - upper (%) Explosive limit - lower (%)	1.8 11.8 Not available.
Flammability limit - lower (%) Flammability limit - upper (%) Explosive limit - lower (%) Explosive limit - upper (%)	1.8 11.8 Not available. Not available.
Flammability limit - lower (%) Flammability limit - upper (%) Explosive limit - lower (%) Explosive limit - upper (%) Vapor pressure	1.8 11.8 Not available. Not available. 145 mm Hg @ 20 C
Flammability limit - lower (%) Flammability limit - upper (%) Explosive limit - lower (%) Explosive limit - upper (%) Vapor pressure Vapor density	 1.8 11.8 Not available. Not available. 145 mm Hg @ 20 C 2.5
Flammability limit - lower (%) Flammability limit - upper (%) Explosive limit - lower (%) Explosive limit - upper (%) Vapor pressure Vapor density Relative density	1.8 11.8 Not available. Not available. 145 mm Hg @ 20 C 2.5 0.94 +/- 0.02
Flammability limit - lower (%) Flammability limit - upper (%) Explosive limit - lower (%) Explosive limit - upper (%) Vapor pressure Vapor density Relative density Solubility(ies)	1.8 11.8 Not available. 145 mm Hg @ 20 C 2.5 0.94 +/- 0.02
Flammability limit - lower (%) Flammability limit - upper (%) Explosive limit - lower (%) Explosive limit - upper (%) Vapor pressure Vapor density Relative density Solubility(ies) Solubility (water)	1.8 11.8 Not available. 145 mm Hg @ 20 C 2.5 0.94 +/- 0.02 Negligible
Flammability limit - lower (%) Flammability limit - upper (%) Explosive limit - lower (%) Explosive limit - upper (%) Vapor pressure Vapor density Relative density Solubility(ies) Solubility(ies) Solubility (water) Partition coefficient (n-octanol/water)	1.8 11.8 Not available. Not available. 145 mm Hg @ 20 C 2.5 0.94 +/- 0.02 Negligible Not available.

Decomposition temperature	Not available.
Viscosity	500 - 1500 cP
Other information	
Bulk density	7.8 lb/gal
VOC (Weight %)	470 g/l SQACMD 1168/M316A

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Ammonia. Amines. Isocyanates. Caustics.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May be fatal if swallowed and enters airways. Headache. Nausea, vomiting. May cause irritation to the respiratory system. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Prolonged inbalation may be harmful
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	May be fatal if swallowed and enters airways. Harmful if swallowed. Harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Symptoms related to the physical, chemical and toxicological characteristics	Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects

Acute toxicity May be fatal if swa	llowed and enters airways. Narcotic e	ffects. May cause respiratory irritation.
------------------------------------	---------------------------------------	---

Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
Dermal		
LD50	Rabbit	20 ml/kg
Inhalation		
LC50	Rat	50 mg/l, 8 Hours
Oral		
LD50	Rat	5800 mg/kg
Cyclohexanone (CAS 108-94-1)	
Acute		
Dermal		
LD50	Rabbit	948 mg/kg
Inhalation		
LC50	Rat	8000 ppm, 4 hours
Oral		
LD50	Rat	1540 mg/kg
* Estimates for product ma	y be based on additional component data not	shown.
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	

Respiratory or skin sensitization			
Respiratory sensitization			
Skin sensitization	I his product is not expected to cause skin sensitization.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	In 2012 USEPA Integrated Risk Information System (IRIS) reviewed a two species inhalation lifetime study on THF conducted by NTP (1998). Male rats developed renal tumors and female mice developed liver tumors while neither the female rats nor the male mice showed similar results. Because the carcinogenic mechanisms could not be identified clearly in either species for either tumor, the EPA determined that the male rat and female mouse findings are relevant to the assessment of carcinogenic potential in humans. Therefore, the IRIS review concludes that these data in aggregate indicate that there is "suggestive evidence of carcinogenic potential" following exposure to THF by all routes of exposure.		
IARC Monographs. Overall E	valuation of Ca	arcinogenicity	
Cyclohexanone (CAS 108- Silica, amorphous, fumed OSHA Specifically Regulated Not listed.	-94-1) (CAS 112945-5 I Substances ()	2-5) 29 CFR 1910.100	3 Not classifiable as to carcinogenicity to humans. 3 Not classifiable as to carcinogenicity to humans. 01-1050)
Reproductive toxicity	This product is	not expected to	cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Narcotic effect	s. May cause dro	owsiness and dizziness. Respiratory tract irritation.
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	May be fatal if	swallowed and e	enters airways.
Chronic effects	Prolonged inha	alation may be ha	armful.
12. Ecological information			
Ecotoxicity	The product is possibility that	not classified as large or frequent	environmentally hazardous. However, this does not exclude the t spills can have a harmful or damaging effect on the environment.
Components		Species	Test Results
Acetone (CAS 67-64-1) Aquatic			
Fish L	_C50	Fathead minnov	w (Pimephales promelas) > 100 mg/l, 96 hours
Cyclohexanone (CAS 108-94-1)		
Fish L	-C50	Fathead minnov	w (Pimephales promelas) 481 - 578 mg/l, 96 hours
* Estimates for product may be	based on addit	tional component	t data not shown.
Persistence and degradability	No data is ava	ilable on the deg	radability of this product.
Bioaccumulative potential	No data availa	ble.	
Partition coefficient n-octand Acetone (CAS 67-64-1) Cyclohexanone (CAS 108-94-1 Furan, Tetrahydro- (CAS 109-9	b l / water (log k 1) 99-9) 2 2)	(ow)	-0.24 0.81 0.46
Mobility in soil	No data availa	hle	0.29
Other adverse offects	No other adver	rse environmenta	al effects (e.g. ozone depletion, photochemical ozone creation
Other adverse enects	potential, endo	ocrine disruption,	global warming potential) are expected from this component.
13. Disposal consideration	S		
Disposal instructions	Collect and red and its contain sewers/waters container. Disp regulations.	claim or dispose i ler must be dispo supplies. Do not o bose of contents/	in sealed containers at licensed waste disposal site. This material osed of as hazardous waste. Do not allow this material to drain into contaminate ponds, waterways or ditches with chemical or used (container in accordance with local/regional/national/international

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

UN number	UN1993
UN proper shipping name	Flammable liquids, n.o.s. (Methyl ethyl ketone RQ = 23310 LBS, Acetone RQ = 50000 LBS)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	IB2, 17, 1P1, 1P8, 1P28
Packaging exceptions	150
Packaging non bulk	202
Packaging bulk	242
IATA	
UN number	UN1993
UN proper shipping name	Flammable liquid, n.o.s. (Methyl ethyl ketone, Acetone)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	No.
ERG Code	3H
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
IMDG	
UN number	UN1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (Methyl ethyl ketone, Acetone)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not available.

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. Il components are on the U.S. EPA TSCA Inventory List.
TSCA Section 12(b) Export N	tification (40 CFR 707, Subpt. D)
Not regulated.	
OSHA Specifically Regulated	Substances (29 CFR 1910.1001-1050)
Not listed.	
CERCLA Hazardous Substar	e List (40 CFR 302.4)
Acetone (CAS 67-64-1)	LISTED
Cyclohexanone (CAS 108	4-1) LISTED
Furan, Tetrahydro- (CAS	9-99-9) LISTED
Methyl ethyl ketone (CAS	3-93-3) LISTED

Super	fund Amendments and Rea	uthorization Act of 1986 (SAI	RA)	
Ha	azard categories	Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No		
S	ARA 302 Extremely hazardo	ous substance		
	Not listed.			
S/ ch	ARA 311/312 Hazardous nemical	No		
SA	ARA 313 (TRI reporting) Not regulated.			
Other	federal regulations			
CI	ean Air Act (CAA) Section	112 Hazardous Air Pollutants	(HAPs) List	
CI	Not regulated. ean Air Act (CAA) Section	112(r) Accidental Release Pre	evention (40 CFR 68.130)	
	Not regulated.			
Sa (S	afe Drinking Water Act DWA)	Not regulated.		
	Drug Enforcement Admin Chemical Code Number	nistration (DEA). List 2, Esse	ntial Chemicals (21 CFR 1310.02(b) and 1	310.04(f)(2) and
	Acetone (CAS 67-64-	1)	6532	
	Methyl ethyl ketone (C	CAS 78-93-3) nistration (DEΔ) List 1 & 2 Ev	6/14 cempt Chemical Mixtures (21 CER 1310.1)	2(c))
	Acetone (CAS 67-64-	1)	35 %WV	2(0))
	Methyl ethyl ketone (C DEA Exempt Chemical M	CAS 78-93-3) lixtures Code Number	35 %WV	
	Acetone (CAS 67-64- Methyl ethyl ketone (C	1) CAS 78-93-3)	6532 6714	
US sta	te regulations			
US	S. Massachusetts RTK - Su	bstance List		
U	Acetone (CAS 67-64-1) Cyclohexanone (CAS 108- Furan, Tetrahydro- (CAS 1 Methyl ethyl ketone (CAS Silica, amorphous, fumed 5. New Jersey Worker and	-94-1) 09-99-9) 78-93-3) (CAS 112945-52-5) Community Right-to-Know A	ct	
U	Acetone (CAS 67-64-1) Cyclohexanone (CAS 108- Furan, Tetrahydro- (CAS 1 Methyl ethyl ketone (CAS 5. Pennsylvania Worker an	-94-1) 09-99-9) 78-93-3) d Community Right-to-Know	Law	
U	Acetone (CAS 67-64-1) Cyclohexanone (CAS 108- Furan, Tetrahydro- (CAS 1 Methyl ethyl ketone (CAS Silica, amorphous, fumed 5. Rhode Island RTK	-94-1) 09-99-9) 78-93-3) (CAS 112945-52-5)		
	Acetone (CAS 67-64-1) Cyclohexanone (CAS 108- Furan, Tetrahydro- (CAS 1 Methyl ethyl ketone (CAS	-94-1) 09-99-9) 78-93-3)		
U	S. California Proposition 65	;		
	California Safe Drinking W any chemicals currently lis	ater and Toxic Enforcement Acted as carcinogens or reproduct	t of 1986 (Proposition 65): This material is n tive toxins.	ot known to contain
Interna	ational Inventories			
Ca Ca	ountry(s) or region anada	Inventory name Domestic Substances List (DS	SL)	On inventory (yes/no)* Yes

Country(s) or region

Inventory name

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	27-May-2015
Revision date	-
Version #	01
HMIS® ratings	Health: 2 Flammability: 3 Physical hazard: 0
NFPA ratings	2 0

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Oatey Co. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.



SAFETY DATA SHEET

1. Identification

Product identifier	Gray Pipe Joint Compound	
Other means of identification		
SDS number	1703E	
Synonyms	Part Numbers: 31226, 31227, 31228, 32235, 31236, 48005, 48324	
Recommended use	Pipe Joint Compound for Threaded Metal Pipes	
Recommended restrictions	None known.	
Manufacturar/Importar/Supplie	Distributor information	

Manufacturer/Importer/Supplier/Distributor information

Company Name	Oatey Co.
Address	4700 West 160th St.
	Cleveland, OH 44135
Telephone	216-267-7100
E-mail	info@oatey.com
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)
Emergency First Aid	1-877-740-5015
Contact person	MSDS Coordinator

2. Hazard(s) identification

Physical hazards	Not classified.
Health hazards	Not classified.
OSHA defined hazards	Not classified.
Label elements	
Hazard symbol	None.
Signal word	None.
Hazard statement	The mixture does not meet the criteria for classification.
Precautionary statement	
Prevention	Observe good industrial hygiene practices.
Response	Wash hands after handling.
Storage	Store away from incompatible materials.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
Hazard(s) not otherwise classified (HNOC)	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Calcium carbonate	1317-65-3	60-75
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	20-30
Canola Oil, Polymd., Oxidized	129828-25-7	1-5
Crystalline silica (Quartz)	14808-60-7	<0.8

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Skin contact Move to fresh air. Call a physician if symptoms develop or persist. Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.

Specific methodsUse standard firefighting procedures and consider the hazards of other involved materials.General fire hazardsNo unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	The product is immiscible with water and will sediment in water systems. Large Spills: Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Avoid prolonged exposure. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Calcium carbonate (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Туре	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust.
		0.1 mg/m3	Respirable.
US. ACGIH Threshold Limit	Values		
Components	Туре	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
Calcium carbonate (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS	STEL	10 mg/m3	Mist.
64742-52-5)	TWA	5 mg/m3	Mist
ological limit values	No biological exposure limits noted for	the ingredient(s).	
propriate engineering ntrols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.		
lividual protection measures.	such as personal protective equipme	nt	
Eye/face protection	Wear safety glasses with side shields (or goggles).	
Skin protection			
Hand protection	Wear appropriate chemical resistant gl	oves.	
Other	Wear suitable protective clothing.		
Respiratory protection	Use a particulate filter respirator for particulate concentrations exceeding the Occupational Exposure Limit.		
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.		
neral hygiene nsiderations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.		
Physical and chemical r	properties		
pearance	•		

Physical state	Liquid.
Form	Liquid paste.
Color	Gray.
Odor	Odorless
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.

Flash point	> 212.0 °F (> 100.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or expl	osive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	< 1
Relative density	1.75
Solubility(ies)	
Solubility (water)	Insoluble
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	20000 cP
Other information	
VOC (Weight %)	11 g/l
10. Stability and reactivity	

0. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Acids. Fluorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Information on toxicological ef	fects
Acute toxicity	Not available

Acute toxicity	Not available.
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye Direct contact with eyes may cause temporary irritation. irritation	
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity	In 1997, IARC (the Internation inhaled from occupational sou overall evaluation, IARC noted circumstances studied. Carcin crystalline silica or on external polymorphs." (IARC Monogra humans, Silica, silicates dust a	al Agency for Research on Cancer) concluded that crystalline silica rces can cause lung cancer in humans. However in making the I that "carcinogenicity was not detected in all industrial ogenicity may be dependent on inherent characteristics of the factors affecting its biological activity or distribution of its phs on the evaluation of the carcinogenic risks of chemicals to and organic fibres, 1997, Vol. 68, IARC, Lyon, France.)
IARC Monographs. Overall E	Evaluation of Carcinogenicity	
Crystalline silica (Quartz)	(CAS 14808-60-7)	1 Carcinogenic to humans.
(CAS 64742-52-5)	drotreated neavy naphthenic	3 Not classifiable as to carcinogenicity to humans.
NTP Report on Carcinogens	;	
Crystalline silica (Quartz) OSHA Specifically Regulate	(CAS 14808-60-7) d Substances (29 CFR 1910.10	Known To Be Human Carcinogen. 001-1050)
Not listed.		
Reproductive toxicity	This product is not expected to	o cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.	
Further information	This product has no known adverse effect on human health.	
12. Ecological information	I	
Ecotoxicity	The product is not classified a	s environmentally hazardous. However, this does not exclude the

ECOTOXICITY	possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

-	
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according toNot established.Annex II of MARPOL 73/78 andthe IBC Code

Pogulatory information

15. Regulatory information	1	
US federal regulations	All components are on the U.S. EPA TSCA Inventory List. This product is not known to be a "Hazardous Chemical" as defined by th Communication Standard, 29 CFR 1910.1200.	e OSHA Hazard
TSCA Section 12(b) Export I	Notification (40 CFR 707, Subpt. D)	
Not regulated.		
OSHA Specifically Regulate	d Substances (29 CFR 1910.1001-1050)	
Not listed.		
CERCLA Hazardous Substa	nce List (40 CFR 302.4)	
Not listed.		
Superfund Amendments and Re	authorization Act of 1986 (SARA)	
Hazard categories	Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No	
SARA 302 Extremely hazard	lous substance	
Not listed.		
SARA 311/312 Hazardous chemical	No	
SARA 313 (TRI reporting) Not regulated.		
Other federal regulations		
Clean Air Act (CAA) Section	112 Hazardous Air Pollutants (HAPs) List	
Not regulated.		
Clean Air Act (CAA) Section	112(r) Accidental Release Prevention (40 CFR 68.130)	
Safe Drinking Water Act	Not regulated.	
(SDWA)	i i i i i i i i i i i i i i i i i i i	
US state regulations		
US. Massachusetts RTK - Su	ubstance List	
Calcium carbonate (CAS	1317-65-3)	
Crystalline silica (Quartz) Distillates (petroleum), hy US. New Jersey Worker and	(CAS 14808-60-7) drotreated heavy naphthenic (CAS 64742-52-5) Community Right-to-Know Act	
Calcium carbonate (CAS	1317-65-3)	
Crystalline silica (Quartz) US. Pennsylvania Worker ar	(CAS 14808-60-7) ad Community Right-to-Know Law	
Calcium carbonate (CAS	1317-65-3)	
Crystalline silica (Quartz)	(CAS 14808-60-7)	
US. Rhode Island RTK		
Not regulated.		
US. California Proposition 6 WARNING: This product	5 contains a chemical known to the State of California to cause cancer.	
US - California Proposit Crystalline silica (Qua	ion 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance artz) (CAS 14808-60-7)	3
International Inventories		
		On inventery (vec/ne)*
Australia	Australian Inventory of Chemical Substances (AICS)	No.
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	NU Voo
	Inventory of Existing Chemical Substances in China (IECSC)	Tes No.
Furopo	European Inventory of Existing Commercial Chamical	INO No
Europe	Substances (EINECS)	NO

European List of Notified Chemical Substances (ELINCS)

Europe

No

Country(s) or region	Inventory name	On inventory (yes/no)*
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	05-February-2015
Revision date	-
Version #	01
HMIS® ratings	Health: 0 Flammability: 0 Physical hazard: 0
Disclaimer	Oatey Co. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.



SAFETY DATA SHEET

1. Identification

Product identifier	Oatey H2O 5 Paste Flux	
Other means of identification		
SDS number	1613E	
Synonyms	Part Numbers: 30130, 30131, 30132, 30133, 53067	
Recommended use	Joining Copper Pipes. Joining Copper Tubing.	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		

Company Name	Oatey Co.
Address	4700 West 160th St.
	Cleveland, OH 44135
Telephone	216-267-7100
E-mail	info@oatey.com
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)
Emergency First Aid	1-877-740-5015
Contact person	MSDS Coordinator
Contact person	MSDS Coordinator

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Skin corrosion/irritation	Category 1B
	Serious eye damage/eye irritation	Category 1
OSHA defined hazards	Not classified.	

Label elements



	•
Signal word	Danger
Hazard statement	Causes severe skin burns and eye damage.
Precautionary statement	
Prevention	Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dusts or mists.
Response	If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Wash contaminated clothing before reuse.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information Not applicable.	

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Glycerin	56-81-5	7-13
Triethanolamine Hydrochloride	637-39-8	7-13
-------------------------------	------------	------
Zinc chloride	7646-85-7	3-7
Ammonium chloride	12125-02-9	1-5

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Continue rinsing. Call a physician or poison control center immediately. Remove contact lenses, if present and easy to do.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water spray. Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Use water spray to cool unopened containers.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading.
	Small Spills: Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Do not get this material on clothing. Provide adequate ventilation. Wear appropriate

personal protective equipment. Observe good industrial hygiene practices.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form	
Glycerin (CAS 56-81-5)	PEL	5 mg/m3 15 mg/m3	Respirable fraction. Total dust.	
Zinc chloride (CAS 7646-85-7)	PEL	1 mg/m3	Fume.	
US. ACGIH Threshold Limi	t Values			
Components	Туре	Value	Form	
Ammonium chloride (CAS 12125-02-9)	STEL	20 mg/m3	Fume.	
	TWA	10 mg/m3	Fume.	
Zinc chloride (CAS 7646-85-7)	STEL	2 mg/m3	Fume.	
	TWA	1 mg/m3	Fume.	
US. NIOSH: Pocket Guide	o Chemical Hazards			
Components	Туре	Value	Form	
Ammonium chloride (CAS 12125-02-9)	STEL	20 mg/m3	Fume.	
	TWA	10 mg/m3	Fume.	
Zinc chloride (CAS 7646-85-7)	STEL	2 mg/m3	Fume.	
	TWA	1 mg/m3	Fume.	
Biological limit values	No biological exposure limits noted for	the ingredient(s).		
Exposure guidelines	Occupational Exposure Limits are not	relevant to the current physica	al form of the product.	
Appropriate engineering controls	Good general ventilation (typically 10 a should be matched to conditions. If ap or other engineering controls to mainta exposure limits have not been establis wash facilities and emergency shower	air changes per hour) should b plicable, use process enclosu ain airborne levels below reco hed, maintain airborne levels must be available when hand	be used. Ventilation rates res, local exhaust ventilation, mmended exposure limits. If to an acceptable level. Eye lling this product.	
Individual protection measures	s, such as personal protective equipme	nt		
Eye/face protection	Wear safety glasses with side shields	(or goggles) and a face shield		
Skin protection				
Hand protection	Wear appropriate chemical resistant g	loves.		
Other	Wear appropriate chemical resistant clothing.			
Respiratory protection	In case of insufficient ventilation, wear	In case of insufficient ventilation, wear suitable respiratory equipment.		
Thermal hazards	Wear appropriate thermal protective cl	othing, when necessary.		
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.			
9. Physical and chemical	properties			

Appearance	
Physical state	Liquid.
Form	Paste.
Color	Light yellow.
Odor	Slight.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.

Initial boiling point and boiling range	Not Applicable			
Flash point	Not Applicable			
Evaporation rate	Not available.			
Flammability (solid, gas)	Not available.			
Upper/lower flammability or explosive limits				
Flammability limit - lower (%)	Not available.			
Flammability limit - upper (%)	Not available.			
Explosive limit - lower (%)	Not available.			
Explosive limit - upper (%)	Not available.			
Vapor pressure	Not available.			
Vapor density	>1			
Relative density	1.1			
Solubility(ies)				
Solubility (water)	Soluble			
Partition coefficient (n-octanol/water)	Not available.			
Auto-ignition temperature	Not available.			
Decomposition temperature	Not available.			
Viscosity	30000 - 50000			
Other information				
VOC (Weight %)	8 g/l <1% by weight			
10. Stability and reactivity				
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.			
Chemical stability	Material is stable under normal conditions.			
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.			
Conditions to avoid	Contact with incompatible materials.			
Incompatible materials	Strong oxidizing agents.			
Hazardous decomposition products	Decomposition may yield acrolein. No hazardous decomposition products are known.			
11. Toxicological informati	on			

Information on likely routes of ex	kposure
Inhalation	Prolonged inhalation may be harmful. May cause irritation to the respiratory system.
Skin contact	Causes severe skin burns.
Eye contact	Causes serious eye damage.
Ingestion	Causes digestive tract burns.
Symptoms related to the physical, chemical and toxicological characteristics	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Information on toxicological effects

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes severe skin burns and eye damage.
Serious eye damage/eye irritation	Causes serious eye damage.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Risk of cancer cannot be excluded with prolonged exposure.
OSHA Specifically Regulated	l Substances (29 CFR 1910.1001-1050)
Not listed.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful.
12. Ecological information	
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Partition coefficient n-octanc Glycerin (CAS 56-81-5)	ol / water (log Kow) -1.76
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.			
TSCA Section 12(b) Export N	otification (40 CFR 707, Su	bpt. D)		
Not regulated. OSHA Specifically Regulated	l Substances (29 CFR 1910.	1001-1050)		
Not listed.				
CERCLA Hazardous Substan	nce List (40 CFR 302.4)			
Zinc chloride (CAS 7646-8	12125-02-9) 55-7)	LISTED		
Superfund Amendments and Rea Hazard categories	Inthorization Act of 1986 (S Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No	ARA)		
SARA 302 Extremely hazardo	ous substance			
Not listed.				
SARA 311/312 Hazardous chemical	No			
SARA 313 (TRI reporting)				
Chemical name		CAS number	% by wt.	
Zinc chloride Ammonium chloride		7646-85-7 12125-02-9	3-7 1-5	
Other federal regulations				
Clean Air Act (CAA) Section	112 Hazardous Air Pollutan	ts (HAPs) List		
Not regulated. Clean Air Act (CAA) Section	112(r) Accidental Release F	Prevention (40 CFR 6	68.130)	
Not regulated.				
Safe Drinking Water Act (SDWA)	Not regulated.			
US state regulations				
US. Massachusetts RTK - Su	bstance List			
Ammonium chloride (CAS Glycerin (CAS 56-81-5) Zinc chloride (CAS 7646-8	12125-02-9) 25-7)			
US. New Jersey Worker and	Community Right-to-Know	Act		
Ammonium chloride (CAS Glycerin (CAS 56-81-5) Zinc chloride (CAS 7646-8	12125-02-9)			
US. Pennsylvania Worker and	d Community Right-to-Knov	w Law		
Ammonium chloride (CAS Glycerin (CAS 56-81-5) Zinc chloride (CAS 7646-8 US. Rhode Island RTK	12125-02-9) 55-7)			
Ammonium chloride (CAS Zinc chloride (CAS 7646-8	12125-02-9) 95-7)			
US. California Proposition 65 California Safe Drinking W any chemicals currently lis	i ater and Toxic Enforcement ted as carcinogens or reprod	Act of 1986 (Proposit uctive toxins.	ion 65): This material is n	not known to contain
International Inventories				
Country(s) or region	Inventory name			On inventory (yes/no)*
Australia	Australian Inventory of Cher	nical Substances (Al	CS)	Yes
Canada	Domestic Substances List (I	DSL)		Yes
Canada	Non-Domestic Substances L	list (NDSL)		No

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	27-October-2014
Revision date	19-February-2015
Version #	04
HMIS® ratings	Health: 3 Flammability: 0 Physical hazard: 0
Disclaimer	The information in the sheet was written based on the best knowledge and experience currently available. Oatey Co. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for use, handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.



SAFETY DATA SHEET

1. Identification

Product identifier	Oatey H2O 5 Paste Flux	
Other means of identification		
SDS number	1613E	
Synonyms	Part Numbers: 30130, 30131, 30132, 30133, 53067	
Recommended use	Joining Copper Pipes. Joining Copper Tubing.	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		

Company Name	Oatey Co.
Address	4700 West 160th St.
	Cleveland, OH 44135
Telephone	216-267-7100
E-mail	info@oatey.com
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)
Emergency First Aid	1-877-740-5015
Contact person	MSDS Coordinator
Contact person	MSDS Coordinator

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Skin corrosion/irritation	Category 1B
	Serious eye damage/eye irritation	Category 1
OSHA defined hazards	Not classified.	

Label elements



	•
Signal word	Danger
Hazard statement	Causes severe skin burns and eye damage.
Precautionary statement	
Prevention	Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dusts or mists.
Response	If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Wash contaminated clothing before reuse.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information Not applicable.	

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Glycerin	56-81-5	7-13

Triethanolamine Hydrochloride	637-39-8	7-13
Zinc chloride	7646-85-7	3-7
Ammonium chloride	12125-02-9	1-5

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Continue rinsing. Call a physician or poison control center immediately. Remove contact lenses, if present and easy to do.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water spray. Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Use water spray to cool unopened containers.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading.
	Small Spills: Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Do not get this material on clothing. Provide adequate ventilation. Wear appropriate

personal protective equipment. Observe good industrial hygiene practices.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Glycerin (CAS 56-81-5)	PEL	5 mg/m3 15 mg/m3	Respirable fraction. Total dust.
Zinc chloride (CAS 7646-85-7)	PEL	1 mg/m3	Fume.
US. ACGIH Threshold Limi	t Values		
Components	Туре	Value	Form
Ammonium chloride (CAS 12125-02-9)	STEL	20 mg/m3	Fume.
	TWA	10 mg/m3	Fume.
Zinc chloride (CAS 7646-85-7)	STEL	2 mg/m3	Fume.
	TWA	1 mg/m3	Fume.
US. NIOSH: Pocket Guide	o Chemical Hazards		
Components	Туре	Value	Form
Ammonium chloride (CAS 12125-02-9)	STEL	20 mg/m3	Fume.
	TWA	10 mg/m3	Fume.
Zinc chloride (CAS 7646-85-7)	STEL	2 mg/m3	Fume.
	TWA	1 mg/m3	Fume.
Biological limit values	No biological exposure limits noted for	the ingredient(s).	
Exposure guidelines	Occupational Exposure Limits are not	relevant to the current physica	al form of the product.
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.		
Individual protection measures	s, such as personal protective equipme	nt	
Eye/face protection	Wear safety glasses with side shields	(or goggles) and a face shield	
Skin protection			
Hand protection	Wear appropriate chemical resistant g	loves.	
Other	Wear appropriate chemical resistant clothing.		
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.		
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.		
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.		
9. Physical and chemical	properties		

Appearance	
Physical state	Liquid.
Form	Paste.
Color	Light yellow.
Odor	Slight.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.

Initial boiling point and boiling range	Not Applicable
Flash point	Not Applicable
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or expl	osive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	>1
Relative density	1.1
Solubility(ies)	
Solubility (water)	Soluble
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	30000 - 50000
Other information	
VOC (Weight %)	8 g/l <1% by weight
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Decomposition may yield acrolein. No hazardous decomposition products are known.
11. Toxicological informati	on

Information on likely routes of ex	kposure		
Inhalation	Prolonged inhalation may be harmful. May cause irritation to the respiratory system.		
Skin contact	Causes severe skin burns.		
Eye contact	Causes serious eye damage.		
Ingestion	Causes digestive tract burns.		
Symptoms related to the physical, chemical and toxicological characteristics	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.		

Information on toxicological effects

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes severe skin burns and eye damage.	
Serious eye damage/eye irritation	Causes serious eye damage.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Risk of cancer cannot be excluded with prolonged exposure.	
OSHA Specifically Regulated	l Substances (29 CFR 1910.1001-1050)	
Not listed.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be harmful.	
12. Ecological information		
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.	
Persistence and degradability	No data is available on the degradability of this product.	
Bioaccumulative potential	No data available.	
Partition coefficient n-octanc Glycerin (CAS 56-81-5)	ol / water (log Kow) -1.76	
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.			
TSCA Section 12(b) Export N	otification (40 CFR 707, Su	bpt. D)		
Not regulated. OSHA Specifically Regulated	l Substances (29 CFR 1910.	1001-1050)		
Not listed.				
CERCLA Hazardous Substan	nce List (40 CFR 302.4)			
Zinc chloride (CAS 7646-8	12125-02-9) 55-7)	LISTED		
Superfund Amendments and Rea Hazard categories	Inthorization Act of 1986 (S Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No	ARA)		
SARA 302 Extremely hazardo	ous substance			
Not listed.				
SARA 311/312 Hazardous chemical	No			
SARA 313 (TRI reporting)				
Chemical name		CAS number	% by wt.	
Zinc chloride Ammonium chloride		7646-85-7 12125-02-9	3-7 1-5	
Other federal regulations				
Clean Air Act (CAA) Section	112 Hazardous Air Pollutan	ts (HAPs) List		
Not regulated. Clean Air Act (CAA) Section	112(r) Accidental Release F	Prevention (40 CFR 6	68.130)	
Not regulated.				
Safe Drinking Water Act (SDWA)	Not regulated.			
US state regulations				
US. Massachusetts RTK - Su	bstance List			
Ammonium chloride (CAS Glycerin (CAS 56-81-5) Zinc chloride (CAS 7646-8	12125-02-9) 25-7)			
US. New Jersey Worker and	Community Right-to-Know	Act		
Ammonium chloride (CAS Glycerin (CAS 56-81-5) Zinc chloride (CAS 7646-8	12125-02-9)			
US. Pennsylvania Worker and	d Community Right-to-Knov	w Law		
Ammonium chloride (CAS Glycerin (CAS 56-81-5) Zinc chloride (CAS 7646-8 US. Rhode Island RTK	12125-02-9) 55-7)			
Ammonium chloride (CAS Zinc chloride (CAS 7646-8	12125-02-9) 95-7)			
US. California Proposition 65 California Safe Drinking W any chemicals currently lis	i ater and Toxic Enforcement ted as carcinogens or reprod	Act of 1986 (Proposit uctive toxins.	ion 65): This material is n	not known to contain
International Inventories				
Country(s) or region	Inventory name			On inventory (yes/no)*
Australia	Australian Inventory of Cher	nical Substances (Al	CS)	Yes
Canada	Domestic Substances List (I	DSL)		Yes
Canada	Non-Domestic Substances L	list (NDSL)		No

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	27-October-2014
Revision date	19-February-2015
Version #	04
HMIS® ratings	Health: 3 Flammability: 0 Physical hazard: 0
Disclaimer	The information in the sheet was written based on the best knowledge and experience currently available. Oatey Co. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for use, handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.



SAFETY DATA SHEET

1. Identification

Product identifier	Oatey Pipe Joint Lubricant	
Other means of identification		
Product code		
Synonyms	Part Numbers: 30599, 30600, 30601, 30602	
Recommended use	Lubricant	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/	Distributor information	
Company Name	Oatey Inc.	
Address	4700 West 160th Street	
	Cleveland, OH 44135	
Telephone	216-267-7100	
E-mail	info@oatey.com	
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)	
Emergency First Aid	1-877-740-5015	
Contact person	MSDS Coordinator	
2. Hazard(s) identification		
Physical hazards	Not Classified.	
Health hazards	Skin Irritant	Cat 3
	Eye Irritation	Cat 2B
OSHA defined hazards	This chemical is considered non-hazardous according to the OSHA Hazard Standard 2012 (29 CFR 1910.1200)	Communication
Label elements		
Hazard symbol	None.	
Signal word	Warning	
Hazard statement	Causes mild skin irritation. Causes eye irritation.	
Precautionary statement		
Prevention	Wash skin thoroughly after handling.	
Response	If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse ca for several minutes. Remove contact lenses, if present and easy to do. Cor irritation persists: Get medical advice/attention.	autiously with water htinue rinsing. If eye
Storage	Not applicable.	
Disposal	Not applicable.	
Hazard(s) not otherwise classified (HNOC)	None.	

3. Composition/information on ingredients

Mixtures

The product contains no substances which at their given concentration, are considered to be hazardous to health.

Chemical name		CAS number	%
Mixed sodium and potassium salts of tall oil (soap)		68606-06-4	15 - 25
4. First-aid measure	es		
Inhalation	Remove victim to fresh air and kee attention if symptoms occur.	ep at rest in a position comfortable for	breathing. Get med
Skin contact	Wash off immediately with soap an	nd water. If skin irritation persists, call	a physician.
Oatev Pipe Joint Lubricant			S

Eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.		
Ingestion	Do NOT induce vomiting. Drink plenty of water. Rinse mouth. Never give anything by mouth to		
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation. Prolonged or repeated skin contact may cause irritation.		
Indication of immediate medical attention and special treatment needed.	Immediate medical attention is not required.		
General information	Note to physician, treat symptomatically.		
5. Fire-fighting measures			
Suitable extinguishing media	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.		
Unsuitable extinguishing media	Do not use water in a jet.		
Specific hazards arising from the chemical	No information available.		
Special protective equipment and precautions for firefighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.		
Fire fighting equipment/instructions	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Use water spray to keep fire-exposed containers cool. Fire water contaminated with this material must be		

contained and prevented from being discharged to any waterway, sewer or drain.

Specific methods General fire hazards

6. Accidental release measures

None

None

Personal precautions, protective equipment and emergency procedures	Avoid contact with the skin and the eyes. Evacuate personnel to safe areas. Use personal protective equipment. Keep people away from and upwind of spill/leak.	
Methods and materials for containment and cleaning up	Dike to collect large liquid spills. Prevent leakage or spillage if safe to do so. Dam up. Soak up with inert absorbent material Place the bulk of any spilled material into properly labeled containers. Rinse any remaining material to sewage treatment facility. Clean up in accordance with all applicable regulations.	
Environmental precautions	vent further leakage or spillage if safe to do so. Prevent product from entering ins. Do not flush into surface water or sanitary sewer system. Prevent entry into erways, sewers, basements or confined areas. See Section 12 for additional ological information	
7. Handling and storage		
Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Do not breathe vapors or spray mist. Ensure adequate ventilation. Use only in area provided with appropriate	

exhaust ventilation. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Do not take internally.
Conditions for safe storage, including any incompatibilities
Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in properly labeled containers. Keep out of the reach of children.

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Туре	Value
Biological limit values	Data Not available.	
Appropriate engineering controls	No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure	

	limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
Individual protection measures	, such as personal protective equipment
Eye/face protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.
Skin protection	
Hand	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Other	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Thermal hazards	None.
General hygiene considerations	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

9. Physical and chemical properties

Appearance	
Physical state	Liquid
Form	Paste
Color	Off-White
Odor	Slight
Odor threshold	Not available.
рН	9 (5% Solution)
Melting point/freezing point	No data available.
Initial boiling point and boiling	Not determined
range	
Flash point	> 220 °F (> 104°C)
Upper/lower flammability or explose	sive limits
Flammability limit – lower (%)	Not available
Flammability limit – upper (%)	Not available
Explosive limit - lower (%)	Not available
Explosive limit - upper (%)	Not available
Vapor pressure	Not applicable
Vapor density	Not applicable
Relative density	1.2
Solubility(ies)	
Solubility (water)	Completely soluble.
Partition coefficient	
(n-octanol/water)	Not determined.
Auto-ignition temperature	Not applicable
Decomposition temperature	Not available
Viscosity, kinematic	Not determined/
Other information	
VOC (Weight %)	< 1% by weight, < 12 g/L

10. Stability and reactivity

Reactivity	Not reactive under normal conditions
Chemical stability	The product is stable.
Possibility of hazardous reaction	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong Oxidizing Agents.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of exp	oosure	
Inhalation	Not a likely route	
Skin contact	May cause mild skin irritation.	
Eye contact	Causes Eye irritation	
Ingestion	No known significant effects or critical hazards.	
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation. Prolonged or repeated contact may dry skin and cause irritation	
Information on likely routes of exp Acute Toxicity	oosure	
Components	Species	Results
Skin corrosion/irritation	Prolonged exposure may cause skin irritation.	
Serious eye damage/eye irritation	Expected to be slightly irritating.	
Respiratory or skin sensitization Respiratory sensitization	Inhalation of vapors or mists may cause irritation to the	he respiratory system.
Skin sensitization	This product is not expected to cause skin irritation.	

No component of this product is identified as a probable, possible, or confirmed carcinogen by

Not considered a mutagenic hazard

IARC, NTP, Monographs, or OSHA.

Not expected to be a hazard.

Not expected to be a hazard.

Not expected to be a hazard

Not Classified.

None Provided.

No known significant effects or critical hazards.

Further information 12. Ecological information

	0
Ecotoxicity	

Germ cell mutagenicity

Reproductive toxicity

Repeated exposure Aspiration Hazard

Single exposure

Chronic effects

Specific target organ toxicity

Carcinogenicity

Product/ingredient name Re	sults Sr	pecies	Exposure
Persistence and degradability	Not Available.		
Bio accumulative potential	Not Available.		
Mobility in soil	Not determined.		
Other adverse effects	No known significant effects of critical ha	izards.	

13. Disposal considerations

Disposal instructions Local disposal regulations	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Not Applicable
Hazardous waste code	Not Applicable
14. Transportation informat	ion

הטי	г
DU	L

Not Regulated

UN number UN Proper Shipping Name Transportation Hazard

classes

Packing group

ΙΑΤΑ

Not Regulated

UN number

UN Proper Shipping Name Transportation Hazard classes Packing group

IMDG

Not Regulated

UN number UN Proper Shipping Name Transportation Hazard classes Packing group Environmental hazards Marine polluntant

15. Regulatory information

U.S. Federal regulations	TSCA 12(b) - Chemical export notification: None required.
-	TSCA 5(a)2 - Final significant new use rules: Not listed
	TSCA 5(a)2 - Proposed significant new use rules: Not listed
	TSCA 5(e) - Substances consent order: Not listed

US Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42): None known

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302): None Known

US state regulations California Prop 65	This product does not contain a chemical known to the defects, or other reproductive harm.	e State of California to cause cancer, birth
International regulations		
Country(s) or region	Inventory Name	On inventory list (yes/no)*
Canada	DSL/NDSL	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA 8b)	Yes

16. Other information, including date of preparation or last revision

Issue Date	12-May-2015	
Revision Date	-	
Version #	01	
HMIS Rating	Health: 1 Flammability: 0 Physical Hazards: 0	
Disclaimer	Oatey Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.	



SAFETY DATA SHEET

1. Identification

Product identifier	Oatey Plumber's Putty		
Other means of identification			
Product code	1705E		
Synonyms	Part Numbers: 31166, 31167, 31170, 31174, 48003, 48004		
Recommended use	Plumbing Mastic		
Recommended restrictions	Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.		
Manufacturer/Importer/Supplier/E	Distributor information		
Company Name	Oatey Co.		
Address	4700 West 160th St.		
	Cleveland, OH 44135		
Telephone	216-267-7100		
E-mail	info@oatev.com		
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)		
Emergency First Aid	1-877-740-5015		
Contact person	MSDS Coordinator		
2. Hazard(s) identification			
Physical hazards	Not classified.		
Health hazards	Not classified.		
OSHA defined hazards	Not classified.		
Label elements			
Hazard symbol	None.		
Signal word	None.		
Hazard statement	The mixture does not meet the criteria for classification.		
Precautionary statement			
Prevention	Observe good industrial hygiene practices.		
Response	Wash hands after handling.		
Storage	Store away from incompatible materials.		
Disposal	Dispose of waste and residues in accordance with local authority requirements.		
Hazard(s) not otherwise	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.		

classified (HNOC)

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%	
Limestone	1317-65-3	60-90	
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	5-30	
Crystalline silica (Quartz)	14808-60-7	<1	
Other components below reportable levels		9.85	

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
Skin contact	Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. If ingestion of a large amount does occur, call a poison control center immediately.
Most important symptoms/effects, acute and delayed	Coughing.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Use water spray to cool unopened containers.
Specific methods General fire hazards	Use standard firefighting procedures and consider the hazards of other involved materials. No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Stop the flow of material, if this is without risk. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places

Conditions for safe storage, including any incompatibilities

where dust is formed. Do not breathe dust. Avoid prolonged exposure. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	5 mg/m3	Mist.
		2000 mg/m3 500 ppm	
Limestone (CAS 1317-65-3)	PEL	5 mg/m3 15 mg/m3	Respirable fraction. Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Туре	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust.
		0.1 mg/m3	Respirable.
US. ACGIH Threshold Limit	Values		
Components	Туре	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to	o Chemical Hazards		
Components	Туре	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	1800 mg/m3	
,	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Limestone (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
ological limit values	No biological exposure limits noted for the ingredient(s).		
kposure guidelines	Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.		
opropriate engineering ontrols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.		
dividual protection measures,	such as personal protective equipmen	t	
Eye/face protection	Wear safety glasses with side shields (c	or goggles).	
Skin protection			
Hand protection	Wear appropriate chemical resistant gloves.		
Other	Wear suitable protective clothing.		
Respiratory protection	Use a particulate filter respirator for particulate concentrations exceeding the Occupational Exposure Limit.		
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.		
eneral hygiene onsiderations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.		

9. Physical and chemical properties

-	• •
Appearance	
Physical state	Solid.
Form	Putty.
Color	Off-white.
Odor	Slight.
Odor threshold	Not available.
рН	Not applicable
Melting point/freezing point	Not available.

Initial boiling point and boiling range	Not determined
Flash point	> 212.0 °F (> 100.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or expl	osive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	1.87
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	> 500000 cP
Other information	
VOC (Weight %)	20 g/l

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Acids. Fluorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure			
Inhalation	Prolonged inhalation may be harmful.		
Skin contact	No adverse effects due to skin contact are expected.		
Eye contact	Direct contact with eyes may cause temporary irritation.		
Ingestion	Expected to be a low ingestion hazard.		
Symptoms related to the physical, chemical and toxicological characteristics	Coughing.		
Information on toxicological effects			
Acute toxicity	Not available.		
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.		
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.		
Respiratory or skin sensitization			
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected to cause skin sensitization.		

Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) Risk of cancer cannot be excluded with prolonged exposure.		
IARC Monographs. Overall E	valuation of Carcinogenicity		
Crystalline silica (Quartz) (Distillates (petroleum), hyc (CAS 64742-52-5)	z) (CAS 14808-60-7)1 Carcinogenic to humans.nydrotreated heavy naphthenic3 Not classifiable as to carcinogenicity to humans.		
NIP Report on Carcinogens		Kanana Ta Da Ukuman Ormina nan	
OSHA Specifically Regulated	CAS 14808-60-7) Substances (29 CFR 1910.10	Nown To Be Human Carcinogen. 101-1050)	
Not listed.			
Reproductive toxicity	This product is not expected to	o cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not an aspiration hazard.		
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.		
Further information	This product has no known adverse effect on human health.		
12. Ecological information			
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.		
Persistence and degradability	No data is available on the degradability of this product.		
Bioaccumulative potential			
Mobility in soil	No data available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		
13. Disposal consideration	S		
Disposal instructions	Collect and reclaim or dispose	in sealed containers at licensed waste disposal site.	
Local disposal regulations	Dispose in accordance with all	applicable regulations.	
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.		

Waste from residues / unused
productsDispose of in accordance with local regulations. Empty containers or liners may retain some
product residues. This material and its container must be disposed of in a safe manner (see:
Disposal instructions).Contaminated packagingEmpty containers should be taken to an approved waste handling site for recycling or disposal.
Since emptied containers may retain product residue, follow label warnings even after container is

14. Transport information

DOT

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to
Annex II of MARPOL 73/78 and
the IBC CodeNot applicable.

emptied.

15. Regulatory information

US federal regulations This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) Not regulated. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not listed. CERCLA Hazardous Substance List (40 CFR 302.4) Not listed. Superfund Amendments and Reauthorization Act of 1986 (SARA) Hazard categories Immediate Hazard - No **Delayed Hazard - No** Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No SARA 302 Extremely hazardous substance Not listed SARA 311/312 Hazardous No chemical SARA 313 (TRI reporting) Not regulated. Other federal regulations Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Not regulated. Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) Not regulated. Safe Drinking Water Act Not regulated. (SDWA) US state regulations **US. Massachusetts RTK - Substance List** Crystalline silica (Quartz) (CAS 14808-60-7) Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Limestone (CAS 1317-65-3) US. New Jersey Worker and Community Right-to-Know Act Crystalline silica (Quartz) (CAS 14808-60-7) Limestone (CAS 1317-65-3) US. Pennsylvania Worker and Community Right-to-Know Law Crystalline silica (Quartz) (CAS 14808-60-7) Limestone (CAS 1317-65-3) **US. Rhode Island RTK** Not regulated. **US.** California Proposition 65 WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm. US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance Crystalline silica (Quartz) (CAS 14808-60-7) Methanol (CAS 67-56-1) International Inventories Country(s) or region Inventory name On inventory (yes/no)* United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes *A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision 22-April-2015

Issue date

Revision date Version # HMIS® ratings

NFPA ratings

01 Health: 0 Flammability: 0 Physical hazard: 0



Disclaimer

Oatey Co. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

SAFETY DATA SHEET

1. Identification

Product identifier	Oatey Purple Primer Cleaner
Other means of identification	
Product code	1401E
Synonyms	Part Numbers: 30780, 30783, 30796, 30768, 30806, 30769
Recommended use	Joining PVC Pipes
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/E	Distributor information
Company Name	Oatey Co.
Address	4700 West 160th St.
	Cleveland, OH 44135
Telephone	216-267-7100
E-mail	info@oatey.com
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)
Emergency First Aid	1-877-740-5015
Contact person	MSDS Coordinator

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
OSHA defined hazards	Not classified.	

OSHA defined hazards

Label elements



Signal word	Danger
Hazard statement	Highly flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear eye protection/face protection. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If swallowed: Immediately call a poison center/doctor. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. Rinse mouth. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

Supplemental information

Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Acetone	67-64-1	70-100
Cyclohexanone	108-94-1	1-5

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Call a physician or poison control center immediately. Do not induce vomiting. Aspiration may cause pulmonary edema and pneumonitis. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor. This product contains tetrahydrofuran that may form explosive organic peroxide when exposed to air or light or with age.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water.		
	Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.		
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.		
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.		
7. Handling and storage			
Precautions for safe handling	Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.		
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).		

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components		Туре			Value	
Acetone (CAS 67-64-1)		PEL			2400 mg/m3	
					1000 ppm	
Cyclohexanone (CAS		PEL			200 mg/m3	
108-94-1)						
					50 ppm	
US. ACGIH Threshold Li	imit Values					
Components		Туре			Value	
Acetone (CAS 67-64-1)		STEL			750 ppm	
		TWA			500 ppm	
Cyclohexanone (CAS 108-94-1)		STEL			50 ppm	
		TWA			20 ppm	
US. NIOSH: Pocket Guid	le to Chemical Haz	zards				
Components		Туре			Value	
Acetone (CAS 67-64-1)		TWA			590 mg/m3	
					250 ppm	
Cyclohexanone (CAS 108-94-1)		TWA			100 mg/m3	
					25 ppm	
ological limit values						
ACGIH Biological Expos	sure Indices					
Components	Value		Determinant	Specimen	Sampling Time	
Acetone (CAS 67-64-1)	50 mg/l		Acetone	Urine	*	

ACGIH Biological Exposure Indices

	Components	Value	Determinant	Specimen	Sampling Time
	Cyclohexanone (CAS 108-94-1)	80 mg/l	1,2-Cyclohexan ediol, with hydrolysis	Urine	*
		8 mg/l	Cyclohexanol, with hydrolysis	Urine	*
	* - For sampling details, plea	ase see the source docu	iment.		
Exp	oosure guidelines				
	US - California OELs: Skir	designation			
	Cyclohexanone (CAS 1	08-94-1)	Can be	absorbed thro	ugh the skin.
	US - Minnesota Haz Subs:	Skin designation appl	ies		
	Cyclohexanone (CAS 1	08-94-1)	Skin des	signation appli	es.
	US - Tennessee OELs: Sk	in designation			
	Cyclohexanone (CAS 1 US ACGIH Threshold Limi	08-94-1) <mark>t Values: Skin design</mark> a	tion	absorbed thro	ugh the skin.
	Cyclohexanone (CAS 1 US. NIOSH: Pocket Guide	08-94-1) to Chemical Hazards	Can be	absorbed thro	ugh the skin.
	Cyclohexanone (CAS 1	08-94-1)	Can be	absorbed thro	ugh the skin.
Apı cor	propriate engineering htrols	Explosion-proof gen changes per hour) s applicable, use proc maintain airborne le established, maintai shower must be ava	eral and local exhau hould be used. Ven ess enclosures, loca vels below recomme n airborne levels to ilable when handlin	ust ventilation. tilation rates sl al exhaust ven ended exposu an acceptable g this product.	Good general ventilation (typically 10 air nould be matched to conditions. If tilation, or other engineering controls to re limits. If exposure limits have not been level. Eye wash facilities and emergency
Ind	ividual protection measure	s, such as personal pr	otective equipmen	t	
	Eye/face protection	Chemical respirator	with organic vapor	cartridge and f	ull facepiece.
	Skin protection				
	Hand protection	Wear appropriate ch supplier.	nemical resistant glo	oves. Suitable	gloves can be recommended by the glove
	Other	Wear appropriate ch	nemical resistant clo	thing.	
	Respiratory protection	Chemical respirator	with organic vapor	cartridge and f	ull facepiece.
	Thermal hazards	Wear appropriate th	ermal protective clo	thing, when ne	cessary.
Gei cor	neral hygiene nsiderations	When using, do not as washing after har wash work clothing a	eat, drink or smoke ndling the material a and protective equip	Always obser and before eati oment to remov	ve good personal hygiene measures, such ng, drinking, and/or smoking. Routinely ve contaminants.

9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Translucent liquid.
Color	Purple
Odor	Solvent.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	133 °F (56.11 °C)
Flash point	-4.0 °F (-20.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or expl	osive limits
Flammability limit - lower (%)	Not available.

Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	145 mm Hg @ 20 C
Vapor density	2.5
Relative density	0.79 +/- 0.02
Solubility(ies)	
Solubility (water)	Miscible
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	< 10 cP
Other information	
Bulk density	7 lb/gal
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
VOC (Weight %)	180 g/I SQACMD Method 24

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Ammonia. Amines. Isocyanates. Caustics.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May be fatal if swallowed and enters airways. Headache. Nausea, vomiting. May cause irritation to the respiratory system. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Ingestion	May be fatal if swallowed and enters airways. Harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. May cause redness and pain.

Information on toxicological effects

Acute toxicity

May be fatal i	if swallowed and	enters airways.	Narcotic effects.	May c	ause respiratory irr	itation.
,		,				

Components	Species	Test Results	
Acetone (CAS 67-64-1)			
Acute			
Dermal LD50	Rabbit	20 ml/kg	
Inhalation LC50	Rat	50 mg/l, 8 Hours	

Components	Species		Test Results	
Oral				
LD50	Rat		5800 mg/kg	
Cyclohexanone (CAS 108-94-1)				
Acute				
Dermal				
LD50	Rabbit		948 mg/kg	
Inhalation			0000 41	
LC50	Rat		8000 ppm, 4 hours	
Oral	Det		1540 malka	
LD50	Rat		1540 mg/kg	
* Estimates for product may b	e based on add	itional component data not shown.		
Skin corrosion/irritation	Causes skin i	rritation.		
Serious eye damage/eye irritation	Causes serior	us eye irritation.		
Respiratory or skin sensitization	n			
Respiratory sensitization	Not a respirat	ory sensitizer.		
Skin sensitization	This product i	s not expected to cause skin sensitization	on.	
Germ cell mutagenicity	No data availa mutagenic or	able to indicate product or any compone genotoxic.	nts present at greater than 0.1% are	
Carcinogenicity	This product i	s not considered to be a carcinogen by	IARC, ACGIH, NTP, or OSHA.	
IARC Monographs. Overall	Evaluation of C	Carcinogenicity		
Cyclohexanone (CAS 10	8-94-1)	3 Not classifiable as t	o carcinogenicity to humans.	
OSHA Specifically Regulate	ed Substances	(29 CFR 1910.1001-1050)		
Not listed.				
Reproductive toxicity	This product i	This product is not expected to cause reproductive or developmental effects.		
Specific target organ toxicity - single exposure	Narcotic effec	Narcotic effects. May cause drowsiness and dizziness. Respiratory tract irritation.		
Specific target organ toxicity - repeated exposure	Not classified			
Aspiration hazard	May be fatal i	f swallowed and enters airways.		
Chronic effects	Prolonged inh	alation may be harmful.		
12 Ecological information	-			
	The second set is			
Ecotoxicity	possibility tha	s not classified as environmentally haza t large or frequent spills can have a harr	nfollor damaging effect on the environment.	
Components	1	Species	Test Results	
Acetone (CAS 67-64-1)		· ·		
Aquatic				
Fish	LC50	Fathead minnow (Pimephales promela	as) > 100 mg/l, 96 hours	
Cyclohexanone (CAS 108-94	-1)			
Aquatic				
Fish	LC50	Fathead minnow (Pimephales promela	as) 481 - 578 mg/l, 96 hours	
* Entimetra fama da da da				
* Estimates for product may b	be based on add	itional component data not shown.	at .	
ersistence and degradability into data is available on the degradability of this product.				
Bioaccumulative potential				
Partition coefficient n-octar Acetone (CAS 67-64-1)	101 / water (log	KOW) -0 24		
Cyclohexanone (CAS 108-94	-1)	0.81		
Mobility in soil	, No data available.			
Other adverse effects	No other adve potential, end	erse environmental effects (e.g. ozone d ocrine disruption, global warming poten	epletion, photochemical ozone creation ial) are expected from this component.	

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT	
UN number	UN1993
UN proper shipping name	Flammable liquids, n.o.s. (Acetone RQ = 5128 LBS)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	IB2, T7, TP1, TP8, TP28
Packaging exceptions	150
Packaging non bulk	202
Packaging bulk	242
ΙΑΤΑ	
UN number	UN1993
UN proper shipping name	Flammable liquid, n.o.s. (Acetone)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	No.
ERG Code	3H
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
IMDG	
UN number	UN1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (Acetone)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	11
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to	Not established.
Annex II of MARPOL 73/78 and	

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication
-	Standard, 29 CFR 1910.1200.
	All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Exp	ort Notification (40 CFR 707, S	Subpt. D)	
Not regulated. OSHA Specifically Regu	lated Substances (29 CFR 191	0.1001-1050)	
Not listed.	ostance List (40 CFR 302 4)		
Acetone (CAS 67-64- Cyclobexanone (CAS	Acetone (CAS 67-64-1)		
Superfund Amendments and	Regutherization Act of 1986	(SARA)	
Hazard categories	Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No		
SARA 302 Extremely ha	zardous substance		
Not listed.			
SARA 311/312 Hazardou chemical	s No		
SARA 313 (TRI reporting Not regulated.)		
Other federal regulations			
Clean Air Act (CAA) Sec	tion 112 Hazardous Air Polluta	ants (HAPs) List	
Not regulated. Clean Air Act (CAA) Sec	tion 112(r) Accidental Release	Prevention (40 CFR 68.130)	
Not regulated.			
Safe Drinking Water Act (SDWA)	Not regulated.		
Drug Enforcement A Chemical Code Num	dministration (DEA). List 2, E	ssential Chemicals (21 CFR 1310.02(b)) and 1310.04(f)(2) and
Acetone (CAS 67	7-64-1)	6532 2 Exempt Chemical Mixtures (21 CER :	1310 12(c))
Acetone (CAS 67 DEA Exempt Chemi	7-64-1) cal Mixtures Code Number	35 %WV	1010.12(0))
Acetone (CAS 67	/-64-1)	6532	
US state regulations	,		
US. Massachusetts RTK	- Substance List		
Acetone (CAS 67-64- Cyclohexanone (CAS	1) 108-94-1) and Community Pight-to-Knov	w Act	
Acetone (CAS 67-64-			
Cyclohexanone (CAS US. Pennsylvania Worke	, 108-94-1) r and Community Right-to-Kn	low Law	
Acetone (CAS 67-64- Cyclohexanone (CAS US. Rhode Island RTK	1) 108-94-1)		
Acetone (CAS 67-64- Cyclohexanone (CAS	1) 108-94-1)		
US. California Propositio California Safe Drinki any chemicals curren	on 65 ng Water and Toxic Enforcemen tly listed as carcinogens or repro	nt Act of 1986 (Proposition 65): This mate oductive toxins.	rial is not known to contain
International Inventories	- · ·		
Country(s) or region	Inventory name	emical Substances (AICS)	On inventory (yes/no)* ∨≏⊂
Canada	Domestic Substances List	(DSL)	763 Voc
Canada	Non-Domestic Substances	s List (NDSL)	No
China	Inventory of Existing Chen	nical Substances in China (IECSC)	
Unina			103

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	27-May-2015
Revision date	-
Version #	01
HMIS® ratings	Health: 2 Flammability: 3 Physical hazard: 0
Disclaimer	The information in the sheet was written based on the best knowledge and experience currently available. Oatey Co. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.



SAFETY DATA SHEET

1. Identification	
Product identifier	Oatey Silicone Sealant – White or Clear
Other means of identification	
Product code	
Synonyms	Part Numbers: Clear – 30236, White - 30237
Recommended use	Sealant for use around tubs, sinks and other plumbing applications.
Recommended restrictions	Do not use on applications where product will be submerged under water.
Manufacturer/Importer/Supplier	Distributor information
Company Name	Oatey Inc.
Address	4700 West 160th Street
	Cleveland, OH 44135
Telephone	216-267-7100
E-mail	info@oatey.com
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)
Emergency First Aid	1-877-740-5015
Contact person	MSDS Coordinator
2. Hazard(s) identification	
Physical hazards	Not Classified.
Health hazards	Not Classified.
OSHA defined hazards	Not Classified.
Label elements	
Hazard symbol	None.
Signal word	None.
Hazard statement	This product was determined to be non-hazardous.
Precautionary statement	
Prevention	Use outdoors or in a well ventilated area.
Response	Not applicable.
Storage	Not applicable.
Disposal	Not applicable.
Hazard(s) not otherwise classified (HNOC)	None known.

3. Composition/information on ingredients

Mixtures

Inhalation

Chemical name	CAS number	%
Silicon Dioxide	7631-86-9	5 - 10
Distillates (petroleum), hydrotreated middle	64742-46-7	5 - 10
Titanium Dioxide (White Sealant Only)	13463-67-7	0 – 5
Dimethyl siloxane, hydroxyl terminated	70131-67-8	70 - 90

4. First-aid measures

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Ingestion	Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Skin or eye irritation.
Indication of immediate medical attention and special treatment needed.	Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
General information	Note to physician, treat symptomatically.
5. Fire-fighting measures	
Cuitable autin mulable a media	
Suitable extinguishing media	Use dry chemical, CO2, alcohol-resistant foam or water spray (fog).
Unsuitable extinguishing media	Use dry chemical, CO2, alcohol-resistant foam or water spray (fog). water jet
Unsuitable extinguishing media Specific hazards arising from the chemical	Use dry chemical, CO2, alcohol-resistant foam or water spray (fog). water jet No specific fire or explosion hazard.
Unsuitable extinguishing media Specific hazards arising from the chemical Special protective equipment and precautions for firefighters	Use dry chemical, CO2, alcohol-resistant foam or water spray (fog). water jet No specific fire or explosion hazard. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Unsuitable extinguishing media Unsuitable extinguishing media Specific hazards arising from the chemical Special protective equipment and precautions for firefighters Fire fighting equipment/instructions	Use dry chemical, CO2, alcohol-resistant foam or water spray (fog). water jet No specific fire or explosion hazard. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Use water spray to keep fire-exposed containers cool. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Unsuitable extinguishing media Specific hazards arising from the chemical Special protective equipment and precautions for firefighters Fire fighting equipment/instructions	Use dry chemical, CO2, alcohol-resistant foam or water spray (fog). water jet No specific fire or explosion hazard. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Use water spray to keep fire-exposed containers cool. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. None

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Methods and materials for containment and cleaning up	Large Spills: Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal. Small Spills: Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
7. Handling and storage	
Precautions for safe handling	Put on appropriate personal protective equipment (see section 8 of SDS). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Keep container tightly closed and sealed until ready for use.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Туре	Value
Petroleum Distillate	TWA	5 mg/m3
Titanium Dioxide	TWA	10 mg/m3

US OSHA Permissible Exposure Limits

Components	Туре	Value
Petroleum Distillate	TWA	5 mg/m3
Titanium Dioxide	TWA	15 mg/m3
Silicone Dioxide	TWA	80 mg/m3

Biological limit values	No Biological limits.
Appropriate engineering controls	No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
Individual protection measures,	such as personal protective equipment
Eye/face protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.
Skin protection	
Hand	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Other	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Thermal hazards	None.
General hygiene considerations	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

9. Physical and chemical properties

Solid.			
Paste			
White or translucent.			
Acetic acid/vinegar smell			
Not available.			
Not applicable.			
Not applicable.			
Not determined			
> 199 °F (> 93.3 °C)			
Upper/lower flammability or explosive limits			
Not available			
Not applicable			

Oatey Silicone Sealant White and Clear

SDS # Version #: 01 Revision date: Issue date: 12-May-2015

Vapor density	Not applicable
Relative density	1.04 – 1.09
Solubility(ies)	
Solubility (water)	Not available
Partition coefficient	
(n-octanol/water)	Not available
Auto-ignition temperature	Not applicable
Decomposition temperature	Not available
Viscosity	Not available
Other information	
VOC (Weight %)	28 g/L (< 3.0% by weight)

10. Stability and reactivity

Reactivity	Stable under normal conditions.
Chemical stability	The product is stable.
Possibility of hazardous reaction	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	No specific data.
Incompatible materials	No specific data.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Information on likely routes of e	xposure
Inhalation	Acute Toxicity estimates: > 10 mg/l
	Exposure time: 4 h
	Test atmosphere: dust/mist
	Method: Calculation.
Skin contact	No known significant effects or critical hazards.
Eye contact	No known significant effects or critical hazards.
Ingestion	No known significant effects or critical hazards.
Symptoms related to the physical, chemical and toxicological characteristics	No specific data.
Information on likely routes of e Acute Toxicity	xposure

, , , , , , , , , , , , , , , , , , ,			
Components	Species	Results	
Silicone Dioxide			
Acute Oral Toxicity	Rat LD(50)	3,300 mg/kg	
Acute Inhalation Toxicity	Rat LD(50)	2.08 mg/l	
Distillates (petroleum			

Skin corrosion/irritation	Not determined.	
Serious eye damage/eye irritation	Not determined.	
Respiratory or skin sensitization Respiratory sensitization	Not considered a respiratory irritant	
Skin sensitization	This product is not expected to cause skin irritation.	
Germ cell mutagenicity	No specific data	
Carcinogenicity	Sufficient evidence of carcinogenicity in inhalation studies with animals for titanium dioxide exist. However, due to the titanium dioxide being inextricably bound in the silicone matrix, the likelihood of exposure is minimal.	
IARC	Titanium Dioxide – 13463-67-7 Group 2B: Possibly carcinogenic to humans.	
OSHA	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcino- gen by OSHA.	
NTP	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcino- gen by OSHA.	

Reproductive toxicity	No known significant effects or cri	tical hazards.			
Specific target organ toxicity	Not Clossified				
Single exposure Repeated exposure	Not Classified.	Not Classified.			
Aspiration Hazard	Contains Distillates (petroleum), h likely hood of aspirating the produ	Contains Distillates (petroleum), hydrotreated – Which is a category 1 Aspiration Hazard. The likely bood of aspirating the product in this form is very low due to the high viscosity.			
Chronic effects	Not Classified.				
Further information					
12. Ecological informati	on				
Ecotoxicity					
Product/ingredient name	Results	Species	Exposure		
Petroleum Distillates					
	Acute LC50 2,900 μg/l Fresh water	Fish - Rainbow trout,Donaldson trout	96 h		
	Acute LC50 2,200 µg/l Fresh water	Fish - Bluegill	96 h		
Persistence and degradabilit	y Not Available.				
Bio accumulative potential	Not Available.				

No known significant effects of critical hazards.

13. Disposal considerations

Other adverse effects

Disp	osal instructions	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Loca	l disposal regulations	Not Applicable
Haza	rdous waste code	Not Applicable
14	Fransportation informat	ion
DOT		Not Regulated
	UN number	
	UN Proper Shipping Name	
	Transportation Hazard classes	
	Packing group	
ΙΑΤΑ		Not Regulated
	UN number	
	UN Proper Shipping Name	
	Transportation Hazard classes	
	Packing group	
IMDO	ì	Not Regulated
	UN number	
	UN Proper Shipping Name	
	Transportation Hazard classes	
	Packing group	
	Environmental hazards	
Onter	Ciliaana Caalant White and Clear	

15. Regulatory information

U.S. Federal regulations	TSCA 12(b) - Chemical export notification: None required. TSCA 5(a)2 - Final significant new use rules: Not listed TSCA 5(a)2 - Proposed significant new use rules: Not listed TSCA 5(e) - Substances consent order: Not listed	
SARA 311/312		
Classification	Not applicable	
US state regulations California Prop 65	This product does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.	
Canada		
WHMIS (Canada)	Not classified.	
International regulations		
Country(s) or region	Inventory Name	On inventory list (yes/no)*
Canada	DSL/NDSL	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA 8b)	Yes
16. Other information, incl	uding date of preparation or last revision	
Issue Date	12-May-2015	
Revision Date	-	
Version #	01	
HMIS Rating	Health: 1 Flammability: 1 Physical Hazards: 0	
Disclaimer	Oatey Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.	



SAFETY DATA SHEET

1. Identification		
Product identifier	Oatey Tub-N-Tile Ultra Clear Sealant	
Other means of identification		
Product code		
Synonyms	Part Numbers: 30235	
Recommended use	Caulk and sealant for use around tubs, sinks and other plumbing application	IS.
Recommended restrictions	Do not use on applications where product will be submerged under water.	
Manufacturer/Importer/Supplier/	Distributor information	
Company Name	Oatey Inc.	
Address	4700 West 160th Street	
	Cleveland, OH 44135	
Telephone	216-267-7100	
E-mail	info@oatey.com	
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)	
Emergency First Aid	1-877-740-5015	
Contact person	MSDS Coordinator	
2. Hazard(s) identification		
Physical hazards	Not Classified.	
Health hazards	Acute Oral Toxicity	Cat 5
	Eye Irritation	Cat 2B
	Skin Irritation	Cat 3
OSHA defined hazards	Not Classified.	
Label elements		
Hazard symbol	None.	
Signal word	Warning	
Hazard statement	May be harmful if swallowed. Causes mild skin irritation. Causes eye irrita	ation
Precautionary statement		
Prevention	Wash Thoroughly after handling. Wear protective gloves and eye protection.	
Response	If skin irritation occurs: Get medical advice. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.	
Storage	Not applicable.	
Disposal	Not applicable.	
Hazard(s) not otherwise classified (HNOC)	Uncured product is irritating to eyes, skin and respiratory system.	

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Acrylic Emulsion	Mixture	75 - 95
Acrylic Thickener	Mixture	1 - 5
Propylene Glycol	57-55-6	1 - 2
Petroleum Distillate	64742-48-9	0.1 - 1
Non Hazardous Ingredients	Mixture	< 5%

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Ingestion	Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Skin or eye irritation.
Indication of immediate medical attention and special treatment needed.	Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
General information	Note to physician, treat symptomatically.
5. Fire-fighting measures	
Suitable extinguishing media	Use dry chemical, CO2, alcohol-resistant foam or water spray (fog).
Unsuitable extinguishing media	water jet
Specific hazards arising from the chemical	No specific fire or explosion hazard.
Special protective equipment and precautions for firefighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Fire fighting equipment/instructions	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Use water spray to keep fire-exposed containers cool. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Specific methods	None

Specific methods General fire hazards

6. Accidental release measures

None

Personal precautions, protective equipment and emergency procedures	Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Methods and materials for containment and cleaning up	Large Spills: Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal. Small Spills: Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
7. Handling and storage	
Precautions for safe handling	Put on appropriate personal protective equipment (see section 8 of SDS). Eating, drinking and

	smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash bands and face before eating, drinking and smoking. See also Section 8
Conditions for safe storage,	for additional information on hygiene measures. Store in accordance with local regulations. Store in original container protected from direct
	sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10
Oatey Tun-N-Tile Ultra Clear Sealant	SDS US

of SDS) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Туре	Value
Petroleum Distillate	TWA	5 mg/m3
US OSHA Permissible Exposure Limits		
Components	Туре	Value
Petroleum Distillate	TWA	5 mg/m3

Biological limit values	No Biological limits.
Appropriate engineering controls	No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
Individual protection measures,	such as personal protective equipment
Eye/face protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.
Skin protection	
Hand	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Other	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Thermal hazards	None.
General hygiene considerations	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

9. Physical and chemical properties

Appearance	
Physical state	Solid.
Form	Paste
Color	Applies white, dries clear.
Odor	Mild Acrylic, slight ammonia
Odor threshold	Not available.
рН	7 - 10
Melting point/freezing point	Not applicable.
Initial boiling point and boiling	Not determined
range	
Flash point	> 199 °F (> 93.3 °C)
Upper/lower flammability or explo	sive limits
Flammability limit – lower (%)	Not available
Flammability limit – upper (%)	Not available
Explosive limit - lower (%)	Not available
Explosive limit - upper (%)	Not available
Vapor pressure	Not applicable
Vapor density	Not applicable
Relative density	1.04 – 1.08

Oatey Tun-N-Tile Ultra Clear Sealant

Solubility(ies)	
Solubility (water)	Not available
Partition coefficient	
(n-octanol/water)	Not available
Auto-ignition temperature	Not applicable
Decomposition temperature	Not available
Viscosity	Not available
Other information	
VOC (Weight %)	0.5% or 10 g/L

10. Stability and reactivity

Reactivity	Stable under normal conditions.
Chemical stability	The product is stable.
Possibility of hazardous reaction	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	No specific data.
Incompatible materials	No specific data.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

InhalationNo known significant effects or critical hazards.Skin contactNo known significant effects or critical hazards.Eye contactNo known significant effects or critical hazards.IngestionNo known significant effects or critical hazards.Symptoms related to the physical, chemical and toxicological characteristicsNo specific data.Information on likely routes of exposure Acute ToxicityNo known significant effects or critical hazards.	Information on likely routes of exposure		
Skin contactNo known significant effects or critical hazards.Eye contactNo known significant effects or critical hazards.IngestionNo known significant effects or critical hazards.Symptoms related to the physical, chemical and toxicological characteristicsNo specific data.Information on likely routes of exposure Acute ToxicitySuppose of exposure Acute Toxicity	Inhalation	No known significant effects or critical hazards.	
Eye contactNo known significant effects or critical hazards.IngestionNo known significant effects or critical hazards.Symptoms related to the physical, chemical and toxicological characteristicsNo specific data.Information on likely routes of exposure Acute ToxicitySecond Second Sec	Skin contact	No known significant effects or critical hazards.	
IngestionNo known significant effects or critical hazards.Symptoms related to the physical, chemical and toxicological characteristicsNo specific data.Information on likely routes of exposure Acute ToxicityAcute Toxicity	Eye contact	No known significant effects or critical hazards.	
Symptoms related to the No specific data. physical, chemical and Information on likely routes of exposure Acute Toxicity No specific data.	Ingestion	No known significant effects or critical hazards.	
Information on likely routes of exposure Acute Toxicity	bymptoms related to the No specific data. hysical, chemical and oxicological characteristics		
	Information on likely routes of exposure Acute Toxicity		
Components Species Results	Components	Species	Results

Skin corrosion/irritation	Not determined.		
Serious eye damage/eye irritation	Not determined.		
Respiratory or skin sensitization Respiratory sensitization	on Not considered a respiratory irritant		
Skin sensitization	This product is not expected to cause	se skin irritation.	
Germ cell mutagenicity	No specific data		
Carcinogenicity	No known significant effects or critic	cal hazards.	
Reproductive toxicity	No known significant effects or critic	cal hazards.	
Specific target organ toxicity			
Single exposure Repeated exposure	Not Classified. Not Classified.		
Aspiration Hazard	Contains Distillates (petroleum), hyd likely hood of aspirating the product	drotreated – Which is a category 1 A t in this form is very low due to the hi	spiration Hazard. The gh viscosity.
Chronic effects	Not Classified.	2	0 7
Further information			
12. Ecological informatio	n		
Ecotoxicity			
Product/ingredient name F	Results	Species	Exposure
Petroleum Distillates			
A	Acute LC50 2,900 µg/l Fresh water	Fish - Rainbow trout, Donaldson t	rout 96 h

96 h

Persistence and degradability	Not Available.
Bio accumulative potential	Not Available.
Mobility in soil	Not available.
Other adverse effects	No known significant effects of critical hazards.
Other adverse effects	No known significant effects of critical hazards.

13. Disposal considerations

Disposal instruction	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Local disposal regul	ations Not Applicable
	de Not Applicable
14. Transportatio	on information
DOT	Not Regulated
UN number	
UN Proper Shi Transportation classes	oping Name Hazard
Packing group	
	Not Regulated
UN number	
Transportation classes	Hazard
Packing group	
IMDG	Not Regulated
UN number	
UN Proper Shij Transportation classes Packing group Environmental	oping Name Hazard hazards
Marine pollu	ntant
15. Regulatory ir	formation
U.S. Federal regulati	ons TSCA 12(b) - Chemical export notification: None required. TSCA 5(a)2 - Final significant new use rules: Not listed TSCA 5(a)2 - Proposed significant new use rules: Not listed TSCA 5(e) - Substances consent order: Not listed
SARA 311/312	
Classification	Not applicable
US state regulations California Prop 65	This product does not contain any Prop 65 chemicals.

Canada		
WHMIS (Canada)	Not classified.	
International regulations		
Country(s) or region	Inventory Name	On inventory list (yes/no)*
Canada	DSL/NDSL	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA 8b)	Yes
16. Other information, inclu	iding date of preparation or last revision	
Issue Date	12-May-2015	
Revision Date	-	
Version #	01	
HMIS Rating	Health: 1 Flammability: 1 Physical Hazards: 0	
Disclaimer	Oatey Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.	



SAFETY DATA SHEET

1. Identification

Product identifier	PVC Regular Clear Cement	
Other means of identification		
Product code	1100E	
Synonyms	Part Numbers: 31012, 31013, 31014, 31015, 3	1016, 31958, 31959, 31960, 31961
Recommended use	Joining PVC Pipes	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/I	Distributor information	
Company Name	Oatey Co.	
Address	4700 West 160th St.	
	Cleveland, OH 44135	
Telephone	216-267-7100	
E-mail	info@oatey.com	
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)	
Emergency First Aid	1-877-740-5015	
Contact person	MSDS Coordinator	
2. Hazard(s) identification		
Physical hazards	Flammable liquids	Category 2
Llealth hazarda	A outo tovicity, and	Cotogon/ 4

1 • • • • • • • •	1	5 ,
Health hazards	Acute toxicity, oral	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
OSHA defined hazards	Not classified.	
Label elements		
Signal word	Danger	
Hazard statement	Highly flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness.	
Precautionary statement		
Prevention	Keep away from heat/sparks/open flames/hot closed. Ground/bond container and receiving e electrical/ventilating/lighting equipment. Use of measures against static discharge. Avoid brea handling. Do not eat, drink or smoke when usin well-ventilated area. Wear protective gloves/pr	surfaces No smoking. Keep container tightly equipment. Use explosion-proof nly non-sparking tools. Take precautionary thing mist or vapor. Wash thoroughly after ng this product. Use only outdoors or in a rotective clothing/eye protection/face protection.
Response	If swallowed: Immediately call a poison center, contaminated clothing. Rinse skin with water/s keep comfortable for breathing. If in eyes: Rins Remove contact lenses, if present and easy to you feel unwell. Rinse mouth. Do NOT induce advice/attention. If eye irritation persists: Get n clothing and wash before reuse. In case of fire	/doctor. If on skin (or hair): Take off immediately all shower. If inhaled: Remove person to fresh air and se cautiously with water for several minutes. o do. Continue rinsing. Call a poison center/doctor if vomiting. If skin irritation occurs: Get medical nedical advice/attention. Take off contaminated s: Use appropriate media to extinguish.
DVC Begular Clear Comont		SDS 11

Storage

Disposal Hazard(s) not otherwise classified (HNOC)

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May form explosive peroxides. Contains a chemical classified by the US EPA as a suspected possible carcinogen.

Supplemental information

Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Methyl ethyl ketone	78-93-3	25-40
Cyclohexanone	108-94-1	10-25
Furan, Tetrahydro-	109-99-9	10-25
Acetone	67-64-1	5-15
Polyvinyl chloride	9002-86-2	5-15

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Take off immediately all contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.
Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.
Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Skin irritation. May cause redness and pain.
Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).
Do not use water jet as an extinguisher, as this will spread the fire.
Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Use standard firefighting procedures and consider the hazards of other involved materials.
Highly flammable liquid and vapor. This product contains tetrahydrofuran that may form explosive organic peroxide when exposed to air or light or with age.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water.
	Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Туре	Value
Polyvinyl chloride (CAS	STEL	5 ppm
0002 00 2,	TWA	1 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
Cyclohexanone (CAS 108-94-1)	PEL	200 mg/m3	
		50 ppm	
Furan, Tetrahydro- (CAS 109-99-9)	PEL	590 mg/m3	
		200 ppm	
Methyl ethyl ketone (CAS 78-93-3)	PEL	590 mg/m3	
		200 ppm	
Polyvinyl chloride (CAS 9002-86-2)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

US. ACGIH Threshold Limit Values

Components	Туре	Value	Form
Acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
Cyclohexanone (CAS 108-94-1)	STEL	50 ppm	
	TWA	20 ppm	
Furan, Tetrahydro- (CAS 109-99-9)	STEL	100 ppm	
	TWA	50 ppm	
Methyl ethyl ketone (CAS 78-93-3)	STEL	300 ppm	
	TWA	200 ppm	
Polyvinyl chloride (CAS 9002-86-2)	TWA	1 mg/m3	Respirable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Туре	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
		250 ppm	
Cyclohexanone (CAS 108-94-1)	TWA	100 mg/m3	
		25 ppm	
Furan, Tetrahydro- (CAS 109-99-9)	STEL	735 mg/m3	
		250 ppm	
	TWA	590 mg/m3	
		200 ppm	
Methyl ethyl ketone (CAS 78-93-3)	STEL	885 mg/m3	
		300 ppm	
	TWA	590 mg/m3	
		200 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time	
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*	
Cyclohexanone (CAS 108-94-1)	80 mg/l	1,2-Cyclohexan ediol, with hydrolysis	Urine	*	
	8 mg/l	Cyclohexanol, with hydrolysis	Urine	*	
Furan, Tetrahydro- (CAS 109-99-9)	2 mg/l	Tetrahydrofura n	Urine	*	
Methyl ethyl ketone (CAS 78-93-3)	2 mg/l	MEK	Urine	*	

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation	
Cyclohexanone (CAS 108-94-1)	Can be absorbed through the skin.
US - Minnesota Haz Subs: Skin designation applies	
Cyclohexanone (CAS 108-94-1)	Skin designation applies.
US - Tennessee OELs: Skin designation	
Cyclohexanone (CAS 108-94-1)	Can be absorbed through the skin.
US ACGIH Threshold Limit Values: Skin designation	
Cyclohexanone (CAS 108-94-1)	Can be absorbed through the skin.
Furan, Tetrahydro- (CAS 109-99-9)	Can be absorbed through the skin.
US. NIOSH: Pocket Guide to Chemical Hazards	
Cyclohexanone (CAS 108-94-1)	Can be absorbed through the skin.

Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.
Individual protection measure	s, such as personal protective equipment
Eye/face protection	Face shield is recommended. Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves.
Other	Wear appropriate chemical resistant clothing.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance			
Physical state	Liquid.		
Form	Translucent liquid.		
Color	Clear.		
Odor	Solvent.		
Odor threshold	Not available.		
рН	Not available.		
Melting point/freezing point	Not available.		
Initial boiling point and boiling range	151 °F (66.11 °C)		
Flash point	-4.0 °F (-20.0 °C)		
Evaporation rate	5.5 - 8		
Flammability (solid, gas)	Not available.		
Upper/lower flammability or explosive limits			
Flammability limit - lower (%)	1.8		
Flammability limit - upper (%)	11.8		
Explosive limit - lower (%)	Not available.		
Explosive limit - upper (%)	Not available.		
Vapor pressure	145 mm Hg @ 20 C		
Vapor density	2.5		
Relative density	0.9 +/- 0.02		
Solubility(ies)			
Solubility (water)	Negligible		
Partition coefficient (n-octanol/water)	Not available.		
Auto-ignition temperature	Not available.		
Decomposition temperature	Not available.		
Viscosity	80 - 500 cP		
Other information			
VOC (Weight %)	<510 g/l SCAQMD 1168/M316A		

10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Ammonia. Amines. Isocyanates. Caustics.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May be fatal if swallowed and enters airways. Headache. Nausea, vomiting. May cause irritation to the respiratory system. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Prolonged inhalation may be harmful.	
Skin contact	Causes skin irritation.	
Eye contact	Causes serious eye irritation.	
Ingestion	May be fatal if swallowed and enters airways. Harmful if swallowed. Harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.	
Symptoms related to the physical, chemical and toxicological characteristics	Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.	

Information on toxicological effects

Acute toxicity	May be fatal if swallowed and enters airways. Narcotic effects. May cause respiratory irritation.		
Components	Species	Test Results	
Acetone (CAS 67-64-1)			
Acute			
Dermal			
LD50	Rabbit	20 ml/kg	
Inhalation			
LC50	Rat	50 mg/l, 8 Hours	
Oral			
LD50	Rat	5800 mg/kg	
Cyclohexanone (CAS 108-94-1)			
Acute			
Dermal			
LD50	Rabbit	948 mg/kg	
Inhalation			
LC50	Rat	8000 ppm, 4 hours	
Oral			
LD50	Rat	1540 mg/kg	
* Estimates for product may	be based on additional component data no	t shown.	
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye irritation	Causes serious eye irritation.		
Respiratory or skin sensitizati	on		
Respiratory sensitization	Not available.		
Skin sensitization	This product is not expected to cause s	kin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		

Carcinogenicity

In 2012 USEPA Integrated Risk Information System (IRIS) reviewed a two species inhalation lifetime study on THF conducted by NTP (1998). Male rats developed renal tumors and female mice developed liver tumors while neither the female rats nor the male mice showed similar results. Because the carcinogenic mechanisms could not be identified clearly in either species for either tumor, the EPA determined that the male rat and female mouse findings are relevant to the assessment of carcinogenic potential in humans. Therefore, the IRIS review concludes that these data in aggregate indicate that there is "suggestive evidence of carcinogenic potential" following exposure to THF by all routes of exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Cyclohexanone (CAS 108- Polyvinyl chloride (CAS 90 OSHA Specifically Regulated	94-1) 02-86-2) Substances (29 CFR 1910.10	3 Not classifiable as to carcinogenicity to humans. 3 Not classifiable as to carcinogenicity to humans. 01-1050)
Polyvinyl chloride (CAS 90	02-86-2)	Cancer
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Narcotic effects. May cause drowsiness and dizziness. Respiratory tract irritation.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	May be fatal if swallowed and enters airways.	
Chronic effects	Prolonged inhalation may be harmful.	

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results	
Acetone (CAS 67-64	-1)			
Aquatic				
Fish	LC50	Fathead minnow (Pimephales p	promelas) > 100 mg/l, 96 hours	
Cyclohexanone (CAS	S 108-94-1)			
Aquatic				
Fish	LC50	Fathead minnow (Pimephales p	promelas) 481 - 578 mg/l, 96 hours	

* Estimates for product may be based on additional component data not shown.

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential	No data available.	
Partition coefficient n-octa	nol / water (log Kow)	
Acetone (CAS 67-64-1)		-0.24
Cyclohexanone (CAS 108-94	4-1)	0.81
Furan, Tetrahydro- (CAS 109	9-99-9)	0.46
Methyl ethyl ketone (CAS 78	-93-3)	0.29

Mobility in soil No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT	
UN number	UN1133
UN proper shipping name	Adhesives
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	11
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	T11, TP1, TP8, TP27
Packaging exceptions	150
Packaging non bulk	201
Packaging bulk	243
ΙΑΤΑ	
UN number	UN1133
UN proper shipping name	Adhesives
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	11
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
IMDG	
UN number	UN1133
UN proper shipping name	ADHESIVES
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-D
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to	Not available.
Annex II of MARPOL 73/78 and	
the IBC Code	

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Polyvinyl chloride (CAS 9002-86-2)	Cancer
	Central nervous system
	Liver
	Blood
	Flammability
CERCLA Hazardous Substance List (40 CFR 302.4)	
Acetone (CAS 67-64-1)	LISTED
Cyclohexanone (CAS 108-94-1)	LISTED
Furan, Tetrahydro- (CAS 109-99-9)	LISTED
Methyl ethyl ketone (CAS 78-93-3)	LISTED

Superfu	Ind Amendments and Rea	uthorization Act of 1986 (SAF	RA)	
Haz	zard categories	Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No		
SA	RA 302 Extremely hazardo	ous substance		
	Not listed.			
SAI che	RA 311/312 Hazardous emical	No		
SA	RA 313 (TRI reporting) Not regulated.			
Other fe	ederal regulations			
Cle	an Air Act (CAA) Section	112 Hazardous Air Pollutants	(HAPs) List	
Cle	Not regulated. an Air Act (CAA) Section	112(r) Accidental Release Pre	vention (40 CFR 68.130)	
Saf (SD	e Drinking Water Act	Not regulated.		
	Drug Enforcement Admin Chemical Code Number	nistration (DEA). List 2, Esser	ntial Chemicals (21 CFR 1310.02(b) and 13	310.04(f)(2) and
	Acetone (CAS 67-64-	1)	6532	
	Methyl ethyl ketone (C Drug Enforcement Admin	CAS 78-93-3) nistration (DEA). List 1 & 2 Ex	6714 cempt Chemical Mixtures (21 CFR 1310.12	2(c))
	Acetone (CAS 67-64-	1)	35 %WV	
	DEA Exempt Chemical M	lixtures Code Number	55 %WV	
	Acetone (CAS 67-64- Methyl ethyl ketone (C	1) CAS 78-93-3)	6532 6714	
US state	e regulations			
US.	Massachusetts RTK - Su	bstance List		
US.	Acetone (CAS 67-64-1) Cyclohexanone (CAS 108- Furan, Tetrahydro- (CAS 1 Methyl ethyl ketone (CAS 1 New Jersey Worker and 0	-94-1) 09-99-9) 78-93-3) Community Right-to-Know Ac	:t	
US.	Acetone (CAS 67-64-1) Cyclohexanone (CAS 108- Furan, Tetrahydro- (CAS 1 Methyl ethyl ketone (CAS 90 Polyvinyl chloride (CAS 90 Pennsylvania Worker and	-94-1) 09-99-9) 78-93-3) 02-86-2) d Community Right-to-Know I	Law	
US.	Acetone (CAS 67-64-1) Cyclohexanone (CAS 108- Furan, Tetrahydro- (CAS 1 Methyl ethyl ketone (CAS 1 Rhode Island RTK	-94-1) 09-99-9) 78-93-3)		
	Acetone (CAS 67-64-1) Cyclohexanone (CAS 108- Furan, Tetrahydro- (CAS 1 Methyl ethyl ketone (CAS 1	94-1) 09-99-9) 78-93-3)		
US.	California Proposition 65 California Safe Drinking W any chemicals currently lis	ater and Toxic Enforcement Ac ted as carcinogens or reproduc	t of 1986 (Proposition 65): This material is no tive toxins.	ot known to contain
Internat	ional Inventories			
Co ı Car	u ntry(s) or region nada	Inventory name Domestic Substances List (DS	L)	On inventory (yes/no) * Yes

Country(s) or region

Inventory name

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	05-27-2015
Revision date	-
Version #	01
HMIS® ratings	Health: 2 Flammability: 3 Physical hazard: 0
NFPA ratings	2 0

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Oatey Co. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.



SAFETY DATA SHEET

1. Identification	
Product identifier	Oatey Clear Cutting Oil
Other means of identification	
Product code	
Synonyms	Part Numbers: 30200, 30201, 30202
Recommended use	Cutting oil for hand threaded or high speed thread cutting machines.
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/E	Distributor information
Company Name	Oatey Inc.
Address	4700 West 160th Street
	Cleveland, OH 44135
Telephone	216-267-7100
E-mail	info@oatey.com
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)
Emergency First Aid	1-877-740-5015
Contact person	MSDS Coordinator
2. Hazard(s) identification	
Physical hazards	Not Classified.
Health hazards	Not Classified
OSHA defined hazards	Not Classified.
Label elements	
Hazard symbol	None.
Signal word	None
Hazard statement	This product does not require any hazard statements.
Precautionary statement	
Prevention	This product does not require any precautionary statements.
Response	This product does not require any precautionary statements.
Storage	Not applicable.
Disposal	Not applicable.
Hazard(s) not otherwise classified (HNOC)	Used Oil may contain harmful impurities.

3. Composition/information on ingredients

Mixtures

Chemical name		CAS number	%	
Petroleum Hydrocarbon Mixture		Mixture	>95	-
4. First-aid measures				_
Inhalation	Remove victim to fresh air and keep at rest attention if symptoms occur.	t in a position comfortable f	or breathing. Get m	edical
Skin contact	Flush contaminated skin with plenty of wate medical attention if symptoms occur.	er. Remove contaminated	clothing and shoes.	Get
Eye contact	Immediately flush eyes with plenty of water Check for and remove any contact lenses.	r, occasionally lifting the up Get medical attention if irri	per and lower eyelic tation occurs.	ds.
Ingestion	Wash out mouth with water. Remove victim for breathing. If material has been swallowe quantities of water to drink. Do not induce v	n to fresh air and keep at re ed and the exposed persor vomiting unless directed to	est in a position com i is conscious, give s do so by medical	nfortable small
Oatev Clear Cutting Oil				SDS US

	personnel. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Ingestion may result in nausea, vomiting, and or diarrhea.
Indication of immediate medical attention and special treatment needed.	Immediate medical attention is not required.
General information	Note to physician, treat symptomatically.
5. Fire-fighting measures	
Suitable extinguishing media	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water in a jet.
Specific hazards arising from the chemical	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases, oxides of sulfur and phosphorous (smoke). Carbon monoxide.
Special protective equipment and precautions for firefighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Fire fighting equipment/instructions	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Use water spray to keep fire-exposed containers cool. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Specific methods	None

6. Accidental release measures

None

General fire hazards

Personal precautions, protective equipment and emergency procedures	Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel"
Methods and materials for containment and cleaning up	Large Spills: Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal. Small Spills: Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
7. Handling and storage	
Precautions for safe handling	Use local exhaust ventilation if there is risk of inhalation of vapors, mists or aerosols. Properly dispose of any contaminated rags or cleaning materials to prevent fires. Put on appropriate personal protective equipment (see section 8 of SDS). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on bygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.
8 Exposure controls/porcor	al protection

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components		Туре	Value
Oil Mist, Mineral		TLV or PEL	5 mg/m3
US OSHA Permissible Ex	oosure Limits		
Components		Туре	Value
Biological limit values	Data Not available.		
Appropriate engineering controls	No special ventilation worker exposure to a limits, use process e worker exposure bel	n requirements. Good general ventila airborne contaminants. If this product nclosures, local exhaust ventilation o ow any recommended or statutory lin	tion should be sufficient to control contains ingredients with exposure or other engineering controls to keep nits.
Individual protection measures Eye/face protection	, such as personal prot Safety eyewear com indicates this is nece	ective equipment plying with an approved standard sho ssary to avoid exposure to liquid spla	ould be used when a risk assessment ashes, mists, gases or dusts.
Skin protection		, , , , ,	, , , , ,
Hand	Chemical-resistant, i all times when handl	mpervious gloves complying with an ing chemical products if a risk assess	approved standard should be worn at sment indicates this is necessary.
Other	Appropriate footweat the task being perfor handling this product	r and any additional skin protection m med and the risks involved and shou t.	neasures should be selected based on Id be approved by a specialist before
Respiratory protection Thermal hazards	Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. None.		g with an approved standard if a risk ion must be based on known or nd the safe working limits of the
General hygiene considerations	Wash hands, forearr smoking and using the should be used to re not be allowed out or eyewash stations an	ns and face thoroughly after handling he lavatory and at the end of the work move potentially contaminated clothi f the workplace. Wash contaminated d safety showers are close to the wo	g chemical products, before eating, king period. Appropriate techniques ng. Contaminated work clothing should clothing before reusing. Ensure that rkstation location.

9. Physical and chemical properties

Appearance	
Physical state	Liquid
Form	Liquid
Color	Amber
Odor	Slight hydrocarbon
Odor threshold	Not available.
рН	Not applicable
Melting point/freezing point	No data available.
Initial boiling point and boiling	Not determined
range	
Flash point	> 340 °F (> 171°C)
Upper/lower flammability or explose	sive limits
Flammability limit – lower (%)	Not available
Flammability limit – upper (%)	Not available
Explosive limit - lower (%)	Not available
Explosive limit - upper (%)	Not available
Vapor pressure	Not applicable
Vapor density	Not applicable
Relative density	0.91
Solubility(ies)	
Solubility (water)	Negligible
Partition coefficient	
(n-octanol/water)	>6 based on similar products
Auto-ignition temperature	Not applicable

Oatey Clear Cutting Oil SDS # Version #: 01 Revision date: Issue date: 12-May-2015

Decomposition temperature	Not available
Viscosity, kinematic	160 SUS at 100 F (typical)
Other information	
VOC (Weight %)	<1% by weight, < 10 g/L

10. Stability and reactivity

Reactivity	The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph
Chemical stability	The product is stable.
Possibility of hazardous reaction	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Extreme temperature and direct sunlight.
Incompatible materials	Strong Oxidizing Agents.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
11. Toxicological information	on

Information on likely routes of ex	cposure	
Inhalation	Mist from processing.	
Skin contact	Skin contact.	
Eye contact	Eye contact.	
Ingestion	No known significant effects or critical hazards.	
Symptoms related to the physical, chemical and toxicological characteristics	No specific data.	
Information on likely routes of ex Acute Toxicity	cposure	
Components	Species	Results

Skin corrosion/irritation Serious eye damage/eye irritation	May cause skin irritation after prolonged exposure. Prolonged exposure or repeated exposure without proper cleaning can clog pores of the skin. Expected to be slightly irritating.
Respiratory or skin sensitization Respiratory sensitization	Inhalation of vapors or mists may cause irritation to the respiratory system.
Skin sensitization	This product is not expected to cause skin irritation.
Germ cell mutagenicity	Not considered a mutagenic hazard
Carcinogenicity	No component of this product is identified as a probable, possible, or confirmed carcinogen by IARC, NTP, Monographs, or OSHA.
Reproductive toxicity	No known significant effects or critical hazards.
Specific target organ toxicity	
Single exposure Repeated exposure	Not expected to be a hazard. Not expected to be a hazard.
Aspiration Hazard	Contains Distillates (petroleum), hydrotreated – Which is a category 1 Aspiration Hazard. The likely hood of aspirating the product in this form is very low due to the high viscosity.
Chronic effects	Not Classified.
Further information	Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and may present risks to health and the environment on disposal. Used oil should be handled with caution and skin contact should be avoided when possible.

12. Ecological information

Ecotoxicity			
Product/ingredient name	Results	Species	Exposure
Petroleum Distillates			
	Acute LC50 2,900 µg/l Fresh water	Fish - Rainbow trout,Donaldson trou	it 96 h

Persistence and degradability	Not Available.
Bio accumulative potential	Not Available.
Mobility in soil	Liquid under most conditions. Floats on water. If it enters soil, it will adsorb to soil particles and will not be mobile.
Other adverse effects	No known significant effects of critical hazards.

13. Disposal considerations

Disposal instructions	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewere
Local disposal regulations	Not Applicable
Hazardous waste code	Not Applicable
14. Transportation information	tion
DOT .	Not Regulated
UN number	
UN Proper Shipping Name	
Transportation Hazard classes	
Packing group	
ΙΑΤΑ	Not Regulated
UN number	
UN Proper Shipping Name	
Transportation Hazard classes	
Packing group	
IMDG	Not Regulated
UN number	
UN Proper Shipping Name	
Transportation Hazard classes	
Packing group	
Environmental hazards	
Marine polluntant	
15. Regulatory information	
U.S. Federal regulations	TSCA 12(b) - Chemical export notification: None required. TSCA 5(a)2 - Final significant new use rules: Not listed TSCA 5(a)2 - Proposed significant new use rules: Not listed TSCA 5(e) - Substances consent order: Not listed
SARA 311/312	
Classification	Not applicable
US state regulations	
California Prop 65	This product does not contain a chemical known to the State of California to cause cancer, birth defects, or other reproductive harm.
Oatev Clear Cutting Oil	211 2 1 2

16. Other information, including date of preparation or last revision

Issue Date	12-May-2015
Revision Date	-
Version #	01
HMIS Rating	Health: 1 Flammability: 1 Physical Hazards: 0
Disclaimer	Oatey Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.



SAFETY DATA SHEET

1 Identification

Product identifier	Oatey CPVC Flowguard Gold UVI One-Step Yellow Cement	
Other means of identification		
Product code	1203E	
Synonyms	Part Numbers: 31910(TV), 31911(TV), 31912, 32203, 31660, 31661, 31662, 31663, 31917, 3	31913, 31914, 31656, 31657, 32200, 32201, 32202, 31918, 31919
Recommended use	Joining CPVC Pipes	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/I	Distributor information	
Company Name	Oatey Co.	
Address	4700 West 160th St.	
	Cleveland, OH 44135	
Telephone	216-267-7100	
E-mail	info@oatey.com	
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the U	S 1-703-527-3887)
Emergency First Aid	1-877-740-5015	
Contact person	MSDS Coordinator	
2. Hazard(s) identification		
Physical hazards	Flammable liquids	Category 2
Health hazards	Acute toxicity, oral	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
OSHA defined hazards	Not classified.	
Label elements		
Signal word	Danger	
Hazard statement	Highly flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness.	
Precautionary statement		
Prevention	Keep away from heat/sparks/open flames/hot	surfaces No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response	If swallowed: Immediately call a poison center/doctor. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. Rinse mouth. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May form explosive peroxides. Contains a chemical classified by the US EPA as a suspected possible carcinogen.

Supplemental information

Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Furan, Tetrahydro-	109-99-9	30-60
Methyl ethyl ketone	78-93-3	10-30
Ethene, chloro-, homopolymer, chlorinated	68648-82-8	10-20
Acetone	67-64-1	5-15
Cyclohexanone	108-94-1	5-15
Silica, amorphous, fumed	112945-52-5	1-5

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.
Most important symptoms/effects, acute and delayed	Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

the chemical

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor. This product contains tetrahydrofuran that may form explosive organic peroxide when exposed to air or light or with age.
6. Accidental release meas	sures
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water.
	Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
Cyclohexanone (CAS 108-94-1)	PEL	200 mg/m3	
,		50 ppm	
Furan, Tetrahydro- (CAS 109-99-9)	PEL	590 mg/m3	
,		200 ppm	
Methyl ethyl ketone (CAS 78-93-3)	PEL	590 mg/m3	
,		200 ppm	
US. OSHA Table Z-3 (29 CFR 1910	0.1000)		
Components	Туре	Value	
Silica, amorphous, fumed (CAS 112945-52-5)	TWA	0.8 mg/m3	

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Туре	Value	
		20 mppcf	
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
Cyclohexanone (CAS 108-94-1)	STEL	50 ppm	
	TWA	20 ppm	
Furan, Tetrahydro- (CAS 109-99-9)	STEL	100 ppm	
	TWA	50 ppm	
Methyl ethyl ketone (CAS 78-93-3)	STEL	300 ppm	
	TWA	200 ppm	
US. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Туре	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
		250 ppm	
Cyclohexanone (CAS 108-94-1)	TWA	100 mg/m3	
		25 ppm	
Furan, Tetrahydro- (CAS 109-99-9)	STEL	735 mg/m3	
		250 ppm	
	TWA	590 mg/m3	
		200 ppm	
Methyl ethyl ketone (CAS 78-93-3)	STEL	885 mg/m3	
		300 ppm	
	TWA	590 mg/m3	
		200 ppm	
Silica, amorphous, fumed (CAS 112945-52-5)	TWA	6 mg/m3	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
Cyclohexanone (CAS 108-94-1)	80 mg/l	1,2-Cyclohexan ediol, with hydrolysis	Urine	*
	8 mg/l	Cyclohexanol, with hydrolysis	Urine	*
Furan, Tetrahydro- (CAS 109-99-9)	2 mg/l	Tetrahydrofura n	Urine	*
Methyl ethyl ketone (CAS 78-93-3)	2 mg/l	MEK	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Cyclohexanone (CAS 108-94-1)

US - Minnesota Haz Subs: Skin designation applies Cyclohexanone (CAS 108-94-1) Can be absorbed through the skin.

Skin designation applies.

US - Tennessee OELs: Skin o	designation	
Cyclohexanone (CAS 108-94-1)		Can be absorbed through the skin.
US ACGIH Threshold Limit V	alues: Skin designation	
Cyclohexanone (CAS 108-94-1)		Can be absorbed through the skin.
Furan, Tetrahydro- (CAS 109-99-9)		Can be absorbed through the skin.
US. NIOSH: Pocket Guide to	Chemical Hazards	
Cyclohexanone (CAS 108	-94-1)	Can be absorbed through the skin.
Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.	
Individual protection measures, s	such as personal protective ed	quipment
Eye/face protection	Face shield is recommended. Wear safety glasses with side shields (or goggles).	
Skin protection		
Hand protection	Wear appropriate chemical resistant gloves.	
Other	Wear appropriate chemical resistant clothing.	
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.	
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.	
General hygiene considerations	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.	

9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Translucent liquid.
Color	Yellow / Gold
Odor	Solvent.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling	151 °F (66.11 °C)
range	
Flash point	14.0 - 23.0 °F (-10.05.0 °C)
Evaporation rate	5.5 - 8
Flammability (solid, gas)	Not available.
Upper/lower flammability or expl	osive limits
Flammability limit - lower (%)	1.8
Flammability limit - lower (%) Flammability limit - upper (%)	1.8 11.8
Flammability limit - lower (%) Flammability limit - upper (%) Explosive limit - lower (%)	1.8 11.8 Not available.
Flammability limit - lower (%) Flammability limit - upper (%) Explosive limit - lower (%) Explosive limit - upper (%)	1.8 11.8 Not available. Not available.
Flammability limit - lower (%) Flammability limit - upper (%) Explosive limit - lower (%) Explosive limit - upper (%) Vapor pressure	1.8 11.8 Not available. Not available. 145 mm Hg @ 20 C
Flammability limit - lower (%) Flammability limit - upper (%) Explosive limit - lower (%) Explosive limit - upper (%) Vapor pressure Vapor density	 1.8 11.8 Not available. Not available. 145 mm Hg @ 20 C 2.5
Flammability limit - lower (%) Flammability limit - upper (%) Explosive limit - lower (%) Explosive limit - upper (%) Vapor pressure Vapor density Relative density	1.8 11.8 Not available. Not available. 145 mm Hg @ 20 C 2.5 0.94 +/- 0.02
Flammability limit - lower (%) Flammability limit - upper (%) Explosive limit - lower (%) Explosive limit - upper (%) Vapor pressure Vapor density Relative density Solubility(ies)	1.8 11.8 Not available. 145 mm Hg @ 20 C 2.5 0.94 +/- 0.02
Flammability limit - lower (%) Flammability limit - upper (%) Explosive limit - lower (%) Explosive limit - upper (%) Vapor pressure Vapor density Relative density Solubility(ies) Solubility (water)	1.8 11.8 Not available. 145 mm Hg @ 20 C 2.5 0.94 +/- 0.02 Negligible
Flammability limit - lower (%) Flammability limit - upper (%) Explosive limit - lower (%) Explosive limit - upper (%) Vapor pressure Vapor density Relative density Solubility(ies) Solubility(ies) Solubility (water) Partition coefficient (n-octanol/water)	1.8 11.8 Not available. Not available. 145 mm Hg @ 20 C 2.5 0.94 +/- 0.02 Negligible Not available.

Decomposition temperature	Not available.
Viscosity	500 - 1500 cP
Other information	
Bulk density	7.8 lb/gal
VOC (Weight %)	470 g/l SQACMD 1168/M316A

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Ammonia. Amines. Isocyanates. Caustics.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May be fatal if swallowed and enters airways. Headache. Nausea, vomiting. May cause irritation to the respiratory system. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Prolonged inbalation may be harmful
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	May be fatal if swallowed and enters airways. Harmful if swallowed. Harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Symptoms related to the physical, chemical and toxicological characteristics	Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects

Acute toxicity May be fatal if swa	llowed and enters airways. Narcotic e	ffects. May cause respiratory irritation.
------------------------------------	---------------------------------------	---

Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
Dermal		
LD50	Rabbit	20 ml/kg
Inhalation		
LC50	Rat	50 mg/l, 8 Hours
Oral		
LD50	Rat	5800 mg/kg
Cyclohexanone (CAS 108-94-1)	
Acute		
Dermal		
LD50	Rabbit	948 mg/kg
Inhalation		
LC50	Rat	8000 ppm, 4 hours
Oral		
LD50	Rat	1540 mg/kg
* Estimates for product ma	y be based on additional component data not	shown.
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	

Respiratory or skin sensitization			
Respiratory sensitization			
Skin sensitization	This product is not expected to cause skin sensitization.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	In 2012 USEPA Integrated Risk Information System (IRIS) reviewed a two species inhalation lifetime study on THF conducted by NTP (1998). Male rats developed renal tumors and female mice developed liver tumors while neither the female rats nor the male mice showed similar results. Because the carcinogenic mechanisms could not be identified clearly in either species for either tumor, the EPA determined that the male rat and female mouse findings are relevant to the assessment of carcinogenic potential in humans. Therefore, the IRIS review concludes that these data in aggregate indicate that there is "suggestive evidence of carcinogenic potential" following exposure to THF by all routes of exposure.		
IARC Monographs. Overall E	valuation of Ca	arcinogenicity	
Cyclohexanone (CAS 108- Silica, amorphous, fumed OSHA Specifically Regulated Not listed.	-94-1) (CAS 112945-5 I Substances ()	2-5) 29 CFR 1910.100	3 Not classifiable as to carcinogenicity to humans. 3 Not classifiable as to carcinogenicity to humans. 01-1050)
Reproductive toxicity	This product is	not expected to	cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Narcotic effect	s. May cause dro	owsiness and dizziness. Respiratory tract irritation.
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	May be fatal if	swallowed and e	enters airways.
Chronic effects	Prolonged inha	alation may be ha	armful.
12. Ecological information			
Ecotoxicity	The product is possibility that	not classified as large or frequent	environmentally hazardous. However, this does not exclude the t spills can have a harmful or damaging effect on the environment.
Components		Species	Test Results
Acetone (CAS 67-64-1) Aquatic			
Fish L	_C50	Fathead minnov	w (Pimephales promelas) > 100 mg/l, 96 hours
Cyclohexanone (CAS 108-94-1)		
Fish L	-C50	Fathead minnov	w (Pimephales promelas) 481 - 578 mg/l, 96 hours
* Estimates for product may be	based on addit	tional component	t data not shown.
Persistence and degradability	No data is ava	ilable on the deg	radability of this product.
Bioaccumulative potential	No data availa	ble.	
Partition coefficient n-octand Acetone (CAS 67-64-1) Cyclohexanone (CAS 108-94-1 Furan, Tetrahydro- (CAS 109-9	b l / water (log k 1) 99-9) 2 2)	(ow)	-0.24 0.81 0.46
Mobility in soil	No data availa	hle	0.29
Other adverse offects	No other adver	rse environmenta	al effects (e.g. ozone depletion, photochemical ozone creation
Other adverse enects	potential, endo	ocrine disruption,	global warming potential) are expected from this component.
13. Disposal consideration	S		
Disposal instructions	Collect and red and its contain sewers/waters container. Disp regulations.	claim or dispose i ler must be dispo supplies. Do not o bose of contents/	in sealed containers at licensed waste disposal site. This material osed of as hazardous waste. Do not allow this material to drain into contaminate ponds, waterways or ditches with chemical or used (container in accordance with local/regional/national/international

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

UN number	UN1993
UN proper shipping name	Flammable liquids, n.o.s. (Methyl ethyl ketone RQ = 23310 LBS, Acetone RQ = 50000 LBS)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	IB2, 17, 1P1, 1P8, 1P28
Packaging exceptions	150
Packaging non bulk	202
Packaging bulk	242
IATA	
UN number	UN1993
UN proper shipping name	Flammable liquid, n.o.s. (Methyl ethyl ketone, Acetone)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	No.
ERG Code	3H
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
IMDG	
UN number	UN1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (Methyl ethyl ketone, Acetone)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	11
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not available.

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.				
TSCA Section 12(b) Export N	rt Notification (40 CFR 707, Subpt. D)				
Not regulated.					
OSHA Specifically Regulated	Substances (29 CFR 1910.1001-1050)				
Not listed.					
CERCLA Hazardous Substar	e List (40 CFR 302.4)				
Acetone (CAS 67-64-1)	LISTED				
Cyclohexanone (CAS 108	4-1) LISTED				
Furan, Tetrahydro- (CAS	9-99-9) LISTED				
Methyl ethyl ketone (CAS	3-93-3) LISTED				

Superf	fund Amendments and Rea	uthorization Act of 1986 (SA	RA)			
Ha	azard categories	Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No				
SA	ARA 302 Extremely hazard	ous substance				
	Not listed.					
S/ ch	ARA 311/312 Hazardous nemical	No				
SA	ARA 313 (TRI reporting) Not regulated.					
Other	federal regulations					
CI	ean Air Act (CAA) Section	112 Hazardous Air Pollutants	s (HAPs) List			
Cl	Not regulated. Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)					
	Not regulated.					
Sa (S	afe Drinking Water Act DWA)	Not regulated.				
	Drug Enforcement Admi Chemical Code Number	nistration (DEA). List 2, Esse	ntial Chemicals (21 CFR 1310.02(b) and 1	310.04(f)(2) and		
	Acetone (CAS 67-64-	1)	6532			
	Drug Enforcement Admi	nistration (DEA). List 1 & 2 Ex	xempt Chemical Mixtures (21 CFR 1310.1)	2(c))		
	Acetone (CAS 67-64-	1)	35 %WV	-(-)/		
	Methyl ethyl ketone (C DEA Exempt Chemical M	CÁS 78-93-3) lixtures Code Number	35 %WV			
	Acetone (CAS 67-64- Methyl ethyl ketone (C	1) CAS 78-93-3)	6532 6714			
US sta	te regulations					
US	S. Massachusetts RTK - Su	bstance List				
US	Acetone (CAS 67-64-1) Cyclohexanone (CAS 108 Furan, Tetrahydro- (CAS 1 Methyl ethyl ketone (CAS Silica, amorphous, fumed S. New Jersey Worker and	-94-1) 109-99-9) 78-93-3) (CAS 112945-52-5) Community Right-to-Know A	ct			
US	Acetone (CAS 67-64-1) Cyclohexanone (CAS 108 Furan, Tetrahydro- (CAS 1 Methyl ethyl ketone (CAS 5. Pennsylvania Worker and	-94-1) 109-99-9) 78-93-3) d Community Right-to-Know	Law			
US	Acetone (CAS 67-64-1) Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS 109-99-9) Methyl ethyl ketone (CAS 78-93-3) Silica, amorphous, fumed (CAS 112945-52-5) US. Rhode Island RTK					
	Acetone (CAS 67-64-1) Cyclohexanone (CAS 108 Furan, Tetrahydro- (CAS 1 Methyl ethyl ketone (CAS	-94-1) 109-99-9) 78-93-3)				
US	6. California Proposition 65	5				
	California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.					
International Inventories						
Ca Ca	ountry(s) or region anada	Inventory name Domestic Substances List (DS	SL)	On inventory (yes/no)* Yes		
Country(s) or region

Inventory name

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	27-May-2015
Revision date	-
Version #	01
HMIS® ratings	Health: 2 Flammability: 3 Physical hazard: 0
NFPA ratings	2 0

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Oatey Co. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.



SAFETY DATA SHEET

1. Identification

Product identifier	Gray Pipe Joint Compound
Other means of identification	
SDS number	1703E
Synonyms	Part Numbers: 31226, 31227, 31228, 32235, 31236, 48005, 48324
Recommended use	Pipe Joint Compound for Threaded Metal Pipes
Recommended restrictions	None known.
Manufacturar/Importar/Supplie	Distributor information

Manufacturer/Importer/Supplier/Distributor information

Company Name	Oatey Co.
Address	4700 West 160th St.
	Cleveland, OH 44135
Telephone	216-267-7100
E-mail	info@oatey.com
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)
Emergency First Aid	1-877-740-5015
Contact person	MSDS Coordinator

2. Hazard(s) identification

Physical hazards	Not classified.
Health hazards	Not classified.
OSHA defined hazards	Not classified.
Label elements	
Hazard symbol	None.
Signal word	None.
Hazard statement	The mixture does not meet the criteria for classification.
Precautionary statement	
Prevention	Observe good industrial hygiene practices.
Response	Wash hands after handling.
Storage	Store away from incompatible materials.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
Hazard(s) not otherwise classified (HNOC)	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Calcium carbonate	1317-65-3	60-75
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	20-30
Canola Oil, Polymd., Oxidized	129828-25-7	1-5
Crystalline silica (Quartz)	14808-60-7	<0.8

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Skin contact Move to fresh air. Call a physician if symptoms develop or persist. Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.

Specific methodsUse standard firefighting procedures and consider the hazards of other involved materials.General fire hazardsNo unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	The product is immiscible with water and will sediment in water systems. Large Spills: Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Avoid prolonged exposure. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Calcium carbonate (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Туре	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust.
		0.1 mg/m3	Respirable.
US. ACGIH Threshold Limit	Values		
Components	Туре	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
Calcium carbonate (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS	STEL	10 mg/m3	Mist.
64742-52-5)	TWA	5 mg/m3	Mist
ological limit values	No biological exposure limits noted for	the ingredient(s).	
propriate engineering ntrols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.		
lividual protection measures.	such as personal protective equipme	nt	
Eye/face protection	Wear safety glasses with side shields (or goggles).	
Skin protection			
Hand protection	Wear appropriate chemical resistant gl	oves.	
Other	Wear suitable protective clothing.		
Respiratory protection	Use a particulate filter respirator for particulate concentrations exceeding the Occupational Exposure Limit.		
Thermal hazards	Wear appropriate thermal protective clo	othing, when necessary.	
neral hygiene nsiderations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.		
Physical and chemical r	properties		
pearance	•		

Physical state	Liquid.
Form	Liquid paste.
Color	Gray.
Odor	Odorless
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.

Flash point	> 212.0 °F (> 100.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or expl	osive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	< 1
Relative density	1.75
Solubility(ies)	
Solubility (water)	Insoluble
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	20000 cP
Other information	
VOC (Weight %)	11 g/l
10. Stability and reactivity	

0. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Acids. Fluorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.	
Skin contact	No adverse effects due to skin contact are expected.	
Eye contact	Direct contact with eyes may cause temporary irritation.	
Ingestion	Expected to be a low ingestion hazard.	
Symptoms related to the physical, chemical and toxicological characteristics	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.	
Information on toxicological effects		
Acute toxicity	Not available	

Acute toxicity	Not available.
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity	In 1997, IARC (the Internation inhaled from occupational sou overall evaluation, IARC noted circumstances studied. Carcin crystalline silica or on external polymorphs." (IARC Monogra humans, Silica, silicates dust a	al Agency for Research on Cancer) concluded that crystalline silica rces can cause lung cancer in humans. However in making the I that "carcinogenicity was not detected in all industrial ogenicity may be dependent on inherent characteristics of the factors affecting its biological activity or distribution of its phs on the evaluation of the carcinogenic risks of chemicals to and organic fibres, 1997, Vol. 68, IARC, Lyon, France.)	
IARC Monographs. Overall E	Evaluation of Carcinogenicity		
Crystalline silica (Quartz)	(CAS 14808-60-7)	1 Carcinogenic to humans.	
(CAS 64742-52-5)	drotreated neavy naphthenic	3 Not classifiable as to carcinogenicity to humans.	
NTP Report on Carcinogens	;		
Crystalline silica (Quartz) OSHA Specifically Regulate	(CAS 14808-60-7) d Substances (29 CFR 1910.10	Known To Be Human Carcinogen. 001-1050)	
Not listed.			
Reproductive toxicity	This product is not expected to	o cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not an aspiration hazard.		
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.		
Further information	This product has no known adverse effect on human health.		
12. Ecological information	I		
Ecotoxicity	The product is not classified a	s environmentally hazardous. However, this does not exclude the	

ECOTOXICITY	possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

-	
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according toNot established.Annex II of MARPOL 73/78 andthe IBC Code

Pogulatory information

15. Regulatory information	1	
US federal regulations	All components are on the U.S. EPA TSCA Inventory List. This product is not known to be a "Hazardous Chemical" as defined by th Communication Standard, 29 CFR 1910.1200.	e OSHA Hazard
TSCA Section 12(b) Export I	Notification (40 CFR 707, Subpt. D)	
Not regulated.		
OSHA Specifically Regulate	d Substances (29 CFR 1910.1001-1050)	
Not listed.		
CERCLA Hazardous Substa	nce List (40 CFR 302.4)	
Not listed.		
Superfund Amendments and Re	authorization Act of 1986 (SARA)	
Hazard categories	Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No	
SARA 302 Extremely hazard	lous substance	
Not listed.		
SARA 311/312 Hazardous chemical	No	
SARA 313 (TRI reporting) Not regulated.		
Other federal regulations		
Clean Air Act (CAA) Section	112 Hazardous Air Pollutants (HAPs) List	
Not regulated.		
Clean Air Act (CAA) Section	112(r) Accidental Release Prevention (40 CFR 68.130)	
Safe Drinking Water Act	Not regulated.	
(SDWA)	i i i i i i i i i i i i i i i i i i i	
US state regulations		
US. Massachusetts RTK - Su	ubstance List	
Calcium carbonate (CAS	1317-65-3)	
Crystalline silica (Quartz) Distillates (petroleum), hy US. New Jersey Worker and	(CAS 14808-60-7) drotreated heavy naphthenic (CAS 64742-52-5) Community Right-to-Know Act	
Calcium carbonate (CAS	1317-65-3)	
Crystalline silica (Quartz) US. Pennsylvania Worker ar	(CAS 14808-60-7) ad Community Right-to-Know Law	
Calcium carbonate (CAS	1317-65-3)	
Crystalline silica (Quartz)	(CAS 14808-60-7)	
US. Rhode Island RTK		
Not regulated.		
US. California Proposition 6 WARNING: This product	5 contains a chemical known to the State of California to cause cancer.	
US - California Proposit Crystalline silica (Qua	ion 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance artz) (CAS 14808-60-7)	3
International Inventories		
		On inventery (vec/ne)*
Australia	Australian Inventory of Chemical Substances (AICS)	No.
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	NU Voo
	Inventory of Existing Chemical Substances in China (IECSC)	Tes No.
Furopo	European Inventory of Existing Commercial Chamical	INO No
Europe	Substances (EINECS)	NO

European List of Notified Chemical Substances (ELINCS)

Europe

No

Country(s) or region	Inventory name	On inventory (yes/no)*
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	05-February-2015
Revision date	-
Version #	01
HMIS® ratings	Health: 0 Flammability: 0 Physical hazard: 0
Disclaimer	Oatey Co. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.



SAFETY DATA SHEET

1. Identification

Product identifier	Oatey H2O 5 Paste Flux	
Other means of identification		
SDS number	1613E	
Synonyms	Part Numbers: 30130, 30131, 30132, 30133, 53067	
Recommended use	Joining Copper Pipes. Joining Copper Tubing.	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		

Company Name	Oatey Co.
Address	4700 West 160th St.
	Cleveland, OH 44135
Telephone	216-267-7100
E-mail	info@oatey.com
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)
Emergency First Aid	1-877-740-5015
Contact person	MSDS Coordinator
Contact person	MSDS Coordinator

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Skin corrosion/irritation	Category 1B
	Serious eye damage/eye irritation	Category 1
OSHA defined hazards	Not classified.	

Label elements



	•
Signal word	Danger
Hazard statement	Causes severe skin burns and eye damage.
Precautionary statement	
Prevention	Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dusts or mists.
Response	If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Wash contaminated clothing before reuse.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information Not applicable.	

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Glycerin	56-81-5	7-13

Triethanolamine Hydrochloride	637-39-8	7-13
Zinc chloride	7646-85-7	3-7
Ammonium chloride	12125-02-9	1-5

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Continue rinsing. Call a physician or poison control center immediately. Remove contact lenses, if present and easy to do.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water spray. Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Use water spray to cool unopened containers.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading.
	Small Spills: Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Do not get this material on clothing. Provide adequate ventilation. Wear appropriate

personal protective equipment. Observe good industrial hygiene practices.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Glycerin (CAS 56-81-5)	PEL	5 mg/m3 15 mg/m3	Respirable fraction. Total dust.
Zinc chloride (CAS 7646-85-7)	PEL	1 mg/m3	Fume.
US. ACGIH Threshold Limi	t Values		
Components	Туре	Value	Form
Ammonium chloride (CAS 12125-02-9)	STEL	20 mg/m3	Fume.
	TWA	10 mg/m3	Fume.
Zinc chloride (CAS 7646-85-7)	STEL	2 mg/m3	Fume.
	TWA	1 mg/m3	Fume.
US. NIOSH: Pocket Guide	o Chemical Hazards		
Components	Туре	Value	Form
Ammonium chloride (CAS 12125-02-9)	STEL	20 mg/m3	Fume.
	TWA	10 mg/m3	Fume.
Zinc chloride (CAS 7646-85-7)	STEL	2 mg/m3	Fume.
	TWA	1 mg/m3	Fume.
Biological limit values	No biological exposure limits noted for	the ingredient(s).	
Exposure guidelines	Occupational Exposure Limits are not	relevant to the current physica	al form of the product.
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.		
Individual protection measures	s, such as personal protective equipme	nt	
Eye/face protection	Wear safety glasses with side shields	(or goggles) and a face shield	
Skin protection			
Hand protection	Wear appropriate chemical resistant g	loves.	
Other	Wear appropriate chemical resistant clothing.		
Respiratory protection	In case of insufficient ventilation, wear	suitable respiratory equipmer	nt.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.		
General hygiene considerations	Always observe good personal hygien and before eating, drinking, and/or sm equipment to remove contaminants.	e measures, such as washing oking. Routinely wash work cl	after handling the material othing and protective
9. Physical and chemical	properties		

Appearance	
Physical state	Liquid.
Form	Paste.
Color	Light yellow.
Odor	Slight.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.

Initial boiling point and boiling range	Not Applicable
Flash point	Not Applicable
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or expl	osive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	>1
Relative density	1.1
Solubility(ies)	
Solubility (water)	Soluble
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	30000 - 50000
Other information	
VOC (Weight %)	8 g/l <1% by weight
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Decomposition may yield acrolein. No hazardous decomposition products are known.
11. Toxicological information	

Information on likely routes of exposure		
Inhalation	Prolonged inhalation may be harmful. May cause irritation to the respiratory system.	
Skin contact	Causes severe skin burns.	
Eye contact	Causes serious eye damage.	
Ingestion	Causes digestive tract burns.	
Symptoms related to the physical, chemical and toxicological characteristics	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.	

Information on toxicological effects

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes severe skin burns and eye damage.
Serious eye damage/eye irritation	Causes serious eye damage.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Risk of cancer cannot be excluded with prolonged exposure.
OSHA Specifically Regulated	l Substances (29 CFR 1910.1001-1050)
Not listed.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful.
12. Ecological information	
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Partition coefficient n-octanc Glycerin (CAS 56-81-5)	ol / water (log Kow) -1.76
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.			
TSCA Section 12(b) Export N	CA Section 12(b) Export Notification (40 CFR 707, Subpt. D)			
Not regulated. OSHA Specifically Regulated	l Substances (29 CFR 1910.	1001-1050)		
Not listed.				
CERCLA Hazardous Substan	nce List (40 CFR 302.4)			
Zinc chloride (CAS 7646-8	12125-02-9) 55-7)	LISTED		
Superfund Amendments and Rea Hazard categories	Inthorization Act of 1986 (S Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No	ARA)		
SARA 302 Extremely hazardo	ous substance			
Not listed.				
SARA 311/312 Hazardous chemical	No			
SARA 313 (TRI reporting)				
Chemical name		CAS number	% by wt.	
Zinc chloride Ammonium chloride		7646-85-7 12125-02-9	3-7 1-5	
Other federal regulations				
Clean Air Act (CAA) Section	112 Hazardous Air Pollutan	ts (HAPs) List		
Not regulated. Clean Air Act (CAA) Section	112(r) Accidental Release F	Prevention (40 CFR 6	68.130)	
Not regulated.				
Safe Drinking Water Act (SDWA)	Not regulated.			
US state regulations				
US. Massachusetts RTK - Su	bstance List			
Ammonium chloride (CAS Glycerin (CAS 56-81-5) Zinc chloride (CAS 7646-8	12125-02-9) 25-7)			
US. New Jersey Worker and	Community Right-to-Know	Act		
Ammonium chloride (CAS Glycerin (CAS 56-81-5) Zinc chloride (CAS 7646-8	12125-02-9)			
US. Pennsylvania Worker and	d Community Right-to-Knov	w Law		
Ammonium chloride (CAS Glycerin (CAS 56-81-5) Zinc chloride (CAS 7646-8 US. Rhode Island RTK	12125-02-9) 55-7)			
Ammonium chloride (CAS Zinc chloride (CAS 7646-8	12125-02-9) 95-7)			
US. California Proposition 65 California Safe Drinking W any chemicals currently lis	i ater and Toxic Enforcement ted as carcinogens or reprod	Act of 1986 (Proposit uctive toxins.	ion 65): This material is n	not known to contain
International Inventories				
Country(s) or region	Inventory name			On inventory (yes/no)*
Australia	Australian Inventory of Cher	nical Substances (Al	CS)	Yes
Canada	Domestic Substances List (I	DSL)		Yes
Canada	Non-Domestic Substances L	list (NDSL)		No

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	27-October-2014
Revision date	19-February-2015
Version #	04
HMIS® ratings	Health: 3 Flammability: 0 Physical hazard: 0
Disclaimer	The information in the sheet was written based on the best knowledge and experience currently available. Oatey Co. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for use, handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.



SAFETY DATA SHEET

1. Identification

Product identifier	Oatey H2O 5 Paste Flux
Other means of identification	
SDS number	1613E
Synonyms	Part Numbers: 30130, 30131, 30132, 30133, 53067
Recommended use	Joining Copper Pipes. Joining Copper Tubing.
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	

Company Name	Oatey Co.
Address	4700 West 160th St.
	Cleveland, OH 44135
Telephone	216-267-7100
E-mail	info@oatey.com
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)
Emergency First Aid	1-877-740-5015
Contact person	MSDS Coordinator
Contact person	MSDS Coordinator

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Skin corrosion/irritation	Category 1B
	Serious eye damage/eye irritation	Category 1
OSHA defined hazards	Not classified.	

Label elements



	•
Signal word	Danger
Hazard statement	Causes severe skin burns and eye damage.
Precautionary statement	
Prevention	Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dusts or mists.
Response	If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Wash contaminated clothing before reuse.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information Not applicable.	

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Glycerin	56-81-5	7-13

Triethanolamine Hydrochloride	637-39-8	7-13
Zinc chloride	7646-85-7	3-7
Ammonium chloride	12125-02-9	1-5

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Continue rinsing. Call a physician or poison control center immediately. Remove contact lenses, if present and easy to do.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water spray. Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Use water spray to cool unopened containers.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading.
	Small Spills: Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Do not get this material on clothing. Provide adequate ventilation. Wear appropriate

personal protective equipment. Observe good industrial hygiene practices.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form	
Glycerin (CAS 56-81-5)	PEL	5 mg/m3 15 mg/m3	Respirable fraction. Total dust.	
Zinc chloride (CAS 7646-85-7)	PEL	1 mg/m3	Fume.	
US. ACGIH Threshold Limi	t Values			
Components	Туре	Value	Form	
Ammonium chloride (CAS 12125-02-9)	STEL	20 mg/m3	Fume.	
	TWA	10 mg/m3	Fume.	
Zinc chloride (CAS 7646-85-7)	STEL	2 mg/m3	Fume.	
	TWA	1 mg/m3	Fume.	
US. NIOSH: Pocket Guide	o Chemical Hazards			
Components	Туре	Value	Form	
Ammonium chloride (CAS 12125-02-9)	STEL	20 mg/m3	Fume.	
	TWA	10 mg/m3	Fume.	
Zinc chloride (CAS 7646-85-7)	STEL	2 mg/m3	Fume.	
	TWA	1 mg/m3	Fume.	
Biological limit values	No biological exposure limits noted for	No biological exposure limits noted for the ingredient(s).		
Exposure guidelines	Occupational Exposure Limits are not relevant to the current physical form of the product.		al form of the product.	
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.			
Individual protection measures	s, such as personal protective equipme	nt		
Eye/face protection	Wear safety glasses with side shields	(or goggles) and a face shield		
Skin protection				
Hand protection	Wear appropriate chemical resistant g	loves.		
Other	Wear appropriate chemical resistant clothing.			
Respiratory protection	In case of insufficient ventilation, wear	suitable respiratory equipmer	nt.	
Thermal hazards	Wear appropriate thermal protective cl	othing, when necessary.		
General hygiene considerations	Always observe good personal hygien and before eating, drinking, and/or sm equipment to remove contaminants.	e measures, such as washing oking. Routinely wash work cl	after handling the material othing and protective	
9. Physical and chemical	properties			

Appearance	
Physical state	Liquid.
Form	Paste.
Color	Light yellow.
Odor	Slight.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.

Initial boiling point and boiling range	Not Applicable
Flash point	Not Applicable
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or expl	osive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	>1
Relative density	1.1
Solubility(ies)	
Solubility (water)	Soluble
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	30000 - 50000
Other information	
VOC (Weight %)	8 g/l <1% by weight
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Decomposition may yield acrolein. No hazardous decomposition products are known.
11. Toxicological informati	on

Information on likely routes of exposure		
Inhalation	Prolonged inhalation may be harmful. May cause irritation to the respiratory system.	
Skin contact	Causes severe skin burns.	
Eye contact	Causes serious eye damage.	
Ingestion	Causes digestive tract burns.	
Symptoms related to the physical, chemical and toxicological characteristics	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.	

Information on toxicological effects

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes severe skin burns and eye damage.
Serious eye damage/eye irritation	Causes serious eye damage.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Risk of cancer cannot be excluded with prolonged exposure.
OSHA Specifically Regulated	l Substances (29 CFR 1910.1001-1050)
Not listed.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful.
12. Ecological information	
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Partition coefficient n-octanc Glycerin (CAS 56-81-5)	ol / water (log Kow) -1.76
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.			
TSCA Section 12(b) Export N	otification (40 CFR 707, Su	bpt. D)		
Not regulated. OSHA Specifically Regulated	l Substances (29 CFR 1910.	1001-1050)		
Not listed.				
CERCLA Hazardous Substan	nce List (40 CFR 302.4)			
Zinc chloride (CAS 7646-8	12125-02-9) 55-7)	LISTED		
Superfund Amendments and Rea Hazard categories	Inthorization Act of 1986 (S Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No	ARA)		
SARA 302 Extremely hazardo	ous substance			
Not listed.				
SARA 311/312 Hazardous chemical	No			
SARA 313 (TRI reporting)				
Chemical name		CAS number	% by wt.	
Zinc chloride Ammonium chloride		7646-85-7 12125-02-9	3-7 1-5	
Other federal regulations				
Clean Air Act (CAA) Section	112 Hazardous Air Pollutan	ts (HAPs) List		
Not regulated. Clean Air Act (CAA) Section	112(r) Accidental Release F	Prevention (40 CFR 6	68.130)	
Not regulated.				
Safe Drinking Water Act (SDWA)	Not regulated.			
US state regulations				
US. Massachusetts RTK - Su	bstance List			
Ammonium chloride (CAS Glycerin (CAS 56-81-5) Zinc chloride (CAS 7646-8	12125-02-9) 25-7)			
US. New Jersey Worker and	Community Right-to-Know	Act		
Ammonium chloride (CAS Glycerin (CAS 56-81-5) Zinc chloride (CAS 7646-8	12125-02-9)			
US. Pennsylvania Worker and	d Community Right-to-Knov	w Law		
Ammonium chloride (CAS Glycerin (CAS 56-81-5) Zinc chloride (CAS 7646-8 US. Rhode Island RTK	12125-02-9) 55-7)			
Ammonium chloride (CAS Zinc chloride (CAS 7646-8	12125-02-9) 95-7)			
US. California Proposition 65 California Safe Drinking W any chemicals currently lis	i ater and Toxic Enforcement ted as carcinogens or reprod	Act of 1986 (Proposit uctive toxins.	ion 65): This material is n	not known to contain
International Inventories				
Country(s) or region	Inventory name			On inventory (yes/no)*
Australia	Australian Inventory of Cher	nical Substances (Al	CS)	Yes
Canada	Domestic Substances List (I	DSL)		Yes
Canada	Non-Domestic Substances L	list (NDSL)		No

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	27-October-2014
Revision date	19-February-2015
Version #	04
HMIS® ratings	Health: 3 Flammability: 0 Physical hazard: 0
Disclaimer	The information in the sheet was written based on the best knowledge and experience currently available. Oatey Co. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for use, handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.



SAFETY DATA SHEET

1. Identification

Product identifier	Oatey Pipe Joint Lubricant	
Other means of identification		
Product code		
Synonyms	Part Numbers: 30599, 30600, 30601, 30602	
Recommended use	Lubricant	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/	Distributor information	
Company Name	Oatey Inc.	
Address	4700 West 160th Street	
	Cleveland, OH 44135	
Telephone	216-267-7100	
E-mail	info@oatey.com	
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)	
Emergency First Aid	1-877-740-5015	
Contact person	MSDS Coordinator	
2. Hazard(s) identification		
Physical hazards	Not Classified.	
Health hazards	Skin Irritant	Cat 3
	Eye Irritation	Cat 2B
OSHA defined hazards	This chemical is considered non-hazardous according to the OSHA Hazard Standard 2012 (29 CFR 1910.1200)	Communication
Label elements		
Hazard symbol	None.	
Signal word	Warning	
Hazard statement	Causes mild skin irritation. Causes eye irritation.	
Precautionary statement		
Prevention	Wash skin thoroughly after handling.	
Response	If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse ca for several minutes. Remove contact lenses, if present and easy to do. Cor irritation persists: Get medical advice/attention.	autiously with water htinue rinsing. If eye
Storage	Not applicable.	
Disposal	Not applicable.	
Hazard(s) not otherwise classified (HNOC)	None.	

3. Composition/information on ingredients

Mixtures

The product contains no substances which at their given concentration, are considered to be hazardous to health.

Chemical name Mixed sodium and potassium salts of tall oil (soap)		CAS number	%
		68606-06-4	15 - 25
4. First-aid measure	es		
Inhalation	Remove victim to fresh air and kee attention if symptoms occur.	ep at rest in a position comfortable for	breathing. Get med
Skin contact	Wash off immediately with soap an	nd water. If skin irritation persists, call	a physician.
Oatev Pipe Joint Lubricant			S

Eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Ingestion	Do NOT induce vomiting. Drink plenty of water. Rinse mouth. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation. Prolonged or repeated skin contact may cause irritation.
Indication of immediate medical attention and special treatment needed.	Immediate medical attention is not required.
General information	Note to physician, treat symptomatically.
5. Fire-fighting measures	
Suitable extinguishing media	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water in a jet.
Specific hazards arising from the chemical	No information available.
Special protective equipment and precautions for firefighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Fire fighting equipment/instructions	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Use water spray to keep fire-exposed containers cool. Fire water contaminated with this material must be

contained and prevented from being discharged to any waterway, sewer or drain.

Specific methods General fire hazards

6. Accidental release measures

None

None

Personal precautions, protective equipment and emergency procedures	Avoid contact with the skin and the eyes. Evacuate personnel to safe areas. Use personal protective equipment. Keep people away from and upwind of spill/leak.
Methods and materials for containment and cleaning up	Dike to collect large liquid spills. Prevent leakage or spillage if safe to do so. Dam up. Soak up with inert absorbent material Place the bulk of any spilled material into properly labeled containers. Rinse any remaining material to sewage treatment facility. Clean up in accordance with all applicable regulations.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological information
7. Handling and storage	
Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Do not breathe vapors or spray mist. Ensure adequate ventilation. Use only in area provided with appropriate

exhaust ventilation. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Do not take internally.
Conditions for safe storage, including any incompatibilities
Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in properly labeled containers. Keep out of the reach of children.

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Туре	Value
Biological limit values	Data Not available.	
Appropriate engineering controls	ropriate engineering trolsNo special ventilation requirements. Good general ventilation should be sufficient to con worker exposure to airborne contaminants. If this product contains ingredients with expo	

	limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
Individual protection measures	, such as personal protective equipment
Eye/face protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.
Skin protection	
Hand	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Other	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Thermal hazards	None.
General hygiene considerations	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

9. Physical and chemical properties

Appearance	
Physical state	Liquid
Form	Paste
Color	Off-White
Odor	Slight
Odor threshold	Not available.
рН	9 (5% Solution)
Melting point/freezing point	No data available.
Initial boiling point and boiling	Not determined
range	
Flash point	> 220 °F (> 104°C)
Upper/lower flammability or explose	sive limits
Flammability limit – lower (%)	Not available
Flammability limit – upper (%)	Not available
Explosive limit - lower (%)	Not available
Explosive limit - upper (%)	Not available
Vapor pressure	Not applicable
Vapor density	Not applicable
Relative density	1.2
Solubility(ies)	
Solubility (water)	Completely soluble.
Partition coefficient	
(n-octanol/water)	Not determined.
Auto-ignition temperature	Not applicable
Decomposition temperature	Not available
Viscosity, kinematic	Not determined/
Other information	
VOC (Weight %)	< 1% by weight, < 12 g/L

10. Stability and reactivity

Reactivity	Not reactive under normal conditions
Chemical stability	The product is stable.
Possibility of hazardous reaction	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong Oxidizing Agents.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of exp	oosure		
Inhalation	Not a likely route		
Skin contact	May cause mild skin irritation.		
Eye contact	Causes Eye irritation		
Ingestion	No known significant effects or critical hazards.		
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation. Prolonged or repeated contact may dry skin and cause irritation		
Information on likely routes of exp Acute Toxicity	oosure		
Components	Species	Results	
Skin corrosion/irritation	Prolonged exposure may cause skin irritation.		
Serious eye damage/eye irritation	Expected to be slightly irritating.		
Respiratory or skin sensitization Respiratory sensitization	Inhalation of vapors or mists may cause irritation to the	he respiratory system.	
Skin sensitization	This product is not expected to cause skin irritation.		

No component of this product is identified as a probable, possible, or confirmed carcinogen by

Not considered a mutagenic hazard

IARC, NTP, Monographs, or OSHA.

Not expected to be a hazard.

Not expected to be a hazard.

Not expected to be a hazard

Not Classified.

None Provided.

No known significant effects or critical hazards.

Further information 12. Ecological information

	0
Ecotoxicity	

Germ cell mutagenicity

Reproductive toxicity

Repeated exposure Aspiration Hazard

Single exposure

Chronic effects

Specific target organ toxicity

Carcinogenicity

Product/ingredient name Re	sults Sr	pecies	Exposure
Persistence and degradability	Not Available.		
Bio accumulative potential	Not Available.		
Mobility in soil	Not determined.		
Other adverse effects	No known significant effects of critical ha	izards.	

13. Disposal considerations

Disposal instructions Local disposal regulations	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Not Applicable
Hazardous waste code	Not Applicable
14. Transportation informat	ion

הטי	г
DU	L

Not Regulated

UN number UN Proper Shipping Name Transportation Hazard

classes

Packing group

ΙΑΤΑ

Not Regulated

UN number

UN Proper Shipping Name Transportation Hazard classes Packing group

IMDG

Not Regulated

UN number UN Proper Shipping Name Transportation Hazard classes Packing group Environmental hazards Marine polluntant

15. Regulatory information

U.S. Federal regulations	TSCA 12(b) - Chemical export notification: None required.
-	TSCA 5(a)2 - Final significant new use rules: Not listed
	TSCA 5(a)2 - Proposed significant new use rules: Not listed
	TSCA 5(e) - Substances consent order: Not listed

US Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42): None known

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302): None Known

US state regulations California Prop 65	This product does not contain a chemical known to the defects, or other reproductive harm.	e State of California to cause cancer, birth
International regulations		
Country(s) or region	Inventory Name	On inventory list (yes/no)*
Canada	DSL/NDSL	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA 8b)	Yes

16. Other information, including date of preparation or last revision

Issue Date	12-May-2015
Revision Date	-
Version #	01
HMIS Rating	Health: 1 Flammability: 0 Physical Hazards: 0
Disclaimer	Oatey Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.



SAFETY DATA SHEET

1. Identification

Product identifier	Oatey Plumber's Putty
Other means of identification	
Product code	1705E
Synonyms	Part Numbers: 31166, 31167, 31170, 31174, 48003, 48004
Recommended use	Plumbing Mastic
Recommended restrictions	Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.
Manufacturer/Importer/Supplier/E	Distributor information
Company Name	Oatey Co.
Address	4700 West 160th St.
	Cleveland, OH 44135
Telephone	216-267-7100
E-mail	info@oatev.com
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)
Emergency First Aid	1-877-740-5015
Contact person	MSDS Coordinator
2. Hazard(s) identification	
Physical hazards	Not classified.
Health hazards	Not classified.
OSHA defined hazards	Not classified.
Label elements	
Hazard symbol	None.
Signal word	None.
Hazard statement	The mixture does not meet the criteria for classification.
Precautionary statement	
Prevention	Observe good industrial hygiene practices.
Response	Wash hands after handling.
Storage	Store away from incompatible materials.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
Hazard(s) not otherwise	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

classified (HNOC)

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Limestone	1317-65-3	60-90
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	5-30
Crystalline silica (Quartz)	14808-60-7	<1
Other components below reportable levels		9.85

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
Skin contact	Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. If ingestion of a large amount does occur, call a poison control center immediately.
Most important symptoms/effects, acute and delayed	Coughing.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Use water spray to cool unopened containers.
Specific methods General fire hazards	Use standard firefighting procedures and consider the hazards of other involved materials. No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Stop the flow of material, if this is without risk. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places

Conditions for safe storage, including any incompatibilities

where dust is formed. Do not breathe dust. Avoid prolonged exposure. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	5 mg/m3	Mist.
		2000 mg/m3 500 ppm	
Limestone (CAS 1317-65-3)	PEL	5 mg/m3 15 mg/m3	Respirable fraction. Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Туре	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust.
		0.1 mg/m3	Respirable.
US. ACGIH Threshold Limit	Values		
Components	Туре	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to	o Chemical Hazards		
Components	Туре	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	1800 mg/m3	
,	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Limestone (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
ological limit values	No biological exposure limits noted for the	he ingredient(s).	
kposure guidelines	Occupational exposure to nuisance dus should be monitored and controlled.	t (total and respirable) and re	spirable crystalline silica
opropriate engineering ontrols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.		
dividual protection measures,	such as personal protective equipmen	t	
Eye/face protection	Wear safety glasses with side shields (c	or goggles).	
Skin protection			
Hand protection	Wear appropriate chemical resistant glo	ves.	
Other	Wear suitable protective clothing.		
Respiratory protection	Use a particulate filter respirator for part Exposure Limit.	iculate concentrations excee	ding the Occupational
Thermal hazards	Wear appropriate thermal protective clo	thing, when necessary.	
eneral hygiene onsiderations	Always observe good personal hygiene and before eating, drinking, and/or smol equipment to remove contaminants.	measures, such as washing king. Routinely wash work clo	after handling the material othing and protective

9. Physical and chemical properties

-	• •
Appearance	
Physical state	Solid.
Form	Putty.
Color	Off-white.
Odor	Slight.
Odor threshold	Not available.
рН	Not applicable
Melting point/freezing point	Not available.

Initial boiling point and boiling range	Not determined
Flash point	> 212.0 °F (> 100.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or expl	osive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	1.87
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	> 500000 cP
Other information	
VOC (Weight %)	20 g/l

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Acids. Fluorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure		
Inhalation	Prolonged inhalation may be harmful.	
Skin contact	No adverse effects due to skin contact are expected.	
Eye contact	Direct contact with eyes may cause temporary irritation.	
Ingestion	Expected to be a low ingestion hazard.	
Symptoms related to the physical, chemical and toxicological characteristics	Coughing.	
Information on toxicological effects		
Acute toxicity	Not available.	
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	

Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) Risk of cancer cannot be excluded with prolonged exposure.		
IARC Monographs. Overall E	valuation of Carcinogenicity		
Crystalline silica (Quartz) (CAS 14808-60-7) Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)		1 Carcinogenic to humans. 3 Not classifiable as to carcinogenicity to humans.	
NIP Report on Carcinogens		Kanan Ta Da Ukuman Ormina nan	
OSHA Specifically Regulated	Substances (29 CFR 1910.10	Nown To Be Human Carcinogen. 001-1050)	
Not listed.			
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.		
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not an aspiration hazard.		
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.		
Further information	This product has no known adverse effect on human health.		
12. Ecological information			
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.		
Persistence and degradability	No data is available on the degradability of this product.		
Bioaccumulative potential			
Mobility in soil	No data available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		
13. Disposal consideration	S		
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site.		
Local disposal regulations	Dispose in accordance with all applicable regulations.		
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.		

Waste from residues / unused
productsDispose of in accordance with local regulations. Empty containers or liners may retain some
product residues. This material and its container must be disposed of in a safe manner (see:
Disposal instructions).Contaminated packagingEmpty containers should be taken to an approved waste handling site for recycling or disposal.
Since emptied containers may retain product residue, follow label warnings even after container is

14. Transport information

DOT

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to
Annex II of MARPOL 73/78 and
the IBC CodeNot applicable.

emptied.

15. Regulatory information

US federal regulations This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) Not regulated. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not listed. CERCLA Hazardous Substance List (40 CFR 302.4) Not listed. Superfund Amendments and Reauthorization Act of 1986 (SARA) Hazard categories Immediate Hazard - No **Delayed Hazard - No** Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No SARA 302 Extremely hazardous substance Not listed SARA 311/312 Hazardous No chemical SARA 313 (TRI reporting) Not regulated. Other federal regulations Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Not regulated. Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) Not regulated. Safe Drinking Water Act Not regulated. (SDWA) US state regulations **US. Massachusetts RTK - Substance List** Crystalline silica (Quartz) (CAS 14808-60-7) Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Limestone (CAS 1317-65-3) US. New Jersey Worker and Community Right-to-Know Act Crystalline silica (Quartz) (CAS 14808-60-7) Limestone (CAS 1317-65-3) US. Pennsylvania Worker and Community Right-to-Know Law Crystalline silica (Quartz) (CAS 14808-60-7) Limestone (CAS 1317-65-3) **US. Rhode Island RTK** Not regulated. **US.** California Proposition 65 WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm. US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance Crystalline silica (Quartz) (CAS 14808-60-7) Methanol (CAS 67-56-1) International Inventories Country(s) or region Inventory name On inventory (yes/no)* United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes *A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision 22-April-2015

Issue date

Revision date Version # HMIS® ratings

NFPA ratings

01 Health: 0 Flammability: 0 Physical hazard: 0



Disclaimer

Oatey Co. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

SAFETY DATA SHEET

1. Identification

Product identifier	Oatey Purple Primer Cleaner			
Other means of identification				
Product code	1401E			
Synonyms	Part Numbers: 30780, 30783, 30796, 30768, 30806, 30769			
Recommended use	Joining PVC Pipes			
Recommended restrictions	None known.			
Manufacturer/Importer/Supplier/Distributor information				
Company Name	Oatey Co.			
Address	4700 West 160th St.			
	Cleveland, OH 44135			
Telephone	216-267-7100			
E-mail	info@oatey.com			
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)			
Emergency First Aid	1-877-740-5015			
Contact person	MSDS Coordinator			

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
OSHA defined hazards	Not classified.	

OSHA defined hazards

Label elements



Signal word	Danger
Hazard statement	Highly flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear eye protection/face protection. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If swallowed: Immediately call a poison center/doctor. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. Rinse mouth. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.
Supplemental information

Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Acetone	67-64-1	70-100
Cyclohexanone	108-94-1	1-5

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Call a physician or poison control center immediately. Do not induce vomiting. Aspiration may cause pulmonary edema and pneumonitis. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor. This product contains tetrahydrofuran that may form explosive organic peroxide when exposed to air or light or with age.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water.
	Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components		Туре			Value	
Acetone (CAS 67-64-1)		PEL		2400 mg/m3		
					1000 ppm	
Cyclohexanone (CAS		PEL			200 mg/m3	
108-94-1)						
					50 ppm	
US. ACGIH Threshold Li	imit Values					
Components		Туре			Value	
Acetone (CAS 67-64-1)		STEL			750 ppm	
		TWA			500 ppm	
Cyclohexanone (CAS 108-94-1)		STEL			50 ppm	
		TWA			20 ppm	
US. NIOSH: Pocket Guid	le to Chemical Haz	zards				
Components		Туре			Value	
Acetone (CAS 67-64-1)		TWA			590 mg/m3	
					250 ppm	
Cyclohexanone (CAS 108-94-1)		TWA		100 mg/m3		
					25 ppm	
ological limit values						
ACGIH Biological Expos	sure Indices					
Components	Value		Determinant	Specimen	Sampling Time	
Acetone (CAS 67-64-1)	50 mg/l		Acetone	Urine	*	

ACGIH Biological Exposure Indices

	Components	Value	Determinant	Specimen	Sampling Time
	Cyclohexanone (CAS 108-94-1)	80 mg/l	1,2-Cyclohexan ediol, with hydrolysis	Urine	*
		8 mg/l	Cyclohexanol, with hydrolysis	Urine	*
	* - For sampling details, plea	ase see the source docu	iment.		
Exp	oosure guidelines				
	US - California OELs: Skir	designation			
	Cyclohexanone (CAS 1	08-94-1)	Can be	absorbed thro	ugh the skin.
	US - Minnesota Haz Subs:	Skin designation appl	lies		
	Cyclohexanone (CAS 1	08-94-1)	Skin des	signation appli	es.
US - Tennessee OELs: Skin designation					
	Cyclohexanone (CAS 1 US ACGIH Threshold Limi	08-94-1) <mark>t Values: Skin design</mark> a	tion	absorbed thro	ugh the skin.
	Cyclohexanone (CAS 1 US. NIOSH: Pocket Guide	08-94-1) to Chemical Hazards	Can be	absorbed thro	ugh the skin.
	Cyclohexanone (CAS 1	08-94-1)	Can be	absorbed thro	ugh the skin.
Appropriate engineering controls Explosion-proof general and loc changes per hour) should be us applicable, use process enclosu maintain airborne levels below r established, maintain airborne li shower must be available when		eral and local exhau hould be used. Ven ess enclosures, loca vels below recomme n airborne levels to ilable when handlin	ust ventilation. tilation rates sl al exhaust ven ended exposu an acceptable g this product.	Good general ventilation (typically 10 air nould be matched to conditions. If tilation, or other engineering controls to re limits. If exposure limits have not been level. Eye wash facilities and emergency	
Ind	ividual protection measure	s, such as personal pr	otective equipmen	t	
	Eye/face protection	Chemical respirator	with organic vapor	cartridge and f	ull facepiece.
	Skin protection				
	Hand protection	Wear appropriate ch supplier.	nemical resistant glo	oves. Suitable	gloves can be recommended by the glove
	Other	Wear appropriate ch	nemical resistant clo	thing.	
	Respiratory protection	Chemical respirator	with organic vapor	cartridge and f	ull facepiece.
	Thermal hazards	Wear appropriate thermal protective clothing, when necessary.			cessary.
Gei cor	neral hygiene nsiderations	When using, do not as washing after har wash work clothing a	eat, drink or smoke ndling the material a and protective equip	Always obser and before eati oment to remov	ve good personal hygiene measures, such ng, drinking, and/or smoking. Routinely ve contaminants.

9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Translucent liquid.
Color	Purple
Odor	Solvent.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	133 °F (56.11 °C)
Flash point	-4.0 °F (-20.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or expl	osive limits
Flammability limit - lower (%)	Not available.

Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	145 mm Hg @ 20 C
Vapor density	2.5
Relative density	0.79 +/- 0.02
Solubility(ies)	
Solubility (water)	Miscible
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	< 10 cP
Other information	
Bulk density	7 lb/gal
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
VOC (Weight %)	180 g/I SQACMD Method 24

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Ammonia. Amines. Isocyanates. Caustics.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May be fatal if swallowed and enters airways. Headache. Nausea, vomiting. May cause irritation to the respiratory system. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Ingestion	May be fatal if swallowed and enters airways. Harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. May cause redness and pain.

Information on toxicological effects

Acute toxicity

May be fatal i	if swallowed and	enters airways.	Narcotic effects.	May c	ause respiratory irr	itation.
,		,			1 2	

Components	Species	Test Results	
Acetone (CAS 67-64-1)			
Acute			
Dermal LD50	Rabbit	20 ml/kg	
Inhalation LC50	Rat	50 mg/l, 8 Hours	

Components	Species		Test Results			
Oral						
LD50	Rat		5800 mg/kg			
Cyclohexanone (CAS 108-94-1)						
Acute						
Dermal						
LD50	Rabbit		948 mg/kg			
Inhalation			0000 41			
LC50	Rat		8000 ppm, 4 hours			
Oral	Det					
LD50	Rat		1540 mg/kg			
* Estimates for product may b	e based on add	itional component data not shown.				
Skin corrosion/irritation	Causes skin i	rritation.				
Serious eye damage/eye irritation	Causes seriou	us eye irritation.				
Respiratory or skin sensitization	n					
Respiratory sensitization	Not a respirate	ory sensitizer.				
Skin sensitization	This product is	s not expected to cause skin sensitization	on.			
Germ cell mutagenicity	No data availa mutagenic or	able to indicate product or any compone genotoxic.	nts present at greater than 0.1% are			
Carcinogenicity	This product is	s not considered to be a carcinogen by	IARC, ACGIH, NTP, or OSHA.			
IARC Monographs. Overall	Evaluation of C	arcinogenicity				
Cyclohexanone (CAS 10	8-94-1)	3 Not classifiable as to	o carcinogenicity to humans.			
OSHA Specifically Regulate	ed Substances ((29 CFR 1910.1001-1050)				
Not listed.			· · · · · · · · · · · · · · · · · · ·			
Reproductive toxicity	This product is	s not expected to cause reproductive or	developmental effects.			
Specific target organ toxicity - single exposure	Narcotic effec	Narcotic effects. May cause drowsiness and dizziness. Respiratory tract irritation.				
Specific target organ toxicity - repeated exposure	Not classified.					
Aspiration hazard	May be fatal if	swallowed and enters airways.				
Chronic effects	Prolonged inh	alation may be harmful.				
12 Ecological information	`					
Fostovisity	The product is	a not classified as any ironmontally baza	rdous. However, this does not exclude the			
Ecoloxicity	possibility that	t large or frequent spills can have a harr	nful or damaging effect on the environment.			
Components		Species	Test Results			
Acetone (CAS 67-64-1)						
Aquatic						
Fish	LC50	Fathead minnow (Pimephales promela	as) > 100 mg/l, 96 hours			
Cyclohexanone (CAS 108-94-	-1)					
Aquatic						
Fish	LC50 Fathead minnow (Pimephales promelas) 481 - 578 mg/l, 96 hours					
* Estimates for product may b	e based on add	itional component data not shown				
Persistence and degradability No data is available on the degradability of this product						
Bioaccumulative potential	No data available.					
Partition coefficient n-octan Acetone (CAS $67-64-1$)	nol / water (log	Kow)				
Cyclohexanone (CAS 108-94-	-1)	0.81				
Mobility in soil	No data available.					
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component					

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT			
UN number	UN1993		
UN proper shipping name	Flammable liquids, n.o.s. (Acetone RQ = 5128 LBS)		
Transport hazard class(es)			
Class	3		
Subsidiary risk	-		
Label(s)	3		
Packing group	1		
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.		
Special provisions	IB2, T7, TP1, TP8, TP28		
Packaging exceptions	150		
Packaging non bulk	202		
Packaging bulk	242		
ΙΑΤΑ			
UN number	UN1993		
UN proper shipping name	Flammable liquid, n.o.s. (Acetone)		
Transport hazard class(es)			
Class	3		
Subsidiary risk	-		
Packing group	II		
Environmental hazards	No.		
ERG Code	3H		
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.		
IMDG			
UN number	UN1993		
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (Acetone)		
Transport hazard class(es)			
Class	3		
Subsidiary risk			
Packing group	11		
Environmental hazards			
Marine pollutant	No.		
EmS	F-E, S-E		
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.		
Transport in bulk according to	Not established.		
Annex II of MARPOL 73/78 and			

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication
-	Standard, 29 CFR 1910.1200.
	All components are on the U.S. EPA TSCA Inventory List.

Not regulated. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not listed. CERCLA Hazardous Substance List (40 CFR 302.4) Acetone (CAS 67-64-1) LISTED Cyclohexanone (CAS 108-94-1) LISTED Superfund Amendments and Reauthorization Act of 1986 (SARA) Hazard categories Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - No Fire Hazard - No Reactivity Hazard - No Reactivity Hazard - No Reactivity Hazard - No Reactivity Hazard - No SARA 302 Extremely hazard-us substance Not listed. SARA 311/312 Hazardous No chemical SARA 313 (TRI reporting) Not regulated.	
Not listed. CERCLA Hazardous Substance List (40 CFR 302.4) Acetone (CAS 67-64-1) LISTED Cyclohexanone (CAS 108-94-1) LISTED Superfund Amendments and Reacthorization Act of 1986 (SARA) Hazard categories Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - No Fire Hazard - No Reactivity Hazard - No Reacti	
Acetone (CAS 67-64-1) LISTED Cyclohexanone (CAS 108-94-1) LISTED Superfund Amendments and Reauthorization Act of 1986 (SARA) Hazard categories Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Reactivity Hazard - No Not listed. SARA 311/312 Hazardous No chemical SARA 313 (TRI reporting) Not regulated.	
Cyclohexanone (CAS 108-94-1) LISTED Superfund Amendments and Reauthorization Act of 1986 (SARA) Hazard categories Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Reactivity Hazard - No Reactivity Hazard - No Reactivity Hazard - No SARA 302 Extremely hazardous substance Not listed. SARA 311/312 Hazardous No chemical SARA 313 (TRI reporting) Not regulated.	
Superfund Amendments and Reathorization Act of 1986 (SARA) Hazard categories Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No SARA 302 Extremely hazardous Not listed. No SARA 311/312 Hazardous chemical No SARA 313 (TRI reporting) Not regulated. No	
Hazard categories Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No SARA 302 Extremely hazardous substance Not listed. No SARA 311/312 Hazardous No chemical No SARA 313 (TRI reporting) Not regulated. No	
SARA 302 Extremely hazardous substance Not listed. SARA 311/312 Hazardous No chemical SARA 313 (TRI reporting) Not regulated.	
Not listed. SARA 311/312 Hazardous No chemical SARA 313 (TRI reporting) Not regulated.	
SARA 311/312 Hazardous No chemical SARA 313 (TRI reporting) Not regulated.	
SARA 313 (TRI reporting) Not regulated.	
Other federal regulations	
Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List	
Not regulated. Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)	
Not regulated.	
Safe Drinking Water Act Not regulated. (SDWA)	
Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number	
Acetone (CAS 67-64-1) 6532	
Acetone (CAS 67-64-1) 35 %WV	
DEA Exempt Chemical Mixtures Code Number	
Acetonie (CAS 67-64-1) 6552	
US Massachusetts RTK - Substance List	
Acetone (CAS 67-64-1) Cyclohexanone (CAS 108-94-1)	
US. New Jersey Worker and Community Right-to-Know Act	
Cyclohexanone (CAS 108-94-1) US. Pennsylvania Worker and Community Right-to-Know Law	
Acetone (CAS 67-64-1)	
Cyclohexanone (CAS 108-94-1) US. Rhode Island RTK	
Acetone (CAS 67-64-1) Cyclohexanone (CAS 108-94-1)	
US. California Proposition 65 California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to con any chemicals currently listed as carcinogens or reproductive toxins.	tain
International Inventories	
Country(s) or region Inventory name On inventory (yes/no)*
Australia Australian Inventory of Chemical Substances (AICS)	Yes
Canada Domestic Substances List (DSL)	Yes
Canada Non-Domestic Substances List (NDSL)	No
China Inventory of Existing Chemical Substances in China (IECSC)	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	27-May-2015
Revision date	-
Version #	01
HMIS® ratings	Health: 2 Flammability: 3 Physical hazard: 0
Disclaimer	The information in the sheet was written based on the best knowledge and experience currently available. Oatey Co. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.



SAFETY DATA SHEET

1. Identification	
Product identifier	Oatey Silicone Sealant – White or Clear
Other means of identification	
Product code	
Synonyms	Part Numbers: Clear – 30236, White - 30237
Recommended use	Sealant for use around tubs, sinks and other plumbing applications.
Recommended restrictions	Do not use on applications where product will be submerged under water.
Manufacturer/Importer/Supplier/	Distributor information
Company Name	Oatey Inc.
Address	4700 West 160th Street
	Cleveland, OH 44135
Telephone	216-267-7100
E-mail	info@oatey.com
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)
Emergency First Aid	1-877-740-5015
Contact person	MSDS Coordinator
2. Hazard(s) identification	
Physical hazards	Not Classified.
Health hazards	Not Classified.
OSHA defined hazards	Not Classified.
Label elements	
Hazard symbol	None.
Signal word	None.
Hazard statement	This product was determined to be non-hazardous.
Precautionary statement	
Prevention	Use outdoors or in a well ventilated area.
Response	Not applicable.
Storage	Not applicable.
Disposal	Not applicable.
Hazard(s) not otherwise classified (HNOC)	None known.

3. Composition/information on ingredients

Mixtures

Inhalation

Chemical name	CAS number	%
Silicon Dioxide	7631-86-9	5 - 10
Distillates (petroleum), hydrotreated middle	64742-46-7	5 - 10
Titanium Dioxide (White Sealant Only)	13463-67-7	0 – 5
Dimethyl siloxane, hydroxyl terminated	70131-67-8	70 - 90

4. First-aid measures

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.

Skin contact	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Ingestion	Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Skin or eye irritation.
Indication of immediate medical attention and special treatment needed.	Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
General information	Note to physician, treat symptomatically.
5. Fire-fighting measures	
Cuitable autinautiable a media	
Suitable extinguishing media	Use dry chemical, CO2, alcohol-resistant foam or water spray (fog).
Unsuitable extinguishing media	Use dry chemical, CO2, alcohol-resistant foam or water spray (fog). water jet
Unsuitable extinguishing media Specific hazards arising from the chemical	Use dry chemical, CO2, alcohol-resistant foam or water spray (fog). water jet No specific fire or explosion hazard.
Unsuitable extinguishing media Specific hazards arising from the chemical Special protective equipment and precautions for firefighters	Use dry chemical, CO2, alcohol-resistant foam or water spray (fog). water jet No specific fire or explosion hazard. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Unsuitable extinguishing media Unsuitable extinguishing media Specific hazards arising from the chemical Special protective equipment and precautions for firefighters Fire fighting equipment/instructions	Use dry chemical, CO2, alcohol-resistant foam or water spray (fog). water jet No specific fire or explosion hazard. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Use water spray to keep fire-exposed containers cool. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Unsuitable extinguishing media Specific hazards arising from the chemical Special protective equipment and precautions for firefighters Fire fighting equipment/instructions	Use dry chemical, CO2, alcohol-resistant foam or water spray (fog). water jet No specific fire or explosion hazard. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Use water spray to keep fire-exposed containers cool. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. None

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	
Methods and materials for containment and cleaning up	Large Spills: Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal. Small Spills: Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.	
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).	
7. Handling and storage		
Precautions for safe handling	For the personal protective equipment (see section 8 of SDS). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.	
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Keep container tightly closed and sealed until ready for use.	

Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Туре	Value
Petroleum Distillate	TWA	5 mg/m3
Titanium Dioxide	TWA	10 mg/m3

US OSHA Permissible Exposure Limits

Components	Туре	Value
Petroleum Distillate	TWA	5 mg/m3
Titanium Dioxide	TWA	15 mg/m3
Silicone Dioxide	TWA	80 mg/m3

Biological limit values	No Biological limits.
Appropriate engineering controls	No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
Individual protection measures,	such as personal protective equipment
Eye/face protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.
Skin protection	
Hand	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Other	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Thermal hazards	None.
General hygiene considerations	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

9. Physical and chemical properties

Solid.
Paste
White or translucent.
Acetic acid/vinegar smell
Not available.
Not applicable.
Not applicable.
Not determined
> 199 °F (> 93.3 °C)
sive limits
Not available
Not available
Not available
Not available
Not applicable

Oatey Silicone Sealant White and Clear

SDS # Version #: 01 Revision date: Issue date: 12-May-2015

Vapor density	Not applicable
Relative density	1.04 – 1.09
Solubility(ies)	
Solubility (water)	Not available
Partition coefficient	
(n-octanol/water)	Not available
Auto-ignition temperature	Not applicable
Decomposition temperature	Not available
Viscosity	Not available
Other information	
VOC (Weight %)	28 g/L (< 3.0% by weight)

10. Stability and reactivity

Reactivity	Stable under normal conditions.
Chemical stability	The product is stable.
Possibility of hazardous reaction	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	No specific data.
Incompatible materials	No specific data.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Information on likely routes of e	xposure
Inhalation	Acute Toxicity estimates: > 10 mg/l
	Exposure time: 4 h
	Test atmosphere: dust/mist
	Method: Calculation.
Skin contact	No known significant effects or critical hazards.
Eye contact	No known significant effects or critical hazards.
Ingestion	No known significant effects or critical hazards.
Symptoms related to the physical, chemical and toxicological characteristics	No specific data.
Information on likely routes of e Acute Toxicity	xposure

, , , , , , , , , , , , , , , , , , ,			
Components	Species	Results	
Silicone Dioxide			
Acute Oral Toxicity	Rat LD(50)	3,300 mg/kg	
Acute Inhalation Toxicity	Rat LD(50)	2.08 mg/l	
Distillates (petroleum			

Skin corrosion/irritation	Not determined.	
Serious eye damage/eye irritation	Not determined.	
Respiratory or skin sensitization Respiratory sensitization	Not considered a respiratory irritant	
Skin sensitization	This product is not expected to cause skin irritation.	
Germ cell mutagenicity	No specific data	
Carcinogenicity	Sufficient evidence of carcinogenicity in inhalation studies with animals for titanium dioxide exist. However, due to the titanium dioxide being inextricably bound in the silicone matrix, the likelihood of exposure is minimal.	
IARC	Titanium Dioxide – 13463-67-7 Group 2B: Possibly carcinogenic to humans.	
OSHA	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcino- gen by OSHA.	
NTP	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcino- gen by OSHA.	

Reproductive toxicity	No known significant effects or cri	tical hazards.	
Specific target organ toxicity	Not Clossified		
Single exposure Repeated exposure	Not Classified.		
Aspiration Hazard	Contains Distillates (petroleum), h likely hood of aspirating the produ	ydrotreated – Which is a category 1 Aspir	ation Hazard. The /iscosity.
Chronic effects	Not Classified.	, , , , , , , , , , , , , , , , , , , ,	, , , , , , , , , , , , , , , , , , ,
Further information			
12. Ecological informati	on		
Ecotoxicity			
Product/ingredient name	Results	Species	Exposure
Petroleum Distillates			
	Acute LC50 2,900 μg/l Fresh water	Fish - Rainbow trout,Donaldson trout	96 h
	Acute LC50 2,200 µg/l Fresh water	Fish - Bluegill	96 h
Persistence and degradabilit	y Not Available.		
Bio accumulative potential	Not Available.		

No known significant effects of critical hazards.

13. Disposal considerations

Other adverse effects

Disp	osal instructions	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Loca	l disposal regulations	Not Applicable
Haza	rdous waste code	Not Applicable
14	Fransportation informat	ion
DOT		Not Regulated
	UN number	
	UN Proper Shipping Name	
	Transportation Hazard classes	
	Packing group	
ΙΑΤΑ		Not Regulated
	UN number	
	UN Proper Shipping Name	
	Transportation Hazard classes	
	Packing group	
IMDO	ì	Not Regulated
	UN number	
	UN Proper Shipping Name	
	Transportation Hazard classes	
	Packing group	
	Environmental hazards	
Oata	Ciliaana Caalant White and Clear	

15. Regulatory information

U.S. Federal regulations	TSCA 12(b) - Chemical export notification: None required. TSCA 5(a)2 - Final significant new use rules: Not listed TSCA 5(a)2 - Proposed significant new use rules: Not listed TSCA 5(e) - Substances consent order: Not listed	
SARA 311/312		
Classification	Not applicable	
US state regulations California Prop 65	This product does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.	
Canada		
WHMIS (Canada)	Not classified.	
International regulations		
Country(s) or region	Inventory Name	On inventory list (yes/no)*
Canada	DSL/NDSL	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA 8b)	Yes
16. Other information, incl	uding date of preparation or last revision	
Issue Date	12-May-2015	
Revision Date	-	
Version #	01	
HMIS Rating	Health: 1 Flammability: 1 Physical Hazards: 0	
Disclaimer	Oatey Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.	



SAFETY DATA SHEET

1. Identification		
Product identifier	Oatey Tub-N-Tile Ultra Clear Sealant	
Other means of identification		
Product code		
Synonyms	Part Numbers: 30235	
Recommended use	Caulk and sealant for use around tubs, sinks and other plumbing application	IS.
Recommended restrictions	Do not use on applications where product will be submerged under water.	
Manufacturer/Importer/Supplier/	Distributor information	
Company Name	Oatey Inc.	
Address	4700 West 160th Street	
	Cleveland, OH 44135	
Telephone	216-267-7100	
E-mail	info@oatey.com	
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)	
Emergency First Aid	1-877-740-5015	
Contact person	MSDS Coordinator	
2. Hazard(s) identification		
Physical hazards	Not Classified.	
Health hazards	Acute Oral Toxicity	Cat 5
	Eye Irritation	Cat 2B
	Skin Irritation	Cat 3
OSHA defined hazards	Not Classified.	
Label elements		
Hazard symbol	None.	
Signal word	Warning	
Hazard statement	May be harmful if swallowed. Causes mild skin irritation. Causes eye irrita	ation
Precautionary statement		
Prevention	Wash Thoroughly after handling. Wear protective gloves and eye protection	on.
Response	If skin irritation occurs: Get medical advice. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.	
Storage	Not applicable.	
Disposal	Not applicable.	
Hazard(s) not otherwise classified (HNOC)	Uncured product is irritating to eyes, skin and respiratory system.	

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Acrylic Emulsion	Mixture	75 - 95
Acrylic Thickener	Mixture	1 - 5
Propylene Glycol	57-55-6	1 - 2
Petroleum Distillate	64742-48-9	0.1 - 1
Non Hazardous Ingredients	Mixture	< 5%

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Ingestion	Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Skin or eye irritation.
Indication of immediate medical attention and special treatment needed.	Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
General information	Note to physician, treat symptomatically.
5. Fire-fighting measures	
Suitable extinguishing media	Use dry chemical, CO2, alcohol-resistant foam or water spray (fog).
Unsuitable extinguishing media	water jet
Specific hazards arising from the chemical	No specific fire or explosion hazard.
Special protective equipment and precautions for firefighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Fire fighting equipment/instructions	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Use water spray to keep fire-exposed containers cool. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Specific methods	None

Specific methods General fire hazards

6. Accidental release measures

None

Personal precautions, protective equipment and emergency procedures	Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Methods and materials for containment and cleaning up	Large Spills: Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal. Small Spills: Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
7. Handling and storage	
Precautions for safe handling	Put on appropriate personal protective equipment (see section 8 of SDS). Eating, drinking and

	smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash bands and face before eating, drinking and smoking. See also Section 8
Conditions for safe storage,	for additional information on hygiene measures. Store in accordance with local regulations. Store in original container protected from direct
	sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10
Oatey Tun-N-Tile Ultra Clear Sealant	SDS US

of SDS) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Туре	Value
Petroleum Distillate	TWA	5 mg/m3
US OSHA Permissible Exposure Limits		
Components	Туре	Value
Petroleum Distillate	TWA	5 mg/m3

Biological limit values	No Biological limits.
Appropriate engineering controls	No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
Individual protection measures,	such as personal protective equipment
Eye/face protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.
Skin protection	
Hand	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Other	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Thermal hazards	None.
General hygiene considerations	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

9. Physical and chemical properties

Appearance	
Physical state	Solid.
Form	Paste
Color	Applies white, dries clear.
Odor	Mild Acrylic, slight ammonia
Odor threshold	Not available.
рН	7 - 10
Melting point/freezing point	Not applicable.
Initial boiling point and boiling	Not determined
range	
Flash point	> 199 °F (> 93.3 °C)
Upper/lower flammability or explo	sive limits
Flammability limit – lower (%)	Not available
Flammability limit – upper (%)	Not available
Explosive limit - lower (%)	Not available
Explosive limit - upper (%)	Not available
Vapor pressure	Not applicable
Vapor density	Not applicable
Relative density	1.04 – 1.08

Oatey Tun-N-Tile Ultra Clear Sealant

Solubility(ies)	
Solubility (water)	Not available
Partition coefficient	
(n-octanol/water)	Not available
Auto-ignition temperature	Not applicable
Decomposition temperature	Not available
Viscosity	Not available
Other information	
VOC (Weight %)	0.5% or 10 g/L

10. Stability and reactivity

Reactivity	Stable under normal conditions.
Chemical stability	The product is stable.
Possibility of hazardous reaction	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	No specific data.
Incompatible materials	No specific data.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

InhalationNo known significant effects or critical hazards.Skin contactNo known significant effects or critical hazards.Eye contactNo known significant effects or critical hazards.IngestionNo known significant effects or critical hazards.Symptoms related to the physical, chemical and toxicological characteristicsNo specific data.Information on likely routes of exposure Acute ToxicityNo known significant effects or critical hazards.	Information on likely routes of ex	cposure	
Skin contactNo known significant effects or critical hazards.Eye contactNo known significant effects or critical hazards.IngestionNo known significant effects or critical hazards.Symptoms related to the physical, chemical and toxicological characteristicsNo specific data.Information on likely routes of exposure Acute ToxicitySuppose of exposure Acute Toxicity	Inhalation	No known significant effects or critical hazards.	
Eye contactNo known significant effects or critical hazards.IngestionNo known significant effects or critical hazards.Symptoms related to the physical, chemical and toxicological characteristicsNo specific data.Information on likely routes of exposure Acute ToxicitySecond Second Sec	Skin contact	No known significant effects or critical hazards.	
IngestionNo known significant effects or critical hazards.Symptoms related to the physical, chemical and toxicological characteristicsNo specific data.Information on likely routes of exposure Acute ToxicityAcute Toxicity	Eye contact	No known significant effects or critical hazards.	
Symptoms related to the No specific data. physical, chemical and Information on likely routes of exposure Acute Toxicity No specific data.	Ingestion	No known significant effects or critical hazards.	
Information on likely routes of exposure Acute Toxicity	Symptoms related to the physical, chemical and toxicological characteristics	No specific data. s	
	Information on likely routes of exposure Acute Toxicity		
Components Species Results	Components	Species	Results

Skin corrosion/irritation	Not determined.	Not determined.	
Serious eye damage/eye irritation	Not determined.		
Respiratory or skin sensitization Respiratory sensitization	on Not considered a respiratory irritant		
Skin sensitization	This product is not expected to cause	se skin irritation.	
Germ cell mutagenicity	No specific data		
Carcinogenicity	No known significant effects or critic	cal hazards.	
Reproductive toxicity	No known significant effects or critic	cal hazards.	
Specific target organ toxicity			
Single exposure Repeated exposure	Not Classified. Not Classified.		
Aspiration Hazard	Contains Distillates (petroleum), hyd likely hood of aspirating the product	drotreated – Which is a category 1 A t in this form is very low due to the hi	spiration Hazard. The gh viscosity.
Chronic effects	Not Classified.	2	0 7
Further information			
12. Ecological information			
Ecotoxicity			
Product/ingredient name F	Results	Species	Exposure
Petroleum Distillates			
A	Acute LC50 2,900 µg/l Fresh water	Fish - Rainbow trout, Donaldson t	rout 96 h

96 h

Persistence and degradability	Not Available.
Bio accumulative potential	Not Available.
Mobility in soil	Not available.
Other adverse effects	No known significant effects of critical hazards.
Other adverse effects	No known significant effects of critical hazards.

13. Disposal considerations

Disposal instruction	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Local disposal regul	ations Not Applicable
	de Not Applicable
14. Transportatio	on information
DOT	Not Regulated
UN number	
UN Proper Shi Transportation classes	oping Name Hazard
Packing group	
	Not Regulated
UN number	
Transportation classes	Hazard
Packing group	
IMDG	Not Regulated
UN number	
UN Proper Shij Transportation classes Packing group Environmental	oping Name Hazard hazards
Marine pollu	ntant
15. Regulatory ir	formation
U.S. Federal regulati	ons TSCA 12(b) - Chemical export notification: None required. TSCA 5(a)2 - Final significant new use rules: Not listed TSCA 5(a)2 - Proposed significant new use rules: Not listed TSCA 5(e) - Substances consent order: Not listed
SARA 311/312	
Classification	Not applicable
US state regulations California Prop 65	This product does not contain any Prop 65 chemicals.

Canada		
WHMIS (Canada)	Not classified.	
International regulations		
Country(s) or region	Inventory Name	On inventory list (yes/no)*
Canada	DSL/NDSL	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA 8b)	Yes
16. Other information, inclu	iding date of preparation or last revision	
Issue Date	12-May-2015	
Revision Date	-	
Version #	01	
HMIS Rating	Health: 1 Flammability: 1 Physical Hazards: 0	
Disclaimer	Oatey Inc. cannot anticipate all conditions under which this in and its product, or the products of other manufacturers in con- used. It is the user's responsibility to ensure safe conditions for the product, and to assume liability for loss, injury, damage or information in the sheet was written based on the best knowle available.	formation nbination with its product, may be or handling, storage and disposal of r expense due to improper use. The edge and experience currently



SAFETY DATA SHEET

1. Identification

Product identifier	PVC Regular Clear Cement	
Other means of identification		
Product code	1100E	
Synonyms	Part Numbers: 31012, 31013, 31014, 31015, 3	1016, 31958, 31959, 31960, 31961
Recommended use	Joining PVC Pipes	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/I	Distributor information	
Company Name	Oatey Co.	
Address	4700 West 160th St.	
	Cleveland, OH 44135	
Telephone	216-267-7100	
E-mail	info@oatey.com	
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the U	S 1-703-527-3887)
Emergency First Aid	1-877-740-5015	
Contact person	MSDS Coordinator	
2. Hazard(s) identification		
Physical hazards	Flammable liquids	Category 2
Llealth hazarda	A outo tovicity, oral	Cotogon/ 4

, , , , , , , , , ,	1	5 ,
Health hazards	Acute toxicity, oral	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
OSHA defined hazards	Not classified.	
Label elements		
Signal word	Danger	
Hazard statement	Highly flammable liquid and vapor. Harmful if s airways. Causes skin irritation. Causes serious cause drowsiness or dizziness.	swallowed. May be fatal if swallowed and enters s eye irritation. May cause respiratory irritation. May
Precautionary statement		
Prevention	Keep away from heat/sparks/open flames/hot closed. Ground/bond container and receiving e electrical/ventilating/lighting equipment. Use of measures against static discharge. Avoid brea handling. Do not eat, drink or smoke when usin well-ventilated area. Wear protective gloves/pr	surfaces No smoking. Keep container tightly equipment. Use explosion-proof nly non-sparking tools. Take precautionary thing mist or vapor. Wash thoroughly after ng this product. Use only outdoors or in a rotective clothing/eye protection/face protection.
Response	If swallowed: Immediately call a poison center, contaminated clothing. Rinse skin with water/s keep comfortable for breathing. If in eyes: Rins Remove contact lenses, if present and easy to you feel unwell. Rinse mouth. Do NOT induce advice/attention. If eye irritation persists: Get n clothing and wash before reuse. In case of fire	/doctor. If on skin (or hair): Take off immediately all shower. If inhaled: Remove person to fresh air and se cautiously with water for several minutes. o do. Continue rinsing. Call a poison center/doctor if vomiting. If skin irritation occurs: Get medical nedical advice/attention. Take off contaminated s: Use appropriate media to extinguish.
DVC Begular Clear Comont		SDS 11

Storage

Disposal Hazard(s) not otherwise classified (HNOC)

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May form explosive peroxides. Contains a chemical classified by the US EPA as a suspected possible carcinogen.

Supplemental information

Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Methyl ethyl ketone	78-93-3	25-40
Cyclohexanone	108-94-1	10-25
Furan, Tetrahydro-	109-99-9	10-25
Acetone	67-64-1	5-15
Polyvinyl chloride	9002-86-2	5-15

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Take off immediately all contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.
Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.
Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Skin irritation. May cause redness and pain.
Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).
Do not use water jet as an extinguisher, as this will spread the fire.
Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Use standard firefighting procedures and consider the hazards of other involved materials.
Highly flammable liquid and vapor. This product contains tetrahydrofuran that may form explosive organic peroxide when exposed to air or light or with age.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water.
	Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Туре	Value
Polyvinyl chloride (CAS	STEL	5 ppm
0002 00 2,	TWA	1 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
Cyclohexanone (CAS 108-94-1)	PEL	200 mg/m3	
		50 ppm	
Furan, Tetrahydro- (CAS 109-99-9)	PEL	590 mg/m3	
		200 ppm	
Methyl ethyl ketone (CAS 78-93-3)	PEL	590 mg/m3	
		200 ppm	
Polyvinyl chloride (CAS 9002-86-2)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

US. ACGIH Threshold Limit Values

Components	Туре	Value	Form
Acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
Cyclohexanone (CAS 108-94-1)	STEL	50 ppm	
	TWA	20 ppm	
Furan, Tetrahydro- (CAS 109-99-9)	STEL	100 ppm	
	TWA	50 ppm	
Methyl ethyl ketone (CAS 78-93-3)	STEL	300 ppm	
	TWA	200 ppm	
Polyvinyl chloride (CAS 9002-86-2)	TWA	1 mg/m3	Respirable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Туре	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
		250 ppm	
Cyclohexanone (CAS 108-94-1)	TWA	100 mg/m3	
		25 ppm	
Furan, Tetrahydro- (CAS 109-99-9)	STEL	735 mg/m3	
		250 ppm	
	TWA	590 mg/m3	
		200 ppm	
Methyl ethyl ketone (CAS 78-93-3)	STEL	885 mg/m3	
		300 ppm	
	TWA	590 mg/m3	
		200 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time	
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*	
Cyclohexanone (CAS 108-94-1)	80 mg/l	1,2-Cyclohexan ediol, with hydrolysis	Urine	*	
	8 mg/l	Cyclohexanol, with hydrolysis	Urine	*	
Furan, Tetrahydro- (CAS 109-99-9)	2 mg/l	Tetrahydrofura n	Urine	*	
Methyl ethyl ketone (CAS 78-93-3)	2 mg/l	MEK	Urine	*	

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation	
Cyclohexanone (CAS 108-94-1)	Can be absorbed through the skin.
US - Minnesota Haz Subs: Skin designation applies	
Cyclohexanone (CAS 108-94-1)	Skin designation applies.
US - Tennessee OELs: Skin designation	
Cyclohexanone (CAS 108-94-1)	Can be absorbed through the skin.
US ACGIH Threshold Limit Values: Skin designation	
Cyclohexanone (CAS 108-94-1)	Can be absorbed through the skin.
Furan, Tetrahydro- (CAS 109-99-9)	Can be absorbed through the skin.
US. NIOSH: Pocket Guide to Chemical Hazards	
Cyclohexanone (CAS 108-94-1)	Can be absorbed through the skin.

Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.
Individual protection measure	s, such as personal protective equipment
Eye/face protection	Face shield is recommended. Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves.
Other	Wear appropriate chemical resistant clothing.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Translucent liquid.
Color	Clear.
Odor	Solvent.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	151 °F (66.11 °C)
Flash point	-4.0 °F (-20.0 °C)
Evaporation rate	5.5 - 8
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	1.8
Flammability limit - upper (%)	11.8
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	145 mm Hg @ 20 C
Vapor density	2.5
Relative density	0.9 +/- 0.02
Solubility(ies)	
Solubility (water)	Negligible
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	80 - 500 cP
Other information	
VOC (Weight %)	<510 g/l SCAQMD 1168/M316A

10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Ammonia. Amines. Isocyanates. Caustics.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May be fatal if swallowed and enters airways. Headache. Nausea, vomiting. May cause irritation to the respiratory system. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	May be fatal if swallowed and enters airways. Harmful if swallowed. Harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Symptoms related to the physical, chemical and toxicological characteristics	Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects

Acute toxicity	May be fatal if swallowed and enters airways. Narcotic effects. May cause respiratory irritation.	
Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
Dermal		
LD50	Rabbit	20 ml/kg
Inhalation		
LC50	Rat	50 mg/l, 8 Hours
Oral		
LD50	Rat	5800 mg/kg
Cyclohexanone (CAS 108-94-1)		
Acute		
Dermal		
LD50	Rabbit	948 mg/kg
Inhalation		
LC50	Rat	8000 ppm, 4 hours
Oral		
LD50	Rat	1540 mg/kg
* Estimates for product may	be based on additional component data	not shown.
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitization	on	
Respiratory sensitization	Not available.	
Skin sensitization	This product is not expected to cause	e skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	

Carcinogenicity

In 2012 USEPA Integrated Risk Information System (IRIS) reviewed a two species inhalation lifetime study on THF conducted by NTP (1998). Male rats developed renal tumors and female mice developed liver tumors while neither the female rats nor the male mice showed similar results. Because the carcinogenic mechanisms could not be identified clearly in either species for either tumor, the EPA determined that the male rat and female mouse findings are relevant to the assessment of carcinogenic potential in humans. Therefore, the IRIS review concludes that these data in aggregate indicate that there is "suggestive evidence of carcinogenic potential" following exposure to THF by all routes of exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Cyclohexanone (CAS 108- Polyvinyl chloride (CAS 90 OSHA Specifically Regulated	94-1) 02-86-2) Substances (29 CFR 1910.10	3 Not classifiable as to carcinogenicity to humans. 3 Not classifiable as to carcinogenicity to humans. 01-1050)
Polyvinyl chloride (CAS 90	02-86-2)	Cancer
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Narcotic effects. May cause drowsiness and dizziness. Respiratory tract irritation.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	May be fatal if swallowed and e	enters airways.
Chronic effects	Prolonged inhalation may be ha	armful.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results	
Acetone (CAS 67-64	-1)			
Aquatic				
Fish	LC50	Fathead minnow (Pimephale	es promelas) > 100 mg/l, 96 hours	
Cyclohexanone (CAS	S 108-94-1)			
Aquatic				
Fish	LC50	Fathead minnow (Pimephale	es promelas) 481 - 578 mg/l, 96 hours	

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential	No data available.	
Partition coefficient n-octa	anol / water (log Kow)	
Acetone (CAS 67-64-1)		-0.24
Cyclohexanone (CAS 108-9	4-1)	0.81
Furan, Tetrahydro- (CAS 10	9-99-9)	0.46
Methyl ethyl ketone (CAS 78	3-93-3)	0.29

Mobility in soil No data available.

Other adverse effects

No data avaliable.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT	
UN number	UN1133
UN proper shipping name	Adhesives
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	11
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	T11, TP1, TP8, TP27
Packaging exceptions	150
Packaging non bulk	201
Packaging bulk	243
ΙΑΤΑ	
UN number	UN1133
UN proper shipping name	Adhesives
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	11
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
IMDG	
UN number	UN1133
UN proper shipping name	ADHESIVES
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-D
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to	Not available.
Annex II of MARPOL 73/78 and	
the IBC Code	

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Polyvinyl chloride (CAS 9002-86-2)	Cancer
	Central nervous system
	Liver
	Blood
	Flammability
CERCLA Hazardous Substance List (40 CFR 302.4)	
Acetone (CAS 67-64-1)	LISTED
Cyclohexanone (CAS 108-94-1)	LISTED
Furan, Tetrahydro- (CAS 109-99-9)	LISTED
Methyl ethyl ketone (CAS 78-93-3)	LISTED

Superfu	Ind Amendments and Rea	uthorization Act of 1986 (SAF	RA)		
Haz	zard categories	Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No			
SA	SARA 302 Extremely hazardous substance				
	Not listed.				
SAI che	RA 311/312 Hazardous emical	No			
SA	RA 313 (TRI reporting) Not regulated.				
Other fe	ederal regulations				
Cle	an Air Act (CAA) Section	112 Hazardous Air Pollutants	(HAPs) List		
Cle	Not regulated. an Air Act (CAA) Section	112(r) Accidental Release Pre	vention (40 CFR 68.130)		
Saf (SD	e Drinking Water Act	Not regulated.			
	Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number				
	Acetone (CAS 67-64-	1)	6532		
	Methyl ethyl ketone (C Drug Enforcement Admin	CAS 78-93-3) nistration (DEA). List 1 & 2 Ex	6714 cempt Chemical Mixtures (21 CFR 1310.12	2(c))	
	Acetone (CAS 67-64-	1)	35 %WV		
	DEA Exempt Chemical M	lixtures Code Number	55 %WV		
	Acetone (CAS 67-64- Methyl ethyl ketone (C	1) CAS 78-93-3)	6532 6714		
US state	e regulations				
US. Massachusetts RTK - Substance List					
US.	Acetone (CAS 67-64-1) Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS 109-99-9) Methyl ethyl ketone (CAS 78-93-3) US. New Jersey Worker and Community Right-to-Know Act				
US.	Acetone (CAS 67-64-1) Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS 109-99-9) Methyl ethyl ketone (CAS 78-93-3) Polyvinyl chloride (CAS 9002-86-2) US. Pennsylvania Worker and Community Right-to-Know Law				
US.	Acetone (CAS 67-64-1) Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS 109-99-9) Methyl ethyl ketone (CAS 78-93-3) US. Rhode Island RTK				
	Acetone (CAS 67-64-1) Cyclohexanone (CAS 108- Furan, Tetrahydro- (CAS 1 Methyl ethyl ketone (CAS 1	94-1) 09-99-9) 78-93-3)			
US.	JS. California Proposition 65 California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.				
Internat	ional Inventories				
Co ı Car	u ntry(s) or region nada	Inventory name Domestic Substances List (DS	L)	On inventory (yes/no) * Yes	

Country(s) or region

Inventory name

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	05-27-2015
Revision date	-
Version #	01
HMIS® ratings	Health: 2 Flammability: 3 Physical hazard: 0
NFPA ratings	2 0

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Oatey Co. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.